

MICROORGANISM CONTROL CHEMICAL

ACTIVE INGREDIENTS: (% by weight) 1-alkyl (C ₆ to C ₁₈)*-amino-3-aminopropane
propionate-copper acetate complex
Isopropanol
*As in fatty acids of coconut oil.
INERT INGREDIENTS*:
Total
Inert ingredients contain dispersants, penetrants and stabilizers.
Weight per gallon = 7.9 lb
Copper as Cu

PRINCIPAL USE: For bacterial and fungal slime and algae control in industrial recirculation cooling water towers use 240–290 ppm (2½–3 gallons per 10,000 gallons of system water) NALCO 25-L initially to achieve control. Badly fouled systems must be precleaned. Once the desired degree of control is achieved add 24–190 ppm (¼–2 gallons per 10,000 gallons of system water) NALCO 25-L weekly or as needed to maintain control.

Apply NALCO 25-L to a point in the system where it will be uniformly mixed and evenly distributed. This product should be applied when the system efficiency is in jeopardy of becoming affected or after cleaning of systems whose efficiency is already impaired. Feed NALCO 25-L directly from the drum or through a proportioning pump. Feeding equipment should be plastic or plastic lined. Foaming may occur following use of high end dosages. To control foam use 5-10 ppm NALCO 71-D5 or other suitable antifoam. Technical assistance on individual site problems obtainable from your Nalco Representative.

NOTE: NALCO 25-L INTENDED FOR INDUSTRIAL USE ON! Y

Do not apply to potable water or domestic water systems.

This product is toxic to fish. Do not discharge treated effluent where it will arain into lakes, streams or ponds.

Do not reuse this container. Destroy when empty.

Do not use in humidifying air systems. Apply this product only as specified on this label.

WARNING: CAUSES SEVERE BURNS TO EYES AND SKIN. DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

Avoid contact with skin, eyes, and clothing. Keep container closed when not in use. Avoid breathing vapor. Store in a cool area. Do not take internally. In case of contact, immediately flush skin or eyes with large amounts of water for at least 15 minutes; for eyes also get medical attention. Remove and wash contaminated clothing before reuse.

NALCO CHEMICAL COMPANY

6216 WEST 66TH PLACE

EPA Registration No. 1706-25

CHICAGO, ILLINOIS 60638

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER