



# NALCO

# 7323

### MICROORGANISM CONTROL CHEMICAL

#### ACTIVE INGREDIENTS:

Methylene bis (thiocyanate) . . . . .	3.0%
2, 4, 5-trichlorophenol . . . . .	6.0%

INERT INGREDIENTS: . . . . . 91.0%

Total . . . . . 100.0%

Weight per gallon = 8.11 lb

EPA REGISTRATION NO. 1706-81

# NALCO CHEMICAL COMPANY

6216 WEST 66TH PLACE

CHICAGO, ILLINOIS 60638

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

**DIRECTIONS:** For use in recirculating cooling water systems. Apply NALCO 7323 (per gallon) to the system at the rate of 1.0 ounce per week. Cooling systems will require an initial dosage of NALCO 7323 (per gallon) of 2.0 ounces weekly, or as needed, to maintain a chlorine concentration of 1.0 ppm in the product.

NALCO 7323 should be applied to the system in a clean drum. Feeding equipment should be stainless steel, nickel, or polypropylene or Teflon. Apply NALCO 7323 to the system where it will be uniformly mixed and evenly distributed such as in the tower sump. Technical assistance on individual site problems may be obtained from your Nalco Representative.

**NOTE: NALCO 7323 INTENDED FOR INDUSTRIAL USE ONLY. Do not apply to potable water or domestic water systems.**

**This product is toxic to fish and wildlife. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water.**

Do not reuse this container. Destroy when empty.

**WARNING: IRRITATING TO SKIN AND EYES. ABSORPTION THROUGH SKIN HARMFUL. HARMFUL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN.** Do not get in eyes, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. In case of contact, immediately wash skin with plenty of soap and water for at least 15 minutes; for eyes, immediately flush with large amounts of water for at least 15 minutes, and get medical attention. Remove and wash contaminated clothing before reuse.