

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

February 8, 2017

Rachel Majerczak Regulatory Specialist Nalco Company LLC 1601 West Diehl Road Naperville, IL 60563

Subject: Notification per PRN 98-10 – Revised to Add Patent Statement

Product Name: Nalcon 7647

EPA Registration Number: 1706-158 Application Date: January 19, 2017

Decision Number: 525652

Dear Ms. Majerczak:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped "Notification" and will be placed in our records.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If you have any questions, you may contact Terria Northern at 703-347-0265 or via email at northern.terria@epa.gov.

Sincerely,

for

John Hebert, Branch Chief Regulatory Management Branch I Antimicrobials Division (7510P) Office of Pesticide Programs

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE OR SKIN BURNS. HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH SKIN. Do not get in eyes, on skin or on clothing. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Mixers, loaders, and others exposed to this product must wear: longsleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling the product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. Do not apply this product in a way that will contact workers or other persons.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

PHYSICAL AND CHEMICAL HAZARDS

This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

(Instructions for refillable containers:)

Container Handling: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times. Then offer for recycling, if available, or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

(Instructions for non-refillable containers greater than 5 gallons:)

Container Handling: Non-refillable container. Do not reuse or refill this container. Triple rinse (or equivalent) container promptly after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling, if available, or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities. If burned, stay out of smoke.

(Instructions for non-refillable containers 5 gallons or less:)

Revised: 01/19/2017

Container Handling: Non-refillable container. Do not reuse or refill this container. Triple rinse (or equivalent) container promptly after emptying. Triple rinse as follows: Empty remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the TOTI frie particular to patented | Ce produit peut être breveté | Este producto puede ser container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling, if available, or reconditioning, or punctified applicant has certified that no and dispose of in a sanitary landfill, or incinerate or burn, if allowed by state and local authorities halfiges, other than those reported to burned, stay out of smoke.



PAPERMILL SLIMICIDE

ACTIVE INGREDIENTS:	
5-Chloro-2-methyl-4-isothiazolin-3-one	1.1%
2-Methyl-4-isothiazolin-3-one	0.4%
INERT INGREDIENTS:	98.5%
Total	100.0%

This product contains the active ingredients at 0.127 pounds per gallon

KEEP OUT OF REACH OF CHILDREN **DANGER PELIGRO**

FIRST AID

If in eves:

- · Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- · After at least 15 minutes of rinsing or after it is judged that nearly all of the contamination has been removed. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Call a poison control center or a doctor immediately for treatment advice.

If swallowed:

- · Call a poison control center or a doctor immediately for treatment advice.
- DO NOT INDUCE VOMITING.
- · Do not give anything to drink

If on skin or clothing:

- Take off contaminated clothing.
- · Rinse skin immediately with plenty of water for 15-20 minutes.
- · Call a poison control center or a doctor for treatment advice.

If inhaled:

- · Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to- mouth if possible.
- Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN:

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA REG. NO. 1706-158

EPA EST. NO. 1706-CA-1 (CR) EPA EST. NO. 1706-PA-1 (EL) EPA EST. NO. 1706-CN-1 (BU) EPA EST. NO. 1706-WA-1 (VW) EPA EST. NO. 1706-LA-1 (GV) EPA EST. NO. 68708-TX-1 (SL)

Letter in () matches first letter in batch number identifies the establishment number.

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

patentado: www.ecolab.com/patents] 1706-158

the Agency have been made to the

Nalco Company 1601 West Diehl Road Naperville, IL 60563-1198 labeling. The Agency acknowledgemergency PHONE NO. (800) 424-9300

this notification by letter dated: 02/08/2017

UN 3265, Corrosive Liquid. Acidic. Organic. N.O.S. (Isothiazolinone Microbiocide), 8, II

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PAPERMILL WATERS

NALCON 7647 is recommended for the control of bacterial and fungal slime in the production of paper.

POINT OF ADDITION: NALCON 7647 should be added to a point in the system to insure uniform mixing such as the Beater, Hydropulper, or Fan or Broke Storage Pumps.

DOSAGE: Apply 0.44 to 1.5 lbs. (7 to 23 fluid ounces) of NALCON 7647 per ton (dry basis) of pulp or paper produced as a slug dose. If needed repeat daily. Badly fouled systems should be cleaned before

POLYMER LATEX AND SOLUTION PRESERVATION

NALCON 7647 is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer lattices and solutions including: acrylic; styrene/butadiene; carboxylated styrene/butadiene; ethylene/vinyl acetate; and biopolymers intended for industrial use, such as xanthan gum, gum arabic, guar gum, protein-derived polymers, starches, and casein-derived polymers.

Add 0.43 - 3.3 lbs. of NALCON 7647 (195 g. - 1.5 kg.) to each 1,000 lbs. (453.6 kg.) of emulsion or solution to provide 425 to 3,350 ppm product (6.25 to 50 ppm active isothiazolones).

NOTE: To insure uniform mixing, add NALCON 7647 to latex or solutions slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated. frequency of repeated microbial contamination expected, and level of synthetic fiber finish coatings.

COATING PRESERVATION

NALCON 7647 is recommended as an in-container preservative for the control of bacteria and fungi in water-based coatings such as paper coatings or synthetic fiber finish coatings.

Add 0.43 - 1.65 lbs. of NALCON 7647 (195 - 750 g.) to each 1,000 lbs. (453 kg.) of fluid to provide 425 to 1,675 ppm product (6.25 to 25 ppm active isothiazolones).

DISPERSED PIGMENT PRESERVATION

NALCON 7647 is recommended for the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin clay, montmorillite clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselguhr used in paper production.

Add 0.43 - 1.65 lbs. of NALCON 7647 (195 - 750 g.) to each 1,000 lbs. (453 kg.) of fluid to provide 425 to 1,675 ppm product (6.25 to 25 ppm active isothiazolones).

ELECTRODEPOSITION SYSTEMS (NOTE: THIS USE NOT CURRENTLY AUTHORIZED IN CALIFORNIA)

For control of bacteria, and fungi in Electrodeposition Systems (such as automotive or industrial equipment systems) slug feed NALCON 7647 at a rate of 1 gallon per 1000 gallons of paint in the system (1000 ppm) as needed, depending upon results of cultures taken from the system.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm NALCON 7647 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of NALCON 7647 per 1000 gallons of water in the system). Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm NALCON 7647 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces per 1000 gallons of water in the system). Weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm NALCON 7647 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of NALCON 7647 per 1000 gallons of water in the

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm NALCON 7647 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces per 1000 gallons of makeup water). Badly fouled systems must be cleaned before initial treatment.