

ACCEPTED
2/7/72
2693-4

ONE U.S. GALLON
WARNING!
KEEP OUT OF REACH OF CHILDREN
See other warnings on back panel

LASTING PROTECTION

1370 WOOD PRESERVATIVE

ZINC NAPHTHENATE CLEAR

ACTIVE INGREDIENTS	
Petroleum Distillate	67.3 %
Zinc Naphthenate	30.5 %
(Zinc content 1.0)	
INERT INGREDIENT	2.2 %
	100.0 %

HARMFUL IF SWALLOWED

FACTORIES

U.S.A.	UNION, N. J.
U.S.A.	SAN FRANCISCO
U.S.A.	NEW ORLEANS
AUSTRALIA	SYDNEY
BRAZIL	RIO DE JANEIRO
CANADA	MONTREAL
CANADA	REGINA
CANADA	VANCOUVER
DENMARK	COPENHAGEN
ENGLAND	FELLING-ON-TYNE
FRANCE	ROUEN
GERMANY	HAMBURG
HOLLAND	RIJSWIJK
ITALY	GENOA
ITALY	TRIESTE
MEXICO	MEXICO CITY
NEW ZEALAND	AUCKLAND
NEW ZEALAND	WELLINGTON
NIGERIA	IKEJA
NORWAY	BERGEN
PORTUGAL	SETUBAL
SCOTLAND	GLASGOW
SPAIN	BILBAO
SWEDEN	GOTHENBURG
VENEZUELA	MARACAIBO

ACCEPTED
2/7/72

E.P.A. 2693 4 A A

CAUTION
COMBUSTIBLE
MIXTURE

N.Y.F.D. C of A No. 1816

DO NOT USE, POUR, SPILL OR STORE
NEAR HEAT OR OPEN FLAME.

INTER-TOX 1370 WOOD PRESERVATIVE
ZINC NAPHTHENATE CLEAR

DIRECTIONS

*May cause skin irritation. Avoid contact with skin.

This effective preservative is formulated with a special solvent which permeates and seals the pores of the wood, preventing the entry and carrying with it the moisture which causes rot and decay. It kills and keeps dry rot and destroys termites and other wood-boring insects. The initial treatment should be done on all new wood.

This preservative should be applied to all new wood. It can be brushed or dipped. For dipping, the wood should be completely dry. For wooden members, the wood should be completely dry and the wood should be immersed in the product for approximately 12 to 18 hours. It is a non-toxic wood preservative.

For general application, apply two flowing coats to the wood and coat being treated. The second coat should be applied after the first coat has dried. For better protection, the wood should be completely dry before dipping. For dipping, the wood should be completely dry and the wood should be immersed in the product for approximately 12 to 18 hours. It is a non-toxic wood preservative.

The nature of this preservative is such that it will not cause any staining or discoloration of the wood. It is a non-toxic wood preservative. It is a non-toxic wood preservative.