## UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460



## **SEPA** United States: Office of Pesticide Programs Approv Office of Pesticide Programs

International Paints, LLC 2270 Morris Avenue Union, N. J. 07083

FEB 17 2010

Attention: John P. Pazdera

Pesticide Registration Manager

Subject: MIL-P15931B Formula 121/63 Antifouling Paint Vinyl RED

EPA Registration No. 2693-46

Notification Dated January 21, 2010

This will acknowledge receipt of your notification, submitted under the provisions of FIFRA Section 3(c)(9).

## **Proposed Notification**

- To revise Storage and Disposal statement per PR Notice 2007-4

## **General Comments**

Based on a review of the submitted material, the following comments apply:

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been added to your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Martha Leny from Marshall Swindell

Product Manager (33)

Regulatory Management Branch 1 Antimicrobials Division (7510P)

Please read instructions on reverse before completing form.	Form Approved	∵∪MB No. 2070-000	Print Form
United States Environmental Protectio Washington, DC 2046	· .	Registration Amendment Other	OPP Identifier Number
Application for Pesticide - Section I			
1. Company/Product Number 2693-46	2. EPA Product Manager M. Swindell	3.	Proposed Classification
4. Company/Product (Name) MIL-P-15931B Formula 121/63 Antifouling Paint Vinvl Red	PM# 33		X None Restricted
5. Name and Address of Applicant (Include ZIP Code) International Paint LLC 2270 Morris Ave. Unjon NV 07083 Check if this is a new address			th FIFRA Section 3(c)(3) composition and labeling
Section - II			
Amendment - Explain below.  Resubmission in response to Agency letter dated			
Notification - revise Storage and Disposal statement in accord with PR Notice 2007-4			
Section - III			
1. Material This Product Will Be Packaged In:  Child-Resistant Packaging  Yes*  No  * Cartification must be submitted  Vinit Packaging wgt.  No. per container	Water Soluble Packaging  Yes No  If "Yes" No. per Package wgt Container	2. Type of Contain  Meta Plasti Glass Pape Other	l ic i
3. Location of Net Contents Information 4. Size(s) Return Lebel Container	ail Container 5. L	ocation of Label Direction On Label On Labeling acc	ompanying product
6. Manner in Which Label is Affixed to Product Lithograph Other Stenciled			
Section - IV			
Contact Point   Complete items directly below for identification     Name     John P. Pazdera	n of individual to be contacted, if no Title Pesticide Regis. Manager	Teleph	one No. (Include Area Code) 064-2288
Certification  I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete.  I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.  6. Date Application Received  (Stamped)			
2. Signature John P. Pazdera	3. Title Pesticide Registration Manager		
4. Typed Name !  John P. Pazdera	<b>5. Date</b> Jan 21, 2010		

ris Avenue T 908 686 1300 F 908 686 8545 www.yachtpaint.com




## **CERTIFICATION FOR NOTIFICATION**

"Notification of label change per PR Notice 2007-4. This notification is consistent with the guidance in PR Notice 2007-4 and the requirements of EPA's regulations at 40 CFR §§ 156.10, 156.140, 156.144, 156.146, and 156.156. No other changes have been made to the labeling or the Confidential Statement of Formula for this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if the amended label is not consistent with the requirements of 40 CFR §§ 156.10, 156.140, 156.144, 156.146, and 156.156, this product may be in violation of FIFRA, and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA."

Sesticide Registration Manager



1)



Mr. Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division
Office of Pesticide Programs (7504P)
U.S. EPA
Room S-4900, One Potomac Yard
2777 South Crystal Drive
Arlington, VA 22202-4501

<u>Via Federal Express</u>

January 21, 2010

Re: MIL-P-15931B Formula 121/63 Antifouling Paint Vinyl Red EPA Reg. No. 2693-46
Notification-Response to PR Notice 2007-4

Dear Mr. Swindell:

The enclosed Notification pertains to our product MIL-P-15931B Formula 121/63 Antifouling Paint Vinyl Red, EPA Reg. No. 2693-46. Specifically, we wish to make the following label change:

- Revise the Storage and Disposal statement in accord with PR Notice 2007-4. No other changes are being made.

As this is an Agency-initiated amendment, no registration service fee is required.

In support of this application, please find enclosed:

- Application for Amendment Form (8570-1)
- Five (5) copies of revised labeling
- Copy of EPA stamped label dated 7/15/03
- Certification Statement







Mr. Marshall Swindell January 21, 2010 Page 2

Please do not hesitate to contact me at 908-964-2288 if there are any questions concerning this submission.

Very truly yours,

John P. Pazdera

Pesticide Registration Manager

JPP/cd

Enclosures

## MIL-P-15931B

Formula 121/63 ANTIFOULING PAINT, **VINYL RED** 

For Hot Spray

## FOR COMMERCIAL USE ONLY

Active Ingredient: Cuprous Oxide Inert-Ingredients:

66.80%

-- 33:20%

100.00%

## **ELEMENTAL COPPER 58.45%**

Contains petroleum distillates.

## KEEP OUT OF REACH OF CHILDREN **WARNING**

- See side panel for additional Precautionary Statement -

EPA Reg. No.: 2693-46

EPA Est. No.: 2693-NJ-1

## **NET FIVE U.S. GALLONS**

**International Paint LLC** UNION, NJ 07083 · HOUSTON, TX 77091

# PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and by the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

#### FIRST AID

#### If Swallowed:

- Immediately call a poison control center or doctor.
- Do not induce vomiting unless told to do so by a poison control center or doctor.
- Do not give any liquid to the person.
- Do not give anything by mouth to an unconscious person.

#### If on skin or clothing:

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

#### If inhaled:

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or doctor for further treatment advice.

#### If in eyes:

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

Other: Have the product container or label with you when calling a poison control center or doctor or going for treatment.

Note to Physician: Contains petroleum distillate – vomiting may cause aspiration pneumonia.

#### **ENVIRONMENTAL HAZARDS**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

## PHYSICAL OR CHEMICAL HAZARD

FLAMMABLE! Keep away from heat or open flame.

#### GENERAL DESCRIPTION

This product is an antifouling protective coating designed for use on boats and ships, which is resistant to algae, barnacles and other marine fouling. For use in fresh, salt and brackish water.

#### **DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

#### STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. **PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

## DIRECTIONS FOR USE (CONTINUED)

SURFACE PREPARATION: Surface preparation directions must be followed exactly in order to insure adhesion. Surface must always be clean and dry prior to painting. Do not apply below 35°F unless care is taken to insure absence of frost or ice. (See Application Systems).

GENERAL APPLICATION PROCEDURES: Airless spray is recommended: tip size 21-26 thou., pump ratio of 30:1 or greater. For small areas, brush or roller application may be used but multiple coats may be required to achieve the required dry film thickness. It is normally recommended to apply by airless spray one (1) or two (2) full coats of this product.

SPECIAL INSTRUCTIONS: Do not store in direct sunlight for prolonged periods, such that the paint temperature is above 100°F. Contents may be applied by hot spray (temperature not to exceed 95°F) airless spray, or regular cold spray (normally no thinning required). Where thinning is necessary, use Methyl sobutyl Ketone:

MIXING AND THINNING INSTRUCTIONS: Mix thoroughly with power mixer prior to application. This coating is designed to be applied without thinning.

CLEAN UP: For tools, equipment, etc., use INTERNATIONAL THINNER GTA407.

MINIMUM DRY AND LAUNCHING TIMES: Minimum drying time between coats is 8 hours, and before launching is 24 hours at a temperature of 73°F.

THEORETICAL COVERAGE: 489 square feet per gallon, per coat at 2.0 mils dry film thickness. Consult your International representative for practical application coverages. Practical square foot coverage per gallon, per coat is directly proportional to surface, application techniques and climatic conditions.

#### **APPLICATION SYSTEMS**

EXISTING MIL-P-15931F VINYL ANTIFOULING SYSTEMS: High pressure fresh water wash with a minimum of 2500 p.s.i. to remove all marine growth, slime, salts, etc. Spot blast all areas of corrosion to Near White Metal. Blow down with clean dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

POOR HULL CONDITION: For "optimum" results, blast entire area to Near White Metal. Apply an approved underwater anticorrosive system.

**NEW SHIP CONSTRUCTION:** Blast entire area to Near White Metal. Blow down with clean dry high pressure air to remove all spent abrasives. Apply an approved underwater anticorrosive system.

WOOD AND NON-FERROUS SURFACES: Contact an INTERNATIONAL PAINT representative.

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of International Paint Inc. including surface preparation, proper application, and environmental conditions. Therefore, International Paint Inc. cannot guarantee this product's suitability for your particular purpose or application. IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE AND OF MERCHANTABILITY ARE EXCLUDED. INTERNATIONAL PAINT INC SHALL NOT, UNDER ANY CIRCUMSTANCES, BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at International Paint Inc's option.



AKZO NOBEL UNION, NJ 07083 • HOUSTON, TX 77091

Rev.-5/99