



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

July 9, 2020

Vanessa Villagran  
PSRA Specialist  
International Paint  
6001 Antone Drive  
Houston, TX 7791

Subject: Label Amendment – To update label language  
Product Name: INTERCLEN BRA 540 RED  
EPA Registration Number: 2693-132  
Application Date: January 29, 2020  
Decision Number: 559930

Dear Ms. Villagran:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6. If you have any questions, you may contact Emilia Oiguenblik by phone

Page 2 of 2  
EPA Reg. No. 2693-132  
Decision No. 559930

at 703 347 0199, or via email at [Oiguenblik.emilia@epa.gov](mailto:Oiguenblik.emilia@epa.gov) or Eric Miederhoff by phone at 703 347 8028, or via email at [Miederhoff.eric@epa.gov](mailto:Miederhoff.eric@epa.gov)



Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Enclosure: Stamped label

# INTERCLEN BRA540 RED

**ACCEPTED**

07/09/2020

Under the Federal Insecticide, Fungicide  
and Rodenticide Act as amended, for the  
pesticide registered under  
EPA Reg. No. 2693-132

[Antifouling Performance for All Conditions]  
[Controlled Release for Long Lasting Protection]  
[Multi-Season, Self-Polishing, No Buildup]  
[For Fiberglass, Wood or Steel Boats]  
[Haul & Relaunch Without Repainting]  
[Controlled Depletion Polymer Antifouling]  
[Suitable for Power and Sailboats]  
[Proven Performance for 20 Years]  
[All the Benefits of Micron Technology]

**[FOR COMMERCIAL USE ONLY]**

---

## Alternative Brand Names (ABNs)

- [INTERCLEN 245 NA BRA570 RED]
- [INTERCLEN 245 NA BRA572 BLACK]
- [INTERSPEED 6400NA BLACK BQA679/5GAL]
- [INTERSPEED 6400NA RED BQA674/5GAL]
- [MICRON CSC]
- [MICRON CSC 5586 DARK BLUE]
- [MICRON CSC BLUE]
- [MICRON CSC Y5580 Blue]
- [MICRON CSC Y5581 Green]
- [MICRON CSC Y5582 Red]
- [MICRON CSC Y5583 Black]
- [MICRON CSC Y5584 Shark White]
- [MICRON CSC Y5586 Dark Blue]
- [Micron CSC Extra Black 5583]
- [Micron CSC Extra Blue 5580]
- [Micron CSC Extra Brown 5585]
- [Micron CSC Extra Green 5581]
- [Micron CSC Extra Red 5582]
- [Micron CSC Extra Shark White 5584]
- [Micron CSC Sea-Ray Burgundy 4804]
- [Micron CSC Sea-Ray Dark Blue 4801]
- [INTERLUX MICRON CSC 5580 BLUE]
- [INTERLUX MICRON CSC 5581 GREEN]
- [INTERLUX MICRON CSC 5582 RED]
- [INTERLUX MICRON CSC 5583 BLACK]
- [INTERLUX MICRON CSC 5584 SHARK WHITE]

---

[GRAPHICS]

**AkzoNobel**

 **Interlux**



Micron, Interlux, InterProtect and the AkzoNobel logo are trademarks of AkzoNobel. © AkzoNobel [XXXX- year label is printed].



Interlux and the AkzoNobel logo  
are trademarks of Akzo Nobel.

**[FRONT PANEL]**

**KEEP OUT OF REACH OF CHILDREN**

**WARNING**

See side panel for additional precautionary statements

Active Ingredient:

Cuprous Oxide = 37.20%

Other Ingredients: = 62.80%

100.00%

Copper as Metallic = 32.90%

Contains Petroleum Distillates.

EPA Registration No. 2693-132

EPA Establishment No. 2693-TX-1

[DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of INTERNATIONAL PAINT, LLC., including surface preparations, proper application and environmental conditions. Therefore, INTERNATIONAL PAINT, LLC., cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, INTERNATIONAL PAINT, LLC., EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of this product. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.]

**International Paint, LLC.  
6001 Antoine Drive  
Houston, Texas 77091**

**[Interlux.com]**

NET CONTENTS: FIVE U.S. GALLONS (18.927 LITERS)

[SIDE PANEL]

**PRECAUTIONARY STATEMENTS**  
**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**  
**WARNING**

May be fatal if swallowed or inhaled. Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. Do not breathe vapor or spray mist. While painting or sanding or sandblasting boat surfaces, wear a minimum of a NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and combination N, R, or P filters; OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air purifying respirator with OV cartridges and combination HE filters. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

<b>FIRST AID</b>	
<b>If swallowed:</b>	<ul style="list-style-type: none"><li>• Immediately call a poison control center or doctor.</li><li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li><li>• Do not give any liquid to the person.</li><li>• Do not give anything by mouth to an unconscious person.</li></ul>
<b>If on skin or clothing:</b>	<ul style="list-style-type: none"><li>• Take off contaminated clothing.</li><li>• Rinse skin immediately with plenty of water for 15-20 minutes.</li><li>• Call a poison control center or doctor for treatment advice</li></ul>
<b>If inhaled:</b>	<ul style="list-style-type: none"><li>• Move person to fresh air.</li><li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible.</li><li>• Call a poison control center or doctor for further treatment advice.</li></ul>
<b>If in eyes:</b>	<ul style="list-style-type: none"><li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li><li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li><li>• Call a poison control center or doctor for treatment advice.</li></ul>
<b>Other:</b> Have the product container or label with you when calling a poison control center or doctor or going for treatment. For medical emergencies, call the poison control center at 1-800-222-1222. For general information on this product, contact the National Pesticides Information Center (NPIC) at 1-800-858-7378, Monday through Friday, 8 AM to 12 PM PST, or at <a href="http://npic.orst.edu">http://npic.orst.edu</a> .	

**Note to Physician:** Contains petroleum distillate - vomiting may cause aspiration pneumonia.

**ENVIRONMENTAL HAZARDS**

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS**

**Flammable.** Keep away from heat and open flame.

## STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

**STORAGE:** Exposure to air and extremes of temperature must be avoided. Keep the container firmly closed. Keep out of direct sunlight. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER HANDLING:** Nonrefillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

[For Chemical Emergency, Spill, Leak, Exposure or Accident, Call Toll Free – Day or Night – CHEMTREC 1-800-424-9300. Medical Advisory Number – Contact your Local Poison Control Center or Call 1-800-854-6813.]

## [Subset A - For Heavy Duty Marine Market]

**PRODUCT DESCRIPTION:** An economical antifouling designed to offer fouling protection against algae, barnacles and other marine fouling for extended periods of time. For use in fresh, salt and brackish waters. This product is for industrial use and professional application only. Not for sale to the general public.

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

#### PRODUCT INFORMATION:

<b>Finish /Sheen</b>	Semi-Gloss (ASTM 0-523)
<b>Converter</b>	One pack
<b>Volume Solids</b>	60% ± 2% (ASTM 0-2697)
<b>Mix Ratio</b>	One pack
<b>Flash Point</b>	79°F (26°C) (Setaflash) (ASTM 0-3278)
<b>Film "Thickness"</b>	4.0 mils-(102microns) dry specified equivalent to 6:7mils (170 microns) wet. 4.0-5.0 mils (102-127 microns) dry practical range equivalent to 6.7-8.3 mils (170-211 microns) wet.
<b>Theoretical Coverage</b>	240 sq. ft./gal. (4.0 mils (102 microns) OFT) <b>Allow appropriate loss factors.</b>

#### APPLICATION DETAILS:

<b>Method</b>	Airless spray, brush or roller
<b>Thinner</b>	Not recommended. If necessary use GTA007, see thinning section.
<b>Cleaner</b>	GTA007

Drying Time (hours)	(ASTM 0 16407.5.1) Touch	Overcoating Interval by		Minimum drying time* before flooding (for 2x5 microns) OFT coats)
		Self (ASTM 0-16407.8) Minimum	Maximum mil (125 microns)	
41°F(5°C)	6	12	Indefinite	3 days
77°F (23°C)	4	6	Indefinite	2 days
95°F (35°C)	2	4	Indefinite	1 day

\* Refer to your International Representative for minimum drying time before flooding at higher dry film thicknesses and to Limitations section for maximum recommended atmospheric exposure time before flooding.

#### REGULATORY DATA

**VOC:** 2.8 lb /gal (336 g/l) as supplied (EPA Method 24)

**SYSTEMS AND COMPATIBILITY:** International should be consulted for detailed application advice, specification recommendations and as to the suitability of specific products on individual vessels.

**LIMITATIONS:** Apply in good weather when air and surface temperatures are above 35°F (2°C). Surface temperatures must be at least 5°F (3°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40° and 100°F (4°-38°C).

Prolonged atmospheric exposure of this product may detract from antifouling performance.

Recommended maximum exposure time before flooding:

Temperate conditions 28 days

Tropical conditions 7 days

These times may be extended under certain conditions. Refer to your International Representative for recommendations.

To maximize performance, a minimum of two full coats at the recommended dry film thickness should be applied.

Technical and application data herein is for the purpose of establishing a general guideline of the coating and proper coating application procedures. Test performance results were obtained in a controlled laboratory environment and International makes no claim that the exhibited published test results, or any other tests, accurately represent results

actually found in all field environments. As application, environmental and design factors can vary significantly due care should be exercised in the selection, verification of performance, and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, soluble contaminants and other detrimental foreign matter by "solvent cleaning" (SSPC-SP1).

*New Construction:* Dependent on yard procedures, consult International.

*Unpainted surfaces:* Prepare surface and apply recommended primer. Apply one or more coats of this product as specified. (Consult the relevant primer data sheet for surface preparation and overcoating information.)

*Maintenance:* Use controlled close high pressure fresh water washing (3,000 psi, 211 kg/sq. cm.) to clean the entire area and remove any leached layer at the surface of the existing antifouling system.

Repair corroded areas with the recommended anticorrosive primer and apply this product within the overcoating interval specified for the primer (consult relevant primer data sheet). Apply the specified number of full coats of this product.

**MIXING:** This material is a one component coating. Always mix thoroughly with a power agitator before application.

**APPLICATION:** Apply by airless spray only. Application by other methods, brush or roller, may require more than one coat and is suggested for small areas only or initial stripe coating. Apply 6-7 mils (170 microns) wet which will yield 4.0 mils (100 microns) dry film thickness. Consult the following equipment recommendations or utilize suitable equal.

#### **Equipment**

*Brush:* Use appropriate size China bristle brush.

*Roller:* Use All Purpose Roller Cover 3/8" (9.5 mm) pile smooth to medium. Prewash roller cover to remove loose fibers prior to use.

*Airless Spray:* Minimum 28:1 ratio pump; .021"-.026" (533-660 microns) orifice tip; 3/8" (9.5 mm) 10 high pressure material hose; 60 mesh tip filter.

**THINNING:** DO NOT THIN BEYOND YOUR STATE'S COMPLIANCY. Material is supplied at spray viscosity and normally does not need thinning. If thinning is necessary, thin up to a maximum of 4 ounces (118 ml) per gallon (3.79 lt) with International GTA007 Thinner.

**WORK STOPPAGES AND CLEANUP:** Clean all equipment immediately after use with International GTA007 Thinner. Spray equipment requires flushing with this solvent. It is good working practice to periodically flush out spray equipment during the course of the working day. Frequency will depend upon factors such as amount sprayed, temperature and elapsed time including work stoppages. Monitor material condition.

**[WELDING:** In the event welding or flame cutting is performed on metal coated with this product, Do so in accordance with instruction in ANS1/ASC Z49.1 "Safety in Welding and Cutting."]

**[SAFETY:** This product is not to be used without reference to the current relevant Product Data Sheet and Material Safety Data Sheets (MSDS). Prior to use, obtain, consult and follow both the Material Safety and Product Data Sheets for this product concerning both product and health and safety information. Read and follow all precautionary notices on the Material Safety and Product Data Sheets and this container label. If you do not fully understand these warnings and instructions or if you cannot strictly comply with them, do not use this product. Proper ventilation and protective measures must be provided during application and drying to keep solvent vapor concentrations within safe limits and to protect against toxic or oxygen deficient hazards *and /or* flash fire. Actual safety measures are dependent on application methods and work environment. This safety information is not a substitute for that contained in the Material Safety and Product Data Sheets. Medical Advisory Number 1-800-854-6813.]

**[UN SHIPPING NO: 1263]**

**[STORAGE:** *Store in cool, dry conditions.*]

**[Shelf Life** One year minimum from date of manufacture when maintained in protected storage at 40-100°F (4-38°C). Subject to reinspection thereafter.]

[International and Interspeed are trademarks of the AkzoNobel Group of Companies.]

*[All representations and statements concerning the product on this label are accurate to the best of International's knowledge. Any statements herein are not intended to be specific recommendations or warranties of any product,*



*combination of products or fitness for any particular purpose. Any warranty, if given, or specific Terms and Conditions of Sale are contained in International's Terms and Conditions of Sale. You should request a copy of this document and review it carefully.]*

[Subset B - for Yacht Market]

[Alternate Directions for Use]

[INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name]

**PRODUCT DESCRIPTION:** [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [This product] uses Micron® Technology to provide excellent, long lasting antifouling protection against all types of fouling. [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [This product] controlled polishing means that it wears away like a bar of soap, reducing buildup of old coatings and minimizing sanding at reapplication. [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [This product] can be hauled and relaunched without repainting. [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [This product] is suitable for use in all waters.

#### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Shake or mix well prior to use. Do not apply thin coats. The service life of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product] is directly related to the amount of paint applied. Certain areas of the hull experience faster polishing than other areas. These areas include the waterline, leading edges of the keel, the rudder, bow and stern areas. It is suggested that an additional coat of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product] be applied to these areas to ensure that it does not polish away in these areas before the other areas on the rest of the hull. [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [This product] can be applied by brush, roller or spray.

**COMPATIBILITY:** [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [This product] can be applied over most other antifouling paints provided the old coating is tightly adhered, is in sound condition and has been thoroughly sanded with 80 grit wet-or-dry sandpaper.

**VOC:** Less than 400 grams/liter (3.34 lbs/gallon) as supplied

**THINNER:** Brushing - Interlux® Brush Ease 433  
Spraying - Interlux® Special Thinner 216

**THINNING:** Thin only when necessary. Do not exceed 10% by volume.

**THEORETICAL COVERAGE:** 440 square feet per gallon/coat will yield 2 mils dry film thickness.

**DRY TIMES:** 77°F (25°C) Touch Dry - 2 hours  
Dry to overcoat - 16 hours minimum\*  
Dry to launch - 16 hours minimum\*

**APPLICATION TEMPERATURE:** 50°F (10°C) and above. (Air and hull).

\*If either the air or hull temperature falls below 50°F (10°C) during the 16-hour dry time extend the dry times to a minimum of 36 hours.

#### PREPARATION

**PREVIOUSLY PAINTED SURFACES – GOOD CONDITION:** Remove all traces of loose paint and contamination by sanding the entire surface with 80 grit wet-or-dry sandpaper; wipe surface clean. Apply 2 coats of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product].

**PREVIOUSLY PAINTED SURFACES – POOR CONDITION:** Completely remove all old antifouling paint, with Interlux® Interstrip 299E for fiberglass, and wood and by sandblasting or grinding to near white metal for steel. Follow application systems below.

**BARE FIBERGLASS:** It is very important that bare fiberglass be properly prepared to prevent delamination of the antifouling paint. Begin by scrubbing the surface thoroughly with a stiff brush using soap and water to remove loose dirt and contamination. Flush with fresh water to remove the soap residue and allowing the surface to dry. Remove mold release wax using one of the following Interlux® products. [Fiberglass Surface Prep YMA601 or Fiberglass Solvent Wash 202] following the product label instructions. Fill any surface

imperfections with Interlux® Watertite YAV135 following the label instructions. After the surface has been properly cleaned, proceed with one of the application systems below.

## APPLICATION SYSTEMS

**BARE FIBERGLASS - NO SAND SYSTEM:** Clean the surface following the preparation procedure above. Apply one coat, of [Interlux® InterProtect® 2000 or Fiberglass No-Sand Primer YPA200] following the label instructions for applying the primer and overcoating with antifouling paint. Apply two coats of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product] allowing for the appropriate dry times.

**BARE FIBERGLASS - SANDING SYSTEM:** Clean the surface following the preparation procedure above for bare fiberglass. Sand the entire surface with 80-grit sandpaper until a flat matte finish is obtained. Wipe the sanding residue off the surface with Fiberglass Solvent Wash 202. Sand and wipe clean. Apply two coats of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product] allowing for appropriate dry times.

**BARE FIBERGLASS - BLISTER PREVENTION SYSTEM:** Apply the InterProtect® system for the prevention of blisters. Contact the Interlux Technical Service Department at [Interlux.com, interluxtechnicalservice@akzonobel.com, 1-800-468-7589] for full information on how to properly apply the InterProtect® system.

**BARE WOOD:** Sand the entire surface with 80-grit sandpaper. Wipe the sanding residue off the surface. Apply the first coat of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product] thinned 10% with Brush-Ease 433. Fill seams with Interlux® Seam Compound 30 (if necessary). Apply two more coats of [INTERCLENÉ BRA540 RED], [Micron® CSC], [Alternate Brand Name], [this product] unthinned, allowing for the appropriate dry times.

**UNDERWATER METALS:** Contact the Interlux Technical Service Department at [Interlux.com, interluxtechnicalservice@akzonobel.com, 1-800-468-7589] for full information on how to properly prime underwater metals. DO NOT USE ON ALUMINUM

[Color difference may occur between actual paint and color swatch on front of can.]

---

**[Subset C - Label to be used with Alternate Formulas]**

**[Alternate Directions for Use]**

**PRODUCT DESCRIPTION:** This product is a multi-season antifouling paint based on Controlled Solubility Copolymer™ technology that is formulated to meet the strict regulations in the country while providing excellent antifouling protection. These products are designed to wear away (polish) at a controlled rate similar to a bar of soap. As a result, there will be a reduced buildup of old coatings and minimized sanding at reapplication. In addition, this technology allows the boat to be hauled and relaunched the following season without repainting. This product contains high solids and dries to bright colors. It will provide excellent antifouling longevity against all types of algae, weeds, barnacles, and other shell fouling. This product can be used below the waterline in fresh, salt or brackish water on fiberglass, wood and properly primed metal boat hull and parts. Do not use on aluminum.

**DIRECTIONS FOR USE:**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**COMPATIBILITY:** This product can be applied over most hard conventional antifouling paints as long as the old coating is tightly adhered and is in sound condition. This product should not be applied over **Micron® 33, Micron® 44** or soft antifouling paints. These coatings should be removed. This product is compatible with conventional bottom paints after they have been thoroughly sanded with 80-grit wet or dry sandpaper.

**VOC:** Less than 330 grams/liter (2.75 lbs. / gallon) as supplied

**THINNER:** [Brushing - Interlux® Brush-Ease 433™]  
[Spraying - Interlux® Special Thinner 216™]

**THINNING:** Thin only when necessary. Do not exceed 10% by volume.

**CLEAN-UP:** [Special Thinner 216™ or Brush-Ease 433™.]

**Note:** [THINNING: The addition of thinners may affect the VOC compliance of this product.]

**[Please check local regulations before adding thinners.]**

**THEORETICAL COVERAGE:** 440 square feet per gallon/coat will yield 2 mils dry film thickness.

**DRY TIMES:** Touch dry - 2 hours  
77°F (25°C) Dry to overcoat - 16 hours minimum\*  
Dry to launch - 16 hours minimum\*

**APPLICATION TEMPERATURE:** 50°F (10°C) and above. (Air and hull).

\*If either the air or hull temperature falls below 50°F (10°C) during the 16 hour dry time extend the dry times to a minimum of 36 hours.

**APPLICATION SYSTEMS**

**GENERAL APPLICATION PROCEDURES:** Shake or mix well prior to use. Apply 2 full coats (3 coats on bare wood) of this product by brush or solvent resistant 3/8" nap roller. Do not apply thin coats. Keep in mind that the life of the paint is directly related to the amount of paint applied. If during application, brush pulls or roller drags, use Interlux® Brush-Ease 433™ to improve handling. Certain areas of hull experience faster polishing than other areas. These areas include the waterline, the leading edge of the keel and rudder, and the bow stem. On these areas, it is suggested that an additional coat of paint be applied to insure this product does not wash away before the other areas of the bottom.

**PREVIOUSLY PAINTED SURFACES - GOOD CONDITION:** Remove all traces of loose paint and contamination by sanding the entire surface well with 80-grit wet or dry sandpaper; wipe surface clean with Interlux® Special Thinner 216™. Apply 2 coats of this product, allowing proper dry times.

**PREVIOUSLY PAINTED SURFACES - POOR CONDITION:** Completely remove all old antifouling paint with Interlux® Interstrip® 299E for fiberglass, wood and by sandblasting steel surfaces to a near white metal. Proceed with application system for bare work as described below.

**BARE FIBERGLASS - NO SAND SYSTEM:** Wash entire surface thoroughly with Interlux® Fiberglass Solvent Wash 202™ changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax and other contaminants are removed). Failure to properly clean the surface will result in paint delamination. Sand any imperfections and repair with Interlux® Watertite YAV135; sand and wipe clean. Apply one thin, continuous coat of Interlux® Fiberglass No Sand Primer YPA200 with brush or roller. Do not spray, do not sand. Please refer to label directions for application. Apply first coat of this product and allow to dry overnight. Apply one more coat of this product allowing proper dry times.

**BARE FIBERGLASS - SANDING SYSTEM:** Wash entire surface thoroughly with Interlux® Fiberglass Solvent Wash 202, changing rags frequently. Before liquid dries, wipe clean with a dry cloth. (Be sure all wax and other contaminants are removed). Failure to properly clean the surface will result in paint delamination. Sand any imperfections and repair with Interlux® Watertite YAV135; sand and wipe clean. Sand entire gelcoat well with 80-grit wet or dry sandpaper until a flat, matte finish is obtained; wipe surface clean with Interlux® Fiberglass Solvent Wash 202™. Apply 2 or more coats of this product allowing proper dry times.

**BARE WOOD:** Sand entire surface thoroughly with 80 grit production sandpaper; wipe surface clean with Interlux® Brush-Ease 433™. Repair imperfections with Interlux® Watertite YAV135; sand and wipe clean. Apply first coat of this product reduced with Interlux® Brush-Ease 433™ (10% maximum). Fill seams with Interlux® Seam Compound 30 between first and second coats of this product.

**UNDERWATER METALS:** Contact the Interlux® Technical Service Department at [Interlux.com, interluxtechnicalservice@akzonobel.com, 1-800-468- 7589] for full information on how to properly prime underwater metals.  
DO NOT USE ON ALUMINUM.

**[Color difference may occur between actual paint and color swatch on front of can.]**