

D

5

**DIRECTIONS
GENERAL CLASSIFICATION**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

This optional bacteriostatic cartridge is designed to inhibit bacteria growth in and on the cartridge and can be used in place of the standard cartridge in 10 inch pre-filter housings in Culligan reverse osmosis systems that are applied to potable water which is microbiologically safe for drinking.

Do not operate at flow rates greater than 20 gallons per day, or at temperatures over 100° F.

ACCEPTED
29 APR 1980
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
ED UNDER NO. 2938-10

**BACTERIOSTATIC FILTER CARTRIDGE
10 Micron, Silver, 10-Inch Length
Part No. 9553-09**

ACTIVE INGREDIENT
Silver, as elemental 1.3%
INERT INGREDIENTS 98.7%
NET CONTENTS
1 Bacteriostatic Filter Cartridge

U.S. EPA Reg. No. 2938-10
U.S. EPA Est. No. 2938

Rated capacity at 20 GPD flow: 7500 gallons or until flow becomes unacceptable.

DISPOSAL: Wrap used cartridge in newspaper and discard with trash.

INSTALLATION: Wet under flowing tap water before installing in standard 10-inch pre-filter housing.

LIMITED USE: Further treatment of filtered water by reverse osmosis filtration is required.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Culligan.

CULLIGAN USA, ONE CULLIGAN PARKWAY, NORTHBROOK, IL 60062
TELEPHONE: (312) 498-2000 · TWX 910-888-0006 · CABLE CULLING

203