PM 21 3008-68

1912

Pluase read instructions on reverse before completing form.	Form	Approved. OMB No. 2070-0060	D. Approval expires 05-31-98	
SEPA Environmental Protection Washington, DC 204	on Agency 60 NOTIFICATIO	Registration Amendment X Other	OPP Identifier Number	
Application for Pesticide - Section I				
1. Company/Product Number 3008-68	2. EPA Product	Manager 3. F	roposed Classification	
4. Company/Product (Name) OSMOPLASTIC SD WOOD PRESERVING CO	PM# DMPOUND 21		None Restricted	
5. Name and Address of Applicant (Include ZIP Code)	6. Expedited	Review. In accordance with	h FIFRA Section 3(c)(3)	
Osmose Wood Preserving, Inc. 980 Ellicott Street Buffalo, NY 14209	to:	duct is similar or identical in c	omposition and labeling	
Check if this is a new address Product Name				
	Section - II			
Amendment - Explain below. Resubmission in response to Agency letter dated	Final p	printed labels in temporare to by letter dated oo" Application.		
Notification - Explain below.	Other	- Explain below.		
Explanation: Notification of Alternate Brand Names per PR Notice 95-2. Alternative names: OSMOPLASTIC WOOD PRESERVING COMPOUND and TIMBERLIFE WOOD PRESERVING COMPOUND. This Notification is consistent with the provisions of PR Notice 95-2 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the Confidential Statement of Formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 95-2 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA. Section - III				
1. Material This Product Will Be Packaged In:		<u> </u>		
Child-Resistant Packaging Yes* No * Certification must be submitted Unit Packaging No If "Yes" Unit Packaging No. per Unit Packaging wgt.		Metal Plastic Glass		
3. Location of Net Contents Information 4. Size(s) Retail Container 5. Location of Label Directions On Label On Labeling accompanying product				
6. Manner in Which Label is Affixed to Product Lithograph Other				
	Section - IV			
1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)				
Name Teri Müchow	Title Adm. Assis Permitting &	Dog Affaira	nne Wo: (Include Area Code) -882-5905	
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment complete. (Stamped)				
2. Signature Ton Muchae	3. Tite Adm. Ass Permitting &	istant, Regulatory Affair	.	
4. Typed Name Teri Muchow	5. Date July 18	, 1996	6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	

DESCRIPTION

OSMOPLASTIC contains recognized salt preservatives used successfully in the art of wood preservation for more than forty (40) years. These coloriess salts penetrate deeply into the wood and give long-lasting protection against decay.

OSMOPLASTIC is designed for remedial treatment of in-service poles, piling, posts and other timber members. It may be applied by brush, trowel or pump.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Stir to an even consistency.

EXTERNAL TREATMENT: Apply at a rate of 1/16" to pole or imber exterior. Typical pole application is from 3" above to 18" pelow groundline and lower where deeper decay is suspected. Application on poles to be restored should extend the length of wrap-around type repair systems. Wrap treated area with water-proof bandage, OSMOSHIELD.

NTERNAL TREATMENT: For control of internal decay in poles and other timbers, holes may be drilled in areas of the pole or imber where protection is required. Fill decay pockets and oids using a grease gun or other pressurized applicator. Plug pplication holes with secure fitting dowels.

STORAGE AND DISPOSAL

TORAGE: Do not contaminate water, food or feed by storage disposal.

ISPOSAL: Completely empty bag into application equipment. nen dispose of empty bag in a sanitary landfill or by cineration, or, if allowed by State and local authorities, by ming. If burned, stay out of smoke.

ESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper sposal of excess pesticide, spray mixture, or rinsate is a plation of Federal Law. If these wastes cannot be disposed of use according to label instruction, contact your State sticide or Environmental Control Agency, or the Hazardous aste representative at the nearest EPA Regional Office for dance.

PHYSICAL OR CHEMICAL HAZARDS

not use, pour, spill or store near heat or open flame.

RESTRICTED USE PESTICIDE

DUE TO ONE INGREDIENT, CREOSOTE, WHICH IS LINKED TO CHRONIC TOXICITY IN ANIMAL STUDIES. For retail sale to and use only by Certified Applicators or persons under their direct supervision, and only for those uses covered by the Certified Applicator's certification.

GROUNDLINE TREATMENT FOR ALL STANDING POLES



OSMOPLASTIC

WOOD PRESERVING COMPOUND

ACTIVE INGREDIENTS:

Sodium Fluoride	44.42%
Creosote (P-7)	45.62%
Sodium Dichromate	
INERT INGREDIENTS:	6.76%
	100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Call a physician or poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching the back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

IF INHALED: Remove victim to fresh air. Apply respiration if indicated. Call a physician immediately.

IF ON SKIN: Remove contaminated clothing and wash affected area with soap and water. Get medical attention.

IF IN EYES: Flush eyes with plenty of water. Call a physician immediately.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS EPA Registration No. 3008-68 EPA Est. 3008-NY-1



Osmose Wood Preserving, Inc. 980 Ellicott Street Buffalo, NY 14209

NET CONTENTS: 5 Gailons (18.93 L.)

2022年第二届23年月末日**88年**8年8年8年2<u>年2年2年2月</u>

PRECAUTIONA HAZARDS TO HUMANS

DANGER: May be fatal if through the skin. Causes eye vapor crispray mist. Do not ge May cause severe burns. Was before eating or smoking. Do adequate ventilation.

Applicators must wear gloves in formulations (e.g. polyvinyl ac [PVC], or neoprene) in al situal expected (e.g., during the actual handling freshly treated wood).

Applicators must wear long impermeable apron during the all and all situation where dermal co

Work clothing must be chang contamination. Launder work c household laundry. Dispose of w shoes or boots in any general launder manner approved for pestic

Applicators must not eat, drink, or those parts of the application pro the wood treatment formulation. contact, and before eating, drinking using restrooms.

ENVIRONMENT

This pesticide is toxic to fish a effluent containing this product estuaries, oceans or public w specifically identified and address not discharge effluent to sewe notifying the sewage treatment prontact your State Water Board of

Do not apply directly to water, or to present or to intertidal areas belo Do not apply where runoff is likely water when disposing of equipments