

## Net Contents

# 123 ALGAECIDE

	Percentage by weight
Active Ingredient .....	1.0%
Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloride] .....	1.0%
Inert Ingredient .....	99.0%
Weight per gallon .....	8.36 pounds
Weight of active ingredient per gallon .....	0.084 pound

EPA REG. NO. 3837-43  
EPA EST. NO. 3837-MO-1

## CAUTION

### KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should be discharged where it will not drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only as directed on label.

Do not reuse empty drum. Return to drum conditioner or destroy by perforating or crushing and burying in a safe place.

## APPLICATION

123 Algaecide is used to control algae in recirculating commercial and industrial. Prior to its use, systems must be clear of growth, microbiological slime and other. slug addition of 62.3 to 152.2 fluid ounces per 1000 gallons of water to provide a concentration of 1 to 1190 parts per million of 123 Algaecide weight of water in the system is recommended dosage until control is evident. Subsequent dosing of 13.8 to 152.2 fluid ounces of 123 Algaecide per 1000 gallons of water (110 to 1190 parts per million of 123 Algaecide weight of water) should be employed every 2 to 5 days or as needed. Frequency of addition depends upon the relative amount of algae and the severity of the microbiological problem. Treatment should be made in the sump of water circulation.

MANUFACTURED BY

**LUBAR COMPANY**

1708 Campbell

Kansas

# ALGAECIDE

	Percentage by weight	
.....	1.0%	
.....	1.0%	
.....	99.0%	
.....	8.36 pounds	
.....	0.084 pound	
REG. NO. 3837-43		
T. NO. 3837-MO-1		

## CAUTION

### KEEP OFF REACH OF CHILDREN

Do not get in eyes. Avoid contact with skin. Wash with plenty of water for at least 15 minutes. If irritation persists, get medical attention. Do not eat, drink, or smoke.

Do not discharge into water bodies. Do not discharge into streams, ponds, or waterways. Do not discharge into water used for drinking. Do not discharge into water used for irrigation. Do not discharge into water used for fishing. Treated effluent should be discharged into lakes, streams, ponds, or waterways after treatment. Do not discharge into water used for drinking. Do not discharge into water used for irrigation. Do not discharge into water used for fishing. Use only as directed on label.

Do not discharge into water used for drinking. Do not discharge into water used for irrigation. Do not discharge into water used for fishing. Return to drum reconditioner or contact manufacturer for recycling information. Do not crush or bury in a safe.

## APPLICATION

123 Algaecide is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 62.3 to 152.2 fluid ounces of 123 Algaecide per 1000 gallons of water to provide a concentration of 490 to 1190 parts per million of 123 Algaecide based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 13.8 to 152.2 fluid ounces of 123 Algaecide per 1000 gallons of water (110 to 1190 parts per million of 123 Algaecide) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

MANUFACTURED BY

**LUBAR COMPANY**

1708 Campbell

Kansas City, Missouri 64108