

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

RECIRCULATING COOLING WATER SYSTEMS

BETZ Slimicide C-66 aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, commercial and industrial cooling towers, influent systems such as flow through, infilco units, filters, lagoons etc., industrial water scrubbing systems and brewery pasteurizers.

This product may be added to the systems either continuously or intermittently or as needed. The frequency of feeding and duration of the treatment will depend upon the severity of the problem.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

FOR CONTROL OF BACTERIA AND FUNGI INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add 2.9 to 7.3 fluid ounces to 1000 gallons of water in the system or 24 to 60 ppm. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is SUBSEQUENT DOSE: Continuously feed to evident, add 0.73 to 7.3 fluid ounces to 1000 gallons of water in the system or 6 to 60 ppm every 2 to 5 days or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 2.9 to 7.3 fluid ounces to 1000 gallons of water in the system or 24 to 60 ppm.

SUBSEQUENT DOSE: Continuously feed to maintain a dosage of 1.5 to 6.0 fluid ounces to 1000 gallons of water in the system or 12 to 50 ppm.

FOR CONTROL OF ALGAE INTERMITIENT OR SLUG METHOD

!N!TIAL DOSE: When the system is noticeably fouled, add 2.9 to 7.3 fluid ounces to 1000 gallons of water in the system or 24 to 60 ppm Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 0.73 to 7.3 fluid ounces to 1000 gallons of water in the system or 6 to 60 ppm every 2 to 5 days or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 2.9 to 7.3 fluid ounces to 1000 gallons of water in the system or 24 to 60 ppm

maintain a dosage of 1.5 to 6.0 fluid ounces to 1000 gallons of water in the system or 12 to 50 ppm.

(Directions for use continued on right panel.)

PRECAUTIONARY STA HAZARDS TO HUMAN DOMESTIC ANIM

CAUTION

HARMFUL IF SWALLOWED. eyes on skin or on clothing ing vapors or mist, Avoid sta and feed products.

ENVIRONMENTAL I

This pesticide is toxic to fi charge into lakes, streams, water unless in accordance permit. For guidance conta-Office of the EPA. Do not co by cleaning of container as disposal of wastes. Apply: as specified on this label.

> KEEP CONTAINER PROTECT FROM FI DO NOT STOR ELEVATED TEMPE

BIC745 8106



micide C-66

1000

eably ppm.

ed to ices to 12 to

ceably 1000 to 60

ntrol is > 1000 U ppm wintain

⊥:eably 1000 to 60

red to inces to ⊩ 12 to

panel.)

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC AN AALS

CAUTION

HARMFUL IF SWALLOWED. Do not get into eyes on skin or on clothing. Avoid breathing vapors or mist. Avoid storage near food and feed products.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge into lakes, streams, ponds or public water unless in accordance with a NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of container and equipment or disposal of wastes. Apply this product only as specified on this label.

> KEEP CONTAINER CLOSED PROTECT FROM FREEZING DO NOT STORE AT **ELEVATED TEMPERATURES**

Contents: LIQUID

Active Ingredient: Poly(oxyethylene(dimethyliminio) ethylene(dimethyliminio)ethylene dichloride\ 20.0% Inert Ingredients*: 80.0%

*Inart ingredients include solubilizing and dispersing agents

EPA Reg. No. 3876-141 WEIGHT PER GALLON OF PRODUCT 8.69 Pounds

KEEP OUT OF REACH OF CHILDREN CAUTION

STATEMENT OF PRACTICAL TREATMENT

In case of contact with skin, wash well with soap and water.

In case of contact with eyes, flush promptly and thoroughly with clear water for at least 15 minutes, Immediately contact physician.

If swallowed, drink promptly a large quantity of milk, egg whites gelatin solution, or if these are not available, drink large quantities of water Avoid alcohol. Immediately contact physician.

Immediately remove and wash contaminated clothing before reuse. Wash thoroughly after handling.

AIR WASHERS

BA for

D

st

h.

cí

51

T

n

ь

T€

For use only in industrial air washer systems that maintain effective mist eliminating components.

BETZ Slimicide C-66 controls slime-forming bacteria and fungi in industrial air washer systems. Add 7.5 to 18.3 fluid ounces to 1000 gallons of water in the system or 62 to 152 ppm depending upon the severity of contamination.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, add 11.1 to 18.3 fluid ounces Slimicide C-66 to 1000 gallons of water to the system or 92 to 152 ppm. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 7.5 to 18.3 fluid ounces to 1000 gallons of water in the system or 62 to 152 ppm every 2 to 5 days or as needed to maintain control.

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 11.1 to 18 3 fluid ounces Slimicide C-66 to 1000 gallons of water in the system or 92 to 152 ppm.

SUBSEQUENT DOSE: Maintain this level by pumping a continuous feed of 7.5 to 18.3 fluid ounces Slimicide C-66 per 1000 gallons of water in the system per day or 62 to 152 ppm.

BETZ Laboratories. Inc./TREVOSE, PENNSY



Corners . 635

Ingredent y oxyettyleneid metry min o yeneidimetry min ojettylene ionde, iogredentsi

Agent eigheig einig verlade, so vollende end dagens nig bigen s

FPA Peg 140 3876 (4) MICHI PER CALLON OF PRODUCT 860 Pounds

255%

80.5%

FEP OUT OF REACH OF CHILDREN CAUTION

TEMENT OF PRACTICAL TREATMENT

is of contact with skin, wash well with and water

 a of contact with eyes, flush promptly thoroughly with clear water for at least cinutes. Immediately contact physician.

wallowed, drink promptly a large quanof milk, egg whites, gelatin solution, or one not available, drink large quanof water. Avoid alcohol Immediately lact physician

rediately remove and wash contamiis dothing before reuse. Wash thoristy after handling

AIR WASHERS

For use on vilninguistra, air washer systems, that maintain effective mist eim hating camconents.

BETZ 3 micide. C-66 controls is me-forming porteriological fung in industrial air washer systems. Add 7.5 to 18.3 fluid cunces to 1000 gallors of water in the system or 62 to 152 pair depending upon the seventy of contamination.

INTERMITTENT OF SLUG METHOD

Itilitia. DOSE When the system is noticeably fooled, add 11.1 to 18.3 fluid ounces Slimicide C.66 to 1000 gailons of water to the system or 92 to 152 ppm. Repeat until control is achieved.

SUBSEQUENT DOSE When microbial control is evident, add 7.5 to 18.3 fluid cunces to 1000 gallons of water in the system or 62 to 152 ppm every 2 to 5 days or as needed to maintain control

BADLY FOULED SYSTEMS must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is noticeably fouled, add 11.1 to 18.3 fluid ounces Slimicide C-66 to 1000 gallons of water in the system or 92 to 152 ppm.

SUBSEQUENT DOSE- Maintain this level by pumping a continuous feed of 7.5 to 18.3 fluid ounces Slimicide C-66 per 1000 gallons of water in the system per day or 62 to 152 ppm.

20 NOV 1981 3876-/4/

BADLY FOULED SYSTEMS must be cleaned before treatment is begun

STORAGE AND DISPOSAL

Do not contaminate water faca or feesible storage or alsposal. Open aumping in pronibled. Do not reuse empty container

Pesticide or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfile approved for pesticides or buried in a safe place away from water supplies.

Triple rinse metal container or equivalent method before sending to drum conditioner or destroving by perforation or crushing and burying in a safe place. Do not reuse. Consult Federal, state or local authorities for approved alternative procedures.

Do not reuse empty plastic container. Triple rinse and incinerate or dispose of in a approved landfill or bury in a safe place, Consult Federal, state or local authorities for approved alternative procedures.

FOR INDUSTRIAL USE ONLY

Technical advice regarding specific site problems is available from BETZ.

NET WEIGHT AND VOLUME
As Marked on Container

SE, PENNSYLVANIA/U.S.A./19047