

bioMeT® Yellow Antifouling Paint No. 14122  
Antifouling Paint

KEEP OUT OF REACH OF CHILDREN!

DANGER!

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

Danger! Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes, or on clothing. Wear chemical worker goggles or full face shield. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. Avoid breathing spray mist when applying or dust from sanding old paint. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

5204-10.1

While spraying paint or sanding vessel surfaces, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get Medical Attention. Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage. If on skin: Wash with plenty of soap and water. Get medical attention if irritation persists: If in eyes: Flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL or CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Active Ingredients Tributyltin Fluoride....6.5%  
Inert Ingredients .....93.5%

E

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Commercial Use Only!

The product is intended for application to metal and fiberglass hulls to prevent algal, slime and macrofouling in marine service. The surface should be clean and dry and a suitable anticorrosive applied prior to application. One to two coats of biMeT<sup>®</sup> Yellow Antifouling Paint No 1412<sup>®</sup> applied by either spray (preferably airless) or rolling are required.

STORAGE AND DISPOSAL

Paint or cleanup solvent that cannot be used must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act. Waste paint containers should be triple rinsed (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

EPA Reg. No. 5204-18  
EPA Est. No. 5204-NJ-1