

bioMeT® 204 AF-14 Red
Antifouling Paint



KEEP OUT OF REACH OF CHILDREN!
DANGER!

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

Corrosive. Causes irreversible eye damage and skin irritation. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes, or on clothing. Wear chemical worker goggles or full face shield. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. Avoid breathing spray mist when applying or dust from sanding old paint. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

While spraying paint wear complete impervious protective clothing including rubber gloves, protective suit and a fullface air-supplied respirator jointly approved by the Mining Enforcement and Safety Administration (formerly U.S. Bureau of Mines) and the National Institute for Occupational Safety and Health under provisions of 30CFR11. Painters and other workers in the immediate vicinity must wear full protective clothing. Note that women of child bearing years should not be exposed to paint or paint residues during the use or removal of this product.

FIRST AID: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get Medical Attention. Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage. If on skin: Wash with plenty of soap and water. Get medical attention if irritation persists: If in eyes: Flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL or CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Active Ingredients: Triphenyltin Fluoride..10.9%
Tributyltin Fluoride....2.7%
Inert Ingredients86.4%

.....
.....
.....

DIRECTIONS FOR

It is a violation of the Clean Water Act to discharge this product in a manner inconsistent with the following directions.

For Use in Conjunction with the Application of the 204 AF 14 anti-fouling paint on fiberglass hulls in marine service. Not for sale to marina personnel. The product is a suitable anti-fouling paint for use on fiberglass hulls in marine service. Application can be by brush or spray. The spray is strong.

STORAGE AND DISPOSAL: Store in original container. Do not use for cleaning or disposal of paint. Dispose of according to local, state, and federal procedures. Do not use for cleaning or disposal of paint. Conservation of resources should be triplicated by recycling or reusing a sanitary land disposal procedures.

EPA Reg. No. 500.01-01
EPA Est. No. 500.01-01

JAN 10 1993
5204-69

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Use in Commercial or Navy Shipyards Only.

Not for sale to, use or storage by private applicators or marina personnel.

The product is intended for application to wood, metal and fiberglass hulls to prevent algal, slime and macrofouling in marine service. The surface should be clean and dry and a suitable anticorrosive applied prior to application.

Application can be by spray, brush or roller. Airless spray is strongly recommended. One to two coats of bioMeT[®] 204 AF 14 antifouling paint may be required.

STORAGE AND DISPOSAL

Paint or cleanup solvent that cannot be used must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act. Waste paint containers should be triple rinsed (or equivalent), then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

EPA Reg. No. 5204-60
EPA Est. No. 5204-NJ-1

ge and skin irritation. Harmful if absorbed through skin, in eyes, or on clothing. Wear chemical protective clothing such as gloves, long-sleeved clothing, and a respirator. Avoid breathing spray mist when applying or dust from sanding old paint after handling and before eating or smoking. Use

vious protective clothing including rubber gloves, a respirator jointly approved by the Mining (formerly U.S. Bureau of Mines) and the National Institute for Occupational Safety and Health. Note that women of child bearing years should avoid residues during the use or removal of this product.

a large quantity of milk, egg whites, gelatin or drink large quantities of water. Avoid alcohol. Probable mucosal damage may contraindicate the use of soap and water. Get medical attention if in eyes: Flush with plenty of water. Get medical attention if in eyes.

toxic to fish. Do not apply directly to water by spraying. Do not allow chips and dust generated during application of paint debris in an approved landfill.

Do not use or store near heat or open flame.

de..10.9%
e....2.7%
.....86.4%

JAN 10 1983
5204-60