

PENTA WOOD PRESERVATIVE O prevents dry rot - mildew - attack by termites, powder post beetles and carpenter ants.
Repels water - prevents splitting, checking and warping. Reduces swelling due to moisture absorption.

DIRECTIONS FOR USE

Use **PENTA WOOD PRESERVATIVE O** as it comes from the can. Wood must be free of bark, dry and well-seasoned. Always brush or spray two liberal coats. Soak two hours for lumber up to two inches thick. Heavier timbers and posts should soak overnight.

Not recommended for surfaces which are to be painted after treatment, use **PENTA WOOD PRESERVATIVE-R**.

WARNING

COMBUSTIBLE MIXTURE--KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. CONTAINS FUEL OIL & PENTACHLOROPHENOL. MAY CAUSE BURNS.

Do not get in eyes, on skin or clothing. Avoid breathing of vapors. If swallowed, call a physician immediately; do not induce vomiting. In case of contact, immediately remove all contaminated clothing including shoes, and flush skin for at least 15 minutes. For eyes, get medical attention. Wash clothes before reuse. Wear rubber gloves and protective clothing when handling the freshly treated lumber. Do not transfer contents to unmarked containers. Close tightly when not in use.

This product will kill fish and wildlife. Keep out of ponds, lakes and streams. Do not contaminate water by cleaning of equipment or disposal of wastes.

FULTON CHEMICAL COMPANY

Sumter, S.C. 29150



41-4002

Active Ingredients5.0%
Pentachlorophenol4.5
Related Chlorophenol0.5
Inert Ingredients95.0%

U.S.D.A. REG. NO. 5351-6

WARNING: HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN

See Warning on Back Panel.

LN 83

NET CONTENTS 1 GALLON

ACCEPTED
 6-3-71
 5351-6
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND RODENTICIDE ACT
 FOR ECONOMIC POISON REGISTRY
 ED UNDER NO. 5351-6
 TO ALLY OF CONSUMERS

PENTA WOOD PRESERVATIVE O prevents dry rot, mildew, attack by termites, powder post beetles and carpenter ants.

Repels water, prevents splitting, checking and warping. Reduces swelling due to moisture absorption.

DIRECTIONS FOR USE

Use **PENTA WOOD PRESERVATIVE O** as it comes from the can. Wood must be free of bark, dry and well seasoned. Always brush or spray two liberal coats. Soak two hours for lumber up to two inches thick. Heavier timbers and posts should soak overnight.

Not recommended for surfaces which are to be painted after treatment, use **PENTA WOOD PRESERVATIVE-R**.

WARNING

COMBUSTIBLE MIXTURE--KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. CONTAINS FUEL OIL & PENTACHLOROPHENOL. MAY CAUSE BURNS.

Do not get in eyes, on skin or clothing. Avoid breathing of vapors. If swallowed, call a physician immediately; do not induce vomiting. In case of contact, immediately remove all contaminated clothing including shoes, and flush skin for at least 15 minutes. For eyes, get medical attention. Wash clothes before reuse. Wear rubber gloves and protective clothing when handling the freshly treated lumber. Do not transfer contents to unmarked containers. Close tightly when not in use.

This product will kill fish and wildlife. Keep out of ponds, lakes and streams. Do not contaminate water by cleaning of equipment or disposal of wastes.

FULTON CHEMICAL COMPANY

Sumter, S.C. 29150



PENTA WOOD PRESERVATIVE O

41-4002

| | |
|----------------------------|-------|
| Active Ingredients | 5.0% |
| Pentachlorophenol | 4.5 |
| Related Chlorophenol | 0.5 |
| Inert Ingredients | 95.0% |

U.S.D.A. REG. NO. 5351-6

WARNING: HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF THE REACH OF CHILDREN

See Warning on Back Panel.

LN 83

NET CONTENTS 1 GALLON