

# Parade



**EXTERIOR INTERIOR USE**

U.S.D.A. Reg. No. 6354-4

6354-4  
73

# PENTA-TREAT

## WATER REPELLENT — WOOD PRESERVATIVE

### For All EXTERIOR - INTERIOR - WOOD SURFACES

**ACCEPTED**  
JAN 21, 1973  
UNDER THE FEDERAL  
FUNGICIDE AND  
FOR ECONOMIC PEST  
REGISTER.  
SUBJECT

ACTIVE INGREDIENTS:	
PENTACHLOROPHENOL.....	4.2%
OTHER CHLOROPHENOLS.....	.6%
TOTAL ACTIVE INGREDIENTS.....	4.8%
INERT INGREDIENTS.....	95.2%
TOTAL INGREDIENTS.....	100.0%

### WARNING:

**KEEP OUT OF REACH OF CHILDREN.  
HARMFUL OR FATAL IF SWALLOWED  
OR ABSORBED THROUGH THE SKIN.  
READ CAUTION ON BACK PANEL.**

NET 1 GALLON

**CAUTION — COMBUSTIBLE MIXTURE**  
**DO NOT USE, POUR, SPILL, OR STORE NEAR HEAT, OR OPEN FLAME.**  
**FIRE PERMIT No. U573152**

**WARNING!** Contains Petroleum Distillate. Causes skin irritation. Do not get in eyes, or skin, or on clothing. Keep contents and treated articles away from flame, food, and living plants.

**WARNING!** Vapors will cause injury if adequate ventilation is not insured. Do not use or mix this product indoors or in any other confined areas where the vapors may concentrate and cause injury to plant or animal life.

**ANTIDOTE:** External: Wash with soap and water.

Internal: If swallowed, force vomiting by drinking warm water mixed with a tablespoon of salt, milk, or egg white. Lie down and keep warm. Call a physician immediately.

**KEEP OUT OF REACH OF CHILDREN.**

## **PENTA-TREAT**

**PENTA-TREAT** is a superior water repellent wood preservative. When properly applied, Penta-Treat will retard swelling, warping and discoloration caused by the normal penetration of water into the wood.

**PENTA-TREAT** acts as an excellent first coat on bare wood surfaces as the initial coat in a three part system. Penta-Treat will inhibit future peeling and common paint problems. Controls grain raising and checking. Penta-Treat is very pale in color, leaving a superior surface for staining or painting.

When used as a preservative stain, mix one pint of color in oil, one quart Boiled Linseed Oil to three quarts of Penta-Treat. Stir thoroughly while using.

**PENTA-TREAT** prevents wood rot and attack of the wood by Woodborers, Beetles, Carpenter Ants. Penta-Treat is very effective against termites and will prevent damage by all common forms of fungi.

**PENTA-TREAT** is used indoors and outdoors for wood sash — doors — porches — posts — flooring — stairs — fences and boats.

**DIRECTIONS** — Penta-Treat must saturate the materials being coated. Fence posts, poles, foundation timbers, and heavy wood members should be free of bark, dry and well seasoned. In brush application, two or more liberal coats should be applied. Special care should be given to end grain where water most easily penetrates. Where practical, soaking is recommended. Doors and sashes should be soaked for 3 minutes. Structural members, joists and sub flooring — 30 minutes. Heavy materials, posts and all items in direct contact with the soil should be soaked 48 hours.

**PENTA-TREAT** is ready to use. For clean up, use Mineral Spirits. Coverage — 100 to 300 square feet per gallon. Wear protective clothing and rubber gloves when handling the freshly treated lumber. Do not reuse empty container. Wash thoroughly with water and detergent. Discard in a safe place away from water supplies.

This product is toxic to fish. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

*Nanke Aluminum Paint Co., INC.*

MANUFACTURERS

OFFICES AND FACTORY

FARMINGDALE, L. I., N. Y. 11735