

7313-8, (M-21)

305 159096 1/9  
17 4

MAR 31 1986

The Olympic Homecare Products Company  
c/o The Clorox Technical Center, PS & RCII  
7200 Johnson Drive  
Pleasanton, CA 94566

Attention: Ms. Virginia C. Lew

Gentlemen:

Subject: Olympic Semi-Transparent Weather Screen  
EPA Registration No. 7313-5  
Olympic Wood Preservative (Clear)  
EPA Registration No. 7313-6  
Olympic Wood Preservative (Green)  
EPA Registration No. 7313-7  
Olympic Solid Color Weather Screen  
EPA Registration No. 7313-8  
Your Submissions Dated September 6 and October 30, 1985

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, is acceptable subject to the comments listed below. Five copies of the finished labeling must be submitted.

1. Change the Precautionary Statement "Harmful or fatal if swallowed" to "May be fatal if swallowed" wherever it appears on the label.
2. Assure that the complete product name is used throughout the labels for each subject product or appropriate language, i.e., This product, in order to eliminate confusion between similarly named products referred to on the label.

88898:Jackson:J-4:KENCO:3/27/86:4/5/86:eg:VO

CONCURRENCES

SYMBOL	SURNAME	DATE						

3. Add "Statement of Practical Treatment" heading on each label along with associated precautionary statements and first aid procedures. This information block should follow the ingredient statement (see enclosed Attachment A for format guidelines). Also, move content statement to follow immediately after ingredient statement.
4. Storage and Disposal statement on proposed labeling of 55-gallon sized containers for products 7313-6 and 7317-7 is acceptable.

Sincerely yours,



Henry M. Jacoby  
Product Manager (21)  
Fungicide-Herbicide Branch  
Registration Division (TS-767C)

Enclosure

OLYMPIC SOLID COLOR WEATHER SCREEN - Center Panel

1 GALLON U.S. - 604090-2

RECEIVED  
10/30/85

SCJ

\*\*\*\*\*

OLYMPIC SOLID COLOR WEATHER SCREEN

PRESERVES WOOD BEAUTIFULLY

OLYMPIC<sup>R</sup>

SOLID COLOR

WEATHER SCREEN<sup>TM</sup>

PRESERVATIVE

OIL STAIN

REPELS WATER AND PRESERVES WOOD, LETS TEXTURE SHOW,

HIDES WOOD COLOR - FOR EXTERIOR WOOD SIDING, TRIM AND FENCES

MADE FROM NATURAL LINSEED OIL

KEEP OUT OF REACH OF CHILDREN

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

1 GALLON - 3.785 LITERS

ACTIVE INGREDIENTS

Bis(tributyltin)oxide. . . . .0.50%

Folpet[N-[(trichloromethylthio-phthalimide)]. . . .0.50%

INERT INGREDIENTS. . . . . 99.00%

TOTAL . . .100.00%

MEETS FED.SPEC.TT-W-572B 3.7

EPA Est.No.7313-WA-1,7313-IL-1,7313-KY-1

\*\*\*\*\*

PL/1:22

8/29/85

ACCEPTED  
with COMMENTS  
in EPA Letter Detail

MAR 31 1986

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

7313-8

OLYMPIC SOLID COLOR WEATHER SCREEN - Left Panel

1 GALLON U.S. - 604000-2

\*\*\*\*\*

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND

DOMESTIC ANIMALS

DANGER! CONTAINS MINERAL SPIRITS. KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. COMBUSTIBLE. Keep away from heat and open flame. Avoid contact with skin, eyes and clothing. Avoid breathing of vapors or spray mist.

Wear rubber gloves and protective clothing when applying or handling freshly treated lumber. USE ONLY IN WELL VENTILATED AREAS. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, nausea or dizziness, leave the area until symptoms cease. Do not drive, operate machinery or climb ladders while symptoms persist. Increase fresh air or wear properly fitted respiratory protection (NIOSH/MSHA TC-23C with an organic vapor cartridge) before resuming application. Do not drink alcohol while working with product.

FIRST AID: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. EYES: Immediately flush eyes with water and continue for at least 15 minutes. Call a physician. SKIN: Wash with soap and water. Remove and wash contaminated clothing before reuse.

to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water or wetlands. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. COMBUSTIBLE. Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

APPROXIMATE COVERAGE: On rough wood, 150 square feet per gallon; smooth wood, 250 square feet per gallon.

DRYING: *weather strip*  
OLYMPIC<sup>®</sup> Preservative Oil Stain will require 24 to 48 hours to dry under ideal conditions.

CLEANUP: Clean brushes and other tools with mineral spirits.



5/1

OLYMPIC SOLID COLOR WEATHER SCREEN - Left Panel, Continued

1 GALLON U.S. - 604000-2

\*\*\*\*\*

LIMITED WARRANTY: If, after proper surface preparation and proper application in accordance with label directions, this product is shown to be defective within one year of the date of purchase, Olympic, at its option, will either replace the product or refund its purchase price. Contact your Olympic dealer to make a claim under this warranty. You must supply proof of purchase.

Proper surface preparation is essential to the applicability of this warranty. Read and follow the label instructions.

Labor costs are not covered by this warranty. Cracking, peeling or blistering caused by inadequate ventilation or the breakdown of the underlying surface or previous paint film are also not covered by this warranty.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

THE OLYMPIC HOMECARE PRODUCTS COMPANY

2233 112th Ave. N.E., Bellevue, WA 98004

MADE IN U.S.A.

c 1985 The Olympic HomeCare Products Company

OLYMPIC SOLID COLOR WEATHER SCREEN - Right (of Center) Panel

1 GALLON U.S. - 604000-2

\*\*\*\*\*

DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of federal law to use this product in a manner inconsistent with its labeling.

OLYMPIC<sup>R</sup> ↑ Preservative Oil Stain is a penetrating, linseed oil base solid color stain with WEATHER SCREEN<sup>TM</sup> additives to repel water and preserve wood.

OLYMPIC<sup>R</sup> ↓ Preservative Oil Stain exceeds the Federal specification for water repellency, TT-W-572B Paragraph 3.7.

FOR EXTERIOR USE ONLY. Use on bare redwood, cedar, mahogany and Douglas fir which may be exposed to attack by wood rot, mildew or excess moisture.

OLYMPIC<sup>R</sup> ← *Latex Stain* Preservative Oil Stain preserves wood. To maintain wood preservation properties, reapplications are recommended every 3 to 5 years.

Apply Preservative Oil Stain to wood siding, shakes, shingles, fascia, trim and fences. For solid color stain application to southern yellow pine, two coats of OLYMPIC<sup>R</sup> Latex Stain are recommended. Where a solid color finish is desired when recoating, use OLYMPIC<sup>R</sup> Latex Stain or Overcoat<sup>R</sup>.

DO NOT USE ON HORIZONTAL SURFACES SUCH AS DECKS, PORCHES, RAILINGS, STEPS, PATIOS OR OUTDOOR FURNITURE. Use OLYMPIC<sup>R</sup> Semi-Transparent Preservative Oil Stain on horizontal surfaces. To protect and preserve wood before painting or on structural lumber, timbers, millwork or roofs use OLYMPIC<sup>R</sup> Wood Preservative Clear. Use OLYMPIC<sup>R</sup> Wood Preservative Green on wood used below ground or in contact with water. For severe exposure to wood rot, "pressure treated wood" offers maximum protection.

OLYMPIC SOLID COLOR WEATHER SCREEN - Right Panel, Continued

1 GALLON U.S. - 604000-2

\*\*\*\*\*

**SURFACE PREPARATION:** Proper surface preparation is essential for satisfactory results. All surfaces must be clean, dry and free of mildew. Remove all dirt, dust, oil, soot or other contaminants by washing with a detergent solution. Rinse thoroughly and allow to dry completely before staining.

Remove mildew by scrubbing the surface with this solution: 1 cup non-ammoniated detergent and 1 quart household bleach dissolved into 3 quarts water. (CAUTION: Household bleach is a potentially harmful material. Follow manufacturer's precautions. Use protective clothing, eye goggles and good rubber gloves.) Rinse thoroughly with clear water and ~~depending on the severity,~~ <sup>if mildew remains,</sup> apply a <sup>second</sup> solution of 50% household bleach and 50% water. Rinse and allow this final treatment to dry before staining.

**STAIN PREPARATION:** THOROUGH MIXING IS ESSENTIAL. Pour top oils into another can and stir the remaining pigment thoroughly. Pour the oil back into the can and mix. Pour from one can to another several times to ensure the pigments are mixed. When using more than one container, use only two-thirds of one can and then intermix with stain from the next can to assure an equal balance of pigment and oil. 'STIR REGULARLY DURING USE. DO NOT THIN.

**EXTRACTIVE BLEEDING:** Some woods contain water soluble colorings or extractives that tend to "bleed" to the surface. This bleeding may be unsightly but is not damaging to the finish. If it has occurred, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water. For stubborn stains, a <sup>second</sup> solution of 50% alcohol and 50% water may be necessary.



OLYMPIC SOLID COLOR WEATHER SCREEN - Right Panel, Continued

1 GALLON U.S. - 604000-2

\*\*\*\*\*

APPLICATION: OLYMPIC<sup>R</sup> *Weather Screen* Preservative Oil Stain is best applied with a natural bristle brush. Thoroughly stain ends and edges of boards. To help avoid lap marks, stain only a few boards at a time, working from top to bottom or from side to side keeping the leading edge "wet". Roller applications should be limited to rough surfaces.

FOR ADDITIONAL INFORMATION - ASK YOUR DEALER OR REFER to the  
*Olympic Information Manual*

604000-2