U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460

PA REGISTRATION NO. 79**95-51** 

DATE OF ISSUANCE

TERM OF ISSUANCE

JUL 29 1985

NOTICE OF PESTICIDE: REGISTRATION REREGISTRATION

(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT

Alumanacket 17 Alue

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

L

Rule Paint & Chemical Co. Cape Ann Industrial Fack Gloudester, MA 01930

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

for the content of a positive manager and the contract was a first and the content of the conten The Physical Physics of the Principles William

- 1. Comput and for outer all call one alone and teat remodification, rerequistration or your product until PDEA los. 3(c) (b) With the Adency requires att constrant of the amiliar crosses to the established cars.
- Bare the for line during a percentic with the velocity are the product for diagness.
  - And the phrasic "EPA bear trate of No. 1995-5 ."
  - It the "Procant whaty Statements"

Deleve the phases: "May be dermal sensitizer," or submat data which indicate that the dischart cases, this reaction.

Expand to contine Thear protective obething, e.g., gioves, hat, chart, pants" to a "Near protection of othing such as force operation best, which tanks, was and glocos."

Expand the sen once "West torroughly after us, and before eatime or smoking" to "Wash thoroughly with soan and water after handling. Pemca contrainst of cloths we and wash before rouse."

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

EPA Form 8570-6 (Rev. 5-76)

PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

BEST AVAILABLE COPY

Add the phrase "Do not get in eyes or on clothing" after the words "Corrosive, causes skin burns."

- c. The words "Active Ingredients and Inert Ingredients" must be given equal prominence and they must be of the same type size. Use the words "Inert Ingredients" for "Inert."
- d. The preferred declaration for the first active ingredient should be: "Tributyltin fluoride," note the spelling of word "fluoride."
- e. The substatement to the second active ingredient should be enclosed in parenthesis: (As part of a polymer). Replace the word "copolymer" with "polymer."
- f. The label should bear a statement below the ingredient statement "Contains petroleum distillates."
- 3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with PIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

John H. Leey, Product Manager (31)

Disinfectants Branch

Registration Division (TS-767c)

#### Enclosure

RD/DIS: JOB: 91178:Lee: RD: 85/34: Kendrick&Co: 898-1270: 6/10/85: Del: 6/18/85: DKD

Gloucester

Marine Paints

Alumajacket 517 Blue

517 Blue ONE U.S. QUART 946 ML

ACCEPTED
with COMMENTS
in EPA Letter Dated:

ACTIVE INGREDIENTS
Tri-n-butyltin Flouride 2.54%
Tributyltin Methacrylate 12.12
as part of a Copolymer
Inert 85.34
Total 100.00%

JUL 2.9 1985
Under the Federal Insecticide.
Functional and Rodenticide Act

Fungicide, and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

### DANGER

Keep out of reach of children. See back panel for additional precautionary statements.

Gloucester Aluminum Boat and Outdrive Anti-Fouling Bottom Paint This product is an anti-fouling protective paint, resistant to algae, barnacles and other marine fouling.

It is a one-part epoxy-based Tri-n-butyltin Flouride paint designed specifically to solve the problems of electrolysis between copper ingredients and aluminum. While formulated for aluminum boats and outdrives, it is fully as effective and useful on fiberglass and wood.

Directions for Use
It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Aluminum: Bare aluminum should be cleaned and degreased with Gloucester #551 Epoxy Thinner & Cleaner, lacquer thinner, or other suitable product. Wipe dry. Sand with 80-grit mandpaper. Immediately apply Gloucester #414 Wash Primer mixed with Activator per label instructions.

On previously painted surfaces, may be applied over itself or most hard anti-fouling paints. Test a small area for compatibility. Before application sand old finish lightly with 80-grit paper. ...

Aluminum Outdrives: Follow directions above. May be applied overmost factory finishes.

BEST AVAILABLE COPY

Under the 4 control to extende Entre a reduction of the Ar

as any select, for the pesticite regeleses ander EPA Reg. No.

Fiberglass: New fiberglass must be dewaxed. Gloucester #551 Thirmer & Cleaner is recommended for this purpose. Lacquer Thinner or other suitable solvent may be used. Sand With 80-grit sandpaper and prime with Gloucester B370 Epoxy Primer.

On previously painted surfaces, check for compatibility. Sand with 80-grit sandpaper. Old paints in poor condition should be stripped. Proceed as for new fiberglass.

Wood: New wood and previously painted bottoms need only be properly sanded. Apply three coats. The first coat may be reduced with no more than 10% Gloucester #551 Thinner & Cleaner.

# Application Information

Stir thoroughly. Allow overnight drying between coats and before launching. Two costs are recommended for best results. short-nap roller or brush. Use only Gloucester #551 Thinner & Cleaner if thinning is necessary. Also use for cleaning brushes and equipment. Recommended application temperature is 65°-85°F. Application in temperatures below 60° F will unduly extend cure time. Average coverage is 250 sq. ft./gal.

## Maintenance

Since man-made and natural pollution can reduce the effectiveness of all anti-foulant paint, it is recommended that the bottom paint be checked from time to time, and lightly scrubbed with a soft material.

## STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage in disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rerisate is a violation of Federal law. If these wastes cannot be disposed of according to label instructions, contact your State Pe ticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA regional office for guidance. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture of and dispose of in a sanitar ' landfill, or by other procedure approved to hard of by state and local authorities. Store in original tightly scaled container. JUL 29 1985

PRECAUTIONARY STATEMENTS Hazards to Humans and Domestic Animals.

Use only with adequate ventilation. Corrosive; causes skin burner, May be dermal sensitizer. Wear protective clothing, e.g., gloves, hat, shirt, and pants. Causes irreversible eye damage and burns. May be fatal if swallowed or inhaled. Harmful if absorbed through skin. Do not breath vapors or spray mist. Wash thoroughly after use and before eating or smoking. When used in enclosed areas while spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the katiqual Institute for Occupational Safety and Health. Wear goggles, face shield, or safety glasses.

1 - Jan - Marine Marin

Practical Treatment. If swallowed, promptly drink a large quantity of milk, egg whites, gelatin solution, or if not availabel, drink large quantities of water. Avoid alcohol. Get medical attention. Note to M.D.: probable mucosal damage may contraindicate the use of gastric lavage. If in eyes, flush eyes with water. Get medical attention. If on skin, wash with scap and water. Get medical attention. If inhaled, remove victim to fresh air. If not breathing, give mouth-to-mouth respiration. Get medical attention.

# ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARD

FLAMMABLE. Do not use or store near heat or open flame.

ACCEPTED
with COMMENTS
in EPA Lotter Datest

E.P.A. Registration #7995-E.P.A. Est. #7995-MA-1

JUL 29 1985

Rule paint and Chemical, Inc. Gloucuster, Massachusetts 01930 U.S.A.

Rule Registered Trademark

Under the last of harms le. Fungassie is in mentione act as amended for the pesticide regimered under EPA Reg. No.