



May be fatal er material. Avoid car contact, immediate least 15 minutes. breathing dust. Co Moisture contamina chlorine-containing container closed an not re-use contained

EXTERNAL: Immedi

INTERNAL: Feed br

or cooki Call a 1

Manufa

560..

WARNING

May be fatal or harmful if swallowed. Strong oxidizing material. Avoid contact with skin, eyes or clothing. In case of contact, immediately flush skin or eyes with cold water for at least 15 minutes. For eyes get medical attention. Avoid breathing dust. Contact with organic matter may cause fire. Moisture contamination may liberate irritating and hazardous chlorine-containing gases. Keep away from open flame. Keep container closed and in a cool dry place when not in use. Do not re-use container. Destroy when empty.

POISON - ANTIDOTE

EXTERNAL: Immediately flush with plenty of cold water.

INTERNAL: Feed bread soaked in milk followed by olive oil or cooking oil.

Call a physician.

U.S.D.A. Reg. No. 9556 - 10

Manufactured for

Ortex Products Inc.

560 Ferry St., Newark, N. J. 07105

The purpose of Algae Pool Shock is to provide urgent and immediate treatme of pool water when the following conditions exist:

- Green colored water due to algae growth
- Visable argae clinging to floor & sides
- Water with cloudy conditions
- Freshly tilled pools that are green or brown due in minerals.
- Treatment of previous season's water
- Periodic shock treatment as regular maintenance

DIRECTIONS

- Remove any foreign debris in the water.
- 2. Adjust pH of water to 7.2 & 7.8 with the use of a test kit.
- 3. With filter running, sprinkle Algae Pool Shock in the deepest part of the pool at the rate of 1 1b. for each 8,000 gailons of water which will provide 10 ppm chlorine. It is possible for some of the granules to reach the bottom of the pool before completely dissolved, it is then recommended that the floor of the pool be brushed for at least 10 to 15 minutes to prevent possible bleaching of the liner or painted surface. As an occasional shock treat, Algae Pool Shock could be applied through the skimmer, but is not recommended as a regular maintenance application.
- 4. Allow filter to run continuously and watch for build-up of dead algae in filter which will require repeated backwashing. If your condition is not corrected during the first 24 hours, repeat dosage on second day. If there is not improvement on the third day, consult there is not improvement on the third day, consult your dealer for additional advice. Resumb regular chlorine dosage when chlorine residual reads 1 & chlorine dosage when chlorine residual reads 1 & 2 ppm on your test kit.