

walling

Phone 605/336-6710

P.O. Box 408

Sioux Falls, So. Dak. 57101

A-160

LOW FOAM WATER TREATMENT FOR BUILDING AND INDUSTRIAL COOLING TOWERS

COMPOSITION

	Percent
Active ingredients	
Diocetyl dimethyl ammimum chloride	50
Ethyl alcohol	10
Inert ingredients	40
Weight per gallon	7.98 lb.
Weight of active ingredients per gallon	3.99 lb.

APPLICATIONS

Walling A-160 is used to inhibit the growth of algae in recirculating commercial and industrial cooling water systems. Before treatment with Walling A-160 systems must be free of microbiological slime, and other deposits. Then the system should be treated with an initial slug addition of 16 to 21 fluid ounces of Walling A-160 per 1,000 gallons of water. Subsequent slug additions of 6 to 9 fluid ounces of Walling A-160 per 1,000 gallons of water should be made every 1 to 5 days or as needed. Dosage depends on the relative amount of bleedoff and the severity of the microbiological problem. Slug additions of Walling A-160 should be made to the sump of water circulation.

DANGER — KEEP OUT OF REACH OF CHILDREN

Keep Out of Reach of Children. Corrosive. Causes severe eye and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves. Do not swallow. Avoid contamination of food. Do not use, pour, spill or store near heat or open flame.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution; or if these are not available, drink large quantities of water. Avoid alcohol. Call physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and coma.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment.

Apply this product only as specified on this label.

EPA Reg. No. 11659-9