

Nutmeg Chemical Co.

WATER SPECIALTIES DIVISION

ACCEPTED NEW HAVEN, CONNECTICUT
NOV 19 1975
NUTMEG NC-151
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
UNDER NO. 20375-10

COMPOSITION

	Percent by weight
ACTIVE INGREDIENT	85 percent
Sodium 2, 4, 5 – Trichlorophenate	85 percent
INERT INGREDIENTS	15 percent

APPLICATION

Nutmeg NC-151 is used to control fungal and bacterial-induced slimes in industrial recirculating cooling water systems. Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. Badly fouled systems must be cleaned before treatment is begun. Initial NC-151 dosage would be 0.425 to 0.85 pounds of NC-151 per 1,000 gallons of water in the system. This dose may be repeated as needed to obtain control, then apply 0.425 pounds of NC-151 per 1,000 gallons of water in the system weekly, or as needed. NC-151 should be applied at a point in the system where the product will be uniformly mixed.

DANGER

KEEP OUT OF THE REACH OF CHILDREN

CORROSIVE — CAUSES EYE BURNS — MAY PRODUCE SEVERE BURNS.

Do not get in eyes, on skin or on clothing. Protect eyes and skin when handling. Harmful or fatal if swallowed, inhaled or absorbed through skin. Do not breathe dust.

FIRST AID: In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention. In case of skin contact, wash with soap and plenty of water. Wash contaminated clothing before re-use. If swallowed, induce vomiting by sticking finger down the throat or by giving an emetic such as 2 tablespoons of salt in a glass of warm water. Call a physician.

NOTE TO PHYSICIAN: THE

COMPOSITION

	Percent by weight
ACTIVE INGREDIENT	85 percent
Sodium 2, 4, 5 – Trichlorophenate	85 percent
INERT INGREDIENTS	15 percent

APPLICATION

Nutmeg NC-151 is used to control fungal and bacterial-induced slimes in industrial recirculating cooling water systems. Begin treatment when the system is in jeopardy of becoming affected or after cleaning systems whose efficiency is already impaired. Badly fouled systems must be cleaned before treatment is begun. Initial NC-151 dosage would be 0.425 to 0.85 pounds of NC-151 per 1,000 gallons of water in the system. This dose may be repeated as needed to obtain control, then apply 0.425 pounds of NC-151 per 1,000 gallons of water in the system weekly, or as needed. NC-151 should be applied at a point in the system where the product will be uniformly mixed.

DANGER

KEEP OUT OF THE REACH OF CHILDREN

CORROSIVE – CAUSES EYE BURNS – MAY PRODUCE SEVERE BURNS.

Do not get in eyes, on skin or on clothing. Protect eyes and skin when handling. Harmful or fatal if swallowed, inhaled or absorbed through skin. Do not breathe dust.

FIRST AID: In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention. In case of skin contact, wash with soap and plenty of water. Wash contaminated clothing before re-use. If swallowed, induce vomiting by sticking finger down the throat or by giving an emetic such as 2 tablespoons of salt in a glass of warm water. Call a physician.

NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

Do not re-use empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies.

This product is toxic to fish and wildlife. Do not contaminate water by cleaning of equipment or disposal of wastes. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Apply this product only as specified on this label.