

N.Y.F.D. C. of A. No.

CAUTION: COMBUSTIBLE MIXTURE

Do not use or store near heat or open flame.

3C STAIN AND WOOD PRESERVATIVE

For all exterior and interior stain uses. 3C Brand Stain and Wood Preservative brings out the beauty of wood grains and protects wood from warpage, rot and mildew discoloration.

3C Stain available in Redwood, Brown, Grey and Green colors. For Natural Finish use 3C Clear Wood Preservative and Water Repellent.

- Durable, natural pigment resists fading.
- Water repellent additive enhances the resistance to water absorption.

IMPORTANT NOTICE TO PURCHASERS: Since the conditions attending our customers' use of our materials are beyond our control, no guarantee or warranty, express or implied, is made as to such use, or effects incidental to such use, handling or possession. We in no event assume liability for any damages beyond the purchase price of the materials furnished by us, and we will replace any part of such materials which shall be returned to us within fifteen days after delivery, and provided our examination shall disclose that the material is defective. No representative of ours has authority to change this provision which relates to all sales.



WATER REPELLENT

PRESERVATIVE

WOOD STAIN GRAY

**ADDS BEAUTY TO WOOD • REPELS WATER
MILDEW & ROT RESISTANT**

EPA Reg. No. 25579-3

WARNING:

Keep out of reach of children
Combustible Mixture
Do not use near heat or open flame
See other details on back

ACTIVE INGREDIENTS:
bis (tributyltin) oxide 0.30%
INERT INGREDIENTS: 99.70%
Total 100.00%

Contents 32 FL OZ (1 QT.)

DIRECTIONS:

Thoroughly stir contents of can before using and stir occasionally during use. Do not apply below 40°F. Apply heavy coating with brush or roller. A second coat may be applied if necessary, after 2 hours. Siding and millwork may be dipped for deep penetration. (3-5 minutes dipping time.) Since the color varies on different types of wood, a test brush-out is suggested before proceeding with either the first or second coats. Clean brush and roller with mineral spirits or paint thinner. Coverage 200-400 sq. ft. per gallon. Textured woods give lowest coverage.

WARNING:

Harmful if swallowed or absorbed through the skin. Avoid inhaling vapor or spray. Avoid contact with eyes. If stain is splashed into eyes or on skin, flush with water at once. Call physician (for eye checkup). Wash hands after using each hour with soap and water. Wash clothing before reuse if contaminated with stain.

Crush empty can and properly discard. Do not contaminate natural waters or plants.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

KEEP OUT OF REACH OF CHILDREN.

MANUFACTURED BY

3C COMPANY

DIVISION OF
CONTINENTAL CHEMICAL
AND COATINGS CORP.
WOBURN, MA 01801

FOR USE ON FENCES • SHUTTERS • SILLWORK

AND OTHER INTERIOR MILLWORK



ACCEPTED
JUN 27 1971
UNDER THE FEDERAL
FUNGICIDE AND RODENT
FOR ECONOMIC PESTICIDE
ED UNDER FEDERAL
TO ATTACHED COM

WOOD STAIN

GRAY

WARNING

EPA Reg. No. 25579-3

WARNING:

Keep out of reach of children
Combustible Mixture
Do not use near heat or open flame
(See other details on back)

ACTIVE INGREDIENTS:
bis (tributyltin) oxide 0.30%
INERT INGREDIENTS: 99.70%
Total 100.00%

Contents: 32 FL. OZ. (1 QT.)