


Reg # 39492-28

PM-31

132

ONE U.S. GALLON



# NAVICOTE<sup>®</sup> ANTI-FOULING

KEEP OUT OF REACH OF CHILDREN  
**WARNING**

SEE SIDE PANEL FOR PRECAUTIONARY STATEMENTS

**BEST AVAILABLE COPY**

**ACCEPTED**

JUL 26 1982

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 39492-28



ACTIVE INGREDIENTS	
Cuprous Oxide..	38.46%*
INERT	
INGREDIENTS ..	61.54%
	<hr/>
	100.00%

\*Equivalent to 34.1%  
Metallic Copper

**CONTAINS  
PETROLEUM DISTILLATES**

**NAVICOTE<sup>®</sup> 1000  
PERMANENT RED ANTI-FOULING PAINT**

**MD-3606**

**PRECAUTIONARY STATEMENTS**

**WARNING**

**HAZARD TO HUMANS AND DOMESTIC ANIMALS**

Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear a face shield and rubber gloves when handling. Use in a well ventilated area. When used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if swallowed or inhaled. Do not breathe vapors or spray mist.

**PRACTICAL TREATMENT**

In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get medical attention. If swallowed, do not induce vomiting. This product contains petroleum distillates. Get medical attention. If in eyes, immediately flush with plenty of water. Get medical attention.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**CHEMICAL AND PHYSICAL HAZARDS**

Do not use or store near heat or open flame.

**NAVICOTE® 000 ANTI-FOULING PAINT**

**Directions for Use**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Navicote Anti-Fouling Paint -- for application to the underwater areas of fiberglass, wood aluminum and steel vessels subject to fouling by barnacles, algae, tube worms and other fouling organisms. When boat is hauled, remove any fouling and all loose, old paint with a scraper or wire brush. When sanding, do not breathe dust - wear a dust mask. Scrub hull with a stiff fiber brush and wash down with fresh water. All surfaces must be free of marine growth, loose old paint, moisture, grease, oil or dirt before paint is applied. Mix paint thoroughly before using and stir from time to time during application. Apply one or two coats allowing four hours dry time between coats. Paint is furnished at brushing viscosity and should not be thinned for brush or roller application. For spraying, thin, if necessary, up to 5% with #1 Solvent, MD-174. Do not add oil or varnishes to this paint. Wear appropriate NIOSH approved respirators during spray application. Protective clothing, rubber gloves and goggles should be worn during application. Contaminated clothing should be laundered before reuse. Clean up with #1 Solvent, MD-174. Launching may be accomplished as soon as coating is dry, or later if desired.

**FIBERGLASS HULLS**

Roughen surface and apply two coats Navicote Anti-Fouling Paint as above. Gelcoat should be weathered one full season before first painting.

**WOOD HULLS**

Clean and sand thoroughly and apply two coats Navicote Anti-Fouling Paint as above. On new wood, after proper filling of seams and thorough sanding, apply two coats, thinning the first coat approximately 5% for good penetration.

**STEEL AND ALUMINUM HULLS**

Do not apply directly to metal surfaces. A suitable barrier coat must be applied prior to application of anti-fouling paint. When repainting an existing system in good condition, clean thoroughly, sand lightly, and build up any bare spots with anti-corrosive. Apply two coats Navicote Anti-Fouling Paint as above.

**STORAGE AND DISPOSAL**

Do not contaminate water, food or feed by storage or disposal. Pesticide Disposal - Anti-Fouling paint or rinsate that cannot be used according to label directions must be disposed of according to Federal, State or local procedures under the Resource Conservation and Recovery Act. Container Disposal - Triple rinse (or equivalent) and dispose of in a sanitary landfill or by other approved State and local procedures.

**DEVOE MARINE COATINGS CO.**

Louisville, Ky. 40207

Division of CROW GROUP, INC.

MADE IN U.S.A.

**BEST AVAILABLE COPY**