## **BLANCO FOGASOL**

### KILLS EXPOSED ROACHES, ANTS, TICKS, FLEAS, SPIDERS, SCORPIONS

TREATS UP TO 10,000 CUBIC FEET

Entire contents released from one spot. Fog penetrates throughout the area.

**ACTIVE INGREDIENTS:** 

2,2-Dichlorovinyl dimethylphosphate	0.47%
Related compounds	0.03%
INERT INGREDIENTS	99 50%

# KEEP OUT OF REACH OF CHILDREN

**CAUTION** 

See Additional Precautionary Statements

on Back Panel

ACCEPTED 40018-9 FEB 2 3 1981

BLANCO CHEMICAL HOUSTON, TX. 77090

**NET WEIGHT 12 OUNCES** 

EPA Reg. No. 40018-9

EPA Est. 40018-TX-1

#### **FOGASOL**

#### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS & DOMESTIC ANIMALS CAUTION

Harmful if swallowed. Avoid broathing of mist, Avoid contact with eyes. Avoid contact with skin. Wash hands after handling. Do not contaminate feed, water or foodstuff. Food should be removed or covered during treatment. Do not use in edible product areas of food processing plants, restaurants or other areas where food is commercially prepared or processed. Do not use in serving areas while food is exposed

#### PHYSICAL OR CHEMICAL HAZARDS

Contents Under Pressure. Do not puncture or incinerate container or throw into fire. Exposure to temperatures above 130° F may cause bursting

#### FOR USE ONLY WHEN BUILDING IS VACATED BY HUMANS AND PETS

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Use at least one canister for each 10,000 cubic feet of unobstructed area. Use additional units for remote rooms or where free flow of mist is not assured.

IMPORTANT:

Locate fogger in center of room or area being treated. Place newspapers under fogger unit and for 3 or 4 feet around the can to prevent staining or marring of surfaces. Close doors and windows. Remove pets. Cover exposed foods and dishes. Open cabinets and doors to areas being treated. Shut off fans and eir conditioners. Pirt out all open flames except pilot light. Place at least 6 feet away from pilot light. Keep at arms length when releasing. Point top of can away from face and eyes. To start fogging action, press plastic tob on valve down until it clicks. Set in upright position and leave the building at once, Leave undisturbed for at least 2 hours. Open doors and windows and allow to

Sowents may soften some asphalt or synthetic tile floors. If used directly over asp halt or synthetic tile, newspaper should be spread on the floor for several feet around the area of release. Do not use with freshly waxed floors; allow wax. to become hardened. Some plastics may be affected. Remove or cover plastic dems such as eyeglasses, stereo covers, notion boxes.

DISPOSAL: Do not reuse empty container. Wrap container and put in