

Tower Power 3008

ACTIVE INGREDIENTS

Disodium cyanodithioimide carbonate 7.26% 3.68%

Potassium N-methylthioacetamide 5.07%

INERT INGREDIENTS

91.25%

TOTAL

100.00%

This product contains 2.77 lb. of active ingredients per gallon and weighs 8.81 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

WARNING

PRECAUTIONARY STATEMENTS HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes eye damage and irritation. Do not get eyes, on face, or on clothing. Wear goggles, or face shield and rubber gloves. Wash thoroughly. Harmful or fatal if swallowed. Avoid contact with skin and hair.

FIRST AID: In case of contact immediately flush eyes with copious amounts of water for at least 15 minutes. If eye irritation persists, consult a physician. If irritation continues before reaching a physician, call the National Poison Center. Drink 1 or 2 glasses of water and spit out. Do not induce vomiting. If on throat or in lungs, do not expectorate. Do not breathe vapors. May be fatal if inhaled by conscious person.

ENVIRONMENTAL HAZARD: This product is highly toxic to aquatic life. Do not discharge into lakes, streams, or other bodies of water. Do not discharge into an NPDES permit discharge area. Do not discharge into ground water.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Tower Power 3008 is used to control algae and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 6.9 to 13.9 fluid ounces of Tower Power 3008 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 2.3 to 13.9 fluid ounces of Tower Power 3008 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

STORAGE AND DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinsate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides, or buried in a safe place away from water supplies.

CONTAINER DISPOSAL:

METAL: Triple rinse (or equivalent) and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place. Containers over 30 gallons should be resealed before offering for reconditioning.

PLASTIC: Containers under 30 gallons must not be reused but should be triple rinsed and disposed of in an incinerator or landfill approved for pesticide containers or buried in a safe place. Containers over 30 gallons are to be resealed and offered for reconditioning or triple rinsed (or equivalent) and offered for re-use, reconditioning, or disposal in an approved landfill or buried in a safe place.

GENERAL: Consult Federal, State, or Local disposal authorities for approved alternative procedures.

Manufactured by

Wolcott Inc.

P.O. Box 1315

War Rock, AR 72205

EPA REG. NO.