

1663

5454-1

54554-1

(VERTICAL PLANK)
(WOOD GRAIN GROUND)
FRONT PANEL

ACCEPTED
NOV 19 1986
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 54554-1

WOOD PRESERVATIVE
AND SEALER
450
CLEAR

KEEP OUT OF REACH OF CHILDREN

WARNING


See side panel for additional precautionary statements.

ACTIVE INGREDIENTS
2-Iodo-2-Propynyl Butyl Carbamate 0.50 %
INERT INGREDIENTS _____ 99.50 %
TOTAL _____ 100.00 %

Contains Petroleum Distillates

1 GALLON 3.785 LITERS

EPA REG NO. 54554-
EPA EST NO. 54554-CA



206-5

(

PRECAUTIONARY STATEMENT
HAZARDS TO HUMAN AND DOMESTIC ANIMALS

WARNING: CONTAINS PETROLEUM DISTILLATES. Use only with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Harmful if swallowed. Causes substantial but temporary eye injury. Do not get in eyes, on skin or on clothing. Wear goggles and rubber gloves when handling, and rubber gloves and protective clothing when handling freshly treated lumber. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before re-use.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.
IF SWALLOWED: Do not induce vomiting. Promptly drink a large quantity of milk, egg whites or gelatin solution; if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention immediately.
IF INHALED: Remove victim to fresh air.
IF IN EYES: Flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS

COMBUSTIBLE: Do not use, pour, or spill near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical.

THIS PRODUCT IS NON-PHOTOCHEMICALLY REACTIVE.

SINCLAIR PAINT COMPANY
LOS ANGELES, CALIFORNIA 90040

CALIFORNIA ARIZONA NEVADA COLORADO HAWAII MANILA BANGKOK HONG KONG

MADE IN U.S.A.

450 WOOD PRESERVATIVE AND SEALER

450 WOOD PRESERVATIVE AND SEALER is a clear chemical treatment for bare exterior wood. It is an effective fungicide and water repellent that will protect against wood rot, mildew, warping and swelling. Will not chip, peel, or blister. May be tinted with Sinclair's All Tint Universal Colorants.

ALWAYS FOLLOW DIRECTIONS - STIR THOROUGHLY

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling. This product is for exterior use only and is recommended for shingles (not asbestos), shakes, clap-boards, smooth or rough-cut wood siding, decks, porches, railings, outdoor furniture, structural support timbers, flat beds, cold frames and green-houses. No sealers are necessary for frequent contact surfaces. The product is not recommended for use on primed or previously painted surfaces nor for wood used for ground, food, feed or potable water. Cover desirable plants and shrubs to avoid possible injury. This product can be used where dairy and farm animals may come in contact with the treated wood.

APPLICATION: MIX WELL. DO NOT THIN. Apply liberally by brush, roller or spray. The more the wood absorbs, the deeper and more lasting the protection will be. Surface must be clean and free of dirt, oil, grease and mildew.

COVERAGE: Approximately 100-300 square feet per gallon, depending upon method of application and the porosity of the wood.

CLEAN-UP: Clean equipment with 350 Regular Paint Thinner.

RETREATMENT: For best results and uniformity of appearance, re-treat once every three years.

STORAGE AND DISPOSAL

STORAGE: Do not expose this product to excessive heat.

DISPOSAL:

Household Users: Securely wrap original container in several layers of newspaper and discard in trash.
Commercial Users: Pesticide/Product Disposal-Do not contaminate water, food or feed by storage or disposal. Waste resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. Container Disposal - Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.