

57227E8

8/5/2008

page 1 of 6



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
Washington, D.C. 20460

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

AUG - 5 2008

Irene Boone
Agent for Contechem, Inc.
Regulatory Services Inc.
17220 Westview Rd.
Lake Oswego, OR 97034

Subject: Britewood Select Sapstain Control
EPA Reg. No.57227-8
Application Dated: June 27, 2008
Receipt Date: July 07, 2008

Dear Irene Boone

The following notification submitted in connection with registration under the provisions of PR Notice 98-10, Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) section 3(c)9. is acceptable.

Proposed Notification

- Revising Container Disposal Per PR Notice 2007-4

Comments

Based on a review of the material submitted, the following comments apply:
This application for notification to revise the container disposal section per PR-notice 2007-4 is acceptable. A copy of this letter has been placed in our records for future reference.

Should you have any questions or comments concerning this letter, please contact Velma Noble at (703) 308-6233.

Sincerely,

Velma Noble

CONCURRENCES Product Manager (31)

SYMBOL	7510						
URNAME							
ATE							

Regulatory Management Branch I
Antimicrobial Division (7510c)



	United States Environmental Protection Agency Washington, DC 20460	<input type="checkbox"/> Registration <input type="checkbox"/> Amendment <input checked="" type="checkbox"/> Other	OPP Identifier Number
--	---	--	-----------------------

Application for Pesticide - Section I

1. Company/Product Number Contechem Inc./57227-8	2. EPA Product Manager Adam Heyward	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Contechem Inc./ Britewood Select Sapstain Control	PM# 34	
5. Name and Address of Applicant (Include ZIP Code) Contechem Inc. PO Box 3255, Portland, OR 97208 <input type="checkbox"/> Check if this is a new address		6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____

Section - II

<input type="checkbox"/> Amendment - Explain below. <input type="checkbox"/> Resubmission in response to Agency letter dated _____ <input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____ <input type="checkbox"/> "Me Too" Application. <input type="checkbox"/> Other - Explain below.
--	---

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification of label change per PR Notice 2007-4. One label enclosed with revisions underlined. Notification statement attached.
 Non-PRIA II action.
 Fax: 503/536-6505 Email: boone5121@comcast.net

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			<input checked="" type="checkbox"/> Metal <input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted If "Yes" Unit Packaging wgt. No. per container		If "Yes" Package wgt No. per container			
3. Location of Net Contents Information <input checked="" type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container 55 gallon drum		5. Location of Label Directions <input type="checkbox"/> on label	
6. Manner in Which Label is Affixed to Product <input checked="" type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled <input type="checkbox"/> Other _____					

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Irene Boone	Title Agent for Contechem Inc.	Telephone No. (Include Area Code) 503/675-8525
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Agent for Contechem, Inc.	
4. Typed Name Irene Boone	5. Date June 27, 2008	

BRITEWOOD SELECT, SAPSTAIN CONTROL

For Fresh Cut Lumber and Wood Products

Active Ingredient:

N-Alkyl (67% C12, 25% C14, 7% C16, 1% C18)
dimethyl benzyl ammonium chloride..... 25.00%
Propiconazole 2.50%
3-Iodo-2-propynyl butyl carbamate 2.50%
Inert Ingredients 70.00%
Total..... 100.00%

BRITEWOOD Select, Sapstain Control, inhibits the growth of mold and fungus that may cause discoloration and/or deterioration of freshly cut lumber and wood products during storage and shipment.

KEEP OUT OF REACH OF CHILDREN

DANGER PELIGRO

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals
DANGER: Corrosive. Causes irreversible eye damage or skin burns. May be fatal if swallowed. Harmful if inhaled. Avoid breathing vapors or spray mist. Harmful if absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear protective eye wear (goggles, face shield or safety glasses). Wear protective clothing and rubber gloves. Wash thoroughly with soap and water after handling and before eating, drinking or using tobacco. Remove contaminated clothing and wash clothing before reuse. See side panel for additional precautionary and first aid information.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Applicators and other handlers must wear:

- Coveralls over long-sleeved shirt and long pants
- Chemical resistant footwear and socks
- Chemical resistant gloves that are waterproof
- Protective eyewear
- Chemical resistant apron when cleaning equipment, mixing or loading
- Dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C)

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

Manufactured by:
CONTECHEM INC.
PO Box 3255
Portland, Oregon 97208 USA
(503) 283-3021

EPA Reg. No. 57227-8
EPA Est. No. 57227-OR-003

Revised 5/13/2008

FIRST AID:	
IF IN EYES:	<ul style="list-style-type: none"> • Hold eyes open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. • Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
IF SWALLOWED:	<ul style="list-style-type: none"> • Call a poison control center or doctor immediately for treatment advice. • Have affected person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
IF INHALED:	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. • Call a poison control center or doctor for further treatment.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. For emergency information call 1-877-283-3021, M-F 8:00am-4:30pm PST, Chemtrec 24 hours, 1-800-424-9300, or your local poison control center.	
NOTES TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.	

BRITEWOOD SELECT, SAPSTAIN CONTROL

For Fresh Cut Lumber and Wood Products

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: This product must be kept under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your state Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

Non-refillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Then offer for recycling, if available, or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE

FOR INDUSTRIAL AND COMMERCIAL USE ONLY

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For control of mold and fungus on green or freshly cut lumber and other wood products.

Examples of other wood products include:

Logs: Staining can be inhibited in freshly debarked logs used for log home construction, export, yarding prior to sawing, and other purposes.

Particle Board: Wood furnish for particle board, wafer board, oriented strand board, and similar products can be protected from discoloration during storage by treatment with BRITEWOOD SELECT, Sapstain Control.

Wood Chips/Saw Dust: Treatment of wood chips, saw dust, or other similar byproducts intended for paper making (Not for food-grade/ food-contact paper or paper board). Reduces discoloration and lowers bleaching requirements for finished paper products.

Plywood Veneer: Treatment with BRITEWOOD SELECT, Sapstain Control is effective on freshly peeled green veneer and other similar plywood furnish that can be especially subject to mold development that can interfere with appearance or laminating adhesive performance.

For best results, lumber and wood products should be treated immediately, at least within twenty-four hours after cutting or sawing. Mold and fungus growth begins immediately after cutting, so delayed treatment is much less effective and requires increased chemical concentration. Green untreated lumber should not be used for stickers. Freshly treated lumber should not be allowed to remain unprotected in heavy rains.

BRITEWOOD SELECT, Sapstain Control may be used in a dip tank or spray application. Seasonal variation in storage and shipping conditions, species and condition of wood should be considered in selection of end use concentration. For effective inhibition of mold and fungus, lumber and logs must be dipped or sprayed such that all surfaces are uniformly treated.

Dip Tank Application: The most effective sapstain treatment of lumber is done using 1 gallon of product to 50-200 gallons of water in a dip tank application. For use in black iron tanks, this product and other products using this active ingredient must be considered corrosive when the pH is less than 8. Iron will dissolve at pH 8 or less and can then react with the tannic acids in wood to cause chemical darkening with iron stain. Chain and equipment marks will exacerbate this chemical staining. The use of a buffer is recommended to maintain an alkaline pH (typically greater than pH 8) at which iron is not soluble. This

effectively inhibits corrosion and eliminates iron stain. The type of buffer recommended depends on mill water conditions (e.g. mineral content, hardness, pH, etc.). Dip tanks and drip aprons must be roofed, paved, and drained to prevent dilution and loss of the antistain solution.

Spray Application: Low pressure equipment using a medium to coarse spray at 1 gallon of product to 20-150 gallons of water is recommended for spray applications. A moderately fine spray, not an aerosol or fog, generally provides the best coverage at practical product concentrations. For treatment of wood chips, sawdust or other particle board like products, spray application should be made at a convenient location in the process where mixing and uniform coverage can be accomplished. Use of a buffer is recommended where black iron equipment might cause chemical staining, as discussed above.

DOT Proper Shipping Name:

Corrosive liquid, n.o.s., 8, UN 1760, PG II (Quaternary ammonium chloride)

DISCLAIMER

The manufacturer and distributor make no warranty, expressed or implied, concerning the use of this product other than as directed on the label. The use of this product being beyond the control of the manufacturer or distributor, no warranty, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. Upon acceptance of delivery of this product, the buyer assumes all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.