



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

May 13, 2021

Sandy Lea
Pesticide Registrar
Kop-Coat, Inc.
36 Pine Street
Rockaway, NJ 07866

Subject: Notification per PRN 98-10 – Disclaimer Change
Product Name: PETTIT MARINE PAINT ALUMASPRAY +
AEROSOL ANTIFOULING PAINT
EPA Registration Number: 60061-120
Received Date: April 29, 2021
Action Case Number/Decision Number: 00299251

Dear Sandy Lea,

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Assurance.

If you have any questions, you may contact Carlos Corona via email at Corona.Carlos@epa.gov.

Sincerely,

A handwritten signature in black ink, appearing to read "Aline Heffernan".

Aline Heffernan
Acting Product Manager Team 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

PETTIT MARINE PAINT ALUMASPRAY + AEROSOL ANTIFOULING PANT

For Aluminum Outdrives and outboards

1863 Black

- Advanced Slime Resistance
- Excellent for All Underwater Metal Surfaces

DANGER! EXTREMELY FLAMMABLE
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN

NOTIFICATION

60061-120

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

05/13/2021

ACTIVE INGREDIENT:

Zinc Omadine®	1.43%
OTHER INGREDIENTS	<u>98.57%</u>
Total	100.0%

Contains Petroleum Distillates

EPA EST. NO: 81405-WI-001

EPA Reg. No.: 60061-120

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of **the company**, including surface preparation, proper application and environmental conditions. Therefore, **the company** cannot guarantee this product's suitability for your particular purpose of application. To the extent consistent with applicable law, **the company** EXPRESSLY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE or otherwise that extend beyond the statements made on this label, and shall not be liable for special, incidental, or consequential damages resulting from the use or handling of this product, the exclusive remedy being the replacement of this product or refund of the purchase price of the product, at **the company's** sole discretion. To the extent consistent with applicable law, buyer/user assumes all risk of possession, handling, or use of this material when use and/or handling is contrary to label instructions.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes skin burns and moderate eye irritation. Do not get in eyes, on skin, or on clothing. Avoid breathing spray mist, vapors or sanding dust While spraying and/or sanding boat surfaces. Wear a minimum of a NIOSH-approved elastomeric half mask respirator with organic vapor (OV) cartridges and a combination N, R or P filter; OR a NIOSH-approved gas mask with OV canisters; OR a NIOSH-approved powered air purifying respirator with OV cartridges and combination HE filters. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Wear coveralls worn over long-sleeved shirt and long pants, chemical resistant gloves, protective eyewear (goggles, face shield or safety glasses), socks, and chemical resistant footwear. Remove contaminated clothing and wash clothing before reuse.

FIRST AID	
IF IN EYES	<ul style="list-style-type: none"> * Hold eye open and rinse slowly and gently with water for 15-20 minutes * Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. * Call a poison control center or doctor for treatment advice.
IF SWALLOWED :	<ul style="list-style-type: none"> * Call a poison control center or doctor immediately for treatment advice. * Do not give any liquid to the person. * Do not induce vomiting unless told to do so by a poison control center or doctor. * Do not give anything by mouth to an unconscious person.
IF INHALED:	<ul style="list-style-type: none"> * Move person to fresh air. * If person is not breathing, call 911 or an ambulance. Then give artificial respiration, preferably mouth-to-mouth, if possible. * Call a poison control center or doctor for further treatment advice.
IF ON SKIN OR CLOTHING	<ul style="list-style-type: none"> * Take off contaminated clothing. * Rinse skin immediately with plenty of water for 15-20 minutes. * Call a poison control center or doctor for treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0489 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage. This product contains petroleum distillates. Vomiting may cause aspiration pneumonia.	

Kop-Coat, Inc.
36 Pine Street
Rockaway, NJ 07866

NET WEIGHT 12 OZ. (340g)

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

NEW OUTDRIVE UNIT: Lightly sand the factory paint with 80-grit sandpaper to dull the surface, clean with Pettit 120/T-10 Brushing Thinner and apply two coats of Alumaspray + Aerosol Antifouling Paint allowing a minimum of 6 hours at 70°F or 12 hours at 50°F drying time between coats.

OUTDRIVES PREVIOUSLY PAINTED WITH ANTIFOULING PAINT: Lightly sand the old antifouling paint, and then clean the sanded surface with Pettit 120/T-10 Brushing Thinner. Apply one coat of Pettit 6627 Tie-Coat Primer and allow to dry at least 4 hours, then apply two coats of Alumaspray + Aerosol Antifouling Paint allowing a minimum of 6 hours drying time between coats. If the old paint has been chipped to bare metal, the entire surface must be primed. Smaller areas less than one square inch can be spot primed prior to applying Alumaspray + Aerosol Antifouling Paint.

BARE ALUMINUM OUTDRIVES AND OUTBOARDS: The metal surface should be properly sandblasted or cleaned to a bright metal. Apply two coats of Pettit Aluma Protect Aluminum Epoxy

Primer 4400/4401 followed by two coats of Pettit Protect High Build Epoxy Primer 4700/4701 and two coats of Alumaspray + Aerosol Antifouling Paint.

DRY TIMES: This paint will dry to the touch in 30 minutes. The minimum recoat time is 6 hours. The minimum dry time between the final coat and launching is 16 hours. Under adverse drying conditions such as those encountered on cool or damp days extend the dry times by 50% in order to ensure that all the solvent is out of the paint film. There is no maximum time before launching.

APPLICATION: Shake can vigorously at least one minute after the mixing ball begins to rattle. Shake can often during use. Hold can 10-12 inches from the surface. Depress nozzle and spray with smooth even strokes. When finished spraying, clear spray valve by turning can upside down and spraying until no more paint comes out.

COVERAGE: One can covers approximately 15 square feet. Use entire contents of one can for each lower unit or outboard.

CLEAN-UP: Use Pettit 120/T-10 Brushing Thinner.

[PREVIOUSLY PAINTED SURFACES: If the previous coating is in good condition, thoroughly sand with 80-grit sandpaper, then solvent clean with [Pettit 120 Brushing Thinner] [thinner] to remove residue. Apply two finish coats of this product. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using a paint and varnish remover. Proceed with appropriate bare system as described below.]

[BARE FIBERGLASS: All bare fiberglass, regardless of age, should be thoroughly cleaned several times with [92 Bio-Blue Pre-Paint Cleaner] [dewaxer] following the instruction of the [dewaxer] [Bio-Blue] can. Sand thoroughly with 80-grit sandpaper to a dull, frosty finish and rewash the sanded surface with fresh water to remove sanding residue. Then apply two coats of this product following application instructions. Careful observation of the above instructions will help ensure long-term adhesion of this and subsequent years' antifouling paint. To eliminate the sanding operation, scrub the surface using [92 Bio-Blue Pre-Paint Cleaner] [cleaner] and a coarse Scotch-Brite® pad. Clean-up all residue with fresh water and allow the hull to dry thoroughly. Then apply one coat of [Pettit Protect 4700/4701] [primer]. Read and follow carefully the application and topcoating instructions on the [Skip Sand Primer] [primer] label. Apply two coats of this antifouling paint.]

[BARE ALUMINUM: [See Product Data Sheet for application instructions.] Sandblast to clean, bright metal and remove blasting residue with clean, dry compressed air or a clean brush. Immediately apply three coats of [Pettit 4400/4401 Aluma Protect Epoxy Primer] [primer] followed by two finish coats of this product. Read and follow carefully the instructions on the Pettit 4400/4401 Aluma Protect Epoxy Primer label.]

ENVIRONMENTAL HAZARDS: This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge.

Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: EXTREMELY FLAMMABLE! Contents under pressure. Keep away from heat, sparks or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130° F may cause bursting. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fires, blanket flames with foam, CO2 or dry chemical. Wear NIOSH certified breathing equipment.

STORAGE AND DISPOSAL

PESTICIDE STORAGE: Keep away from heat, sparks and open flame. Store in a closed, properly labeled container in a cool, dry place. Keep container tightly closed and upright to prevent leakage. In case of spillage, absorb and dispose of in accordance with local and state authorities.

PESTICIDE DISPOSAL: Do Not Puncture or Incinerate! If empty: Place in trash or offer for recycling, if available. If partly filled: Call your local solid waste agency for disposal centers. At present, there are only a few such centers in the country. Before offering for recycling, empty the can by using the product according to the label.(DO NOT PUNCTURE!). If recycling option is not available, discard in the trash. If partly filled: Call your local solid waste agency for disposal center.

CONTAINER DISPOSAL: Do not puncture or incinerate. This container may be recycled in aerosol recycling centers. At present, there are only a few such centers in the country.

MAXIMUM VOC: 75%

NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.

GENERAL DESCRIPTION: Pettit Marine Paint Alumaspray+ Aerosol Antifouling Paint is an antifouling protective coating resistant to slime, algae, barnacles and other marine and freshwater fouling organisms. This product's unique controlled erosion polymers combined with the latest organic biocide technology minimizes coating build-up and keeps underwater surfaces smooth and clean. This product is for use in fresh, salt or brackish water on underwater metal parts such as outdrive units and outboard motors below the waterline. This paint is intended for use on underwater metal surfaces of recreational and commercial vessels of any size.

MEDICAL EMERGENCIES: 1-800-548-0489

PRODUCT INFORMATION: 1-800-221-4466

MANUFACTURED IN USA

[Product Information Number 1-800-497-0010] [Emergency Contact Information 1-800-535-5053]