

P.M

33

68687-6

3/16/99

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

Page 1 of 6



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

68687-6

Date of Issuance:

MAR 16 1999

Term of Issuance:

Conditional

Name of Pesticide Product:

7067HS Purple C.R. Anti-Fouling Paint

NOTICE OF PESTICIDE:

- x Registration
Reregistration

(under FIFRA, as amended)

Name and Address of Registrant (include ZIP Code):

Sea-Master Marine Coatings, Inc.
P.O. Box 339
Channelview, Texas 77530

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

- 1. Submit and/or cite all data required for registration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4.
2. Make the following label changes:
a. Revise the EPA Registration Number to read, "EPA Registration No. "68687-6".

Signature of Approving Official:

Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobials Division (7510C)

Date:

MAR 16 1999

EPA Form 8570-6

CONCURRENCES

Table with columns for SYMBOL, SURNAME, and DATE, containing handwritten entries like 7510C, M. Swindell, and 3/3/99.

EPA Form 1320-1A (1/90)

Printed on Recycled Paper

OFFICIAL FILE COPY

page 2  
EPA Reg. No. 68687-6

- b. According to the Confidential Statement of Formula dated August 7, 1998, the label should declare: Cuprous Oxide 45.9%.
- 3. Submit two copies of the revised final printed label for the record.


The Confidential Statement of Formula dated August 7, 1998 is acceptable.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Pam Hasty at (703) 308-7933.

Sincerely,



Marshall Swindell  
Acting Product Manager 33  
Regulatory Management Branch 1  
Antimicrobials Division (7510C)

Enclosure

# SEA-MASTER

## 7067 HS

### PURPLE C.R. ANTI-FOULING PAINT

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

68687-6

ACTIVE INGREDIENT:	45.9%
Cuprous Oxide	46.7%
INERT INGREDIENTS	53.5% 54.1%
Total	100.0%

KEEP OUT OF REACH OF CHILDREN

### "WARNING"

THIS PRODUCT CONTAINS PETROLEUM DISTILLATES  
SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

BATCH # J000001 MANUFACTURE DATE: OCTOBER 1998

5 U.S. GALLONS / 18.93 LITERS

EPA Establishment No. 068687

EPA Registration No. 68687-?

TEXAS D.O.A. REGISTRANT # 0000000 PRODUCT LICENSE # 000000

This product is an antifoulant for boat and barge bottoms.

### STORAGE AND DISPOSAL

Do not contaminate water, food, feed by storage or disposal. Open dumping is prohibited. Close container after each use.


#### PESTICIDE DISPOSAL:

Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resources Conservation and Recovery Act.

#### CONTAINER DISPOSAL

Dispose of container by triple rinse and recycling or puncturing and disposing in a sanitary landfill or by other approved state and local procedures. If burned, stay out of smoke.

DIRECTIONS FOR USE: "IT IS A VIOLATION OF FEDERAL LAW  
TO USE THIS PRODUCT IN A MANNER INCONSISTANT WITH  
ITS LABELING"



### ENVIRONMENTAL HAZARDS

"This pesticide is toxic to aquatic organisms, including fish and shellfish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips or dust generated by paint removal to enter water. Dispose of paint debris in an approved landfill."

**FOR COMPLETE APPLICATION INSTRUCTIONS:** Refer to product data sheet.

**SURFACE PREPARATION:** Remove surface contaminants, loose dirt, paint and oil. Surface should be dry before applying primer and anti-fouling topcoat.

**DRY FILM THICKNESS:** 2.0 - 3.0 mils dft per coat.

**MIXING:** Mix well with mechanical agitation to a smooth and uniform consistency.

**THINNING:** Not required, if necessary, 10% maximum (by volume) of T-10X may be used.

**APPLICATION:** Airless or conventional spray preferred. Apply in a smooth even pattern. Avoid excessive film build and overspray. Minimum temperatures, 50°F for paint, 40°F for surfaces. Maximum 110°F for paint, 150°F for surfaces.

**DRYING TIME:** Before recoat, 4 to 8 hours. Before launch, 12-36 hours.

**CLEANUP:** Use T-10X or gun cleaner for equipment. Do not contaminate water, food or feed by storage, cleaning of equipment, disposal, or solvents. Open dumping prohibited.

**SHELF LIFE:** 6-12 months      **FLASHPOINT:** 60°F (T.C.C.)

#### PRECAUTIONARY STATEMENTS:

##### HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

**WARNING:** Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long sleeved shirt, long pants and hat. May be fatal if swallowed or inhaled. Do not breath dust or vapor. Wear a mask or respirator approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

#### STATEMENT OF PRACTICAL TREATMENT

**If Inhaled:** If you experience difficulty in breathing, leave the area or remove victim to fresh air. If difficulty continues, get medical attention immediately.

**If On Eyes:** Flush eyes with plenty of water for at least 15 minutes and get medical attention.

**If Swallowed:** Drink promptly a large quantity of water. Avoid alcohol. Get medical attention.

**If On Skin:** Wash thoroughly with soap and water. Get medical attention.

**This is an Industrial Product and NOT intended for Household use. The contents of this can are intended for use by industrial or commercial applicators.**

**MANUFACTURED BY : SEA-MASTER MARINE COATINGS, INC.**

**P. O. BOX 339**

**CHANNELVIEW, TEXAS 77530**

**FOR INDUSTRIAL AND COMMERCIAL**


**BOAT PAINT APPLICATORS**

**ACCEPTED  
with COMMENTS  
in EPA Letter Dated:**

**MAR 16 1999**

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

686876



# SEA-MASTER MARINE COATINGS, INC.

281 452-6200 \* FAX 281 452-5112 \* P.O. BOX 339 \* CHANNELVIEW, TEXAS 77530

## 7067 HS PURPLE C.R. ANTI-FOULING PAINT

**DESCRIPTION:** Sea-Master 7067 HS is a VOC compliant a one package anti-fouling coating for boat bottoms which may be applied over properly primed surfaces.

### PRODUCT DATA:

Weight/gallon	15.5 lbs
Sp.Gr.	1.861
Flashpoint	60' F.
Solids Content	78.5 % wt. 52.5 % vol
Temperature limit	150'F dry 100'F wet

### PRODUCT FEATURES:

Flexibility	Good
Abrasion Resistance	Good
Weatherability	Fair
Dry Time	1/2 hr to touch 2 hrs to handle 4 to 8 hrs to recoat
Coverage	735sq ft/gal @ 1 dry mil
Thickness	2.0 mils dry/ 4.0 mils wet

### RECOMMENDATIONS:

This coating has good anti-fouling properties, flexibility, and has excellent recoatability.

### APPLICATIONS:

Apply by spray, roll or brush to primed steel. Applied coverage is 190 sq ft/gal at 4 wet mils (10% loss). You may use Sea-Master T-10 X thinner for cleanup.

**PRECAUTIONS:** This product contains solvent and anti-fouling toxicants, that are hazardous to humans and animals. Please read M.S.D.S. and dispose of waste according to federal, state and local regulations under the Resources Conservation and Recovery Act..

For best results, apply one coat by brush roll, or spray at 2.0 mils dft (4.0 wet) to a clean and dry surface.


**PACKAGING:** This product is available in one gallon and five gallon steel pails.

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act as  
amended, for the pesticide,  
registered under EPA Reg. No.

68687-6



The technical data presented here, to the best of our knowledge, is accurate and conforms to our Quality Control guidelines. The manufacturer does not assume any responsibility of the user in connection with application, performance or coverage. Product liability, if any, is limited to the replacement of the product. User must refer to the M.S.D.S. and is responsible for following their precautions and recommendations allowed by the guidelines.

APPLICATION INFORMATION

IMMERSION SERVICE

Recommended for constant immersion  
Blast clean to a Commercial metal surface (SSPC SP-6 or NACE # 3) or to a SSPC SP-3 surface with power tools. Then apply to a properly primed surface.

MIXING

Mix well with mechanical agitation before applying. You can use T-10 X to clean your equipment, brushes and rollers.

NON-IMMERSION SERVICE:

Not Recommended.

APPLICATION:

Airless or conventional spray is preferred. Apply in a smooth even pattern. Avoid high film thickness which may result in running or sagging of the coating. May be applied by brush or roller.

SPRAY INFORMATION:

AIRLESS;

Pump Ratio	30:1
Air Supply	100 psi
Hose Dia (ID)	1/4 inch
Hose Length (Max)	75 ft
Tip Size	.011-.018
Atomization	2200 psi

CONVENTIONAL;

Spray Pot	10-20 psi
Air Supply	100 psi
Hose Dia (ID)	3/16 inch
Hose Length	50 ft
Tip Size	.042-.048
Atomization	50-60 psi

SHIPPING DATA:

Name	Paint, Liquid
Hazard Class	3, Flammable Liquid
UN Number	UN-1263
Flashpoint	60 F (T.C.C.)
Packaging Group	II
5 gallons (18.92 liters)	81.0 lbs

ACCEPTED with COMMENTS in EPA Letter Dated:

MAR 16 1999

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

68687-6

[DEC 1998]

