SNUMPER STATES. CONSOL	U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Antimicrobials Division (7510P) 1200 Pennsylvania Ave., N.W. Washington, D.C. 20460	EPA Reg. Number: 71704-3	Date of Issuance: 5/26/22	
NOTICE OF PESTICIDE: <u>X</u> Registration <u>Cunder FIFRA, as amended</u>		Term of Issuance:	Term of Issuance:	
		Conditional	Conditional	
		Name of Pesticide Proc	Name of Pesticide Product:	
			OSP GQ 123	
Name and Address of Registrant (include ZIP Code).			
Jennifer Brandon, Agen OSP Telomer Corporation c/o Delta Analytical Con 12510 Prosperity Drive, Silver Spring, MD 2090	on, Inc. p. Suite 160			
Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.				
	ion furnished by the registrant, the ab icide, Fungicide and Rodenticide Act	-	hereby registered	
Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.				
This product is condition with the following cond	nally registered in accordance with FI	(FRA section 3(c)(7)(A)). You must comply	
	te all data required for registration/ren FRA when the Agency requires all re		-	
Signature of Approving Official:		Date:		
Steven Dryderman		5/26/22	5/26/22	
Steven Snyderman, Proc				
Regulatory Management Branch II				
Antimicrobials Division	(7510M)			
Office of Pesticide Prog EPA Form 8570-6	rams			
Registration Notice Conditional v.20150320				

Page 2 of 2 EPA Reg. No. 71704-3 Action Case No. 00337952

- 2. You are required to comply with the data requirements described in the DCI identified below:
 - a. Glutaraldehyde: GDCI-043901-1668
 - b. Alkyl* dimethyl benzyl ammonium chloride *(50%C14, 40%C12, 10%C16) (ADBAC): GDCI-069105-1679

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36): <u>http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division</u>

- 3. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, "EPA Reg. No. 71704-3."
- 4. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under FIFRA and is subject to review by the Agency. See FIFRA section 2(p)(2). If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) lists examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process, FIFRA section 12(a)(1)(B). Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Assurance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

• Basic CSF dated January 5, 2022

If you have any questions, please contact Zebora Johnson by phone at (202) 560-0730 or via email at johnson.zebora@epa.gov.

Enclosure: Accepted Label

OSP GQ 123

(Alternate Brand Name: OSP GQ 123W)

ACTIVE INGREDIENTS

Glutaraldehyde	. 12.00%
Alkyl (50% C14, 40% C12, 10% C16)	
dimethyl benzyl ammonium chlorides	3.00%
INERT INGREDIENTS	<u>85.00%</u>
TOTAL	100.00%

KEEP OUT OF REACH OF CHILDREN DANGER

(Note to Reviewer: In accordance with 40 CFR 156.68(d), all first aid statements, as prescribed, will appear on the front panel of the product label.)

SEE [{SIDE} {BACK}] PANELS FOR ADDITIONAL PRECAUTIONARY STATEMENTS

FIRST AID

If in eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.

If on skin: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15- 20 minutes. **If swallowed:** Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

If inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.

In case of emergency, call a poison control center or doctor for treatment advice. Have the product container or label with you when calling a poison control center or doctor, or going for treatment. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

You may contact 1-800-222-1222 for chemical, medical, or environmental emergencies.

EPA REG. NO. 71704-EPA EST. NO.

[{Manufactured for} {Sold by}]:

OSP TELOMER CORPORATION, INC. 16223 PARK ROW, SUITE 190 HOUSTON TX 77084 {281/497-2692}

Net Contents:



Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under

EPA Reg. No. 71704-3

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed. Harmful if absorbed through the skin or inhaled. Do not get in eyes, on skin or on clothing. Do not breathe spray mist. Wear goggles or face shield, chemical-resistant gloves and protective clothing when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

{MARKETING CLAIMS}

- This product is a microbiocide for use in controlling sulfate-reducing bacteria (SRB) and slime forming bacteria in oil well drilling, oil field processing applications, oil field water systems, oil and gas productions and transmission pipelines and systems, and gas storage fields and equipment; such as steam-injection water holding tanks, flood water, injection water, holding pond water, disposal-well water, water holding tanks, fuel storage tanks and related refinery and oil field closed systems, industrial recirculating water handling systems.
- This product is for control of algae, algal, fungal and bacterial slimes in recirculating water systems, auxiliary water and waste water systems and water cooling systems, oil field water flood systems.
- This product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations.
- To control algae and bacterial slimes, use this water treatment microbiocide as directed.
- Aids in the control of bacterial, fungal and algal slimes in evaporative condensers, heat exchange water systems, industrial and commercial cooling towers, air washers, dairy sweetwater systems, hydrostatic sterilizers and retorts, pasteurizers, warmers, and industrial water scrubbing systems.
- A water treatment microbiocide for industrial and/or commercial recirculating cooling water towers, retort water systems and flood systems and fracturing fluids.
- A microbiocide for use in controlling slime forming bacteria, sulfate-reducing bacteria (SRB) and fungi (yeast and molds) and algae in air washers and industrial scrubbing systems, process water systems including those that contain reverse osmosis membranes and in service water and auxiliary systems and heat transfer systems and in wastewater systems including wastewater sludge and holding tanks.
- Controls algae and algal slime growth in industrial and/or commercial recirculating cooling water towers.
- Cooling tower waters that are inherently low in algae growth and bacteria count may be adequately controlled by the lower range of the dosages on the label.
- Effective against the growth of algae.
- Has been designed specifically for control of sulfate-reducing bacteria that contribute to souring, the production of sulfide, and abiotic corrosion in water cooling systems, oil field systems, gas production and transmission pipelines and systems.
- Helps inhibit the growth of unsightly algae.

- Is a microbiocide that helps clean and loosen slime debris from cooling and flooding system surfaces.
- Is a water treatment microbiocide that will control algae and bacterial slimes found in recirculating cooling tower waters.
- Kills and prevents algae.
- The residual effectiveness of this algaecide tends to stabilize the total chemical treatment system.
- This product is effective for the control of odor-forming and slime-forming bacterial, fungi and algae in auxiliary service water systems such as fire protection systems and pump or screen bays, waste water systems such as storage tanks, storage piles, associated piping, setting ponds or lagoons, transport spillways or canals and disposal wells.
- This product is used to inhibit fungal growth, which causes discoloration, odor and degradation of non-food contact paper, paperboard or wet lap.
- This product can be used as a slimicide in the manufacture of paper and paperboard, depending on the type of stock, quality of raw water, complexity of the system, and degree of contamination. Do not use to treat paper or paperboard which will contact food.
- This product is for control of bacterial and fungal slimes in pulp mills, paper mills and paper manufacturing.
- This product is for use in (insert location)
- For use {in} {on} (insert location).

{LOCATIONS}

- Air washers
- Auxiliary water systems
- Commercial recirculating cooling water towers
- Drilling, completion and workover fluids systems
- Gas storage wells and systems
- Hydrotesting facilities
- Industrial {and/or} {commercial} recirculating cooling towers.
- Industrial scrubbing systems
- Oil field water flood systems {and fracturing fluid systems}
- Packer fluid systems
- Pipeline pigging and scraping operations
- Recirculating water systems
- Retort water systems
- Waste water systems
- Water cooling systems
- Paper manufacturing (non-food contact)
- Pulp and paper mills {water process systems} (non-food contact)

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

WATER TREATMENT

Do not use water containing residues from use of this product to irrigate crops for food or feed.

(Note to Reviewer: The following sentence must be used with the air washer use listed in the direction:) For use only in industrial air washers and air washer systems which have mist-eliminating components.

AIR WASHERS, INDUSTRIAL SCRUBBING SYSTEMS, INDUSTRIAL RECIRCULATING COOLING WATER TOWERS, RETORT WATER SYSTEMS, EVAPORATIVE CONDENSERS, HEAT SYSTEMS, DAIRY SWEETWATER SYSTEMS, HYDROSTATIC STERILIZERS, PASTEURIZERS AND WARMERS: For best results, clean heavily contaminated systems before treatment with this product. If soap or anionic detergent is used, rinse thoroughly before charging with this algaecide. Repeat every seven days or increase frequency if needed. Should slime develop again, repeat initial dosage.

- 1. **Dosing Location**: This product is to be applied at a point in the system where it will be uniformly mixed, such as the basin area, the sump, or another reservoir or collecting area.
- 2. **Dosing Conditions:** This product must be applied when the system is in jeopardy of being affected or after cleaning systems where efficiency is already impaired.
- 3. Method of Application:
 - a. INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, apply 13 - 52 oz. of this product per 1,000 gal. of water (15 - 60 ppm actives) in the system. Repeat until control is achieved.
Subsequent Dose: When microbial control is evident, add 5 - 26 oz. of this product per 1,000 gal. of water (6 - 30 ppm actives) in the system weekly or as needed to maintain control.

b. CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, apply 13 - 52 oz. of this product per 1,000 gal. of water (15 - 60 ppm actives) in the system.

Subsequent Dose: Maintain this treatment by starting a continuous feed of 3 - 26 oz. of this product per 1,000 gal. of water (3.5 - 30 ppm active) lost by blowdown.

INDUSTRIAL WASTEWATER SYSTEMS: This product is added to a wastewater system or sludge at a convenient point of uniform mixing such as digester. Add 0.5 - 5 gal. of this product per 1,000 gal. of wastewater or sludge (75 - 750 ppm actives).

AUXILIARY SYSTEMS AND SERVICE WATER: Add 13 - 52 oz. of this product per 1,000 gal. of water (15 - 60 ppm actives) in the system continuously. This product must be added to the system at a point of uniform mixing by slug or intermittent feed or by spraying onto a waste pile. The frequency of feed or spray and the duration of treatment will depend upon the severity of the contamination. Additions to water systems must be made during the pumping operation and as close to the pump as possible to ensure adequate mixing.

OIL FIELD, GAS PRODUCTION AND TRANSMISSION PIPELINE AND SYSTEMS: Specific treatment requirements vary among oil and/or gas field sites and subsystem components. The primary point of treatment will vary among oil and/or gas field operations depending on the site problems, water-flood treatment methods and equipment. This product must be added where it will disperse rapidly and uniformly to the desired area of treatment.

Additions of this product must be made with the proper type of metering pump equipment, suction side of pumping equipment or similar device. This product must be added to the system by slug, continuous or on an intermittent basis, depending on the degree of system fouling.

OIL FIELD WATER FLOOD SYSTEMS AND FRACTURING FLUIDS: This product must be added to the water flood water disposal system at a point of uniform mixing.

- Continuous Use: Add 1 100 gal. of this product per 10,000 gal. of water (15 1500 ppm actives) to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.
- 2. Intermittent Use: Add at a rate of 1 to 100 gal. of this product per 10,000 gal. of water (15 1500 ppm actives) for 4 to 8 hours per day, one to four times a week as needed to maintain control.
- Treatment of flow back return water: Dose at a rate of 1 100 gal. of this product per 10,000 gal. of water (15 1500 ppm actives) for 4 8 hours per day, one to four times a week as needed to maintain control.

FRACTURING FLUIDS: Add this product to the frac water storage tanks or directly into the well head injection pipeline as the water is being pumped down-hole. Dose Range: Add 1 - 40 gal. of this product per 10,000 gal. of flood water (15-600 ppm actives) to control slime forming and sulfate reducing bacteria. Levels for effective control will vary depending on conditions at the site.

OIL AND GAS PRODUCTION AND TRANSMISSION PIPELINES AND SYSTEMS: For the control of sulfate-reducing bacteria and slime forming bacteria, this product must be added to a gas production or transmission pipeline via direct injection at a point where uniform and maximum distribution will occur. The application must be conducted to ensure maximum distribution of the product through the internal surface of the pipeline by adding an amount of biocide which eventually comes out the other end of the pipeline. Criteria for success of the treatment will be reduction in bacterial count and/or corrosion rates. To facilitate application, it is desirable to dilute the product with an appropriate solvent immediately before use. The concentration in the solvent must not fall below an active concentration range of 500 - 5000 ppm based on the volume of water in the pipeline. Injections to the system must be weekly, or as needed to maintain control.

GAS STORAGE WELLS AND SYSTEMS: Treat individual injection wells with 6 - 128 oz. of this product per 100 gal. of water (70 - 1500 ppm actives). Update treatment rate as needed. This product must be diluted by the water present in the formation. Injection takes place before gas is injected and may be repeated yearly or as needed to maintain control.

Individual drips should be treated with a sufficient quantity of this product to produce a concentration of 200 to 2000 ppm of this product when diluted by the water present in the drip. Injections should be repeated yearly or as needed to maintain control.

PIPELINE PIGGING AND SCRAPING OPERATIONS: Add this product to slug of water immediately following the scraper (keep the water volume to a minimum and contained between the scraper and the following pig). Add an effective concentration of 0.1 - 2.0 gallons of product per 100 gal. of water (150 - 3000 ppm actives) {to produce 0.015 - 0.30% active solution} depending on the length of the pipeline and the severity of the biofouling.

DRILLING, COMPLETION AND WORKOVER FLUIDS SYSTEMS: This product is to be added to these fluid systems at a point of uniform mixing, such as a circulating, holding or mud tank. Levels for effective control will vary depending on conditions at the site and the severity of the contamination.

^{12/15/21} EPA Master Label Note to Reviewer: Text within braces { } is optional. Marketing text is optional. Brackets [] indicate that at least one option within the brackets must be used on the final label. Parenthesis () are meant to appear on the final label. "This product" can be substituted with actual product name in the marketing and directions for use.

- Initial treatment: Add 0.5 20.0 gal. of this product per 10,000 gal. of freshly prepared fluid (7.5 300 ppm actives).
- Maintenance dosage: Add 0.5 20.0 gal. of this product per 10,000 gal. of freshly prepared fluid (7.5 – 300 ppm actives).

PACKER FLUIDS: This product is to be added to the packer fluid at a point of uniform mixing such as a circulating holding tank. Add 0.5 - 12.0 gal. of this product per 10,000 gal. of freshly prepared packer fluid (7.5 - 180 ppm actives) to a. Levels for effective control vary depending on conditions at the site and the severity of contamination. Seal the treated packer fluid in the wall between the casing and the production tube.

HYDROTESTING: Treat water used to hydrotest pipelines or vessels by adding 0.1 - 8 gallons of this product per 1,000 gal. of water (15 – 1200 ppm actives) depending on the water quality and length of time the equipment will remain idle.

PULP AND PAPER MILLS

Do not use to treat paper or paperboard which will contact food.

SLIMICIDE APPLICATIONS: Do not use to treat paper or paperboard which will contact food. Apply this product to the paper making system at a point of uniform mixing such as, thin or thick stock chests, saveall tank, process tank or whitewater tank.

- Initial Dose: When system is noticeably contaminated, add 1.5 to 10.3 lbs. of this product per ton
 of pulp or paper (dry basis) (100 700 ppm total actives) to be treated as a continuous or slug
 dose. Repeat until control is achieved. Heavily fouled systems must be boiled out prior to initial
 treatment.
- 2. **Subsequent Dose:** When microbial control is evident, add 0.97 to 6.6 lbs. of this product per ton of pulp or paper (dry basis) (66-450 ppm total actives) to be treated as necessary to maintain control.

WATER BASED COATING, PIGMENTS, AND FILLER SLURRIES FOR PULP AND PAPERBOARD:

Application of this product must be made at a point in the system where mixing action is good or can be made at the size press or water box.

Dosing Application: Apply at a rate of 0.33 to 2.0 lbs. of this product per 1,000 lbs. of dry powder or 0.33 to 2.0 kg of this product per metric ton of dry slurry to produce a concentration of 333.3 to 2000 ppm as product (based on slurry solids) in the mixed slurry.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Store only in original container. Keep this product under locked storage sufficient to make it inaccessible to children or persons unfamiliar with its proper use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING:

(Note to Reviewer: One or more of the following paragraphs for Container Handling will be selected, depending on packaging use/type.)

{For non-refillable containers equal to or less than 5 gal.}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container ¼ full with water and recap. Shake for 10 seconds. Drain for 10 seconds after the flow begins to drip. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration.

{For non-refillable containers greater than 5 gal.}

Non-Refillable Container. Do not reuse or refill this container. Triple rinse container {(or equivalent)} promptly after emptying. Triple rinse as follows: Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip back and forth several times. Turn the container over onto its other end and tip back and forth several times. Follow Pesticide Disposal instructions for rinsate disposal. Repeat this procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration