



Archived Publication

This information provided in this document is for reference. Please be aware that the information in this document may be outdated or superseded by additional information.



The Multi-Sector General Permit for Stormwater Discharges Associated with Industrial Activity (2000 MSGP), issued in October 2000, expired at midnight on October 30, 2005. A new permit, the 2008 Multi-Sector General Permit (2008 MSGP) was issued on September 29, 2008. Visit www.epa.gov/npdes/stormwater/msgp to view the final 2008 MSGP and supporting documents.



5.3.2 Alternative Certification of "Not Present or No Exposure"

You are not subject to the analytical monitoring requirements of Part 5.1.2 provided:

5.3.2.1 You make a certification for a given outfall, or on a pollutant-by-pollutant basis in lieu of monitoring required under Part 5.1.2, that material handling equipment or activities, raw materials, intermediate products, final products, waste materials, by-products, industrial machinery or operations, or significant materials from past industrial activity that are located in areas of the facility within the drainage area of the outfall are not presently exposed to storm water and are not expected to be exposed to storm water for the certification period; and

5.3.2.2 Your certification is signed in accordance with Part 9.7, retained in the Storm Water Pollution Prevention Plan, and submitted to EPA in accordance with Part 7. In the case of certifying that a pollutant is not present, the permittee must submit the certification along with the monitoring reports required Part 7; and

5.3.2.3 If you cannot certify for an entire period, you must submit the date exposure was eliminated and any monitoring required up until that date; and

5.3.2.4 No numeric limitation or State-specific monitoring requirement for that parameter is established in Part 5 or Part 13.

5.4 Monitoring Required by the Director

The Director may provide written notice to any facility, including those otherwise exempt from the sampling requirements of Parts 5, 6 and 12, requiring discharge sampling for a specific monitoring frequency for specific parameters. Any such notice will briefly state the reasons for the monitoring, parameters to be monitored, frequency and period of monitoring, sample types, and reporting requirements.

5.5 Reporting Monitoring Results

Deadlines and procedures for submitting monitoring reports are contained in Part 7.

6. Sector-Specific Requirements for Industrial Activity

You only need to comply with the additional requirements of Part 6 that

apply to the sector(s) of industrial activity at your facility. These sector-specific requirements are in addition to the "basic" requirements specified in Parts 1–5 and 7–13 of this permit.

6.A Sector A—Timber Products**6.A.1 Covered Storm Water Discharges**

The requirements in Part 6.A apply to storm water discharges associated with industrial activity from Timber Products facilities as identified by the SIC Codes specified under Sector A in Table 1–1 of Part 1.2.1.

6.A.2 Industrial Activities Covered by Sector A

The types of activities that permittees under Sector A are primarily engaged in are:

6.A.2.1 Cutting timber and pulpwood (those that have log storage or handling areas);

6.A.2.2 Mills, including merchant, lath, shingle, cooperage stock, planing, plywood and veneer;

6.A.2.3 Producing lumber and wood basic materials;

6.A.2.4 Wood preserving;

6.A.2.5 Manufacturing finished articles made entirely of wood or related materials except wood kitchen cabinet manufacturers (covered under Part 6.23);

6.A.2.6 Manufacturing wood buildings or mobile homes.

6.A.3 Special Coverage Conditions

6.A.3.1 *Prohibition of Discharges.* (See also Part 1.2.3.1) Not covered by this permit: storm water discharges from areas where there may be contact with the chemical formulations sprayed to provide surface protection. These discharges must be covered by a separate NPDES permit.

6.A.3.2 *Authorized Non-Storm Water Discharges.* (See also Part 1.2.3.1) Also authorized by this permit, provided the non-storm water component of the discharge is in compliance with SWPPP requirements in Part 4.2.7 (Controls): discharges from the spray down of lumber and wood product storage yards where no chemical additives are used in the spray down waters and no chemicals are applied to the wood during storage.

6.A.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.A.4.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Also identify where any of the following may be exposed to precipitation/surface runoff: processing areas; treatment chemical storage areas; treated wood and residue storage areas; wet decking areas; dry decking areas; untreated wood and residue storage areas; and treatment equipment storage areas.

6.A.4.2 *Inventory of Exposed Materials.* (See also Part 4.2.4) Where such information exists, if your facility has used chlorophenolic, creosote or chromium-copper-arsenic formulations for wood surface protection or preserving, identify the following: areas where contaminated soils, treatment equipment and stored materials still remain, and the management practices employed to minimize the contact of these materials with storm water runoff.

6.A.4.3 *Description of Storm Water Management Controls.* (See also Part 4.2.7). Describe and implement measures to address the following activities/sources: log, lumber and wood product storage areas; residue storage areas; loading and unloading areas; material handling areas; chemical storage areas; and equipment/vehicle maintenance, storage and repair areas. If your facility performs wood surface protection/preservation activities, address the specific BMPs for these activities.

6.A.4.4 *Good Housekeeping.* (See also Part 4.2.7.2.1.1). In areas where storage, loading/unloading and material handling occur, perform good housekeeping to limit the discharge of wood debris; minimize the leachate generated from decaying wood materials; and minimize the generation of dust.

6.A.4.5 *Inspections.* (See also Part 4.2.7.2.1.5). If your facility performs wood surface protection/preservation activities, inspect processing areas, transport areas and treated wood storage areas monthly to assess the usefulness of practices to minimize the deposit of treatment chemicals on unprotected soils and in areas that will come in contact with storm water discharges.

6.A.5 Monitoring and Reporting Requirements (See also Part 5)

TABLE A-1.—SECTOR-SPECIFIC NUMERIC LIMITATIONS AND BENCHMARK MONITORING
[Sector of permit affected/supplemental requirements]

Subsector (Discharge may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cutoff concentration ¹	Numeric limitation ²
General Sawmills and Planning Mills (SIC 2421)	Chemical Oxygen Demand (COD).	120.0 mg/L.	6.0–9.0 s.u. No Discharge of debris that will not pass through a 2.54 cm (1") diameter round opening.
Wood Preserving (SIC 2491)	Total Suspended Solids (TSS).	100 mg/L.	
	Total Zinc	0.117 mg/L.	
	Total Arsenic	0.16854 mg/L.	
Log Storage and Handling (SIC 2411)	Total Copper	0.0636 mg/L.	
	Total Suspended Solids (TSS).	100 mg/L.	
Wet Decking Discharges at Log Storage and Handling Areas (SIC 2411).	pH	
	Debris (woody material such as bark, twigs, branches, heartwood, or sapwood).	
Hardwood Dimension and Flooring Mills; Special Products Sawmills, not elsewhere classified; Millwork, Veneer, Plywood and Structural Wood; Wood Containers; Wood Buildings and Mobile Homes; Reconstituted Wood Products; and Wood Products Facilities not elsewhere classified (SIC Codes 2426, 2429, 2431–2439 (except 2434), 2448, 2449, 2451, 2452, 2593, and 2499).	Chemical Oxygen Demand (COD).	120.0 mg/L.	
	Total Suspended Solids (TSS).	100.0 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 monitoring years.

² Monitor once per year for each monitoring year.

6.B Sector B—Paper and Allied Products Manufacturing

6.B.1 Covered Storm Water Discharges

The requirements in Part 6.B apply to storm water discharges associated with industrial activity from Paper and Allied Products Manufacturing facilities as identified by the SIC Codes specified

under Sector B in Table 1–1 of Part 1.2.1.

6.B.2 Industrial Activities Covered by Sector B

The types of activities that permittees under Sector B are primarily engaged in are:

6.B.2.1 Manufacture of pulps from wood and other cellulose fibers and from rags;

6.B.2.2 Manufacture of paper and paperboard into converted products, *i.e.* paper coated off the paper machine, paper bags, paper boxes and envelopes;

6.B.2.3 Manufacture of bags of plastic film and sheet.

6.B.3 Monitoring and Reporting Requirements (See also Part 5)

TABLE B-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring and cutoff concentration ¹	Numeric limitation
Part of Permit Affected/Supplemental Requirements			
Paperboard Mills (SIC Code 2631)	COD	120.0 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 monitoring years

6.C Sector C—Chemical and Allied Products Manufacturing

6.C.1 Covered Storm Water Discharges

The requirements in Part 6.C apply to storm water discharges associated with industrial activity from Chemical and Allied Products Manufacturing facilities as identified by the SIC Codes specified under Sector C in Table 1–1 of Part 1.2.1.

6.C.2 Industrial Activities Covered by Sector C

The requirements listed under this Part apply to storm water discharges associated with industrial activity from a facility engaged in manufacturing the following products:

6.C.2.1 basic industrial inorganic chemicals;

6.C.2.2 plastic materials and synthetic resins, synthetic rubbers, and

cellulosic and other human made fibers, except glass;

6.C.2.3 soap and other detergents, including facilities producing glycerin from vegetable and animal fats and oils; speciality cleaning, polishing and sanitation preparations; surface active preparations used as emulsifiers, wetting agents and finishing agents, including sulfonated oils; and perfumes, cosmetics and other toilet preparations;

6.C.2.4 paints (in paste and ready mixed form); varnishes; lacquers; enamels and shellac; putties, wood fillers, and sealers; paint and varnish removers; paint brush cleaners; and allied paint producers;

6.C.2.5 industrial organic chemicals;

6.C.2.6 industrial and household adhesives, glues, caulking compounds, sealants, and linoleum, tile and rubber cements from vegetable, animal or synthetic plastic materials; explosives; printing ink, including gravure, screen process and lithographic inks; miscellaneous chemical preparations such as fatty acids, essential oils, gelatin (except vegetable), sizes, bluing, laundry sours, writing and stamp pad ink, industrial compounds such as boiler and heat insulating compounds, and chemical supplies for foundries;

6.C.2.7 ink and paints, including china painting enamels, indian ink, drawing ink, platinum paints for burnt wood or leather work, paints for china painting, artists' paints and artists' water colors;

6.C.2.8 nitrogenous and phosphatic basic fertilizers, mixed fertilizers,

pesticides and other agricultural chemicals.

6.C.3 Limitations on Coverage

6.C.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.3.3) Not covered by this permit: non-storm water discharges containing inks, paints or substances (hazardous, nonhazardous, etc.) resulting from an onsite spill, including materials collected in drip pans; washwater from material handling and processing areas; and washwater from drum, tank or container rinsing and cleaning.

6.C.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.C.4.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Also identify where any of the following may be exposed to precipitation/surface runoff: processing and storage areas; access roads, rail cars and tracks; areas where substances are transferred in bulk; and operating machinery.

6.C.4.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the

following sources and activities that have potential pollutants associated with them: loading, unloading and transfer of chemicals; outdoor storage of salt, pallets, coal, drums, containers, fuels, fueling stations; vehicle and equipment maintenance/cleaning areas; areas where the treatment, storage or disposal (on- or off-site) of waste/wastewater occur; storage tanks and other containers; processing and storage areas; access roads, rail cars and tracks; areas where the transfer of substances in bulk occurs; and areas where machinery operates.

6.C.4.3 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1) As part of your good housekeeping program, include a schedule for regular pickup and disposal of garbage and waste materials, or adopt other appropriate measures to reduce the potential for discharging storm water that has contacted garbage or waste materials. Routinely inspect the condition of drums, tanks and containers for potential leaks.

6.C.5 Monitoring and Reporting Requirements (See also Part 5)

TABLE C-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation ²
Part of Permit Affected/Supplemental Requirements			
Phosphate Subcategory of the Fertilizer Manufacturing Point Source Category (40 CFR § 418.10)—applies to precipitation runoff, that during manufacturing or processing, comes into contact with any raw materials, intermediate product, finished product, by-products or waste product (SIC 2874).	Total Phosphorus (as P)	105.0 mg/L, daily max. 35 mg/L, 30-day avg.
	Fluoride	75.0 mg/L, daily max. 25.0 mg/L, 30-day avg.
Agricultural Chemicals (2873–2879)	Nitrate plus Nitrite Nitrogen	0.68 mg/L.	Nitrate plus Nitrite Nitrogen
	Total Recoverable Lead	0.0816 mg/L.	
	Total Recoverable Iron	1.0 mg/L.	
	Total Recoverable Zinc	0.117 mg/L.	
Industrial Inorganic Chemicals (2812–2819)	Phosphorus	2.0 mg/L.	Nitrate plus Nitrite Nitrogen
	Total Recoverable Aluminum	0.75 mg/L	
Soaps, Detergents, Cosmetics, and Perfumes (SIC 2841–2844).	Total Recoverable Iron.	1.0 mg/L	Nitrate plus Nitrite Nitrogen
	Nitrate plus Nitrite Nitrogen	0.68 mg/L.	
Plastics, Synthetics, and Resins (SIC 2821–2824)	Total Recoverable Zinc	0.117 mg/L..	Nitrate plus Nitrite Nitrogen
	Total Recoverable Zinc	0.117 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

² Monitor once/year for each Monitoring Year.

6.D Sector D—Asphalt Paving and Roofing Materials and Lubricant Manufacturers

6.D.1 Covered Storm Water Discharges

The requirements in Part 6.D apply to storm water discharges associated with industrial activity from Asphalt Paving

and Roofing Materials and Lubricant Manufacturers facilities as identified by the SIC Codes specified under Sector D in Table 1–1 of Part 1.2.1.

6.D.2 Industrial Activities Covered by Sector D

The types of activities that permittees under Sector D are primarily engaged in are:

6.D.2.1 manufacturing asphalt paving and roofing materials;

- 6.D.2.2 portable asphalt plant facilities;
- 6.D.2.3 manufacturing lubricating oils and greases.

6.D.3 Limitations on Coverage

The following storm water discharges associated with industrial activity are not authorized by this permit:

- 6.D.3.1 discharges from petroleum refining facilities, including those that manufacture asphalt or asphalt products that are classified as SIC code 2911;

- 6.D.3.2 discharges from oil recycling facilities;
- 6.D.3.3 discharges associated with fats and oils rendering.

6.D.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

- 6.D.4.1 *Inspections.* (See also Part 4.2.7.2.1.5) Inspect at least once per month, as part of the maintenance

program, the following areas: Material storage and handling areas, liquid storage tanks, hoppers/silos, vehicle and equipment maintenance, cleaning and fueling areas, material handling vehicles, equipment and processing areas. Ensure appropriate action is taken in response to the inspection by implementing tracking or follow up procedures.

6.D.5 Monitoring and Reporting Requirements. (See also part 5)

TABLE D-1.—SECTOR-SPECIFIC NUMERIC LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric Limitation ²
Sector of Permit Affected/Supplemental Requirements			
Asphalt Paving and Roofing Materials (SIC 2951, 2952)	Total Suspended Solids (TSS).	100mg/L.	
Discharges from areas where production of asphalt paving and roofing emulsions occurs (SIC 2951, 2952).	TSS	23.0 mg/L, daily max 15.0 mg/L 30-day avg.
	Oil and Grease	15.0 mg/L daily max. 10mg/L, 30-day avg.
	pH	6.0-9.0

¹ Monitor once/quarter for the year 2 and year 4 monitoring years.

² Monitor once per year for each monitoring year.

6.E Sector E—Glass, Clay, Cement, Concrete, and Gypsum Products

6.E.1 Covered Storm Water Discharges

The requirements in Part 6.E apply to storm water discharges associated with industrial activity from Glass, Clay, Cement, Concrete, and Gypsum Products facilities as identified by the SIC Codes specified under Sector E in Table 1-1 of part 1.2.1.

6.E.2 Industrial Activities Covered by Sector E

The requirements listed under this permit apply to storm water discharges associated with industrial activity from a facility engaged in either manufacturing the following products or performing the following activities:

- 6.E.2.1 flat, pressed, or blown glass or glass containers;
- 6.E.2.2 hydraulic cement;
- 6.E.2.3 clay products including tile and brick;
- 6.E.2.4 pottery and porcelain electrical supplies;
- 6.E.2.5 concrete products;
- 6.E.2.6 gypsum products;
- 6.E.2.7 minerals and earths, ground or otherwise treated;
- 6.E.2.8 non-clay refractories;
- 6.E.2.9 lime manufacturing
- 6.E.2.10 cut stone and stone products

- 6.E.2.11 asbestos products
- 6.E.2.12 mineral wool and mineral wool insulation products.

6.E.3 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

- 6.E.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify the locations of the following, as applicable: bag house or other dust control device; recycle/sedimentation pond, clarifier or other device used for the treatment of process wastewater, and the areas that drain to the treatment device.

- 6.E.3.2 *Good Housekeeping Measures.* (See also Part 4.2.2.3) With good housekeeping prevent or minimize the discharge of: spilled cement; aggregate (including sand or gravel); kiln dust; fly ash; settled dust; or other significant material in storm water from paved portions of the site that are exposed to storm water. Consider using regular sweeping or other equivalent measures to minimize the presence of these materials. Indicate in your SWPPP the frequency of sweeping or equivalent measures. Determine the frequency from the amount of industrial activity occurring in the area and the frequency of precipitation, but it must be

performed at least once a week if cement, aggregate, kiln dust, fly ash or settled dust are being handled/processed. You must also prevent the exposure of fine granular solids (cement, fly ash, kiln dust, etc.) to storm water where practicable, by storing these materials in enclosed silos/hoppers, buildings or under other covering.

- 6.E.3.3 *Inspections.* (See also Part 4.2.7.2.1.5) Perform inspections while the facility is in operation and include all of the following areas exposed to storm water: material handling areas, above ground storage tanks, hoppers or silos, dust collection/containment systems, truck wash down/equipment cleaning areas.

- 6.E.3.4 *Certification.* (See also Part 4.4.1) For facilities producing ready-mix concrete, concrete block, brick or similar products, include in the non-storm water discharge certification a description of measures that insure that process waste water resulting from truck washing, mixers, transport buckets, forms or other equipment are discharged in accordance with NPDES requirements or are recycled.

6.E.4 Monitoring and Reporting Requirements. (See also Part 5)

TABLE F-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Sector of permit affected/supplemental requirements—			
Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cutoff concentration ¹	Numeric limitation
Steel Works, Blast Furnaces, and Rolling and Finishing Mills (SIC 3312–3317). Iron and Steel Foundries (SIC 3321–3325)	Total Recoverable Aluminum	0.75 mg/L	
	Total Recoverable Zinc	0.117 mg/L.	
	Total Recoverable Aluminum	0.75 mg/L.	
	Total Suspended Solids	100 mg/L	
	Total Recoverable Copper	0.0636 mg/L	
	Total Recoverable Iron	1.0 mg/L	
Rolling, Drawing, and Extruding of Non-Ferrous Metals (SIC 3351–3357).	Total Recoverable Zinc	0.117 mg/L.	
	Total Recoverable Copper	0.0636 mg/L	
	Total Recoverable Zinc	0.117 mg/L.	
Non-Ferrous Foundries (SIC 3363–3369)	Total Recoverable Copper	0.636 mg/L.	
	Total Recoverable Zinc	0.117 mg/L.	
	Total Recoverable Zinc	0.117 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.G Sector G—Metal Mining (Ore Mining and Dressing)

6.G.1 Covered Storm Water Discharges

The requirements in Part 6.G apply to storm water discharges associated with industrial activity from active, temporarily inactive and inactive metal mining and ore dressing facilities, including mines abandoned on Federal Lands, as identified by the SIC Codes specified under Sector G in Table 1–1 of Part 1.2.1. Coverage is required for facilities that discharge storm water contaminated by contact with or that has come into contact with, any overburden, raw material, intermediate product, finished product, byproduct, or waste product located on the site of the operation.

6.G.1.1 *Covered Discharges from Inactive Facilities:* All storm water discharges.

6.G.1.2 *Covered Discharges from Active and Temporarily Inactive Facilities:* Only the storm water discharges from the following areas are covered: waste rock/overburden piles if composed entirely of storm water and not combining with mine drainage; topsoil piles; offsite haul/access roads; onsite haul/access roads constructed of waste rock/overburden/spent ore if composed entirely of storm water and not combining with mine drainage; onsite haul/access roads not constructed of waste rock/overburden/spent ore except if mine drainage is used for dust control; runoff from tailings dams/dikes when not constructed of waste rock/tailings and no process fluids are present; runoff from tailings dams/dikes when constructed of waste rock/tailings if and no process fluids are present if composed entirely of storm water and not combining with mine drainage; concentration building if no contact with material piles; mill site if no

contact with material piles; office/administrative building and housing if mixed with storm water from industrial area; chemical storage area; docking facility if no excessive contact with waste product that would otherwise constitute mine drainage; explosive storage; fuel storage; vehicle/equipment maintenance area/building; parking areas (if necessary); power plant; truck wash areas if no excessive contact with waste product that would otherwise constitute mine drainage; unreclaimed, disturbed areas outside of active mining area; reclaimed areas released from reclamation bonds prior to December 17, 1990; and partially/inadequately reclaimed areas or areas not released from reclamation bonds.

6.G.2 Industrial Activities Covered by Sector G

Note: “metal mining” will connote any of the separate activities listed in Part 6.G.2. The types of activities that permittees under Sector G are primarily engaged in are:

- 6.G.2.1 exploring for metallic minerals (ores), developing mines and the mining of ores;
- 6.G.2.2 ore dressing and beneficiating, whether performed at co-located, dedicated mills or separate (*i.e.*, custom) mills.

6.G.3 Limitations on Coverage

6.G.3.1 *Prohibition of Storm Water Discharges.*

Storm water discharges not authorized by this permit: discharges from active metal mining facilities which are subject to effluent limitation guidelines for the Ore Mining and Dressing Point Source Category (40 CFR Part 440).

Note: discharges that come in contact with overburden/waste rock are subject to 40 CFR Part 440, providing: the discharges drain to a point source (either naturally or as a result of intentional diversion) and they combine with “mine drainage” that is otherwise

regulated under the Part 440 regulations. Discharges from overburden/waste rock can be covered under this permit if they are composed entirely of storm water, do not combine with sources of mine drainage that are subject to 40 CFR Part 440, and meet other eligibility criteria contained in Part 1.2.2.1.

6.G.3.2 *Prohibition of Non-Storm Water Discharges.*

Not authorized by this permit: adit drainage and contaminated springs or seeps (see also the standard Limitations on Coverage in Part 1.2.3).

6.G.4 Definitions

6.G.4.1 *Mining Operation*—typically consists of three phases, any one of which individually qualifies as a “mining activity.” The phases are the exploration and construction phase, the active phase, and the reclamation phase.

6.G.4.2 *Exploration and Construction Phase*—entails exploration and land disturbance activities to determine the financial viability of a site. Construction includes the building of site access roads and removal of overburden and waste rock to expose mineable minerals.

6.G.4.3 *Active Phase*—activities including each step from extraction through production of a salable product.

6.G.4.4 *Reclamation Phase*—activities intended to return the land to its pre-mining use

The following definitions are not intended to supercede the definitions of active and inactive mining facilities established by 40 CFR 122.26(b)(14)(iii).

6.G.4.5 *Active Metal Mining Facility*—a place where work or other activity related to the extraction, removal or recovery of metal ore is being conducted. For surface mines, this definition does not include any land where grading has returned the earth to a desired contour and reclamation has begun.

6.G.4.6 *Inactive Metal Mining Facility*—a site or portion of a site where metal mining and/or milling occurred in the past but is not an active facility as defined above, and where the inactive portion is not covered by an active mining permit issued by the applicable State or Federal government agency.

6.G.4.7 *Temporarily Inactive Metal Mining Facility*—a site or portion of a site where metal mining and/or milling occurred in the past but currently are not being actively undertaken, and the facility is covered by an active mining permit issued by the applicable State or Federal government agency.

6.G.5 Clearing, Grading and Excavation Activities

Clearing, grading and excavation activities being conducted as part of the exploration and construction phase of a mining operation cannot be covered under this permit if these activities will disturb one or more acre of land. Instead, coverage for these activities must be under the latest version of EPA's General Permit for Storm Water Discharges from Construction Activities (the "Construction General Permit;" **Federal Register**, Vol. 63, p. 7858 and for Region 6, **Federal Register**, Vol. 63, p. 36490), or an individual construction permit. If the area of disturbance during the initial phase is less than one acre, you must continue to comply with the requirements of the MSGP-2000.

6.G.5.1 *Requirements for Activities Disturbing 5 or More Acres of Earth*. If the one-acre limit as defined in Part 6.G.5 is attained, coverage for these activities must be under the latest version of EPA's Construction General Permit (or individual permit). You must first obtain and comply with the Construction General Permit's requirements before submitting the separate Construction General Permit Notice of Intent (NOI) form (EPA Form 3510-9). The February 17, 1998 version of the permit can be downloaded from the EPA's Web Site at www.epa.gov/owm/sw/construction/cgp/cgp-nat.pdf and Region 6's July 6, 1998 version of the permit at www.epa.gov/owm/sw/construction/cgp/cgp-reg6.pdf or obtained from the Office of Water Resource Center at (202) 260-7786. The NOI form is also available from the Web Site at www.epa.gov/owm/sw/construction/connoi.pdf or from your EPA Regional office at the address listed under Part 8.3. Discharges in compliance with the provisions of the Construction General Permit are also authorized under the MSGP.

6.G.5.2 *Cessation of Earth Disturbing Activities*. If exploration phase clearing,

grading and excavation activities are completed and no further mining activities will occur at the site, you must comply with the requirements for terminating the Construction General Permit, *i.e.*, stabilize and revegetate the disturbed land, submit a Notice of Termination, etc. If active mining activities will ensue, you must apply for coverage under the MSGP-2000 for your storm water discharges and be prepared to implement any new requirements prior to beginning the active phase. It is recommended you terminate your coverage under the Construction General Permit, but it is not mandatory that you do so. If you choose not to terminate your construction General Permit, you will be responsible for complying with all permit conditions of the construction permit in addition to those of the MSGP-2000. The Notice of Termination form is Addendum E to this permit and is available at <http://www.epa.gov/owm/sw/industry/msgp/notform.pdf>.

6.G.6 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.G.6.1 *SWPPP Requirements for Active and Temporarily Inactive Metal Mining Facilities*.

6.G.6.1.1 *Nature of Industrial Activities*. (See also Part 4.2.2.1) Briefly describe the mining and associated activities that can potentially affect the storm water discharges covered by this permit, including: the total acreage within the mine site; the estimated acreage of disturbed land; the estimated acreage of land proposed to be disturbed throughout the life of the mine; and a general description of the location of the site relative to major transportation routes and communities.

6.G.6.1.2 *Site Map*. (See also Part 4.2.2.3) Also identify the locations of the following (as appropriate): mining/milling site boundaries; access and haul roads; outline of the drainage areas of each storm water outfall within the facility and indicate the types of discharges from the drainage areas; equipment storage, fueling and maintenance areas; materials handling areas; outdoor manufacturing, storage or material disposal areas; chemicals and explosives storage areas; overburden, materials, soils or waste storage areas; location of mine drainage (where water leaves mine) or other process water; tailings piles/ponds (including proposed ones); heap leach pads; off-site points of discharge for mine drainage/process water; surface waters; and boundary of tributary areas that are

subject to effluent limitations guidelines.

6.G.6.1.3 *Potential Pollutant Sources*. (See also Part 4.2.4) For each area of the mine/mill site where storm water discharges associated with industrial activities occur, identify the types of pollutants (e.g., heavy metals, sediment) likely to be present in significant amounts. Consider these factors: the mineralogy of the ore and waste rock (e.g., acid forming); toxicity and quantity of chemicals used, produced or discharged; the likelihood of contact with storm water; vegetation of site (if any); history of significant leaks/spills of toxic or hazardous pollutants. Also include a summary of any existing ore or waste rock/overburden characterization data and test results for potential generation of acid rock. If any new data is acquired due to changes in ore type being mined, update your SWPPP with this information.

6.G.6.1.4 *Site Inspections*. (See also Part 4.2.7.2.1.5) Inspect active mining sites at least monthly. Inspect temporarily inactive sites at least quarterly unless adverse weather conditions make the site inaccessible.

6.G.6.1.5 *Employee Training*. (See also Part 4.2.7.2.1.6) Conduct employee training at least annually at active mining and temporarily inactive sites.

6.G.6.1.6 *Controls*. (See also Part 4.2.7) Consider each of the following BMPs. The potential pollutants identified in Part 6.G.6.1.3 shall determine the priority and appropriateness of the BMPs selected. If you determine that one or more of these BMPs are not appropriate for your facility, explain why it is not appropriate. If BMPs are implemented or planned but are not listed here (e.g., substituting a less toxic chemical for a more toxic one), include descriptions of them in your SWPPP.

6.G.6.1.6.1 *Storm Water Diversions*. Consider diverting storm water away from potential pollutant sources. BMP options: interceptor/diversion controls (e.g., dikes, swales, curbs or berms); pipe slope drains; subsurface drains; conveyance systems (e.g., channels or gutters, open top box culverts and waterbars; rolling dips and road sloping; roadway surface water deflector, and culverts); or their equivalents.

6.G.6.1.6.2 *Sediment and Erosion Control*. (See also Part 4.2.7.2.2.1) At active and temporarily inactive sites consider a range of erosion controls within the broad categories of: flow diversion (e.g., swales); stabilization (e.g., temporary or permanent seeding); and structural controls (e.g., sediment traps, dikes, silt fences).

6.G.6.1.6.3 *Management of Runoff.* (See also Part 4.2.7.2.2.) Consider the potential pollutant sources given in Part 6.G.6.1.3 when determining reasonable and appropriate measures for managing runoff.

6.G.6.1.6.4 *Capping.* When capping is necessary to minimize pollutant discharges in storm water, identify the source being capped and the material used to construct the cap.

6.G.6.1.6.5 *Treatment.* If treatment of storm water (e.g., chemical or physical systems, oil/water separators, artificial wetlands, etc.) from active and temporarily inactive sites is necessary to protect water quality, describe the type and location of treatment used.

6.G.6.1.6.6 *Certification of Discharge Testing.* (See also Part 4.4.1) Test or evaluate for the presence of specific mining-related non-storm water discharges such as seeps or adit discharges or discharges subject to effluent limitations guidelines (e.g., 40 CFR Part 440), such as mine drainage or process water. Alternatively (if applicable), you may certify in your SWPPP that a particular discharge comprised of commingled storm water and non-storm water is covered under a separate NPDES permit; and that permit subjects the non-storm water portion to effluent limitations prior to any commingling. This certification shall identify the non-storm water discharges, the applicable NPDES permit(s), the effluent limitations placed on the non-storm water discharge by the permit(s), and the points at which the limitations are applied.

6.G.6.2 SWPPP Requirements for Inactive Metal Mining Facilities.

6.G.6.2.1 *Nature of Industrial Activities.* (See also Part 4.2.2.1) Briefly describe the mining and associated activities that took place at the site that can potentially affect the storm water discharges covered by this permit. Include: approximate dates of operation; total acreage within the mine and/or processing site; estimate of acres of disturbed earth; activities currently occurring onsite (e.g., reclamation); a general description of site location with respect to transportation routes and communities.

6.G.6.2.2 *Site Map.* (See also Part 4.2.2.3) See Part 6.G.6.1.2 for requirements.

6.G.6.2.3 *Potential Pollutant Sources.* (See also Part 4.2.4) See Part 6.G.6.1.3 for requirements.

6.G.6.2.4 *Controls.* (See also Part 4.2.7) Consider each of the following BMPs. The potential pollutants identified in Part 6.G.6.2.3 shall determine the priority and appropriateness of the BMPs selected. If you determine that one or more of these BMPs are not appropriate for your facility, explain why it is not appropriate. If BMPs are implemented or planned but are not listed here (e.g., substituting a less toxic chemical for a more toxic one), include descriptions of them in your SWPPP. The non-structural controls in the general requirements at Part 4.2.7.2.1 are not required for inactive facilities.

6.G.6.2.4.1 *Storm Water Diversions.* See Part 6.G.6.1.6.2 for requirements.

6.G.6.2.4.2 *Sediment and Erosion Control.* (See also Part 4.2.7.2.2.1) See Part 6.G.6.1.6 for requirements.

6.G.6.2.4.3 *Management of Runoff.* (See also Part 4.2.7.2.2.2)

Also consider the potential pollutant sources as described in Part 6.G.6.2.3 (Summary of Potential Pollutant Sources) when determining reasonable and appropriate measures for managing runoff.

6.G.6.2.4.4 *Capping.* See Part 6.G.6.1.7 for requirements.

6.G.6.2.4.5 *Treatment.* See Part 6.G.6.1.8 for requirements.

6.G.6.2.5 *Comprehensive Site Compliance Evaluation.* (See also Part 4.9)

Annual site compliance evaluations may be impractical for inactive mining sites due to remote location/inaccessibility of the site; in which case conduct the evaluation at least once every 3 years. Document in the SWPPP why annual compliance evaluations are not possible. If the evaluations will be conducted more often than every 3 years, specify the frequency of evaluations.

6.G.7 Monitoring and Reporting Requirements. (See also Part 5)

6.G.7.1 *Analytic Monitoring for Copper Ore Mining and Dressing Facilities.* Active copper ore mining and dressing facilities must sample and analyze storm water discharges for the pollutants listed in Table G-1.

TABLE G-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING FOR COPPER ORE MINING AND DRESSING FACILITIES

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation
Part of Permit Affected/Supplemental Requirements			
Copper Ore Mining and Dressing Facilities (SIC 1021)	Total Suspended Solids (TSS). Nitrate plus Nitrite Nitrogen Chemical Oxygen Demand (COD).	100 mg/L. 0.68 mg/L. 120 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.G.7.2 *Analytic Monitoring Requirements for Discharges From Waste Rock and Overburden Piles at Active Ore Mining and Dressing Facilities.* For discharges from waste rock and overburden piles, perform analytic monitoring at least once within the first year of permit coverage for the parameters listed in Table G-2, and twice annually thereafter for any

parameters measured above the benchmark value (based on the initial sampling event) listed in Table G-2. Permittees must also conduct analytic monitoring twice annually for the parameters listed in Table G-3. The twice annual samples must be collected once between January 1 and June 30 and once between July 1 and December 31, with at least 3 months separating the

storm events. The director may, however, notify you that you must perform additional monitoring to accurately characterize the quality and quantity of pollutants discharged from your waste rock/overburden piles. Monitoring requirements for discharges from waste rock and overburden piles are not eligible for the waivers in Part 5.3.2.

TABLE G-2.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING FOR DISCHARGES FROM WASTE ROCK AND OVERBURDEN PILES FROM ACTIVE ORE MINING OR DRESSING FACILITIES

Part of permit affected/supplemental requirements—			
Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cutoff concentration ¹	Numeric limitation
Iron Ores; Copper Ores; Lead and Zinc Ores; Gold and Silver Ores; Ferroalloy Ores Except Vanadium; Miscellaneous Metal Ores (SIC Codes 1011, 1021, 1031, 1041, 1044, 1061, 1081, 1094, 1099). See above, as applicable	Total Suspended Solids (TSS)	100 mg/L.	
	Turbidity (NTUs)	5 NTUs above background.	
	pH	6.0–9.0 standard units.	
	Hardness (as CaCO ₃)	no benchmark value.	
	Antimony, Total	0.636 mg/L.	
	Arsenic, Total	0.16854 mg/L.	
	Beryllium, Total	0.13 mg/L.	
	Cadmium, Total (hardness dependent)	0.0159 mg/L.	
	Copper, Total (hardness dependent)	0.0636 mg/L.	
	Iron, Total	1.0 mg/L.	
	Lead, Total (hardness dependent)	0.0816 mg/L.	
	Manganese, Total	1.0 mg/L.	
	Mercury, Total	0.0024 mg/L.	
	Nickel, Total (hardness dependent)	1.417 mg/L.	
	Selenium, Total	0.2385 mg/L.	
	Silver, Total (hardness dependent)	0.318 mg/L.	
Zinc, Total (hardness dependent)	0.117 mg/L.		

¹ Monitor at least once during the first year of permit coverage, and twice annually thereafter for any parameter that exceeds the benchmark value. Facilities that monitored for the full list of Table G-2 parameters during the previous permit need not sample the entire list again, however they must continue twice annual monitoring for parameters that exceeded the benchmark values in the initial sampling event.

6.G.7.2.1 Additional Analytic Monitoring Requirements for Discharges From Waste Rock and Overburden Piles. Table G-3 contains additional monitoring requirements for specific ore mine categories. Perform the monitoring twice annually using the schedule established in Part 6.G.7.2. The initial sampling event for a pollutant parameter required in Table G-2 satisfies the requirement for the first sample of any pollutant measurement in Table G-3.

TABLE G-3.—ADDITIONAL MONITORING REQUIREMENTS FOR DISCHARGES FROM WASTE ROCK AND OVERBURDEN PILES FROM ACTIVE ORE MINING OR DRESSING FACILITIES

Supplemental requirements—			
Type of Ore mined	Pollutants of concern		
	Total suspended solids (TSS)	pH	Metals, total
Tungsten Ore	X	X	Arsenic, Cadmium (H), Copper (H), Lead (H), Zinc (H).
Nickel Ore	X	X	Arsenic, Cadmium (H), Copper (H), Lead (H), Zinc (H).
Aluminum Ore	X	X	Iron.
Mercury Ore	X	X	Nickel (H).
Iron Ore	X	X	Iron (Dissolved).
Platinum Ore			Cadmium (H), Copper (H), Mercury, Lead (H), Zinc (H).
Titanium Ore	X	X	Iron, Nickel (H), Zinc (H).
Vanadium Ore	X	X	Arsenic, Cadmium (H), Copper (H), Zinc (H).
Copper, Lead, Zinc, Gold, Silver and Molybdenum	X	X	Arsenic, Cadmium (H), Copper (H), Lead, Mercury, Zinc (H).
Uranium, Radium and Vanadium	X	X	Chemical Oxygen Demand, Arsenic, Radium (Dissolved and Total), Uranium, Zinc (H).

Note: (H) indicates that hardness must also be measured when this pollutant is measured.

6.G.7.2.2 Reporting Requirements Storm Water Discharges From Waste Rock And Overburden Piles From Active Ore Mining or Dressing Facilities. From active ore mining and dressing facilities, submit monitoring results for each outfall discharging storm water from waste rock and overburden piles, or certifications in accordance with Part 7. Submit monitoring reports on discharge monitoring report (DMR) forms postmarked no later than January 28 of the next year after the samples were collected.

TABLE G-4.—APPLICABILITY OF THE MULTI-SECTOR GENERAL PERMIT TO STORM WATER RUNOFF FROM ACTIVE ORE (METAL) MINING AND DRESSING SITES

Discharge/source of discharge	Note/comment
Piles	
Waste rock/overburden	If composed entirely of storm water and not combining with mine drainage. See Note below.
Topsoil	
Roads constructed of waste rock or spent ore	
Onsite haul roads	If composed entirely of storm water and not combining with mine drainage. See Note below.
Offsite haul/access roads	
Roads not constructed of waste rock or spent ore	
Onsite haul roads	Except if "mine drainage" is used for dust control.
Offsite haul/access roads	
Milling/concentrating	
Runoff from tailings dams/dikes when constructed of waste rock/tailings	Except if process fluids are present and only if composed entirely of storm water and not combining with mine drainage. See Note below.
Runoff from tailings dams/dikes when not constructed of waste rock/tailings	Except if process fluids are present.
Concentration building	If storm water only and no contact with piles.
Mill site	If storm water only and no contact with piles.
Ancillary areas	
Office/administrative building and housing	If mixed with storm water from the industrial area.
Chemical storage area	
Docking facility	Except if excessive contact with waste product that would otherwise constitute "mine drainage".
Explosive storage	
Fuel storage (oil tanks/coal piles)	
Vehicle/equipment maintenance area/building	
Parking areas	But coverage unnecessary if only employee and visitor-type parking.
Power plant	
Truck wash area	Except when excessive contact with waste product that would otherwise constitute "mine drainage".
Reclamation-related areas	
Any disturbed area (unreclaimed)	Only if not in active mining area.
Reclaimed areas released from reclamation bonds prior to Dec. 17 1990.	
Partially/inadequately reclaimed areas or areas not released from reclamation bond.	

Note: Storm water runoff from these sources are subject to the NPDES program for storm water unless mixed with discharges subject to the 40 CFR Part 440 that are not regulated by another permit prior to mixing. Non-storm water discharges from these sources are subject to NPDES permitting and may be subject to the effluent limitation guidelines under 40 CFR Part 440.

Discharges from overburden/waste rock and overburden/waste rock-related areas are not subject to 40 CFR Part 440 unless: (1) it drains naturally (or is intentionally diverted) to a point source; and (2) combines with "mine drainage" that is otherwise regulated under the Part 440 regulations. For such sources, coverage under this permit would be available if the discharge composed entirely of storm water does not combine with other sources of mine drainage that are not subject to 40 CFR Part 440, as well as meeting other eligibility criteria contained in Part I.B. of the permit. Permit applicants bear the initial responsibility for determining the applicable technology-based standard for such discharges. EPA recommends that permit applicants contact the relevant NPDES permit issuance authority for assistance to determine the nature and scope of the "active mining area" on a mine-by-mine basis, as well as to determine the appropriate permitting mechanism for authorizing such discharges.

6.H Sector H—Coal Mines and Coal Mining Related Facilities

6.H.1 Covered Storm Water Discharges

The requirements in Part 6.H apply to storm water discharges associated with industrial activity from Coal Mines and Coal Mining Related facilities as identified by the SIC Codes specified under Sector H in Table 1–1 of Part 1.2.1.

6.H.2 Industrial Activities Covered by Sector H

Storm water discharges from the following portions of coal mines may be eligible for this permit:

6.H.2.1 Haul roads (nonpublic roads on which coal or coal refuse is conveyed);

6.H.2.2 Access roads (nonpublic roads providing light vehicular traffic within the facility property and to public roadways);

6.H.2.3 Railroad spurs, siding and internal haulage lines (rail lines used for hauling coal within the facility property and to offsite commercial railroad lines or loading areas);

6.H.2.4 Conveyor belts, chutes and aerial tramway haulage areas (areas under and around coal or refuse conveyer areas, including transfer stations); and

6.H.2.5 Equipment storage and maintenance yards, coal handling buildings and structures, and inactive coal mines and related areas (abandoned and other inactive mines, refuse disposal sites and other mining-related areas).

6.H.3 Limitation on Coverage

6.H.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.2.2) Not covered by this permit: discharges from pollutant seeps or underground drainage from inactive coal mines and refuse disposal areas that do not result from precipitation events; and discharges from floor drains in maintenance buildings and other similar

drains in mining and preparation plant areas.

6.H.3.2 *Discharges Subject to Storm Water Effluent Guidelines.* (See also Part 1.2.3.4) Not authorized by this permit: storm water discharges subject to an existing effluent limitation guideline at 40 CFR Part 434.

6.H.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4 of the MSGP.

6.H.4.1 *Other Applicable Regulations.* Most active coal mining-related areas (SIC Codes 1221–1241) are subject to sediment and erosion control regulations of the U.S. Office of Surface Mining (OSM) that enforces the Surface Mining Control and Reclamation Act (SMCRA). OSM has granted authority to most coal producing states to implement SMCRA through State SMCRA regulations. All SMCRA requirements regarding control of storm water-related pollutant discharges must be addressed in the SWPPP (directly or by reference).

6.H.4.2 *Drainage Area Site Map.* (See also Part 4.2.2.3) Also identify where any of the following may be exposed to precipitation/surface runoff: all applicable mining related areas described in Part 6.H.2; acidic spoil, refuse or unreclaimed disturbed areas, and liquid storage tanks containing pollutants such as caustics, hydraulic fluids and lubricants.

6.H.4.3 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the following sources and activities that have potential pollutants associated with them: truck traffic on haul roads and resulting generation of sediment subject to runoff and dust generation; fuel or other liquid storage; pressure lines containing slurry, hydraulic fluid or other potential harmful liquids; and loading or temporary storage of acidic refuse/spoil.

6.H.4.4 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1) As part of your good housekeeping program, consider: using sweepers; covered storage; watering haul roads to minimize dust generation; and conserving vegetation (where possible) to minimize erosion.

6.H.4.5 *Preventive Maintenance.* (See also Part 4.2.7.2.1.3) Also perform inspections of storage tanks and pressure lines of fuels, lubricants, hydraulic fluid or slurry to prevent leaks due to deterioration or faulty connections; or other equivalent measures.

6.H.4.6 *Inspections of Active Mining-Related Areas and Inactive Areas Under SMCRA Bond Authority.* (See also Part 4.2.7.2.1.5) Perform quarterly inspections of areas covered by this permit, corresponding with the inspections, as performed by SMCRA inspectors, of all mining-related areas required by SMCRA. Also maintain the records of the SMCRA authority representative.

6.H.4.7 *Sediment and Erosion Control.* (See also Part 4.2.7.2.2.1) As indicated in Part 6.H.4.1 above, SMCRA requirements regarding sediment and erosion control measures are primary requirements of the SWPPP for mining-related areas subject to SMCRA authority.

6.H.4.8 *Comprehensive Site Compliance Evaluation.* (See also Part 4.9.2) Include in your evaluation program, inspections for pollutants entering the drainage system from activities located on or near coal mining-related areas. Among the areas to be inspected: haul and access roads; railroad spurs, sliding and internal hauling lines; conveyor belts, chutes and aerial tramways; equipment storage and maintenance yards; coal handling buildings/structures; and inactive mines and related areas.

6.H.6 Monitoring and Reporting Requirements. (See also Part 5)

TABLE H–1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cutoff concentration ¹	Numeric limitation
Part of Permit Affected/Supplemental Requirements			
Coal Mines and Related Areas (SIC 1221–1241)	Total Recoverable Aluminum	0.75 mg/L.	
	Total Recoverable Iron	1.0 mg/L.	
	Total Suspended Solids	100 mg/L..	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.I Sector I—Oil and Gas Extraction and Refining

6.I.1 Covered Storm Water Discharges

The requirements in Part 6.I apply to storm water discharges associated with industrial activity from Oil and Gas Extraction and Refining facilities as identified by the SIC Codes specified under Sector I in Table 1–1 of Part 1.2.1.

6.I.2 Industrial Activities Covered By Sector I

The types of activities that permittees under Sector I are primarily engaged in are:

- 6.I.2.1 Oil and gas exploration, production, processing or treatment operations, or transmission facilities;
- 6.I.2.2 Extraction and production of crude oil, natural gas, oil sands and shale; the production of hydrocarbon liquids and natural gas from coal; and associated oil field service, supply and repair industries.

6.I.3 Limitations On Coverage

6.I.3.1 *Prohibition of Storm Water Discharges.* This permit does not authorize contaminated storm water discharges from petroleum refining or drilling operations that are subject to nationally established BAT or BPT guidelines found at 40 CFR Parts 419 and 435, respectively. Note: most contaminated discharges at petroleum refining and drilling facilities are subject to these effluent guidelines and are not eligible for coverage by this permit.

6.I.3.2 *Prohibition of Non-Storm Water Discharges.* Not authorized by this permit: discharges of vehicle and equipment washwater, including tank cleaning operations.

Alternatively, washwater discharges must be authorized under a separate NPDES permit, or be discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.

6.I.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.I.4.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: Reportable Quantity (RQ) releases; locations used for the treatment, storage or disposal of wastes; processing areas and storage areas; chemical mixing areas; construction and drilling areas; all areas subject to the effluent guidelines requirements for “No Discharge” in accordance with 40 CFR 435.32; and the

structural controls to achieve compliance with the “No Discharge” requirements.

6.I.4.2 *Potential Pollutant Sources.* (See also Part 4.2.4)

Also describe the following sources and activities that have potential pollutants associated with them: chemical, cement, mud or gel mixing activities; drilling or mining activities; and equipment cleaning and rehabilitation activities. In addition, include information about the RQ release that triggered the permit application requirements; the nature of release (e.g., spill of oil from a drum storage area); the amount of oil or hazardous substance released; amount of substance recovered; date of the release; cause of the release (e.g., poor handling techniques and lack of containment in the area); areas affected by the release (i.e., land and water); procedure to clean up release; actions or procedures implemented to prevent or improve response to a release; and remaining potential contamination of storm water from release (taking into account human health risks, the control of drinking water intakes and the designated uses of the receiving water).

6.I.4.3 *Inspections.* (See also Part 4.2.7.2.1.5)

6.I.4.3.1 *Inspection Frequency.* Inspect all equipment and areas addressed in the SWPPP at a minimum of 6-month intervals. Routinely (but not less than quarterly) inspect equipment and vehicles which store, mix (including all on and offsite mixing tanks) or transport chemicals/hazardous materials (including those transporting supplies to oil field activities).

6.I.4.3.2 *Temporarily or Permanently Inactive Oil and Gas Extraction Facilities.* For these facilities that are remotely located and unstaffed, perform the inspections at least annually.

6.I.4.4 *Sediment and Erosion Control.* (See also Part 4.2.7.2.2.1) Unless covered by the General Permit for Construction Activity, the additional sediment and erosion control requirements for well drillings, and sand/shale mining areas include the following:

6.I.4.4.1 *Site Description:* Also include: a description of the nature of the exploration activity; estimates of the total area of site and area disturbed due to exploration activity; an estimate of runoff coefficient of the site; site drainage map, including approximate slopes; and the name of all receiving waters. All sediment and erosion control measures must be inspected once every seven days.

6.I.4.4.2 *Vegetative Controls:* Describe and implement vegetative practices designed to preserve existing vegetation where attainable and re-vegetate open areas as soon as practicable after grade drilling. Consider the following (or equivalent measures): temporary or permanent seeding, mulching, sod stabilization, vegetative buffer strips, tree protection practices. Begin implementing appropriate vegetative practices on all disturbed areas within 14 days following the last activity in that area.

6.I.4.5 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.I.4.5.1 *Vehicle and Equipment Storage Areas.* Confine vehicles/equipment awaiting or having undergone maintenance to designated areas (as marked on site map). Describe and implement measures to minimize contaminants from these areas (e.g., drip pans under equipment, indoor storage, use of berms or dikes, or other equivalent measures).

6.I.4.5.2 *Material and Chemical Storage Areas.* Maintain these areas in good conditions to prevent contamination of storm water. Plainly label all hazardous materials.

6.I.4.5.3 *Chemical Mixing Areas.* (See also Part 4.4)

Describe and implement measures that prevent or minimize contamination of storm water runoff from chemical mixing areas.

6.J Sector J—Mineral Mining and Dressing

6.J.1 Covered Storm Water Discharges

The requirements in Part 6.J apply to storm water discharges associated with industrial activity from active and inactive mineral mining and dressing facilities as identified by the SIC Codes specified under Sector J in Table 1–1 of Part 1.2.1.

6.J.2 Industrial Activities Covered by Sector J

The types of activities that permittees under Sector J are primarily engaged in are:

- 6.J.2.1 exploring for minerals (e.g., stone, sand, clay, chemical and fertilizer minerals, non-metallic minerals, etc.), developing mines and the mining of minerals; and
- 6.J.2.2 mineral dressing, and non-metallic mineral services.

6.J.3 Limitations on Coverage

Not authorized by this permit: most storm water discharges subject to an existing effluent limitation guideline at 40 CFR part 436. The exceptions to this limitation and which are therefore covered by the MSGP–2000 are mine

dewatering discharges composed entirely of storm water or ground water seepage from: construction sand and gravel, industrial sand, and crushed stone mining facilities in Regions 1, 2, 3, 6, 8, 9, and 10.

6.J.4 Definitions

6.J.4.1 *Mining Operation*—typically consists of three-phases, any one of which individually qualifies as a “mining activity.” The phases are the exploration and construction phase, the active phase and the reclamation phase.

6.J.4.2 *Exploration and Construction Phase*—entails exploration and land disturbance activities to determine the financial viability of a site. Construction includes the building of site access roads and removal of overburden and waste rock to expose mineable minerals.

6.J.4.3 *Active Phase*—activities including each step from extraction through production of a salable product.

6.J.4.4 *Reclamation phase*—activities intended to return the land to its pre-mining state.

Note: The following definitions are not intended to supercede the definitions of active and inactive mining facilities established by 40 CFR 122.26(b)(14)(iii).

6.J.4.5 *Active Mineral Mining Facility*—a place where work or other activity related to the extraction, removal or recovery of minerals is being conducted. This definition does not include any land where grading has returned the earth to a desired contour and reclamation has begun.

6.J.4.6 *Inactive Mineral Mining Facility*—a site or portion of a site where mineral mining and/or dressing occurred in the past but is not an active facility as defined above, and where the inactive portion is not covered by an active permit issued by the applicable State or Federal government agency.

6.J.4.7 *Temporarily Inactive Mineral Mining Facility*—a site or portion of a site where mineral mining and/or dressing occurred in the past but currently are not being actively undertaken, and the facility is covered by an active mining permit issued by

the applicable State or Federal government agency.

6.J.5 Clearing, Grading and Excavation Activities

Clearing, grading and excavation activities being conducted as part of the exploration and construction phase of a mineral mining operation cannot be covered under this permit if these activities will disturb one or more acre of land. Instead, coverage for these activities must be under the latest version of EPA’s General Permit for Storm Water Discharges from Construction Activities (the “Construction General Permit;” **Federal Register**, Vol. 63, p. 7858) and, for Region 6, **Federal Register**, Vol. 63, p. 36490), or an individual construction permit. If the area of disturbance during the initial phase is less than one acre, you must continue to comply with the requirements of the MSGP–2000.

6.J.5.1 *Obtaining Coverage Under the Construction General Permit.* If the one-acre limit as described in Part 6.J.5 is attained, coverage for these activities must be under the latest version of EPA’s Construction General Permit (or individual permit). You must first obtain and comply with the Construction General Permit’s requirements before submitting the separate Construction General Permit Notice of Intent (NOI) form (EPA Form 3510–9). The February 17, 1998 version of the permit can be downloaded from the EPA’s Web Site at <http://www.epa.gov/owm/sw/construction/cgp/cgp-nat.pdf> or obtained from the Office of Water Resource Center at (202) 260–7786. The NOI form is also available from the Web Site at <http://www.epa.gov/owm/sw/construction/connoi.pdf> or from your EPA Regional office at the address listed under Part 8.3. Discharges in compliance with the provisions of the Construction General Permit are also authorized under the MSGP.

6.J.5.2 *Cessation of Exploration and Construction Activities.* If exploration

phase clearing, grading and excavation activities are completed and no further mining activities will occur at the site, you must comply with the requirements for terminating the Construction General Permit, *i.e.*, stabilize and revegetate the disturbed land, submit a Notice of Termination, etc. If active mining operations will ensue, you must apply for coverage under the MSGP–2000 for your storm water discharges and be prepared to implement any new requirements prior to beginning the active phase. It is recommended you terminate your coverage under the construction general permit, but you are not required to do so. If you choose to not terminate, you will be responsible for complying with all permit conditions of the construction permit in addition to those of the MSGP–2000. The Notice of Termination form is available in Addendum F to this permit and at <http://www.epa.gov/owm/sw/industry/msgp/notform.pdf>.

6.J.6 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4 of the MSGP.

6.J.6.1 *Inspections.* (See also Part 4.2.7.2.1.5) Conduct quarterly visual inspections of all BMPs at active mining facilities. At temporarily or permanently inactive facilities, perform annual inspections. Include in your inspection program: assessment of the integrity of storm water discharge diversions, conveyance systems, sediment control and collection systems and containment structures; inspections to determine if soil erosion has occurred at, or as a result of vegetative BMPs, serrated slopes and benched slopes; inspections of material handling and storage areas and other potential sources of pollution for evidence of actual or potential discharges of contaminated storm water.

6.J.7 Monitoring and Reporting Requirements. (See also Part 5)

TABLE J–1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation ²
Part of Permit Affected/Supplemental Requirements			
Mine Dewatering Activities at Construction Sand and Gravel; Industrial Sand; and Crushed Stone Mining Facilities (SIC 1422–1429, 1442, 1446).	Total Suspended Solids pH	25 mg/L, monthly avg. 45 mg/L, daily max 6.0–9.0
Sand and Gravel Mining (SIC 1442, 1446)	Nitrate plus Nitrogen	0.68 mg/L.	
	Total Suspended Solids	100 mg/L.	

TABLE J-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING—Continued

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation ²
Dimension and Crushed Stone and Nonmetallic Minerals (except fuels) (SIC 1411, 1422–1429, 1481, 1499).	Total Suspended Solids	100 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

² Monitor once/year for Each Monitoring Year.

6.K Sector K—Hazardous Waste Treatment, Storage or Disposal Facilities

6.K.1 Covered Storm Water Discharges

The requirements in Part 6.K apply to storm water discharges associated with industrial activity from Hazardous Waste Treatment, Storage or Disposal facilities as identified by the Activity Code specified under Sector K in Table 1–1 of Part 1.2.1.

6.K.2 Industrial Activities Covered by Sector K

This permit authorizes storm water discharges associated with industrial activity from facilities that treat, store or dispose of hazardous wastes, including those that are operating under interim status or a permit under subtitle C of RCRA.

6.K.3 Limitations on Coverage

For facilities located in Region 6, coverage is limited to Hazardous Waste Treatment Storage or Disposal Facilities (TSDF's) that are self-generating or handle residential wastes only and to those facilities that only store hazardous wastes and do not treat or dispose. Those permits are issued by EPA Region 6 for Louisiana (LAR05*###), New Mexico (NMR05*###), Oklahoma (OKR05*###), and Federal Indian Reservations in these States (LAR05*##F, NMR05*##F, OKR05*##F, or TXR05*##F). Coverage under this permit is not available to commercial hazardous waste disposal/treatment facilities located in Region 6 that dispose and treat on a commercial basis any produced hazardous wastes (not their own) as a service to generators.

6.K.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.3.1) Not authorized by this permit: leachate, gas collection condensate, drained free liquids, contaminated ground water,

laboratory-derived wastewater and contact washwater from washing truck and railcar exteriors and surface areas which have come in direct contact with solid waste at the landfill facility.

6.K.4 Definitions

6.K.4.1 *Contaminated storm water*—storm water which comes in direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater as defined in Part 6.K.4.5. Some specific areas of a landfill that may produce contaminated storm water include (but are not limited to): the open face of an active landfill with exposed waste (no cover added); the areas around wastewater treatment operations; trucks, equipment or machinery that has been in direct contact with the waste; and waste dumping areas.

6.K.4.2 *Drained free liquids*—aqueous wastes drained from waste containers (e.g., drums, etc.) prior to landfilling.

6.K.4.3 *Land treatment facility*—a facility or part of a facility at which hazardous waste is applied onto or incorporated into the soil surface; such facilities are disposal facilities if the waste will remain after closure.

6.K.4.4 *Landfill*—an area of land or an excavation in which wastes are placed for permanent disposal, that is not a land application or land treatment unit, surface impoundment, underground injection well, waste pile, salt dome formation, a salt bed formation, an underground mine or a cave as these terms are defined in 40 CFR 257.2, 258.2 and 260.10.

6.K.4.5 *Landfill wastewater*—as defined in 40 CFR Part 445 (Landfills Point Source Category) all wastewater associated with, or produced by, landfilling activities except for sanitary wastewater, non-contaminated storm water, contaminated groundwater, and

wastewater from recovery pumping wells. Landfill wastewater includes, but is not limited to, leachate, gas collection condensate, drained free liquids, laboratory derived wastewater, contaminated storm water and contact washwater from washing truck, equipment, and railcar exteriors and surface areas which have come in direct contact with solid waste at the landfill facility.

6.K.4.6 *Leachate*—liquid that has passed through or emerged from solid waste and contains soluble, suspended, or miscible materials removed from such waste.

6.K.4.7 *Non-contaminated storm water*—storm water which does not come into direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater as defined in Part 6.K.4.5. Non-contaminated storm water includes storm water which flows off the cap, cover, intermediate cover, daily cover, and/or final cover of the landfill.

6.K.4.8 *Pile*—any non-containerized accumulation of solid, nonflowing hazardous waste that is used for treatment or storage and that is not a containment building.

6.K.4.9 *Surface impoundment*—a facility or part of a facility which is a natural topographic depression, man-made excavation or diked area formed primarily of earthen materials (although it may be lined with man-made materials), which is designed to hold an accumulation of liquid wastes or wastes containing free liquids, and which is not an injection well. Examples of surface impoundments are holding, storage, settling, and aeration pits, ponds and lagoons.

6.K.5 Numeric Limitations, Monitoring and Reporting Requirements. (See also Part 5)

TABLE K-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK AND COMPLIANCE MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cutoff concentration ¹	Numeric limitation ²
Part of Permit Affected/Supplemental Requirements			
ALL—Industrial Activity Code “HZ” (Note: permit coverage limited in some States)	Ammonia	19.0 mg/L	
	Total Recoverable Magnesium.	0.0636 mg/L	
	Chemical Oxygen Demand (COD).	120.0 mg/L	
	Total Recoverable Arsenic	0.16854 mg/L	
	Total Recoverable Cadmium.	0.0159 mg/L	
	Total Cyanide	0.0636 mg/L	
	Total Recoverable Lead	0.0816 mg/L	
	Total Recoverable Mercury	0.0024 mg/L	
	Total Recoverable Selenium.	0.2385 mg/L	
	Total Recoverable Silver ...	0.0318 mg/L	
ALL—Industrial Activity Code “HZ” Subject to the Provisions of 40 CFR Part 445 Subpart A.	BOD5		220 mg/l, daily max. 56 mg/l, monthly avg. maximum.
	TSS		88 mg/l, daily max. 27 mg/l, monthly avg. maximum.
	Ammonia		10 mg/l, daily maximum. 4.9 mg/l, monthly avg. maximum.
	Alpha Terpineol		0.042 mg/l, daily max. 0.019 mg/l, monthly avg. maximum.
	Aniline		0.024 mg/l, daily max. 0.015 mg/l, monthly avg. maximum.
	Benzoic Acid		0.119 mg/l, daily max. 0.073 mg/l, monthly avg. maximum.
	Naphthalene		0.059 mg/l, daily max. 0.022 mg/l, monthly avg. maximum.
	p-Cresol		0.024 mg/l, daily max. 0.015 mg/l, monthly avg. maximum.
	Phenol		0.048 mg/l, daily max. 0.029 mg/l, monthly avg. maximum.
	Pyridine		0.072 mg/l, daily max. 0.025 mg/l, monthly avg. maximum.
	Arsenic (Total)		1.1 mg/l, daily maximum. 0.54 mg/l, monthly avg. maximum.
	Chromium (Total)		1.1 mg/l, daily maximum. 0.46 mg/l, monthly avg. maximum.
	Zinc (Total)		0.535 mg/l, daily max. 0.296 mg/l, monthly avg. maximum.
	pH		Within the range of 6–9 pH units.

¹ These benchmark monitoring cutoff concentrations apply to storm water discharges associated with industrial activity other than contaminated storm water discharges from landfills subject to the numeric effluent limitations set forth in Table K-1. Monitor once/quarter for the year 2 and year 4 monitoring years.

² As set forth at 40 CFR Part 445 Subpart A, these numeric limitations apply to contaminated storm water discharges from hazardous waste landfills subject to the provisions of RCRA Subtitle C at 40 CFR Parts 264 (Subpart N) and 265 (Subpart N) except for any of the facilities described below:

(a) Landfills operated in conjunction with other industrial or commercial operations when the landfill only receives wastes generated by the industrial or commercial operation directly associated with the landfill;

(b) Landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes generated by the industrial or commercial operation directly associated with the landfill and also receives other wastes provided the other wastes received for disposal are generated by a facility that is subject to the same provisions in 40 CFR Subchapter N as the industrial or commercial operation or the other wastes received are of similar nature to the wastes generated by the industrial or commercial operation;

(c) Landfills operated in conjunction with Centralized Waste Treatment (CWT) facilities subject to 40 CFR Part 437 so long as the CWT facility commingles the landfill wastewater with other non-landfill wastewater for discharge. A landfill directly associated with a CWT facility is subject to this part if the CWT facility discharges landfill wastewater separately from other CWT wastewater or commingles the wastewater from its landfill only with wastewater from other landfills; or

(d) Landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes from public service activities so long as the company owning the landfill does not receive a fee or other remuneration for the disposal service.

For the discharges subject to the numeric effluent limitations, monitoring for the specified parameters is required once/year during each year of the term of the permit.

6.L Sector L—Landfills, Land Application Sites and Open Dumps

6.L.1 Covered Storm Water Discharges

The requirements in Part 6.L apply to storm water discharges associated with industrial activity from Landfills and Land Application Sites and Open Dumps as identified by the Activity Codes specified under Sector L in Table 1–1 of Part 1.2.1.

6.L.2 Industrial Activities Covered by Sector L

This permit may authorize storm water discharges for Sector L facilities associated with waste disposal at landfills, land application sites and open dumps that receive or have received industrial waste, including sites subject to regulation under Subtitle D of RCRA.

6.L.3 Limitations on Coverage

6.L.3.1 Prohibition of Non-Storm Water Discharges. (See also Part 1.2.3.1)

Not authorized by this permit: leachate, gas collection condensate, drained free liquids, contaminated ground water, laboratory wastewater, and contact washwater from washing truck and railcar exteriors and surface areas which have come in direct contact with solid waste at the landfill facility.

6.L.4 Definitions

6.L.4.1 *Contaminated storm water*—storm water which comes in direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater. Some specific areas of a landfill that may produce contaminated storm water include (but are not limited to): the open face of an active landfill with exposed waste (no cover added); the areas around wastewater treatment operations; trucks, equipment or machinery that has been in direct contact with the waste; and waste dumping areas.

6.L.4.2 *Drained free liquids*—aqueous wastes drained from waste containers (e.g., drums, etc.) prior to landfilling.

6.L.4.3 *Landfill wastewater*—as defined in 40 CFR Part 445 (Landfills Point Source Category) all wastewater

associated with, or produced by, landfilling activities except for sanitary wastewater, non-contaminated storm water, contaminated groundwater, and wastewater from recovery pumping wells. Landfill process wastewater includes, but is not limited to, leachate, gas collection condensate, drained free liquids, laboratory derived wastewater, contaminated storm water and contact washwater from washing truck, equipment and railcar exteriors and surface areas which have come in direct contact with solid waste at the landfill facility.

6.L.4.4 *Leachate*—liquid that has passed through or emerged from solid waste and contains soluble, suspended or miscible materials removed from such waste.

6.L.4.5 *Non-contaminated storm water*—storm water which does not come in direct contact with landfill wastes, the waste handling and treatment areas, or landfill wastewater. Non-contaminated storm water includes storm water which flows off the cap, cover, intermediate cover, daily cover, and/or final cover of the landfill.

6.L.5 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.L.5.1 *Drainage Area Site Map.* (See also Part 4.2.2.3)

Identify where any of the following may be exposed to precipitation/surface runoff: Active and closed landfill cells or trenches, active and closed land application areas, locations where open dumping is occurring or has occurred, locations of any known leachate springs or other areas where uncontrolled leachate may commingle with runoff, leachate collection and handling systems.

6.L.5.2 *Summary of Potential Pollutant Sources.* (See also Part 4.2.4)

Describe the following sources and activities that have potential pollutants associated with them: fertilizer, herbicide and pesticide application; earth/soil moving; waste hauling and loading/unloading; outdoor storage of significant materials including daily, interim and final cover material stockpiles as well as temporary waste storage areas; exposure of active and inactive landfill and land application areas; uncontrolled leachate flows;

failure or leaks from leachate collection and treatment systems.

6.L.5.3 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

As part of your good housekeeping program, consider providing protected storage areas for pesticides, herbicides, fertilizer and other significant materials.

6.L.5.4 *Preventative Maintenance Program.* (See also Part 4.2.7.1)

As part of your preventive maintenance program, maintain: all containers used for outdoor chemical/significant materials storage to prevent leaking; all elements of leachate collection and treatment systems to prevent commingling of leachate with storm water; the integrity and effectiveness of any intermediate or final cover (including repairing the cover as necessary to minimize the effects of settlement, sinking and erosion).

6.L.5.5 *Inspections.*

6.L.5.5.1 *Inspections of Active Sites.* (See also Part 4.2.7.2.1.5) Inspect operating landfills, open dumps and land application sites at least once every 7 days. Focus on areas of landfills that have not yet been finally stabilized, active land application areas, areas used for storage of material/wastes that are exposed to precipitation, stabilization and structural control measures, leachate collection and treatment systems, and locations where equipment and waste trucks enter/exit the site. Ensure that sediment and erosion control measures are operating properly. For stabilized sites and areas where land application has been completed, or where the climate is seasonally arid (annual rainfall averages from 0 to 10 inches) or semi-arid (annual rainfall averages from 10 to 20 inches), conduct inspections at least once every month.

6.L.5.5.2 *Inspections of Inactive Sites.* (See also Part 4.2.7.2.1.5) Inspect inactive landfills, open dumps and land application sites at least quarterly. Qualified personnel must inspect landfill (or open dump) stabilization and structural erosion control measures and leachate collection and treatment systems, and all closed land application areas.

6.L.5.6 *Recordkeeping and Internal Reporting.* Implement a tracking system for the types of wastes disposed of in each cell or trench of a landfill or open dump. For land application sites, track

the types and quantities of wastes applied in specific areas.

6.L.5.7 *Non-Storm Water Discharge Test Certification.* (See also Part 4.) The discharge test and certification must also be conducted for the presence of leachate and vehicle washwater.

6.L.5.8 *Sediment and Erosion Control Plan.* (See also Part 4.2.7.2.2.1) Provide temporary stabilization (e.g., consider temporary seeding, mulching

and placing geotextiles on the inactive portions of stockpiles); for materials stockpiled for daily, intermediate and final cover; for inactive areas of the landfill or open dump; for any landfill or open dump area that have gotten final covers but where vegetation has yet to established itself; and where waste application has been completed at land application sites but final vegetation has not yet been established.

6.L.5.9 *Comprehensive Site Compliance Evaluation.* (See also Part 4.9.2) Evaluate areas contributing to a storm water discharge associated with industrial activities at landfills, open dumps and land application sites for evidence of, or the potential for, pollutants entering the drainage system.

6.L.6 Numeric Limitations, Monitoring and Reporting Requirements. (See also Part 5)

TABLE L-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK AND COMPLIANCE MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation ²
Section of Permit Affected/Supplemental Requirements			
All Landfill, Land Application Sites and Open Dumps (Industrial Activity Code "LF").	Total Suspended Solids (TSS).	100 mg/L.	
All Landfill, Land Application Sites and Open Dumps, Except Municipal Solid Waste Landfill (MSWLF) Areas Closed in Accordance with 40 CFR 258.60 (Industrial Activity Code "LF").	Total Recoverable Iron	1.0mg/L.	
All Landfills Which are Subject to the Requirements of 40 CFR Part 445 Subpart B (Industrial Activity Code "LF").	BOD5		140 mg/1, daily max. 37 mg/1, monthly ave maximum
	TSS		88 mg/1, daily max. 27 mg/1, monthly ave maximum.
	Ammonia		10 mg/1, daily max. 4.9 mg/1, monthly ave maximum.
	Alpha Terpeneol		0.033 mg/1, daily max. 0.016 mg/1, monthly ave maximum.
	Benzoic Acid		0.12 mg/1, daily max. 0.071 mg/1, monthly ave maximum.
	p-Cresol		0.025 mg/1, daily max. 0.014 mg/1, monthly ave maximum.
	Phenol		0.026 mg/1, daily max. 0.015 mg/1, monthly ave maximum.
	Zinc (Total)		0.20 mg/1, daily max. 0.11 mg/1, monthly ave maximum.
	pH		Within the range of 6–9 pH units.

¹ These benchmark monitoring cutoff concentrations apply to storm water discharges associated with industrial activity other than contaminated storm water discharges from landfills subject to the numeric effluent limitations set forth in Table L-1. Monitor once/quarter for the year 2 and year 4 monitoring years.

² As set forth at 40 CFR Part 445 Subpart B, these numeric limitations apply to contaminated storm water discharges from MSWLFs which have not been closed in accordance with 40 CFR 258.60, and contaminated storm water discharges from those landfills which are subject to the provisions of 40 CFR Part 257 except for discharges from any of facilities described in (a) through (d) below:

- (a) landfills operated in conjunction with other industrial or commercial operations when the landfill only receives wastes generated by the industrial or commercial operation directly associated with the landfill;
- (b) landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes generated by the industrial or commercial operation directly associated with the landfill and also receives other wastes provided the other wastes received for disposal are generated by a facility that is subject to the same provisions in 40 CFR Subchapter N as the industrial or commercial operation or the other wastes received are of similar nature to the wastes generated by the industrial or commercial operation;
- (c) landfills operated in conjunction with Centralized Waste Treatment (CWT) facilities subject to 40 CFR Part 437 so long as the CWT facility commingles the landfill wastewater with other non-landfill wastewater for discharge. A landfill directly associated with a CWT facility is subject to this part if the CWT facility discharges landfill wastewater separately from other CWT wastewater or commingles the wastewater from its landfill only with wastewater from other landfills; or
- (d) landfills operated in conjunction with other industrial or commercial operations when the landfill receives wastes from public service activities so long as the company owning the landfill does not receive a fee or other remuneration for the disposal service.

For the discharges subject to the numeric effluent limitations, monitoring for the specified parameters is required once/year during each year of the term of the permit.

6.M Sector M—Automobile Salvage Yards

6.M.1 Covered Storm Water Discharges

The requirements in Part 6.M apply to storm water discharges associated with industrial activity from Automobile Salvage Yards as identified by the Activity Code specified under Sector M in Table 1–1 of Part 1.2.1.

6.M.2 Industrial Activities Covered by Sector M

The types of activities that permittees under Sector M are primarily engaged in are dismantling or wrecking used motor vehicles for parts recycling/resale and for scrap.

6.M.3 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.M.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Indicate the

location of each monitoring point, and estimate the total acreage used for industrial activity including, but not limited to, dismantling, storage and maintenance of used motor vehicle parts. Also identify where any of the following may be exposed to precipitation/surface runoff:

Dismantling areas; parts (e.g., engine blocks, tires, hub caps, batteries, hoods, mufflers) storage areas; liquid storage tanks and drums for fuel and other fluids.

6.M.3.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Assess the potential for the following to contribute pollutants to storm water discharges: Vehicle storage areas; dismantling areas; parts storage area (e.g., engine blocks, tires, hub caps, batteries, hoods, mufflers); fueling stations.

6.M.3.3 *Spill and Leak Prevention Procedures.* (See also Part 4.2.7.2.1.4) Drain vehicles intended to be dismantled of all fluids upon arrival at the site (or as soon thereafter as feasible); or employ some other equivalent means to prevent spills/leaks.

6.M.3.4 *Inspections.* (See also Part 4.2.7.2.1.5) Immediately (or as soon thereafter as feasible) inspect vehicles

arriving at the site for leaks. Inspect quarterly for signs of leakage, all equipment containing oily parts, hydraulic fluids or any other types of fluids. Also inspect quarterly for signs of leakage, all vessels and areas where fluids are stored, including, but not limited to, brake fluid, transmission fluid, radiator water and antifreeze.

6.M.3.5 *Employee Training.* (See also Part 4.2.7.2.1.6) If applicable to your facility, address the following areas (at a minimum) in your employee training program: Proper handling (collection, storage, and disposal) of oil, used mineral spirits, anti-freeze and solvents.

6.M.3.6 *Management of Runoff.* (See also Part 4.2.7.2.2.2) Consider the following management practices: Berms or drainage ditches on the property line (to help prevent run-on from neighboring properties); berms for uncovered outdoor storage of oily parts, engine blocks and above-ground liquid storage; installation of detention ponds; and the installation of filtering devices and oil/water separators.

6.M.4 Monitoring and Reporting Requirements. (See also Part 5)

TABLE M–1.—SECTOR-SPECIFIC NUMERIC LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation
Sector of Permit Affected/Supplemental Requirements			
Automobile Salvage Yards (SIC 5015)	Total Suspended Solids (TSS). Total Recoverable Aluminum. Total Recoverable Iron Total Recoverable Lead	100.0 mg/L. 0.75 mg/L. 1.0 mg/L. 0.0816 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 monitoring years.

6.N Sector N—Scrap Recycling and Waste Recycling Facilities

6.N.1 Covered Storm Water Discharges

The requirements in Part N apply to storm water discharges associated with industrial activity from Scrap Recycling and Waste Recycling facilities as identified by the SIC Codes specified under Sector N in Table 1–1 of Part 1.2.1.

6.N.2 Industrial Activities Covered by Sector N

The types of activities that permittees under Sector N are primarily engaged in are:

6.N.2.1 processing, reclaiming and wholesale distribution of scrap and

waste materials such as ferrous and nonferrous metals, paper, plastic, cardboard, glass, animal hides;

6.N.2.2 reclaiming and recycling liquid wastes such as used oil, antifreeze, mineral spirits and industrial solvents.

6.N.3 Coverage Under This Permit

Separate permit requirements have been established for recycling facilities that only receive source-separated recyclable materials primarily from non-industrial and residential sources (i.e., common consumer products including paper, newspaper, glass, cardboard, plastic containers, aluminum and tin cans). This includes recycling facilities commonly referred to as material recovery facilities (MRF).

6.N.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.2.2) Not covered by this permit: non-storm water discharges from turnings containment areas (see also Part 6.N.5.1.3). Discharges from containment areas in the absence of a storm event are prohibited unless covered by a separate NPDES permit.

6.N.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4 of the MSGP. Part 6.N.4.1 contains a requirement that applies to all recycling facilities and is followed by Parts 6.N.4.2 to 6.N.4.4.4, which have requirements for specific types of

recycling facilities. Implement and describe in your SWPPP a program to address those items that apply. Included are lists of BMP options which, along with any functional equivalents, should be considered for implementation. Selection or deselection of a particular BMP or approach is up to the best professional judgement of the operator, as long as the objective of the requirement is met.

6.N.4.1 Drainage Area Site Map.
(See also Part 4.2.2.3)

Identify the locations of any of the following activities or sources which may be exposed to precipitation/surface runoff: scrap and waste material storage, outdoor scrap and waste processing equipment, and containment areas for turnings exposed to cutting fluids.

6.N.4.2 Scrap and Waste Recycling Facilities (Non-Source Separated, Non-Liquid Recyclable Materials). Requirements for facilities that receive, process and do wholesale distribution of non-liquid recyclable wastes (e.g., ferrous and nonferrous metals, plastics, glass, cardboard and paper). These facilities may receive both non-recyclable and recyclable materials. This section is not intended for those facilities that only accept recyclables from primarily non-industrial and residential sources.

6.N.4.2.1 Inbound Recyclable and Waste Material Control Program. Minimize the chance of accepting materials that could be significant sources of pollutants by conducting inspections of inbound recyclables and waste materials. BMP options: (a) Provide information/education to suppliers of scrap and recyclable waste materials on draining and properly disposing of residual fluids (e.g., from vehicles and equipment engines, radiators and transmissions, oil filled transformers and individual containers or drums), prior to delivery to your facility; (b) procedures to minimize the potential of any residual fluids from coming into contact with precipitation/runoff; (c) procedures for accepting scrap lead-acid batteries (additional requirements for the handling, storage and disposal or recycling of batteries are contained in the scrap lead-acid battery program provisions in N.5.1.6); (d) training targeted for those personnel engaged in the inspection and acceptance of inbound recyclable materials. In addition, (e) liquid wastes, including used oil, must be stored in materially compatible and non-leaking containers and disposed or recycled in accordance with RCRA.

6.N.4.2.2 Scrap and Waste Material Stockpiles/Storage (Outdoor). Minimize contact of storm water runoff with

stockpiled materials, processed materials and non-recyclable wastes. BMP options: (a) Permanent or semi-permanent covers; (b) to facilitate settling or filtering of pollutants: sediment traps, vegetated swales and strips, catch basin filters and sand filters; (c) divert runoff away from storage areas via dikes, berms, containment trenches, culverts and surface grading; (d) silt fencing; (e) oil/water separators, sumps and dry absorbents for areas where potential sources of residual fluids are stockpiled (e.g., automobile engine storage areas).

6.N.4.2.3 Stockpiling of Turnings Exposed to Cutting Fluids (Outdoor). Minimize contact of surface runoff with residual cutting fluids. BMP options (use singularly or in combination): (a) Store all turnings exposed to cutting fluids under some form of permanent or semi-permanent cover. Storm water discharges from these areas are permitted provided the runoff is first treated by an oil/water separator or its equivalent. Identify procedures to collect, handle and dispose/recycle residual fluids which may be present; (b) establish dedicated containment areas for all turnings that have been exposed to cutting fluids. Storm water runoff from these areas can be discharged provided: The containment areas are constructed of either concrete, asphalt or other equivalent types of impermeable material; there is a barrier around the perimeter of the containment areas (e.g., berms, curbing, elevated pads, etc.) to prevent contact with storm water run-on; there is a drainage collection system for runoff generated from containment areas; you have a schedule to maintain the oil/water separator (or its equivalent); and you identify procedures for properly disposing or recycling collected residual fluids.

6.N.4.2.4 Scrap and Waste Material Stockpiles/Storage (Covered or Indoor Storage). Minimize contact of residual liquids and particulate matter from materials stored indoors or under cover with surface runoff. BMP options: (a) Good housekeeping measures including the use of dry absorbent or wet vacuuming to contain or dispose/recycle residual liquids originating from recyclable containers; (b) not allowing washwater from tipping floors or other processing areas to discharge to the storm sewer system; (c) disconnect or seal off all floor drains connected to the storm sewer system.

6.N.4.2.5 Scrap and Recyclable Waste Processing Areas. Minimize surface runoff from coming in contact with scrap processing equipment. Pay attention to operations that generate

visible amounts of particulate residue (e.g., shredding) to minimize the contact of accumulated particulate matter and residual fluids with runoff (i.e., through good housekeeping, preventive maintenance, etc.). BMP options: (a) Regularly inspect equipment for spills/leaks, and malfunctioning/worn/corroded parts or equipment; (b) a preventive maintenance program for processing equipment; (c) use of dry-absorbents or other cleanup practices to collect and dispose/recycle spilled/leaking fluids; (e) on unattended hydraulic reservoirs over 150 gallons in capacity, install such protection devices as low-level alarms or other equivalent devices, or, alternatively, secondary containment that can hold the entire volume of the reservoir; (f) containment or diversion structures such as dikes, berms, culverts, trenches, elevated concrete pads, grading to minimize contact of storm water runoff with outdoor processing equipment or stored materials; (g) oil/water separators or sumps; (h) permanent or semi-permanent covers in processing areas where there are residual fluids and grease; (i) retention/detention ponds or basins; sediment traps, vegetated swales or strips (for pollutant settling/filtration); (j) catch basin filters or sand filters.

6.N.4.2.6 Scrap Lead-Acid Battery Program. Properly handle, store and dispose of scrap lead-acid batteries. BMP options: (a) Segregate scrap lead-acid batteries from other scrap materials; (b) proper handling, storage and disposal of cracked or broken batteries; (c) collect and dispose leaking lead-acid battery fluid; (d) minimize/eliminate (if possible) exposure of scrap lead-acid batteries to precipitation or runoff; (e) employee training for the management of scrap batteries.

6.N.4.2.7 Spill Prevention and Response Procedures. (See also Part 4.2.7.2.1.4) Minimize storm water contamination at loading/unloading areas, and from equipment or container failures. BMP options: (a) Prevention and response measures for areas that are potential sources of fluid leaks/spills; (b) immediate containment and clean up of spills/leaks. If malfunctioning equipment is responsible for the spill/leak, repairs should also be conducted as soon as possible; (c) cleanup measures including the use of dry absorbents. If this method is employed, there should be an adequate supply of dry absorbent materials kept onsite and used absorbent must be properly disposed of; (d) store drums containing liquids—especially oil and lubricants—either: Indoors, in a bermed area, in overpack containers or spill pallets, or

in other containment devices; (e) install overflow prevention devices on fuel pumps or tanks; (f) place drip pans or equivalent measures under leaking stationary equipment until the leak is repaired. The drip pans should be inspected for leaks and potential overflow and all liquids must be properly disposed of (as per RCRA); (g) install alarms and/or pump shut off systems on outdoor equipment with hydraulic reservoirs exceeding 150 gallons in the event of a line break. Alternatively, a secondary containment system capable of holding the entire contents of the reservoir plus room for precipitation can be used.

6.N.4.2.8 Quarterly Inspection Program. (See also Part 4.2.7.2.1.5) Inspect all designated areas of the facility and equipment identified in the plan quarterly.

6.N.4.2.9 Supplier Notification Program. As appropriate, notify major suppliers which scrap materials will not be accepted at the facility or are only accepted under certain conditions.

6.N.4.3 Waste Recycling Facilities (Liquid Recyclable Materials).

6.N.4.3.1 Waste Material Storage (Indoor). Minimize/eliminate contact between residual liquids from waste materials stored indoors and surface runoff. The plan may refer to applicable portions of other existing plans such as SPCC plans required under 40 CFR Part 112. BMP options: (a) procedures for material handling (including labeling and marking); (b) clean up spills/leaks with dry-absorbent materials or a wet vacuum system; (c) appropriate containment structures (trenching, curbing, gutters, etc.); (d) a drainage system, including appurtenances (e.g., pumps or ejectors, manually operated valves), to handle discharges from diked or bermed areas. Drainage should be discharged to an appropriate treatment facility, sanitary sewer system, or otherwise disposed of properly. These discharges may require coverage under a separate NPDES wastewater permit or industrial user permit under the pretreatment program.

6.N.4.3.2 Waste Material Storage (Outdoor). Minimize contact between

stored residual liquids and precipitation or runoff. The plan may refer to applicable portions of other existing plans such as SPCC plans required under 40 CFR Part 112. Discharges of precipitation from containment areas containing used oil must also be in accordance with applicable sections of 40 CFR Part 112. BMP options: (a) appropriate containment structures (e.g., dikes, berms, curbing, pits) to store the volume of the largest tank with sufficient extra capacity for precipitation; (b) drainage control and other diversionary structures; (c) for storage tanks, provide corrosion protection and/or leak detection systems; (d) use dry-absorbent materials or a wet vacuum system to collect spills.

6.N.4.3.3 Trucks and Rail Car Waste Transfer Areas. Minimize pollutants in discharges from truck and rail car loading/unloading areas. Include measures to clean up minor spills/leaks resulting from the transfer of liquid wastes. BMP options: (a) containment and diversionary structures to minimize contact with precipitation or runoff; (b) use dry-clean up methods, wet vacuuming, roof coverings, or runoff controls.

6.N.4.3.4 Quarterly Inspections. (See also Part 4.2.7.2.1.5) At a minimum, the inspections must also include all areas where waste is generated, received, stored, treated or disposed and that are exposed to either precipitation or storm water runoff.

6.N.4.4 Recycling Facilities (Source Separated Materials). The following identifies considerations for facilities that receive only source-separated recyclables, primarily from non-industrial and residential sources.

6.N.4.4.1 Inbound Recyclable Material Control. Minimize the chance of accepting non-recyclables (e.g., hazardous materials) which could be a significant source of pollutants by conducting inspections of inbound materials. BMP options: (a) information/education measures to inform suppliers of recyclables which materials are acceptable and which are not; (b) training drivers responsible for pickup of recycled material; (c) clearly marking

public drop-off containers regarding which materials can be accepted; (d) reject non-recyclable wastes or household hazardous wastes at the source; (e) procedures for handling and disposal of non-recyclable material.

6.N.4.4.2 Outdoor Storage. Minimize exposure of recyclables to precipitation and runoff. Use good housekeeping measures to prevent accumulation of particulate matter and fluids, particularly in high traffic areas. Other BMP options: (a) provide totally-enclosed drop-off containers for the public; (b) install a sump/pump with each container pit and treat or discharge collected fluids to a sanitary sewer system; (c) provide dikes and curbs for secondary containment (e.g., around bales of recyclable waste paper); (d) divert surface water runoff away from outside material storage areas; (e) provide covers over containment bins, dumpsters, roll-off boxes; (f) store the equivalent one days' volume of recyclable material indoors.

6.N.4.4.3 Indoor Storage and Material Processing. Minimize the release of pollutants from indoor storage and processing areas. BMP options: (a) schedule routine good housekeeping measures for all storage and processing areas; (b) prohibit tipping floor washwater from draining to the storm sewer system; (c) provide employee training on pollution prevention practices.

6.N.4.4.4 Vehicle and Equipment Maintenance. BMP options for those areas where vehicle and equipment maintenance are occurring outdoors: (a) prohibit vehicle and equipment washwater from discharging to the storm sewer system; (b) minimize or eliminate outdoor maintenance areas whenever possible; (c) establish spill prevention and clean-up procedures in fueling areas; (d) avoid topping off fuel tanks; (e) divert runoff from fueling areas; (f) store lubricants and hydraulic fluids indoors; (g) provide employee training on proper handling, storage of hydraulic fluids and lubricants.

6.N.5 Monitoring and Reporting Requirements. (See also Part 5)

TABLE N-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation
Part of Permit Affected/Supplemental Requirements			
Scrap Recycling Facility (SIC 5093)	Chemical Oxygen Demand (COD). Total Suspended Solids (TSS). Total Recoverable Aluminum. Total Recoverable Copper Total Recoverable Iron Total Recoverable Lead Total Recoverable Zinc	120 mg/L. 100 mg/L. 0.75 mg/L. 0.0636 mg/L. 1.0 mg/L. 0.0816 mg/L. 0.117 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.O Sector O—Steam Electric Generating Facilities

6.O.1 Covered Storm Water Discharges

The requirements in Part 6.O apply to storm water discharges associated with industrial activity from Steam Electric Power Generating Facilities as identified by the Activity Code specified under Sector O in Table 1–1 of Part 1.2.1.

6.O.2 Industrial Activities Covered by Sector O

This permit authorizes storm water discharges from the following industrial activities at Sector O facilities:

6.O.2.1 Steam electric power generation using coal, natural gas, oil, nuclear energy, etc. to produce a steam source, including coal handling areas;

6.O.2.2 Coal pile runoff, including effluent limitations established by 40 CFR Part 423;

6.O.2.3 Dual fuel co-generation facilities.

6.O.3 Limitations on Coverage

6.O.3.1 *Prohibition of Non-Storm Water Discharges.* Not covered by this permit: non-storm water discharges subject to effluent limitations guidelines.

6.O.3.2 *Prohibition of Storm Water Discharges.* Not covered by this permit: storm water discharges from ancillary facilities (e.g., fleet centers, gas turbine stations and substations) that are not contiguous to a steam electric power generating facility; and heat capture co-generation facilities.

6.O.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.O.4.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify the locations of any of the following

activities or sources which may be exposed to precipitation / surface runoff: storage tanks, scrap yards, general refuse areas; short and long term storage of general materials (including but not limited to: supplies, construction materials, paint equipment, oils, fuels, used and unused solvents, cleaning materials, paint, water treatment chemicals, fertilizer and pesticides); landfills, construction sites; stock piles areas (e.g., coal or limestone piles).

6.O.4.2 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.O.4.2.1 *Fugitive Dust Emissions.* Describe and implement measures that prevent or minimize fugitive dust emissions from coal handling areas. Consider such procedures to minimize the tracking of coal dust offsite as installing specially designed tires, or washing vehicles in a designated area before they leave the site and controlling the wash water.

6.O.4.2.2 *Delivery Vehicles.* Describe and implement measures that prevent or minimize contamination of storm water runoff from delivery vehicles arriving at the plant site. Consider the following: procedures to inspect delivery vehicles arriving at the plant site and ensure overall integrity of the body or container; and procedures to deal with leakage / spillage from vehicles or containers.

6.O.4.2.3 *Fuel Oil Unloading Areas.* Describe and implement measures that prevent or minimize contamination of precipitation / surface runoff from fuel oil unloading areas. Consider, at a minimum (or their equivalents): using containment curbs in unloading areas; having personnel familiar with spill prevention and response procedures present during deliveries to ensure that any leaks / spills are immediately contained and cleaned up; using spill and overflow protection (e.g., drip pans,

drip diapers or other containment devices placed beneath fuel oil connectors to contain potential spillage during deliveries or from leaks at the connectors).

6.O.4.2.4 *Chemical Loading / Unloading.* Describe and implement measures that prevent or minimize contamination of precipitation / surface runoff from chemical loading / unloading areas. Consider, at a minimum (or their equivalents): using containment curbs at chemical loading / unloading areas to contain spill; having personnel familiar with spill prevention and response procedures present during deliveries to ensure that any leaks / spills are immediately contained and cleaned up; and load / unload in covered areas and store chemicals indoors.

6.O.4.2.5 *Miscellaneous Loading / Unloading Areas.* Describe and implement measures that prevent or minimize contamination of precipitation / surface runoff from loading / unloading areas. Consider, at a minimum (or their equivalents): covering the loading area; grading, berming, or curbing around the loading area to divert run-on; or locating the loading / unloading equipment and vehicles so leaks are contained in existing containment and flow diversion systems.

6.O.4.2.6 *Liquid Storage Tanks.* Describe and implement measures that prevent or minimize contamination of surface runoff from above ground liquid storage tanks. Consider using, at a minimum (or their equivalents): protective guards around tank; containment curbs; spill and overflow protection; and dry cleanup methods.

6.O.4.2.7 *Large Bulk Fuel Storage Tanks.* Describe and implement measures that prevent or minimize contamination of surface runoff from large bulk fuel storage tanks. Consider,

at a minimum, using containment berms (or its equivalent). You must also comply with applicable State and Federal laws, including Spill Prevention Control and Countermeasures (SPCC).

6.O.4.2.8 Spill Reduction Measures. Describe and implement measures to reduce the potential for an oil / chemical spill or reference the appropriate Part of your SPCC plan. At a minimum, visually inspect on a weekly basis, the structural integrity of all above ground tanks, pipelines, pumps and other related equipment, and effect any necessary repairs immediately.

6.O.4.2.9 Oil Bearing Equipment in Switchyards. Describe and implement measures that prevent or minimize contamination of surface runoff from oil bearing equipment in switchyard areas. Consider using level grades and gravel surfaces to retard flows and limit the spread of spills or collecting runoff in perimeter ditches.

6.O.4.2.10 Residue Hauling Vehicles. Inspect all residue hauling vehicles for proper covering over the load, adequate gate sealing and overall integrity of the container body. Repair as soon as practicable, vehicles without load covering or adequate gate sealing, or with leaking containers or beds.

6.O.4.2.11 Ash Loading Areas. Describe and implement procedures to reduce or control the tracking of ash/ residue from ash loading areas. Where practicable, clear the ash building floor and immediately adjacent roadways of spillage, debris and excess water before departure of each loaded vehicle.

6.O.4.2.12 Areas Adjacent to Disposal Ponds or Landfills. Describe and implement measures that prevent or minimize contamination of surface runoff from areas adjacent to disposal ponds or landfills. Develop procedures to reduce ash residue that may be tracked on to access roads traveled by residue handling vehicles, and reduce ash residue on exit roads leading into and out of residue handling areas.

6.O.4.2.13 Landfills, Scrap Yards, Surface Impoundments, Open Dumps, General Refuse Sites.

Address these areas in your SWPPP and include appropriate BMPs as referred to in Part 4.

6.O.4.2.14 Vehicle Maintenance Activities. For vehicle maintenance activities performed on the plant site, use the applicable BMPs outlined in Part 6.P.

6.O.4.2.15 Material Storage Areas. Describe and implement measures that prevent or minimize contamination of

storm water runoff from material storage areas (including areas used for temporary storage of miscellaneous products and construction materials stored in lay-down areas). Consider using (or their equivalents): Flat yard grades; collecting runoff in graded swales or ditches; erosion protection measures at steep outfall sites (e.g., concrete chutes, riprap, stilling basins); covering lay-down areas; storing materials indoors; and covering materials temporarily with polyethylene, polyurethane, polypropylene or hypalon. Storm water run-on may be minimized by constructing an enclosure or building a berm around the area.

6.O.4.3 Comprehensive Site Compliance Evaluation. (See also Part 4.9.3) As part of your evaluation, inspect the following areas on a monthly basis: Coal handling areas, loading/unloading areas, switchyards, fueling areas, bulk storage areas, ash handling areas, areas adjacent to disposal ponds and landfills, maintenance areas, liquid storage tanks, and long term and short term material storage areas.

6.O.5 Monitoring and Reporting Requirements. (See also Part 5)

TABLE O-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric Limitation ²
Part of Permit Affected/Supplemental Requirements			
Steam Electric Generating Facilities (Industrial Activity Code "SE").	Total Recoverable Iron	1.0 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

² Note that the numeric effluent limitation guidelines for coal pile runoff at steam electric generating facilities have been adopted as a standard numeric limits for all coal pile runoff. See Part 5.1.3.

6.P Sector P—Land Transportation and Warehousing

6.P.1 Covered Storm Water Discharges

The requirements in Part 6.P apply to storm water discharges associated with industrial activity from Land Transportation and Warehousing facilities as identified by the Activity Code specified under Sector P in Table 1-1 of Part 1.2.1.

6.P.2 Industrial Activities Covered by Sector P

The types of activities that permittees under Sector P are primarily engaged in are:

6.P.2.1 vehicle and equipment maintenance (vehicle and equipment rehabilitation, mechanical repairs, painting, fueling and lubrication);

6.P.2.2 equipment cleaning.

6.P.3 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.P.3.1 Drainage Site Map. (See also Part 4.2.2.3) Identify the locations of any of the following activities or sources: Fueling stations; vehicle/equipment maintenance or cleaning areas; storage areas for vehicle/equipment with actual or potential fluid leaks; loading/unloading areas; areas where treatment, storage or disposal of wastes occur; liquid storage tanks; processing areas; storage areas; and all monitoring areas.

6.P.3.2 Potential Pollutant Sources. (See also Part 4.2.4) Describe and assess the potential for the following to

contribute pollutants to storm water discharges: Onsite waste storage or disposal; dirt/gravel parking areas for vehicles awaiting maintenance; and fueling areas.

6.P.3.3 Good Housekeeping Measures. (See also Part 4.2.7.2.1.1)

6.P.3.3.1 Vehicle and Equipment Storage Areas. Confine the storage of leaky or leak-prone vehicles/equipment awaiting maintenance to designated areas. Consider the following (or other equivalent measures): The use of drip pans under vehicles/equipment, indoor storage of vehicles and equipment, installation of berms or dikes, use of absorbents, roofing or covering storage areas, and cleaning pavement surfaces to remove oil and grease.

6.P.3.3.2 Fueling Areas. Implement and describe measures that prevent or

minimize contamination of storm water runoff from fueling areas. Consider the following (or other equivalent measures): covering the fueling area; using spill/overflow protection and cleanup equipment; minimizing storm water runoff to the fueling area; using dry cleanup methods; and treating and/or recycling collected storm water runoff.

6.P.3.3.3 Material Storage Areas. Maintain all material storage vessels (e.g., for used oil/oil filters, spent solvents, paint wastes, hydraulic fluids) to prevent contamination of storm water and plainly label them (e.g., "Used Oil," "Spent Solvents," etc.). Consider the following (or other equivalent measures): storing the materials indoors; installing berms/dikes around the areas; minimizing runoff of storm water to the areas; using dry cleanup methods; and treating and/or recycling collected storm water runoff.

6.P.3.3.4 Vehicle and Equipment Cleaning Areas. Implement and describe measures that prevent or minimize contamination of storm water runoff from all areas used for vehicle/equipment cleaning. Consider the following (or other equivalent measures): performing all cleaning operations indoors; covering the cleaning operation, ensuring that all washwater drains to a proper collection system (i.e., not the storm water drainage system unless NPDES permitted); treating and/or recycling collected storm water runoff, or other equivalent measures. Note: the discharge of vehicle/equipment washwater, including tank cleaning operations, are not authorized by this permit and must be covered under a separate NPDES permit or discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.

6.P.3.3.5 Vehicle and Equipment Maintenance Areas. Implement and describe measures that prevent or minimize contamination of storm water runoff from all areas used for vehicle/equipment maintenance. Consider the following (or other equivalent measures): performing maintenance activities indoors; using drip pans; keeping an organized inventory of materials used in the shop; draining all parts of fluid prior to disposal; prohibiting wet clean up practices if these practices would result in the discharge of pollutants to storm water drainage systems; using dry cleanup methods; treating and/or recycling collected storm water runoff, minimizing run on/runoff of storm water to maintenance areas.

6.P.3.3.6 Locomotive Sanding (Loading Sand for Traction) Areas. Consider the following (or other equivalent measures): covering sanding areas; minimizing storm water runoff; or appropriate sediment removal practices to minimize the offsite transport of sanding material by storm water.

6.P.3.4 Inspections. (See also Part 4.2.7.2.1.5) Inspect all the following areas/activities: storage areas for vehicles/equipment awaiting maintenance, fueling areas, indoor and outdoor vehicle/equipment maintenance areas, material storage areas, vehicle/equipment cleaning areas and loading/unloading areas.

6.P.3.5 Employee Training. (See also Part 4.2.7.2.1.6) Train personnel at least once a year and address the following, as applicable: used oil and spent solvent management; fueling procedures; general good housekeeping practices; proper painting procedures; and used battery management.

6.P.3.6 Vehicle and Equipment Washwater Requirements. (See also Part 4.4) Attach to or reference in your SWPPP, a copy of the NPDES permit issued for vehicle/equipment washwater or, if an NPDES permit has not been issued, a copy of the pending application. If an industrial user permit is issued under a pretreatment program, attach a copy to your SWPPP. In any case, address all non-storm water permit conditions or pretreatment conditions in your SWPPP. If washwater is handled in another manner (e.g., hauled offsite), describe the disposal method and attach all pertinent documentation/information (e.g., frequency, volume, destination, etc.) in the plan.

6.Q Sector Q—Water Transportation

6.Q.1 Covered Storm Water Discharges

The requirements in Part 6.Q apply to storm water discharges associated with industrial activity from Water Transportation facilities as identified by the Activity Code specified under Sector Q in Table 1–1 of Part 1.2.1.

6.Q.2 Industrial Activities Covered by Sector Q

The requirements listed under this Part apply to storm water discharges associated with the following activities:

6.Q.2.1 Water transportation facilities classified in SIC Code major group 44 that have vehicle (vessel) maintenance shops and/or equipment cleaning operations including:

6.Q.2.1.1 Water transportation industry includes facilities engaged in foreign or domestic transport of freight

or passengers in deep sea or inland waters;

6.Q.2.1.2 Marine cargo handling operations;

6.Q.2.1.3 Ferry operations;

6.Q.2.1.4 Towing and tugboat services;

6.Q.2.1.5 Marinas.

6.Q.3 Limitations on Coverage

6.Q.3.1 Prohibition of Non-Storm Water Discharges. (See also Part 1.2.3.1) Not covered by this permit: bilge and ballast water, sanitary wastes, pressure wash water and cooling water originating from vessels.

6.Q.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.Q.4.1 Drainage Area Site Map. (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: fueling; engine maintenance/repair; vessel maintenance/repair; pressure washing; painting; sanding; blasting; welding; metal fabrication; loading/unloading areas; locations used for the treatment, storage or disposal of wastes; liquid storage tanks; liquid storage areas (e.g., paint, solvents, resins); and material storage areas (e.g., blasting media, aluminum, steel, scrap iron).

6.Q.4.2 Summary of Potential Pollutant Sources. (See also Part 4.2.4) Describe the following additional sources and activities that have potential pollutants associated with them: outdoor manufacturing or processing activities (i.e., welding, metal fabricating); and significant dust or particulate generating processes (e.g., abrasive blasting, sanding, painting).

6.Q.4.3 Good Housekeeping Measures. (See also Part 4.2.7.2.1.1)

6.Q.4.3.1 Pressure Washing Area. If pressure washing is used to remove marine growth from vessels, the discharge water must be permitted by a separate NPDES permit. Describe in the SWPPP: the measures to collect or contain the discharges from the pressures washing area; the method for the removal of the visible solids; the methods of disposal of the collected solids; and where the discharge will be released.

6.Q.4.3.2 Blasting and Painting Area. Implement and describe measures to prevent spent abrasives, paint chips and over spray from discharging into the receiving water or the storm sewer systems. Consider containing all blasting/painting activities or use other measures to prevent or minimize the discharge the contaminants (e.g.,

hanging plastic barriers or tarpaulins during blasting or painting operations to contain debris). Where necessary, regularly clean storm water conveyances of deposits of abrasive blasting debris and paint chips. Detail in the SWPPP any standard operating practices relating to blasting/painting (e.g., prohibiting uncontained blasting/painting over open water, or prohibiting blasting/painting during windy conditions which can render containment ineffective).

6.Q.4.3.3 Material Storage Areas. Store and plainly label all containerized materials (e.g., fuels, paints, solvents, waste oil, antifreeze, batteries) in a protected, secure location away from drains. Implement and describe measures to prevent or minimize the contamination of precipitation/surface runoff from the storage areas. Specify which materials are stored indoors and consider containment or enclosure for those stored outdoors. If abrasive blasting is performed, discuss the storage and disposal of spent abrasive materials generated at the facility. Consider implementing an inventory control plan to limit the presence of potentially hazardous materials onsite.

6.Q.4.3.4 Engine Maintenance and Repair Areas. Implement and describe measures to prevent or minimize the contamination of precipitation/surface runoff from all areas used for engine maintenance and repair. Consider the following (or their equivalents): performing all maintenance activities indoors; maintaining an organized inventory of materials used in the shop; draining all parts of fluid prior to disposal; prohibiting the practice of hosing down the shop floor; using dry cleanup methods; and treating and/or recycling storm water runoff collected from the maintenance area.

6.Q.4.3.5 Material Handling Area. Implement and describe measures to prevent or minimize the contamination of precipitation/surface runoff from material handling operations and areas (e.g., fueling, paint and solvent mixing, disposal of process wastewater streams from vessels). Consider the following (or their equivalents): covering fueling areas; using spill/overflow protection; mixing paints and solvents in a designated area (preferably indoors or under a shed); and minimize runoff of storm water to material handling areas.

6.Q.4.3.6 Drydock Activities. Describe your procedures for routinely maintaining/cleaning the drydock to prevent or minimize pollutants in storm water runoff. Address the cleaning of accessible areas of the drydock prior to flooding, and final cleanup following removal of the vessel and raising the dock. Include procedures for cleaning up oil, grease or fuel spills occurring on the drydock. Consider the following (or their equivalents): sweeping rather than hosing off debris/spent blasting material from accessible areas of the drydock prior to flooding, and having absorbent materials and oil containment booms readily available to contain/cleanup any spills.

6.Q.4.3.7 General Yard Area. Implement and describe a schedule for routine yard maintenance and cleanup. Regularly remove from the general yard area: scrap metal, wood, plastic, miscellaneous trash, paper, glass, industrial scrap, insulation, welding rods, packaging, etc.

6.Q.4.4 Preventative Maintenance. (See also Part 4.2.7.2.1.4) As part of your preventive maintenance program, perform timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators and sediment traps to

ensure that spent abrasives, paint chips and solids will be intercepted and retained prior to entering the storm drainage system) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters.

6.Q.4.5 Inspections. (See also Part 4.2.7.2.1.5) Include the following areas in all monthly inspections: pressure washing area; blasting, sanding and painting areas; material storage areas; engine maintenance/repair areas; material handling areas; drydock area; and general yard area.

6.Q.4.6 Employee Training. (See also Part 4.2.7.2.1.6) As part of your employee training program, address, at a minimum, the following activities (as applicable): used oil management; spent solvent management; disposal of spent abrasives; disposal of vessel wastewaters; spill prevention and control; fueling procedures; general good housekeeping practices; painting and blasting procedures; and used battery management.

6.Q.4.7 Comprehensive Site Compliance Evaluation. (See also Part 4.9) Conduct regularly scheduled evaluations at least once a year and address those areas contributing to a storm water discharge associated with industrial activity (e.g., pressure washing area, blasting/sanding areas, painting areas, material storage areas, engine maintenance/repair areas, material handling areas, and drydock area). Inspect these sources for evidence of, or the potential for, pollutants entering the drainage system.

6.Q.5 Monitoring and Reporting Requirements. (See also Part 5)

TABLE Q-1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation
Part of Permit Affected/Supplemental Requirements			
Water Transportation Facilities (SIC 4412-4499)	Total Recoverable Aluminum..	0.75 mg/L	
	Total Recoverable Iron.	1.0 mg/L	
	Total Recoverable Lead. ...	0.0816 mg/L	
	Total Recoverable Zinc.	0.117 mg/L	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.R Sector R—Ship and Boat Building or Repair Yards

6.R.1 Covered Storm Water Discharges

The requirements in Part 6.R apply to storm water discharges associated with industrial activity from Ship and Boat Building or Repair Yards as identified by the Activity Codes specified under Sector R in Table 1–1 of Part 1.2.1.

6.R.2 Industrial Activities Covered by Sector R

The types of activities that permittees under Sector R are primarily engaged in are:

6.R.2.1 Ship building and repairing and boat building and repairing³

6.R.3 Limitations on Coverage

6.R.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.3.1) Not covered by this permit: discharges containing bilge and ballast water, sanitary wastes, pressure wash water and cooling water originating from vessels.

6.R.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.R.4.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: fueling; engine maintenance/repair; vessel maintenance/repair; pressure washing; painting; sanding; blasting; welding; metal fabrication; loading/unloading areas; locations used for the treatment, storage or disposal of wastes; liquid storage tanks; liquid storage areas (e.g., paint, solvents, resins); and material storage areas (e.g., blasting media, aluminum, steel, scrap iron).

6.R.4.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the following additional sources and activities that have potential pollutants associated with them (if applicable): outdoor manufacturing/processing activities (e.g., welding, metal fabricating); and significant dust/particulate generating processes (e.g., abrasive blasting, sanding, painting).

6.R.4.3 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.R.4.3.1 *Pressure Washing Area.* If pressure washing is used to remove marine growth from vessels, the discharge water must be permitted as a process wastewater by a separate NPDES permit.

6.R.4.3.2 *Blasting and Painting Area.* Implement and describe measures to prevent spent abrasives, paint chips and over spray from discharging into the receiving water or the storm sewer systems. Consider containing all blasting/painting activities or use other measures to prevent the discharge of the contaminants (e.g., hanging plastic barriers or tarpaulins during blasting or painting operations to contain debris). Where necessary, regularly clean storm water conveyances of deposits of abrasive blasting debris and paint chips. Detail in the SWPPP any standard operating practices relating to blasting/painting (e.g., prohibiting uncontained blasting/painting over open water, or prohibiting blasting/painting during windy conditions which can render containment ineffective).

6.R.4.3.3 *Material Storage Areas.* Store and plainly label all containerized materials (e.g., fuels, paints, solvents, waste oil, antifreeze, batteries) in a protected, secure location away from drains. Implement and describe measures to prevent or minimize the contamination of precipitation/surface runoff from the storage areas. Specify which materials are stored indoors and consider containment or enclosure for those stored outdoors. If abrasive blasting is performed, discuss the storage and disposal of spent abrasive materials generated at the facility. Consider implementing an inventory control plan to limit the presence of potentially hazardous materials onsite.

6.R.4.3.4 *Engine Maintenance and Repair Areas.* Implement and describe measures to prevent or minimize the contamination of precipitation/surface runoff from all areas used for engine maintenance and repair. Consider the following (or their equivalents): performing all maintenance activities indoors; maintaining an organized inventory of materials used in the shop; draining all parts of fluid prior to disposal; prohibiting the practice of hosing down the shop floor; using dry cleanup methods; and treating and/or recycling storm water runoff collected from the maintenance area.

6.R.4.3.5 *Material Handling Area.* Implement and describe measures to prevent or minimize the contamination of precipitation/surface runoff from material handling operations and areas (e.g., fueling, paint and solvent mixing, disposal of process wastewater streams from vessels). Consider the following (or their equivalents): covering fueling areas; using spill/overflow protection; mixing paints and solvents in a designated area (preferably indoors or under a shed); and minimize runoff of storm water to material handling areas.

6.R.4.3.6 *Drydock Activities.* Describe your procedures for routinely maintaining/cleaning the drydock to prevent or minimize pollutants in storm water runoff. Address the cleaning of accessible areas of the drydock prior to flooding, and final cleanup following removal of the vessel and raising the dock. Include procedures for cleaning up oil, grease or fuel spills occurring on the drydock. Consider the following (or their equivalents): sweeping rather than hosing off debris/spent blasting material from accessible areas of the drydock prior to flooding, and having absorbent materials and oil containment booms readily available to contain/cleanup any spills.

6.R.4.3.7 *General Yard Area.* Implement and describe a schedule for routine yard maintenance and cleanup. Regularly remove from the general yard area: scrap metal, wood, plastic, miscellaneous trash, paper, glass, industrial scrap, insulation, welding rods, packaging, etc.

6.R.4.4 *Preventative Maintenance.* (See also Part 4.2.7.2.1.4) As part of your preventive maintenance program, perform timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators and sediment traps to ensure that spent abrasives, paint chips and solids will be intercepted and retained prior to entering the storm drainage system) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters.

6.R.4.5 *Inspections.* (See also Part 4.2.7.2.1.5) Include the following areas in all monthly inspections: pressure washing area; blasting, sanding and painting areas; material storage areas; engine maintenance/repair areas; material handling areas; drydock area; and general yard area.

6.R.4.6 *Employee Training.* (See also Part 4.2.7.2.1.6) As part of your employee training program, address, at a minimum, the following activities (as applicable): used oil management; spent solvent management; disposal of spent abrasives; disposal of vessel wastewaters; spill prevention and control; fueling procedures; general good housekeeping practices; painting and blasting procedures; and used battery management.

6.R.4.7 *Comprehensive Site Compliance Evaluation.* (See also Part 4.9) Conduct regularly scheduled evaluations at least once a year and address those areas contributing to a storm water discharge associated with industrial activity (e.g., pressure

³ According to the U.S. Coast Guard, a vessel 65 feet or greater in length is referred to as a ship, and a vessel smaller than 65 feet is a boat.

washing area, blasting/sanding areas, painting areas, material storage areas, engine maintenance/repair areas, material handling areas, and drydock area). They must be visually inspected for evidence of, or the potential for, pollutants entering the drainage system.

6.S Sector S—Air Transportation

6.S.1 Covered Storm Water Discharges

The requirements in Part 6.S apply to storm water discharges associated with industrial activity from Air Transportation facilities as identified by the SIC Codes specified under Sector S in Table 1–1 of Part 1.2.1.

6.S.2 Industrial Activities Covered by Sector S

The types of activities that permittees under Sector S are primarily engaged in are:

6.S.2.1 Air transportation, scheduled, and air courier;

6.S.2.2 Air transportation, non scheduled;

6.S.2.3 Airports; flying fields, except those maintained by aviation clubs; and airport terminal services including: air traffic control, except government; aircraft storage at airports; aircraft upholstery repair; airfreight handling at airports; airport hangar rental; airport leasing, if operating airport; airport terminal services; and hangar operations.

6.S.2.4 Airport and aircraft service and maintenance including: aircraft cleaning and janitorial service; aircraft servicing/repairing, except on a factory basis; vehicle maintenance shops; material handling facilities; equipment clearing operations; and airport and aircraft deicing/anti-icing.

Note: “deicing” will generally be used to imply both deicing (removing frost, snow or ice) and anti-icing (preventing accumulation of frost, snow or ice) activities, unless specific mention is made regarding anti-icing and/or deicing activities.

6.S.3 Limitations on Coverage

Only those portions of the facility that are involved in vehicle maintenance (including vehicle rehabilitation, mechanical repairs, painting, fueling and lubrication), equipment cleaning operations or deicing operations are addressed in Part 6.S.

6.S.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.3.1) Not covered by this permit: aircraft, ground vehicle, runway and equipment washwaters; and dry weather discharges of deicing chemicals. These discharges must be covered by a separate NPDES permit.

6.S.4 Special Conditions

6.S.4.1 *Hazardous Substances or Oil.* (See also Part 3.1) Each individual permittee is required to report spills equal to or exceeding the reportable quantity (RQ) levels specified at 40 CFR 110, 117 and 302 as described at Part 3.2. If an airport authority is the sole permittee, then the sum total of all spills at the airport must be assessed against the RQ. If the airport authority is a co-permittee with other deicing operators at the airport, such as numerous different airlines, the assessed amount must be the summation of spills by each co-permittee. If separate, distinct individual permittees exist at the airport, then the amount spilled by each separate permittee must be the assessed amount for the RQ determination.

6.S.5 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4 of the MSGP.

(See also Part 4.1) If an airport’s tenant has a SWPPP for discharges from their own areas of the airport, that SWPPP must be integrated with the plan for the entire airport. Tenants of the airport facility include air passenger or cargo companies, fixed based operators and other parties who have contracts with the airport authority to conduct business operations on airport property and whose operations result in storm water discharges associated with industrial activity.

6.S.5.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: aircraft and runway deicing operations; fueling stations; aircraft, ground vehicle and equipment maintenance/cleaning areas; storage areas for aircraft, ground vehicles and equipment awaiting maintenance.

6.S.5.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Include in your inventory of exposed materials a description of the potential pollutant sources from the following activities: aircraft, runway, ground vehicle and equipment maintenance and cleaning; aircraft and runway deicing operations (including apron and centralized aircraft deicing stations, runways, taxiways and ramps). If you use deicing chemicals, you must maintain a record of the types (including the Material Safety Data Sheets [MSDS]) used and the monthly quantities, either as measured or, in the absence of metering, as estimated to the best of your knowledge. This includes all deicing chemicals, not just glycols

and urea (e.g., potassium acetate), because large quantities of these other chemicals can still have an adverse impact on receiving waters. Tenants or other fixed-based operations that conduct deicing operations must provide the above information to the airport authority for inclusion in any comprehensive airport SWPPPs.

6.S.5.3 *Good Housekeeping Measures.* (See also 4.2.7)

6.S.5.3.1 *Aircraft, Ground Vehicle and Equipment Maintenance Areas.* Describe and implement measures that prevent or minimize the contamination of storm water runoff from all areas used for aircraft, ground vehicle and equipment maintenance (including the maintenance conducted on the terminal apron and in dedicated hangers). Consider the following practices (or their equivalents): performing maintenance activities indoors; maintaining an organized inventory of material used in the maintenance areas; draining all parts of fluids prior to disposal; preventing the practice of hosing down the apron or hanger floor; using dry cleanup methods; and collecting the storm water runoff from the maintenance area and providing treatment or recycling.

6.S.5.3.2 *Aircraft, Ground Vehicle and Equipment Cleaning Areas.* Clean equipment only in the areas identified in the SWPPP and site map and clearly demarcate these areas on the ground. Describe and implement measures that prevent or minimize the contamination of storm water runoff from cleaning areas.

6.S.5.3.3 *Aircraft, Ground Vehicle and Equipment Storage Areas.* Store all aircraft, ground vehicles and equipment awaiting maintenance in designated areas only. Consider the following BMPs (or their equivalents): storing aircraft and ground vehicles indoors; using drip pans for the collection of fluid leaks; and perimeter drains, dikes or berms surrounding the storage areas.

6.S.5.3.4 *Material Storage Areas.* Maintain the vessels of stored materials (e.g., used oils, hydraulic fluids, spent solvents, and waste aircraft fuel) in good condition, to prevent or minimize contamination of storm water. Also plainly label the vessels (e.g., “used oil,” “Contaminated Jet A,” etc.). Describe and implement measures that prevent or minimize contamination of precipitation/runoff from these areas. Consider the following BMPs (or their equivalents): storing materials indoors; storing waste materials in a centralized location; and installing berms/dikes around storage areas.

6.S.5.3.5 *Airport Fuel System and Fueling Areas.* Describe and implement

measures that prevent or minimize the discharge of fuel to the storm sewer/ surface waters resulting from fuel servicing activities or other operations conducted in support of the airport fuel system. Consider the following BMPs (or their equivalents): implementing spill and overflow practices (e.g., placing absorptive materials beneath aircraft during fueling operations); using dry cleanup methods; and collecting storm water runoff.

6.S.5.3.6 Source Reduction. Consider alternatives to the use of urea and glycol-based deicing chemicals to reduce the aggregate amount of deicing chemicals used and/or lessen the environmental impact. Chemical options to replace ethylene glycol, propylene glycol and urea include: potassium acetate; magnesium acetate; calcium acetate; anhydrous sodium acetate.

6.S.5.3.6.1 Runway Deicing Operation: Evaluate, at a minimum, whether over-application of deicing chemicals occurs by analyzing application rates and adjusting as necessary, consistent with considerations of flight safety. Also consider these BMP options (or their equivalents): metered application of chemicals; pre-wetting dry chemical constituents prior to application; installing a runway ice detection system; implementing anti-icing operations as a preventive measure against ice buildup.

6.S.5.3.6.2 Aircraft Deicing Operations: As in Part 6.S.5.3.6.1, determine whether excessive application of deicing chemicals occurs and adjust as necessary, consistent with considerations of flight safety. EPA

intends for this evaluation to be carried out by the personnel most familiar with the particular aircraft and flight operations in question (vice an outside entity such as the airport authority). Consider using alternative deicing/anti-icing agents as well as containment measures for all applied chemicals. Also consider these BMP options (or their equivalents) for reducing deicing fluid use: forced-air deicing systems, computer-controlled fixed-gantry systems, infrared technology, hot water, varying glycol content to air temperature, enclosed-basket deicing trucks, mechanical methods, solar radiation, hangar storage, aircraft covers, thermal blankets for MD-80s and DC-9s. Also consider using ice-detection systems and airport traffic flow strategies and departure slot allocation systems.

6.S.5.3.7 Management of Runoff. Where deicing operations occur, describe and implement a program to control or manage contaminated runoff to reduce the amount of pollutants being discharged from the site. Consider these BMP options (or their equivalents): a dedicated deicing facility with a runoff collection/recovery system; using vacuum/collection trucks; storing contaminated storm water/deicing fluids in tanks and releasing controlled amounts to a publicly owned treatment works; collecting contaminated runoff in a wet pond for biochemical decomposition (be aware of attracting wildlife that may prove hazardous to flight operations); and directing runoff into vegetative swales or other infiltration measures. Also consider recovering deicing materials when these materials are applied during non-

precipitation events (e.g., covering storm sewer inlets, using booms, installing absorptive interceptors in the drains, etc.) to prevent these materials from later becoming a source of storm water contamination. Used deicing fluid should be recycled whenever possible.

6.S.5.4 Inspections. (See also Part 4.2.7.2.1.5) Specify the frequency of inspections in your SWPPP. At a minimum they must be conducted monthly during the deicing season (e.g., October through April for most mid-latitude airports). If your facility needs to deice before or after this period, expand the monthly inspections to include all months during which deicing chemicals may be used. Also, if significantly or deleteriously large quantities of deicing chemicals are being spilled or discharged, or if water quality impacts have been reported, increase the frequency of your inspections to weekly until such time as the chemical spills/discharges or impacts are reduced to acceptable levels. The Director may specifically require you to increase inspections and SWPPP reevaluations as necessary.

6.S.5.5 Comprehensive Site Compliance Evaluation. (See also 4.9) (See also Part 4.9)

Using only qualified personnel, conduct your annual site compliance evaluations during periods of actual deicing operations, if possible. If not practicable during active deicing or the weather is too inclement, conduct the evaluations when deicing operations are likely to occur and the materials and equipment for deicing are in place.

6.S.6 Monitoring and Reporting Requirements. (See also Part 5)

TABLE S-1.—SECTOR-SPECIFIC NUMERIC LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation
Sector of Permit Affected/Supplemental Requirements			
Facilities at airports that use more than 100,000 gallons of glycol-based deicing/anti-icing chemicals and/or 100 tons or more of urea on an average annual basis: monitor ONLY those outfalls from the airport facility that collect runoff from areas where deicing/anti-icing activities occur (SIC 45XX).	Biochemical Oxygen Demand (BOD ₅).	30 mg/L Chemical Oxygen Demand (COD).	120.0mg/L. Ammonia 19 mg/L. pH 6/0 to 9 s.u

¹ Monitor once/quarter for the year 2 and year 4 monitoring years.

6.T Sector T—Treatment Works

6.T.1 Covered Storm Water Discharges

The requirements in Part 6.T apply to storm water discharges associated with industrial activity from Treatment Works as identified by the Activity Code

specified under Sector T in Table 1-1 of Part 1.2.1.

6.T.2 Industrial Activities Covered by Sector T

The requirements listed under this Part apply to all existing point source

storm water discharges associated with the following activities:

6.T.2.1 treatment works treating domestic sewage or any other sewage sludge or wastewater treatment device or system used in the storage, treatment, recycling and reclamation of municipal

or domestic sewage; including land dedicated to the disposal of sewage sludge; that are located within the confines of the facility with a design flow of 1.0 MGD or more; or required to have an approved pretreatment program under 40 CFR Part 403.

6.T.2.2 Not required to have permit coverage: farm lands; domestic gardens or lands used for sludge management where sludge is beneficially reused and which are not physically located within the facility; or areas that are in compliance with Section 405 of the CWA.

6.T.3 Limitations on Coverage

6.T.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.3.1) Not authorized by this permit: sanitary and industrial wastewater; and equipment/vehicle washwater.

6.T.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.T.4.1 *Site Map.* (See also Part 4.2.2.3.6) Identify where any of the following may be exposed to precipitation/surface runoff: grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station; and storage areas for process chemicals, petroleum products, solvents, fertilizers, herbicides and pesticides.

6.T.4.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the following additional sources and activities that have potential pollutants associated with them, as applicable: grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station; and access roads/rail lines.

6.T.4.3 *Best Management Practices (BMPs).* (See also Part 4.2.7.2) In addition to the other BMPs considered, consider the following: routing storm water to the treatment works; or covering exposed materials (*i.e.*, from the following areas: grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles; compost piles; septage or hauled waste receiving station).

6.T.4.4 *Inspections.* (See also Part 4.2.7.2.1.5) Include the following areas in all inspections: access roads/rail lines; grit, screenings and other solids handling, storage or disposal areas; sludge drying beds; dried sludge piles;

compost piles; septage or hauled waste receiving station areas.

6.T.4.5 *Employee Training.* (See also Part 4.2.7.2.1.6) At a minimum, must address the following areas when applicable to a facility: petroleum product management; process chemical management; spill prevention and controls; fueling procedures; general good housekeeping practices; proper procedures for using fertilizer, herbicides and pesticides.

6.T.4.6 *Wastewater and Washwater Requirements.* (See also Part 4.4) Attach to your SWPPP a copy of all your current NPDES permits issued for wastewater, industrial, vehicle and equipment washwater discharges or, if an NPDES permit has not yet been issued, a copy of the pending applications. Address any requirements/conditions from the other permits, as appropriate, in the SWPPP. If the washwater is handled in another manner, the disposal method must be described and all pertinent documentation must be attached to the plan.

6.U Sector U—Food and Kindred Products

6.U.1 Covered Storm Water Discharges

The requirements in Part 6.U apply to storm water discharges associated with industrial activity from Food and Kindred Products facilities as identified by the SIC Codes specified in Table 1–1 of Part 1.2.1.

6.U.2 Industrial Activities Covered by Sector U

The types of activities that permittees under Sector U are primarily engaged in are:

- 6.U.2.1 meat products;
- 6.U.2.2 dairy products;
- 6.U.2.3 canned, frozen and preserved fruits, vegetables, and food specialties;
- 6.U.2.4 grain mill products;
- 6.U.2.5 bakery products;
- 6.U.2.6 sugar and confectionery products;
- 6.U.2.7 fats and oils;
- 6.U.2.8 beverages;
- 6.U.2.9 miscellaneous food preparations and kindred products and tobacco products manufacturing.

6.U.3 Limitations on Coverage

Not covered by this permit: storm water discharges identified under Part 1.2.3 from industrial plant yards, material handling sites; refuse sites; sites used for application or disposal of process wastewaters; sites used for

storage and maintenance of material handling equipment; sites used for residential wastewater treatment, storage, or disposal; shipping and receiving areas; manufacturing buildings; and storage areas for raw material and intermediate and finished products. This includes areas where industrial activity has taken place in the past and significant materials remain. "Material handling activities" include the storage, loading/unloading, transportation or conveyance of any raw material, intermediate product, finished product, by-product or waste product.

6.U.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.2.2) Not authorized by this permit: discharges subject to Part 1.2.2.2 include discharges containing: boiler blowdown, cooling tower overflow and blowdown, ammonia refrigeration purging and vehicle washing/clean-out operations.

6.U.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.U.4.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify the locations of the following activities if they are exposed to precipitation/runoff: vents/stacks from cooking, drying and similar operations; dry product vacuum transfer lines; animal holding pens; spoiled product; and broken product container storage areas.

6.U.4.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe, in addition to food and kindred products processing-related industrial activities, application and storage of pest control chemicals (*e.g.*, rodenticides, insecticides, fungicides, etc.) used on plant grounds.

6.U.4.3 *Inspections.* (See also Part 4.2.7.2.1.5) Inspect on a regular basis, at a minimum, the following areas where the potential for exposure to storm water exists: loading and unloading areas for all significant materials; storage areas including associated containment areas; waste management units; vents and stacks emanating from industrial activities; spoiled product and broken product container holding areas; animal holding pens; staging areas; and air pollution control equipment.

6.U.4.4 *Employee Training.* (See also Part 4.2.7.2.1.6) Address pest control in the training program.

6.U.5 Monitoring and Reporting Requirements. (See also Part 5)

TABLE U-1. SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one Sector/Subsector)	Parameter	Benchmark monitoring cut-off concentration ¹	Numeric limitation
Part or Permit Affected/Supplemental Requirements			
Grain Mill Products (SIC 2041–2048)	Total Suspended Solids (TSS).	100 mg/L.	
Fats and Oils Products (SIC 2074–2079)	Biochemical Oxygen Demand (BOD ₅).	30 mg/L.	
	Chemical Oxygen Demand (COD).	120 mg/L.	
	Nitrate plus Nitrate Nitrogen.	0.68 mg/L.	
	Total Suspended Solids (TSS).	100 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.V Sector V—Textile Mills, Apparel and Other Fabric Products

6.V.1 Covered Storm Water Discharges

The requirements in Part 6.V apply to storm water discharges associated with industrial activity from Textile Mills, Apparel, and Other Fabric Product Manufacturing as identified by the Activity Code specified under Sector V in Table 1–1 of Part 1.2.1.

6.V.2 Industrial Activities Covered by Sector V

The types of activities that permittees under Sector V are primarily engaged in are:

6.V.2.1 textile mill products, of and regarding facilities and establishments engaged in the preparation of fiber and subsequent manufacturing of yarn, thread, braids, twine, and cordage, the manufacturing of broadwoven fabrics, narrow woven fabrics, knit fabrics, and carpets and rugs from yarn;

6.V.2.2 processes involved in the dyeing and finishing of fibers, yarn fabrics, and knit apparel;

6.V.2.3 the integrated manufacturing of knit apparel and other finished articles of yarn;

6.V.2.4 the manufacturing of felt goods (wool), lace goods, non-woven fabrics, miscellaneous textiles, and other apparel products.

6.V.3 Limitations on Coverage

6.V.3.1 *Prohibition of Non-Storm Water Discharges.* (See also Part 1.2.3.1) Not authorized by this permit: discharges of wastewater (e.g., wastewater resulting from wet processing or from any processes relating to the production process); reused/recycled water; and waters used in cooling towers. If you have these types of discharges from your facility, you must cover them under a separate NPDES permit.

6.V.4 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.V.4.1 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the following additional sources and activities that have potential pollutants associated with them: industrial-specific significant materials and industrial activities (e.g., backwinding, beaming, bleaching, backing bonding, carbonizing, carding, cut and sew operations, desizing, drawing, dyeing, locking, fulling, knitting, mercerizing, opening, packing, plying, scouring, slashing, spinning, synthetic-felt processing, textile waste processing, tufting, turning, weaving, web forming, winging, yarn spinning, and yarn texturing).

6.V.4.2 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.V.4.2.1 *Material Storage Area.* Plainly label and store all containerized materials (e.g., fuels, petroleum products, solvents, dyes, etc.) in a protected area, away from drains. Describe and implement measures that prevent or minimize contamination of the storm water runoff from such storage areas, including a description of the containment area or enclosure for those materials stored outdoors. Also consider an inventory control plan to prevent excessive purchasing of potentially hazardous substances. For storing empty chemical drums/containers, ensure the drums/containers are clean (consider triple-rinsing) and there is no contact of residuals with precipitation/runoff. Collect and dispose of washwater from these cleanings properly.

6.V.4.2.2 *Material Handling Area.* Describe and implement measures that prevent or minimize contamination of storm water runoff from material handling operations and areas. Consider

the following (or their equivalents): use of spill/overflow protection; covering fueling areas; and covering/enclosing areas where the transfer of material may occur. Where applicable address the replacement or repair of leaking connections, valves, transfer lines and pipes that may carry chemicals, dyes or wastewater.

6.V.4.2.3 *Fueling Areas.* Describe and implement measures that prevent or minimize contamination of storm water runoff from fueling areas. Consider the following (or their equivalents): covering the fueling area, using spill and overflow protection, minimizing runoff of storm water to the fueling areas, using dry cleanup methods, and treating and/or recycling storm water runoff collected from the fueling area.

6.V.4.2.4 *Above Ground Storage Tank Area.* Describe and implement measures that prevent or minimize contamination of the storm water runoff from above ground storage tank areas, including the associated piping and valves. Consider the following (or their equivalents): regular cleanup of these areas; preparation of the spill prevention control and countermeasure program, provide spill and overflow protection; minimizing runoff of storm water from adjacent areas; restricting access to the area; insertion of filters in adjacent catch basins; providing absorbent booms in unbermed fueling areas; using dry cleanup methods; and permanently sealing drains within critical areas that may discharge to a storm drain.

6.V.4.3 *Inspections.* (See also Part 4.2.7.2.1.5) Inspect, at least on a monthly basis, the following activities and areas (at a minimum): transfer and transmission lines; spill prevention; good housekeeping practices; management of process waste products; all structural and non structural management practices.

6.V.4.4 *Employee Training.* (See also Part 4.2.7.2.1.6) As part of your employee training program, address, at a minimum, the following activities (as applicable): use of reused/recycling waters; solvents management; proper disposal of dyes; proper disposal of petroleum products and spent lubricants; spill prevention and control; fueling procedures; and general good housekeeping practices.

6.V.4.5 *Comprehensive Site Compliance Evaluation.* (See also Part 4.9) Conduct regularly scheduled evaluations at least once a year and address those areas contributing to a storm water discharge associated with industrial activity for evidence of, or the potential for, pollutants entering the drainage system. Inspect, at a minimum, as appropriate: storage tank areas; waste disposal and storage areas; dumpsters and open containers stored outside; materials storage areas; engine maintenance and repair areas; material handling areas and loading dock areas.

6.W Sector W—Furniture and Fixtures

6.W.1 Covered Storm Water Discharges

The requirements in Part 6.W apply to storm water discharges associated with industrial activity from Furniture and Fixtures facilities as identified by the Activity Code specified under Sector W in Table 1–1 of Part 1.2.1.

6.W.2 Industrial Activities Covered by Sector W

The types of activities that permittees under Sector W are primarily engaged in the manufacturing of:

- 6.W.2.1 wood kitchen cabinets;
- 6.W.2.2 household furniture;
- 6.W.2.3 office furniture;
- 6.W.2.4 public buildings and related furniture;
- 6.W.2.5 partitions, shelving, lockers, and office and store fixtures;
- 6.W.2.6 miscellaneous furniture and fixtures.

6.W.3 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.W.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: material storage (including tanks or other vessels used for liquid or waste storage) areas; outdoor material processing areas; areas where wastes are treated, stored or disposed; access roads; and rail spurs.

6.X Sector X—Printing and Publishing

6.X.1 Covered Storm Water Discharges

The requirements in Part 6.X apply to storm water discharges associated with industrial activity from Printing and Publishing facilities as identified by the Activity Code specified under Sector X in Table 1.1 of Part 1.2.1.

6.X.2 Industrial Activities Covered by Sector X

The types of activities that permittees under Sector X are primarily engaged in are:

- 6.X.2.1 book printing;
- 6.X.2.2 commercial printing and lithographics;
- 6.X.2.3 plate making and related services;
- 6.X.2.4 commercial printing, gravure;
- 6.X.2.5 commercial printing not elsewhere classified.

6.X.3 Storm Water Pollution Prevention Plan Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.X.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: above ground storage tanks, drums and barrel permanently stored outside.

6.X.3.2 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the following additional sources and activities that have potential pollutants associated with them, as applicable: loading and unloading operations; outdoor storage activities; significant dust or particulate generating processes; and onsite waste disposal practices (e.g., blanket wash). Also identify the pollutant or pollutant parameter (e.g., oil and grease, scrap metal, etc.) associated with each pollutant source.

6.X.3.3 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.X.3.3.1 *Material Storage Areas.* Plainly label and store all containerized materials (e.g., skids, pallets, solvents, bulk inks, and hazardous waste, empty drums, portable/mobile containers of plant debris, wood crates, steel racks, fuel oil, etc.) in a protected area, away from drains. Describe and implement measures that prevent or minimize contamination of the storm water runoff from such storage areas, including a description of the containment area or enclosure for those materials stored outdoors. Also consider an inventory control plan to prevent excessive purchasing of potentially hazardous substances.

6.X.3.3.2 *Material Handling Area.* Describe and implement measures that prevent or minimize contamination of storm water runoff from material handling operations and areas (e.g., blanket wash, mixing solvents, loading/unloading materials). Consider the following (or their equivalents): use of spill/overflow protection; covering fueling areas; and covering/enclosing areas where the transfer of materials may occur. Where applicable address the replacement or repair of leaking connections, valves, transfer lines and pipes that may carry chemicals or wastewater.

6.X.3.3.3 *Fueling Areas.* Describe and implement measures that prevent or minimize contamination of storm water runoff from fueling areas. Consider the following (or their equivalents): covering the fueling area, using spill and overflow protection, minimizing runoff of storm water to the fueling areas, using dry cleanup methods, and treating and/or recycling storm water runoff collected from the fueling area.

6.X.3.3.4 *Above Ground Storage Tank Area.* Describe and implement measures that prevent or minimize contamination of the storm water runoff from above ground storage tank areas, including the associated piping and valves. Consider the following (or their equivalents): regular cleanup of these areas; preparation of the spill prevention control and countermeasure program, provide spill and overflow protection; minimizing runoff of storm water from adjacent areas; restricting access to the area; insertion of filters in adjacent catch basins; providing absorbent booms in unbermed fueling areas; using dry cleanup methods; and permanently sealing drains within critical areas that may discharge to a storm drain.

6.X.3.4 *Employee Training.* (See also Part 4.2.7.2.1.6) As part of your employee training program, address, at a minimum, the following activities (as applicable): spent solvent management; spill prevention and control; used oil management; fueling procedures; and general good housekeeping practices.

6.Y Sector Y—Rubber, Miscellaneous Plastic Products and Miscellaneous Manufacturing Industries

6.Y.1 Covered Storm Water Discharges

The requirements in Part 6.Y apply to storm water discharges associated with industrial activity from Rubber, Miscellaneous Plastic Products and Miscellaneous Manufacturing Industries facilities as identified by the Activity

Code specified under Sector Y in Table 1–1 of Part 1.2.1.

6.Y.2 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.Y.2.1 *Potential Pollutant Sources.* (See also Part 4.2.4) Review the use of zinc at your facility and the possible pathways through which zinc may be discharged in storm water runoff.

6.Y.2.2 *Controls for Rubber Manufacturers.* (See also Part 4.2.7) Describe and implement specific controls to minimize the discharge of zinc in your storm water discharges. Parts 6.Y.2.2.1 to 6.Y.2.2.5 give possible sources of zinc to be reviewed and list some specific BMPs to be considered for implementation (or their equivalents). Some general BMP options to consider: using chemicals which are purchased in pre-weighed, sealed polyethylene bags; storing materials which are in use in

sealable containers; ensuring an airspace between the container and the cover to minimize “puffing” losses when the container is opened; and using automatic dispensing and weighing equipment.

6.Y.2.2.1 *Inadequate Housekeeping.* Review the handling and storage of zinc bags at your facility. BMP options: employee training on the handling/storage of zinc bags; indoor storage of zinc bags; cleanup zinc spills without washing the zinc into the storm drain, and the use of 2,500-pound sacks of zinc rather than 50- to 100-pound sacks;

6.Y.2.2.2 *Dumpsters.* Reduce discharges of zinc from dumpsters. BMP options: covering the dumpster; moving the dumpster indoors; or provide a lining for the dumpster.

6.Y.2.2.3 *Malfunctioning Dust Collectors or Baghouses:* Review dust collectors/baghouses as possible sources in zinc in storm water runoff. Replace or repair, as appropriate, improperly operating dust collectors/baghouses.

6.Y.2.2.4 *Grinding Operations.*

Review dust generation from rubber grinding operations and, as appropriate, install a dust collection system.

6.Y.2.2.5 *Zinc Stearate Coating Operations.* Detail appropriate measures to prevent or clean up drips/spills of zinc stearate slurry that may be released to the storm drain. BMP option: using alternate compounds to zinc stearate.

6.Y.2.3 *Controls for Plastic Products Manufacturers.* Describe and implement specific controls to minimize the discharge of plastic resin pellets in your storm water discharges. BMPs to be considered for implementation (or their equivalents): minimizing spills; cleaning up of spills promptly and thoroughly; sweeping thoroughly; pellet capturing; employee education and disposal precautions.

6.Y.3 Monitoring and Reporting Requirements. (See also Part 5)

TABLE Y–1.—SECTOR-SPECIFIC NUMERIC EFFLUENT LIMITATIONS AND BENCHMARK MONITORING

Subsector	Parameter	Benchmark monitoring cut-off concentration	Numeric limitations
Part of Permit Affected/Supplemental Requirements			
Tires and Inner Tubes; Rubber Footwear; Gaskets, Packing and Sealing Devices; Rubber Hose and Belting; and Fabricated Rubber Products, Not Elsewhere Classified (SIC 3011–3069, rubber.	Total Recoverable Zinc	0.117 mg/L	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years.

6.Z Sector Z—Leather Tanning and Finishing

6.Z.1 Covered Storm Water Discharges

The requirements in Part 6.Z apply to storm water discharges associated with industrial activity from Leather Tanning and Finishing facilities as identified by the Activity Code specified under Sector Z in Table 1–1 of Part 1.2.1.

6.Z.2 Industrial Activities Covered by Sector Z

The types of activities that permittees under Sector Z are primarily engaged are leather tanning, curry and finishing;

6.Z.3 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.Z.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: processing and storage areas of the beamhouse, tanyard, and re-tan wet finishing and

dry finishing operations; and haul roads, access roads and rail spurs.

6.Z.3.2 *Potential Pollutant Sources.* (See also Part 4.2.4) At a minimum, describe the following additional sources and activities that have potential pollutants associated with them (as appropriate): temporary or permanent storage of fresh and brine cured hides; extraneous hide substances and hair; leather dust, scraps, trimmings and shavings; chemical drums, bags, containers and above ground tanks; empty chemical containers and bags; spent solvents; floor sweepings/washings; refuse, waste piles and sludge; and significant dust/particulate generating processes (e.g., buffing).

6.Z.3.3 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.Z.3.3.1 *Storage Areas for Raw, Semiprocessed or Finished Tannery Byproducts.* Pallets/bales of raw, semiprocessed or finished tannery byproducts (e.g., splits, trimmings, shavings, etc.) should be stored indoors or protected by polyethylene wrapping, tarpaulins, roofed storage, etc. Consider placing materials on an impermeable

surface, and enclosing or putting berms (or equivalent measures) around the area to prevent storm water runoff/runoff.

6.Z.3.3.2 *Material Storage Areas.* Label storage containers of all materials (e.g., specific chemicals, hazardous materials, spent solvents, waste materials). Describe and implement measures that prevent/minimize contact with storm water.

6.Z.3.3.3 *Buffing and Shaving Areas.* Describe and implement measures that prevent or minimize contamination of storm water runoff with leather dust from buffing/shaving areas. Consider dust collection enclosures, preventive inspection/maintenance programs or other appropriate preventive measures.

6.Z.3.3.4 *Receiving, Unloading, and Storage Areas.* Describe and implement measures that prevent or minimize contamination of storm water runoff from receiving, unloading, and storage areas. If these areas are exposed, consider (or their equivalent): Covering all hides and chemical supplies; diverting drainage to the process sewer;

or grade berming/curbing area to prevent runoff of storm water.

6.Z.3.3.5 *Outdoor Storage of Contaminated Equipment.* Describe and implement measures that prevent or minimize contact of storm water with contaminated equipment. Consider (or their equivalent): Covering equipment; diverting drainage to the process sewer; and cleaning thoroughly prior to storage.

6.Z.3.3.6 *Waste Management.* Describe and implement measures that prevent or minimize contamination of storm water runoff from waste storage areas. Consider (or their equivalent): Inspection/maintenance programs for leaking containers or spills; covering dumpsters; moving waste management activities indoors; covering waste piles with temporary covering material such as tarpaulins or polyethylene; and minimizing storm water runoff by enclosing the area or building berms around the area.

6.AA Sector AA—Fabricated Metal Products

6.AA.1 Covered Storm Water Discharges

The requirements in Part 6.AA apply to storm water discharges associated with industrial activity from Fabricated Metal Products facilities as identified by the Activity Code specified under Sector AA in Table 1–1 of Part 1.2.1.

6.AA.2 Industrial Activities Covered by Sector AA

The types of activities that permittees under Sector AA are primarily engaged in are:

6.AA.2.1 Fabricated metal products; except for electrical related industries;

6.AA.2.2 Fabricated metal products; except machinery and transportation equipment;

6.AA.2.3 Jewelry, silverware, and plated ware.

6.AA.3 Storm Water Pollution Prevention Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.AA.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: Raw metal storage areas; finished metal storage areas; scrap disposal collection sites; equipment storage areas; retention and detention basins; temporary/permanent diversion dikes or berms; right-of-way

or perimeter diversion devices; sediment traps/barriers; processing areas including outside painting areas; wood preparation; recycling; and raw material storage.

6.AA.3.2 *Spills and Leaks.* (See also Part 4.2.5) When listing significant spills/leaks, pay attention to the following materials at a minimum: Chromium, toluene, pickle liquor, sulfuric acid, zinc and other water priority chemicals and hazardous chemicals and wastes.

6.AA.3.3 *Potential Pollutant Sources.* (See also Part 4.2.4) Describe the following additional sources and activities that have potential pollutants associated with them: Loading and unloading operations for paints, chemicals and raw materials; outdoor storage activities for raw materials, paints, empty containers, corn cob, chemicals, and scrap metals; outdoor manufacturing or processing activities such as grinding, cutting, degreasing, buffing, brazing, etc; onsite waste disposal practices for spent solvents, sludge, pickling baths, shavings, ingots pieces, refuse and waste piles.

6.AA.3.4 *Good Housekeeping Measures.* (See also Part 4.2.7.2.1.1)

6.AA.3.4.1 *Raw Steel Handling Storage.* Describe and implement measures controlling or recovering scrap metals, fines and iron dust. Include measures for containing materials within storage handling areas.

6.AA.3.4.2 *Paints and Painting Equipment.* Describe and implement measures to prevent or minimize exposure of paint and painting equipment to storm water.

6.AA.3.5 *Spill Prevention and Response Procedures.* (See also Part 4.2.7.2.1.4) Ensure the necessary equipment to implement a clean up is available to personnel. The following areas should be addressed:

6.AA.3.5.1 *Metal Fabricating Areas.* Describe and implement measures for maintaining clean, dry, orderly conditions in these areas. Consider the use of dry clean-up techniques.

6.AA.3.5.2 *Storage Areas for Raw Metal.* Describe and implement measures to keep these areas free of condition that could cause spills or leakage of materials. Consider the following (or their equivalents): maintaining storage areas such that there is easy access in the event of a spill; and labeling stored materials to aid in identifying spill contents.

6.AA.3.5.3 *Receiving, Unloading, and Storage Areas.* Describe and

implement measures to prevent spills and leaks; plan for quick remedial clean up; and instruct employees on clean-up techniques and procedures.

6.AA.3.5.4 *Storage of Equipment.* Describe and implement measures for preparing equipment for storage and the proper storage of equipment. Consider the following (or their equivalents): protecting with covers; storing indoors; and cleaning potential pollutants from equipment to be stored outdoors.

6.AA.3.5.5 *Metal Working Fluid Storage Areas.* Describe and implement measures for storage of metal working fluids.

6.AA.3.5.6 *Cleaners and Rinse Water.* Describe and implement measures: to control/cleanup spills of solvents and other liquid cleaners; control sand buildup and disbursement from sand-blasting operations; and prevent exposure of recyclable wastes. Substitute environmentally-benign cleaners when possible.

6.AA.3.5.7 *Lubricating Oil and Hydraulic Fluid Operations.* Consider using monitoring equipment or other devices to detect and control leaks/overflows. Consider installing perimeter controls such as dikes, curbs, grass filter strips or other equivalent measures.

6.AA.3.5.8 *Chemical Storage Areas.* Describe and implement proper storage methods that prevent storm water contamination and accidental spillage. Include a program to inspect containers and identify proper disposal methods.

6.AA.3.6 *Inspections.* (See also Part 4.2.7.2.1.5) Include, at a minimum, the following areas in all inspections: raw metal storage areas; finished product storage areas; material and chemical storage areas; recycling areas; loading and unloading areas; equipment storage areas; paint areas; vehicle fueling and maintenance areas.

6.AA.3.7 *Comprehensive Site Compliance Evaluation.* (See also Part 4.9.2) As part of your evaluation, also inspect: areas associated with the storage of raw metals; storage of spent solvents and chemicals; outdoor paint areas; and drainage from roof. Potential pollutants include chromium, zinc, lubricating oil, solvents, aluminum, oil and grease, methyl ethyl ketone, steel and other related materials.

6.AA.4 Monitoring and Reporting Requirements

(See also Part 5)

TABLE AA-1.—SECTOR-SPECIFIC NUMERIC LIMITATIONS AND BENCHMARK MONITORING

Subsector (Discharges may be subject to requirements for more than one sector/subsector)	Parameter	Benchmark, monitoring, cutoff, concentration ¹	Numeric limitation
Part of Permit Affected/Supplemental Requirements			
Fabricated Metal Products Except Coating (SIC 3411–3471, 3482–3499, 3911–3915).	Total Recoverable Aluminum.	0.75 mg/L.	
	Total Recoverable Iron	1.0 mg/L.	
	Total Recoverable Zinc	0.117 mg/L.	
	Nitrate plus Nitrite Nitrogen	0.68 mg/L.	
Fabricated Metal Coating and Engraving (SIC 3479)	Total Recoverable Zinc	0.117 mg/L.	
	Nitrate plus Nitrite Nitrogen	0.68 mg/L.	

¹ Monitor once/quarter for the year 2 and year 4 Monitoring Years

6.AB Sector AB—Transportation Equipment, Industrial or Commercial Machinery

6.AB.1 Covered Storm Water Discharges

The requirements in Part 6.AB apply to storm water discharges associated with industrial activity from Transportation Equipment, Industrial or Commercial Machinery facilities as identified by the Activity Code specified under Sector AB in Table 1–1 of Part 1.2.1.

6.AB.2 Industrial Activities Covered by Sector AB

The types of activities that permittees under Sector AB are primarily engaged in are:

6.AB.2.1 Industrial and Commercial Machinery (except Computer and Office Equipment) (see Sector AC); and

6.AB.2.2 Transportation Equipment (except Ship and Boat Building and Repairing) (see Sector R).

6.AB.3 Storm Water Pollution Plan (SWPPP) Requirements

In addition to the following requirements, you must also comply with the requirements listed in Part 4.

6.AB.3.1 *Drainage Area Site Map.* (See also Part 4.2.2.3) Identify where any of the following may be exposed to precipitation/surface runoff: vents and stacks from metal processing and similar operations.

6.AB.3.2 *Non-Storm Water Discharges.* (See also Part 4.4) If your facility has a separate NPDES permit (or has applied for a permit) authorizing discharges of wastewater, attach a copy of the permit (or the application) to your SWPPP. Any new wastewater permits issued/reissued to you must then replace the old one in your SWPPP. If you discharge wastewater, other than solely domestic wastewater, to a Publicly Owned Treatment Works (POTW), you must notify the POTW of the discharge (identify the types of

wastewater discharged, including any storm water). As proof of this notification, attach to your SWPPP a copy of the permit issued to your facility by the POTW or a copy of your notification to the POTW.

6.AC Sector AC—Electronic, Electrical Equipment and Components, Photographic and Optical Goods

6.AC.1 Covered Storm Water Discharges

The requirements in Part 6.AC apply to storm water discharges associated with industrial activity from facilities that manufacture Electronic, Electrical Equipment and Components, Photographic and Optical Goods as identified by the SIC Codes specified in Table 1–1 of Part 1.2.1.

6.AC.2 Industrial Activities Covered by Sector AC

The types of manufacturing activities that permittees under Sector AC are primarily engaged in are:

6.AC.2.1 Measuring, analyzing, and controlling instruments;

6.AC.2.2 Photographic, medical and optical goods;

6.AC.2.3 Watches and clocks; and

6.AC.2.4 Computer and office equipment.

6.AC.3 Additional Requirements

No additional sector-specific requirements apply to this sector.

6.AD Storm Water Discharges Designated by the Director as Requiring Permits

6.AD.1 Covered Storm Water Discharges

Sector AD is used to provide permit coverage for facilities designated by the Director as needing a storm water permit, or any discharges of industrial activity that do not meet the description of an industrial activity covered by Sectors A–AC. Therefore, almost any type of storm water discharge could be covered under this sector. You must be

assigned to Sector AD by the Director and may NOT choose sector AD as the sector describing your activities on your own.

6.AD.1.1 *Eligibility for Permit Coverage.* Because this Sector only covers discharges designated by the Director as needing a storm water permit (which is an atypical circumstance) or your facility's industrial activities were inadvertently left out of Sectors A–AC, and your facility may or may not normally be discharging storm water associated with industrial activity, you must obtain the Director's written permission to use this permit prior to submitting a Notice of Intent. If you are authorized to use this permit, you will be required to ensure your discharges meet the basic eligibility provisions of this permit at Part 1.2.

6.AD.2 Storm Water Pollution Prevention Plan (SWPPP) Requirements

The Director will establish any additional Storm Water Pollution Prevention Plan requirements for your facility at the time of accepting your Notice of Intent to be covered by this permit. Additional requirements would be based on the nature of activities at your facility and your storm water discharges.

6.AD.3 Monitoring and Reporting Requirements

The Director will establish any additional monitoring and reporting requirements for your facility at the time of accepting your Notice of Intent to be covered by this permit. Additional requirements would be based on the nature of activities at your facility and your storm water discharges.

7. Reporting

7.1 Reporting Results of Monitoring

Depending on the types of monitoring required for your facility, you may have to submit the results of your monitoring or you may only have to keep the results