

Certification Summary Information Report

Manufacturer	Hyundai Motor Company	Manufacturer Code	HYX
Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG
Certificate Number	VHYXV02.5GP5-031	CARB Executive Order #	--
Certificate Issue Date	06/02/2026	Certificate Revision Date	--
Certificate Effective Date	06/02/2026	Conditional Certificate	No
CSI Revision #	--	CSI Submission/Revision Date	04/24/2026 01:37:05 AM
Model Year	2027		

Test Group Information

CSI Type	New	Running Change Reference Number	--
GHG Exempt Status	Not Exempt		

Drive Sources and Fuel(s)

Drive Source #1: Combustion Engine

Fuel	Basic Fuel Metering System	Lean Burn Strategy Indicator
Gasoline	Spark Ignition direct & ported injection	No

Hybrid Indicator	No		
Multiple Fuel Storage	--	Rechargeable Energy Storage System Indicator	--
Multiple Fuel Combustion	--	Off-board Charge Capable Indicator	--
Fuel Cell Indicator	--	EPA Vehicle Class	LDV
Federal Clean Fuel Vehicle	No	Federal Clean Fuel Vehicle Standard	--
Federal Clean Fuel Vehicle ILEV	No	California Partial Zero Emissions Vehicle Indicator	No
Durability Group Name	VHYXGPGNNGP5	Durability Group Equivalency Factor	1.0
Reduced Fee Test Group	No	Certification Region Code(s)	FA, CA
Complies with HD GHG 2b/3 regulations?	No		
Introduction into Commerce Date	08/15/2026	CAP2000 Conditional Certificate?	No
Independent Commercial Importer?	No	Alternative Fuel Converter Certificate?	No
SFTP Federal Composite Compliance Identifier	Tier 3	SFTP Tier 2 Composite CO Option	No
SFTP LEV-III Composite Compliance Indicator	No		
OBD Compliance Type	CARB	OBD Demonstration Vehicle Test Group	VHYXV02.5UP3
Test Group OBD Compliance Level	Full - no deficiencies	Number of Test Group OBD Deficiencies	0
OBD Deficiencies Comments	--		
Mfr Test Group Comments	The fuel for Litmus test is E10 of Comfort mode. Litmus result(Value/Threshold): City(20.2/19.1) HWY(27.4/26.5). Test No: RHYX10080615(FTP),RHYX10080617(HWY),RHYX10080616(US06),RHYX10080618(SC03),RHYX10080619(Cold).		
Mfr Exhaust / Evap Standards Comments	--		

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG				
Evaporative/Refueling Family Information							
Evaporative Summary Information Type	New	Submission/Correction Date	04/24/2026 01:28:12 AM				
Integrated ORVR?	Yes	Fuel(s)	Gasoline				
Multiple Fuel Storage	--						
Bladder Fuel Tank?	No						
Fuel Tank Material	Plastic	Fuel Tank Material Description	PLASTIC				
Fill Pipe Seal Type	Liquid seal						
Air Intake System Vapor Storage Device?	Yes	Air Intake System Vapor Storage Device Description	HC-Trap				
Fuel System Vapor Storage Canister?	Yes	Other Vapor Storage	--				
Fuel System Vapor Storage Canister(s) Total Working Capacity (grams)	132	Number of Primary Canisters	1				
Number of Bleed Canisters	0	Bleed Canister Total Working Capacity (grams)	--				
Mfr Evaporative/Refueling Family Comments	--						
Leak Family Details							
Leak Family Indicator	Yes						
Canister Bleed Test Indicator	Yes	Applicability of Evaporative Canister Bleed Test	50 State				
Evaporative Canister Bleed Test Comments	--						
CARB Fuel Only (Rig) Test Indicator	No	Applicability of CARB Fuel Only (Rig) Test	--				
CARB Fuel Only (Rig) Test Comments	--						
Leak Family Name	Applicability of Leak Family Requirements	Leak Family Standard (inches)	Leak Family Description				
VHYXR0132GPG-IK1	50 State	0.02	--				
Models Covered by this Certificate							
Carline Manufacturer	Division	Carline	Certification Region Code(s)	Drive System	Trans - Type	- # of Gears	Trans - Lockup
Hyundai Motor Company	2 - GENESIS	333 - G70 AWD	Federal	All Wheel Drive	Semi-Automatic	8	Yes
Hyundai Motor Company	2 - GENESIS	334 - G70 RWD	Federal	2-Wheel Drive, Rear	Semi-Automatic	8	Yes
Hyundai Motor Company	2 - GENESIS	334 - G70 RWD	California + CAA Section 177 states	2-Wheel Drive, Rear	Semi-Automatic	8	Yes
Hyundai Motor Company	2 - GENESIS	333 - G70 AWD	California + CAA Section 177 states	All Wheel Drive	Semi-Automatic	8	Yes
Engine Description							
Hybrid Type	--	Hybrid Description	--				
Engine Type	4-Stroke Spark Ignition	Mfr Engine Description	--				
Engine Block Arrangement	Inline	Mfr Engine Block Arrangement Description	--				
Camless Valvetrain Indicator	No	Oil Viscosity/Classification	0W-30				
Number of Cylinders/Rotors	4	Mechanically Variable Compression Ratio Indicator	N				

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family				VHYXR0132GPG					
After Treatment Device(s) (ATD)											
ATD Number		ATD Type		ATD Precious Metal		Substrate Material		Substrate Construction			
1		Three-way catalyst		Platinum + Palladium + Rhodium		Ceramic		Monolith			
Mfr After Treatment Device (ATD) Comments											
		--									
Direct Ozone Reduction (DOR) Device		Not Equipped									
Mfr Emission Control Device Comments		--									
Engine Configuration Number 1											
Engine Displacement (liters)		2.5		Engine Rated Horsepower		300					
Number of Inlet Valves Per Cylinder		2		Number of Exhaust Valves Per Cylinder		2					
Air Aspiration Method		Turbocharged		Number of Air Aspiration Devices		1					
Air Aspiration Device Configuration		Single		Charge Air Cooler Type		Liquid					
Air Aspiration Drive Method(s)		Mechanical									
Cylinder Deactivation		No									
Cylinder Deactivation Description		--									
Variable Valve Timing		Yes									
Variable Valve Timing System Description		APPLY CVVT									
Variable Valve Lift?		No									
Variable Valve Lift System Description		--									
Number of Knock Sensors		1		Number of Air/Fuel Sensors		2					
Air/Fuel Sensor # 1 Type		Other		Air/Fuel Sensor # 1 Description		WR-HO2S					
Air/Fuel Sensor # 2 Type		Heated oxygen		Air/Fuel Sensor # 2 Description		--					
Mfr Air/Fuel Sensor Comments		--									
Exhaust Gas Recirculation		No		Cooled Exhaust Gas Recirculation		No					
EGR Type		--		Exhaust Gas Recirculation Description if 'Other'		--					
Closed Loop Air Injection System		No									
Air Injection Type		--		Air Injection Type if 'Other'		--					
Mfr Engine Configuration Comments		--									
Official Test Numbers											
Test Group	Fuel	FTP	US06	SC03	Cold CO	Highway	EPA City Litmus Value	EPA City Litmus Threshold	EPA Highway Litmus Value	EPA Highway Litmus Threshold	CREE Weighting Factor
Gasoline		RHYX10080615	RHYX10080616	RHYX10080618	RHYX10080619	RHYX10080617	24	228.2	35.8	286.1	--

Certification Summary Information Report

Test Group		VHYXV02.5GP5		Evaporative/Refueling Family		VHYXR0132GPG	
SFTP LEV-III Official Test Numbers							
Test Group Fuel		FTP		US06		SC03	
Gasoline		RHYX10080615		RHYX10080616		RHYX10080618	

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG						
Emission Data Vehicle Information									
Vehicle ID / Configuration	IK_U4L3TA015A / 0	Manufacturer Vehicle Configuration Number	0						
Original Test Group Name	RHYXV02.5GP4	Original Evaporative/Refueling Family	RHYXR0132GPG						
Original Test Vehicle Model Year	2024								
Vehicle Model									
Represented Test Vehicle Make	Genesis	Represented Test Vehicle Model	G70						
Leak Family Details									
Leak Family Identifier	IK1	Leak Family Name	RHYXR0132GPG-IK1						
Drive Sources and Fuel System Details									
	<table border="1"> <tr> <th>Drive Source and Fuel#</th><th>Drive Source</th><th>Fuel</th></tr> <tr> <td>1</td><td>Combustion Engine</td><td>Gasoline</td></tr> </table>	Drive Source and Fuel#	Drive Source	Fuel	1	Combustion Engine	Gasoline		
Drive Source and Fuel#	Drive Source	Fuel							
1	Combustion Engine	Gasoline							
Hybrid Indicator	No								
Multiple Fuel Storage	--	Multiple Fuel Combustion	--						
Fuel Cell Indicator	--	Rechargeable Energy Storage System Indicator	--						
Rechargeable Energy Storage System	--	Rechargeable Energy Storage System, if 'Other'	--						
Off-board charge Capable Indicator	--								
Odometer Correction -- Initial	86	Odometer Correction Factor	1.0078						
Odometer Correction Sign	- = System Miles is equal to (Test odometer reading - Initial system miles) * Correction factor								
Odometer Correction Units	Miles								
Engine Code	G4KR-AC	Rated Horsepower	300						
Displacement (liters)	2.5								
Air Aspiration Method	Turbocharged	Air Aspiration Method, if 'Other'							
Number of Air Aspiration Devices	1	Air Aspiration Device Configuration	Single						
Charge Air Cooler Type	Liquid	Drive Mode While Testing	2-Wheel Drive, Rear						
Shift Indicator Light Usage	Not equipped	Aged Emission Components	4,000 (mi)						
Curb Weight (lbs)	3829	Equivalent Test Weight (pounds)	4250						
GVWR (lbs)	4916	N/V Ratio	26.5						
Axle Ratio	3.54								
Transmission Type	Semi-Automatic	# of Transmission Gears	8						
Transmission Lockup	Yes	Creep Gear	No						

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family		VHYXR0132GPG	
Dynamometer Coefficients:								
Target Coefficients				Set Coefficients			EPA Calculated Total Road Load Horse Power for City/Highway/Evap Coefficients	
Coefficient Category	A (lbf)	B (lbf/mph)	C (lbf/mph**2)	A (lbf)	B (lbf/mph)	C (lbf/mph**2)		
City/Highway/Evap	37.97	0.52958	0.018422	16.483	0.2628	0.019184	14.7	
Cold CO	41.767	0.58254	0.020264	4.097	0.01138	0.023569	N/A	
US06	37.97	0.52958	0.018422	16.483	0.2628	0.019184	N/A	
Emission Control Device Comments		--						
Manufacturer Test Vehicle Comments		24MY IK 2.5T AWD 8AT 19inch AS tire (EDV) Set Coefficients of City, Highway for FE(E0 fuel) tests are A=17.735, B=0.19916, C=0.019835 Type of Charge Air Cooler is changed from Air to Liquid as TYPO. Target and set coefficients are corrected.						

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10080615	Test Procedure	21 - Federal fuel 2-day exhaust (w/can load)
Exhaust Test # for this Evap Test	--	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)
Test Date	04/25/2023	Fuel	Gasoline
Fuel Batch ID	21T-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4687	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO2 BAG 1 (Bag 1 Carbon Dioxide)	362	--
FE BAG 1 (Bag 1 Fuel Economy)	23.8	23.8
CO2 BAG 2 (Bag 2 Carbon Dioxide)	361	--
FE BAG 2 (Bag 2 Fuel Economy)	24	24
CO2 BAG 3 (Bag 3 Carbon Dioxide)	302	--
FE BAG 3 (Bag 3 Fuel Economy)	28.7	28.7
CO (Carbon Monoxide)	0.3444	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	3.83	--
DT-EER (Drive Trace Energy Economy Rating)	1.22	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	5.52	--
MFR FE (Manufacturer Fuel Economy)	25.087	25.087
NOX (Nitrogen Oxide)	0.0084	--
HC-NM (Non-methane Hydrocarbon)	0.0112	--
NMOG (Non-methane organic gases)	0.0123	--
PM (Particulate Matter)	0.001	--
HC-TOTAL (Total Hydrocarbon)	0.0149	--

Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE
Carbon-Related Exhaust Emissions	346	999

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family				VHYXR0132GPG			
		Test Result Name		Unrounded Test Result			Verify Calculated CO2					
		Carbon dioxide		345.2253			--					
Manufacturer Test Comments		24MY IK PE2 2.5T AWD 19" AS E10 - FTP										
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	120,000 miles	Federal Tier 3 Bin 50	CREE	999	--	--	--	0.242171	--	999	--	--
Fed	150,000 miles	Federal Tier 3 Bin 50	CO	0.34	--	--	--	0.04	--	0.4	1.7	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	CO-COMP	0.33	--	--	--	0	--	0.3	4.2	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0.0123	--	1.1	--	0.0029	--	0.015	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0207	--	--	--	--	--	0.03	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX-COMP	0.0246	--	--	--	0	--	0.025	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0084	--	--	--	0.0067	--	0.015	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	PM	0.001	--	--	--	0	--	0.001	0.003	Pass
CA	150,000 miles	California LEV-IV ULEV50	CO	0.34	--	--	--	0.04	--	0.4	1.7	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0.0123	--	1.1	--	0.0029	--	0.015	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0207	--	--	--	--	--	0.03	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0084	--	--	--	0.0067	--	0.015	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	PM	0.001	--	--	--	0	--	0.001	0.003	Pass
NOTE: For Non-charge depleting tests, the Rounded Result for CREE/OPT-CREE Emission names are Verify-calculated values.												

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG
Test #	RHYX10080619	Test Procedure	11 - Cold CO
Exhaust Test # for this Evap Test	--	Test Fuel Type	28 - Cold CO E10 Regular Gasoline (Tier 3)
Test Date	04/30/2023	Fuel	Gasoline
Fuel Batch ID	22D-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4847	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO2 BAG 1 (Bag 1 Carbon Dioxide)	403	--
FE BAG 1 (Bag 1 Fuel Economy)	21.4	21.4
CO2 BAG 2 (Bag 2 Carbon Dioxide)	375	--
FE BAG 2 (Bag 2 Fuel Economy)	23.1	23.1
CO2 BAG 3 (Bag 3 Carbon Dioxide)	310	--
FE BAG 3 (Bag 3 Fuel Economy)	27.9	27.9
CO (Carbon Monoxide)	0.443	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	2.7	--
DT-EER (Drive Trace Energy Economy Rating)	0.58	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	3.47	--
MFR FE (Manufacturer Fuel Economy)	23.7945	23.7945
NOX (Nitrogen Oxide)	0.0096	--
HC-NM (Non-methane Hydrocarbon)	0.0282	--
HC-TOTAL (Total Hydrocarbon)	0.0346	--

Test Result Name	Unrounded Test Result	Verify Calculated CO2
Carbon dioxide	362.8216	--

Manufacturer Test Comments

24MY IK PE2 2.5T AWD 19" AS E10 - 20F

Certification Summary Information Report

Test Group		VHYXV02.5GP5				Evaporative/Refueling Family				VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	50,000 miles	Federal Tier 3 Bin 50	CO	0.44	--	--	--	0.01	--	0.4	10.0	Pass
Fed	120,000 miles	Federal Tier 3 Bin 50	HC-NM	0.03	--	--	--	0.0021	--	0	0.3	Pass
CA	50,000 miles	California LEV-IV ULEV50	CO	0.44	--	--	--	0.01	--	0.4	10.0	Pass

Certification Summary Information Report

Test Group	VHXXV02.5GP5	Evaporative/Refueling Family	VHXXR0132GPG
Test #	RHXX10080620	Test Procedure	52 - Fed. fuel 50 F exh.
Exhaust Test # for this Evap Test	--	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)
Test Date	04/27/2023	Fuel	Gasoline
Fuel Batch ID	21T-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4779	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO (Carbon Monoxide)	0.3149	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	5.4	--
DT-EER (Drive Trace Energy Economy Rating)	2.98	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	7.2	--
MFR FE (Manufacturer Fuel Economy)	25.2358	25.2358
NOX (Nitrogen Oxide)	0.0081	--
HC-NM (Non-methane Hydrocarbon)	0.0136	--
NMOG (Non-methane organic gases)	0.015	--
HC-TOTAL (Total Hydrocarbon)	0.0178	--

Test Result Name	Unrounded Test Result	Verify Calculated CO2
Carbon dioxide	342.6357	--

Manufacturer Test Comments

24MY IK PE2 2.5T AWD 19" AS E10 - 50F

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family					VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
CA	4,000 miles	California LEV-IV ULEV50	CO	0.31	--	--	--	0	--	0.3	1.7	Pass
CA	4,000 miles	California LEV-IV ULEV50	NMOG	0.015	--	1.1	--	0	--	0.015	99.999	Pass
CA	4,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0231	--	--	--	--	--	0.023	0.100	Pass
CA	4,000 miles	California LEV-IV ULEV50	NOX	0.0081	--	--	--	0	--	0.008	99.999	Pass

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10080626	Test Procedure	21 - Federal fuel 2-day exhaust (w/can load)
Exhaust Test # for this Evap Test	--	Test Fuel Type	61 - Tier 2 Cert Gasoline
Test Date	03/05/2023	Fuel	Gasoline
Fuel Batch ID	22M-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4104	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO2 BAG 1 (Bag 1 Carbon Dioxide)	393	--
FE BAG 1 (Bag 1 Fuel Economy)	22.5	22.5
CO2 BAG 2 (Bag 2 Carbon Dioxide)	411	--
FE BAG 2 (Bag 2 Fuel Economy)	21.7	21.7
CO2 BAG 3 (Bag 3 Carbon Dioxide)	349	--
FE BAG 3 (Bag 3 Fuel Economy)	25.5	25.5
METHANE (CH4 - Methane)	0.0035	--
CO (Carbon Monoxide)	0.6563	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	1.31	--
DT-EER (Drive Trace Energy Economy Rating)	0.04	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	1.51	--
MFR FE (Manufacturer Fuel Economy)	22.8044	22.8044
NOX (Nitrogen Oxide)	0.003	--
N2O (Nitrous Oxide)	0.0002	--
HC-NM (Non-methane Hydrocarbon)	0.0122	--
NMOG (Non-methane organic gases)	0.0127	--
HC-TOTAL (Total Hydrocarbon)	0.0151	--

Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE
Carbon-Related Exhaust Emissions	391	391

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family				VHYXR0132GPG			
		Test Result Name		Unrounded Test Result			Verify Calculated CO2					
		Carbon dioxide		390.3856			--					
Manufacturer Test Comments		24MY IK PE2 2.5T AWD 19" AS E0 - FTP (SPORT+ mode) ADDED TEST RESULTS BY BAGs.										
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	120,000 miles	Federal Tier 3 Bin 50	CREE	391	--	--	--	0.242171	--	391	--	--
Fed	120,000 miles	Federal Tier 3 Bin 50	METHANE	0.0035	--	--	--	0.0044	--	0.008	0.030	Pass
Fed	120,000 miles	Federal Tier 3 Bin 50	N2O	0.0002	--	--	--	0.0019	--	0.002	0.010	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	CO	0.66	--	--	--	0.04	--	0.7	1.7	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0.0127	--	1.1	--	0.0029	--	0.016	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0157	--	--	--	--	--	0.025	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.003	--	--	--	0.0067	--	0.01	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	CO	0.66	--	--	--	0.04	--	0.7	1.7	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0.0127	--	1.1	--	0.0029	--	0.016	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0157	--	--	--	--	--	0.025	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.003	--	--	--	0.0067	--	0.01	99.999	Pass
NOTE: For Non-charge depleting tests, the Rounded Result for CREE/OPT-CREE Emission names are Verify-calculated values.												

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10081169	Test Procedure	21 - Federal fuel 2-day exhaust (w/can load)
Exhaust Test # for this Evap Test	--	Test Fuel Type	61 - Tier 2 Cert Gasoline
Test Date	06/14/2023	Fuel	Gasoline
Fuel Batch ID	22M-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	5118	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO2 BAG 1 (Bag 1 Carbon Dioxide)	338	--
FE BAG 1 (Bag 1 Fuel Economy)	26.2	26.2
CO2 BAG 2 (Bag 2 Carbon Dioxide)	342	--
FE BAG 2 (Bag 2 Fuel Economy)	26.1	26.1
CO2 BAG 3 (Bag 3 Carbon Dioxide)	296	--
FE BAG 3 (Bag 3 Fuel Economy)	30.1	30.1
METHANE (CH4 - Methane)	0.0043	--
CO (Carbon Monoxide)	0.3848	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	3.49	--
DT-EER (Drive Trace Energy Economy Rating)	1.11	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	4.87	--
MFR FE (Manufacturer Fuel Economy)	27.055	27.055
NOX (Nitrogen Oxide)	0.0117	--
N2O (Nitrous Oxide)	0.0009	--
HC-NM (Non-methane Hydrocarbon)	0.0101	--
NMOG (Non-methane organic gases)	0.0105	--
HC-TOTAL (Total Hydrocarbon)	0.0136	--

Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE
Carbon-Related Exhaust Emissions	330	330

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family				VHYXR0132GPG			
		Test Result Name		Unrounded Test Result			Verify Calculated CO2					
		Carbon dioxide		328.7942			--					
Manufacturer Test Comments		24MY IK PE2 2.5T AWD 19" AS E0(MCT) - FTP (ECO mode) ADDED TEST RESULTS BY BAGs										
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	120,000 miles	Federal Tier 3 Bin 50	CREE	330	--	--	--	0.242171	--	330	--	--
Fed	120,000 miles	Federal Tier 3 Bin 50	METHANE	0.0043	--	--	--	0.0044	--	0.009	0.030	Pass
Fed	120,000 miles	Federal Tier 3 Bin 50	N2O	0.0009	--	--	--	0.0019	--	0.003	0.010	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	CO	0.38	--	--	--	0.04	--	0.4	1.7	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0.0105	--	1.1	--	0.0029	--	0.013	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0222	--	--	--	--	--	0.032	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0117	--	--	--	0.0067	--	0.018	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	CO	0.38	--	--	--	0.04	--	0.4	1.7	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0.0105	--	1.1	--	0.0029	--	0.013	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0222	--	--	--	--	--	0.032	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0117	--	--	--	0.0067	--	0.018	99.999	Pass
NOTE: For Non-charge depleting tests, the Rounded Result for CREE/OPT-CREE Emission names are Verify-calculated values.												

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10080617	Test Procedure	3 - HWFE
Exhaust Test # for this Evap Test	--	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)
Test Date	04/25/2023	Fuel	Gasoline
Fuel Batch ID	21T-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4698	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO (Carbon Monoxide)	0.1119	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	8.76	--
DT-EER (Drive Trace Energy Economy Rating)	0.55	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	10.74	--
MFR FE (Manufacturer Fuel Economy)	39.5558	39.5558
NOX (Nitrogen Oxide)	0.0046	--
HC-NM (Non-methane Hydrocarbon)	0	--
NMOG (Non-methane organic gases)	0	--
HC-TOTAL (Total Hydrocarbon)	0.0003	--

Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE
Carbon-Related Exhaust Emissions	219	999

Test Result Name	Unrounded Test Result	Verify Calculated CO2
Carbon dioxide	218.6211	--

Manufacturer Test Comments

24MY IK PE2 2.5T AWD 19" AS E10 - HWY

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family					VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	120,000 miles	Federal Tier 3 Bin 50	CREE	999	--	--	--	0.242171	--	999	--	--
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0	--	1.03	--	0.0029	--	0.003	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0046	--	--	--	--	--	0.014	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0046	--	--	--	0.0067	--	0.011	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0	--	1.03	--	0.0029	--	0.003	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0046	--	--	--	--	--	0.014	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0046	--	--	--	0.0067	--	0.011	99.999	Pass

NOTE: For Non-charge depleting tests, the Rounded Result for CREE/OPT-CREE Emission names are Verify-calculated values.

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10080627	Test Procedure	3 - HWFE
Exhaust Test # for this Evap Test	--	Test Fuel Type	61 - Tier 2 Cert Gasoline
Test Date	03/05/2023	Fuel	Gasoline
Fuel Batch ID	22M-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4115	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO (Carbon Monoxide)	0.1096	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	0.35	--
DT-EER (Drive Trace Energy Economy Rating)	0.05	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	0.37	--
MFR FE (Manufacturer Fuel Economy)	34.5415	34.5415
NOX (Nitrogen Oxide)	0.0017	--
HC-NM (Non-methane Hydrocarbon)	0.0032	--
NMOG (Non-methane organic gases)	0.0033	--
HC-TOTAL (Total Hydrocarbon)	0.0067	--

Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE
Carbon-Related Exhaust Emissions	258	258

Test Result Name	Unrounded Test Result	Verify Calculated CO2
Carbon dioxide	257.5937	--

Manufacturer Test Comments 24MY IK PE2 2.5T AWD 19" AS E0 - HWY (SPORT+ mode)

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family					VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	120,000 miles	Federal Tier 3 Bin 50	CREE	258	--	--	--	0.242171	--	258	--	--
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0.0033	--	1.03	--	0.0029	--	0.006	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.005	--	--	--	--	--	0.015	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0017	--	--	--	0.0067	--	0.008	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0.0033	--	1.03	--	0.0029	--	0.006	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.005	--	--	--	--	--	0.015	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0017	--	--	--	0.0067	--	0.008	99.999	Pass

NOTE: For Non-charge depleting tests, the Rounded Result for CREE/OPT-CREE Emission names are Verify-calculated values.

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG																														
Test #	RHYYX10081168	Test Procedure	3 - HWFE																														
Exhaust Test # for this Evap Test	--	Test Fuel Type	61 - Tier 2 Cert Gasoline																														
Test Date	06/11/2023	Fuel	Gasoline																														
Fuel Batch ID	22M-01	Fuel Calibration Number	1																														
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined																														
Verify Test Lab ID	772-1, Jangduck-Dong																																
E10 Evaporative Test Measurement Method	--																																
Test Start Odometer Reading	5100	Odometer Units	M																														
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--																														
State of Charge Delta	--																																
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes																														
Test Results																																	
<table border="1"> <thead> <tr> <th>Test Result Name</th> <th>Unrounded Test Result</th> <th>Verify Calculated FE Equivalent Value (miles per gallon)</th> </tr> </thead> <tbody> <tr> <td>CO (Carbon Monoxide)</td> <td>0.0863</td> <td>--</td> </tr> <tr> <td>DT-ASCR (Drive Trace Absolute Speed Change Rating)</td> <td>6.04</td> <td>--</td> </tr> <tr> <td>DT-EER (Drive Trace Energy Economy Rating)</td> <td>0.62</td> <td>--</td> </tr> <tr> <td>DT-IWRR (Drive Trace Inertia Work Ratio Rating)</td> <td>7.03</td> <td>--</td> </tr> <tr> <td>MFR FE (Manufacturer Fuel Economy)</td> <td>41.2615</td> <td>41.2615</td> </tr> <tr> <td>NOX (Nitrogen Oxide)</td> <td>0.0039</td> <td>--</td> </tr> <tr> <td>HC-NM (Non-methane Hydrocarbon)</td> <td>0.0008</td> <td>--</td> </tr> <tr> <td>NMOG (Non-methane organic gases)</td> <td>0.0009</td> <td>--</td> </tr> <tr> <td>HC-TOTAL (Total Hydrocarbon)</td> <td>0.0013</td> <td>--</td> </tr> </tbody> </table>				Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)	CO (Carbon Monoxide)	0.0863	--	DT-ASCR (Drive Trace Absolute Speed Change Rating)	6.04	--	DT-EER (Drive Trace Energy Economy Rating)	0.62	--	DT-IWRR (Drive Trace Inertia Work Ratio Rating)	7.03	--	MFR FE (Manufacturer Fuel Economy)	41.2615	41.2615	NOX (Nitrogen Oxide)	0.0039	--	HC-NM (Non-methane Hydrocarbon)	0.0008	--	NMOG (Non-methane organic gases)	0.0009	--	HC-TOTAL (Total Hydrocarbon)	0.0013	--
Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)																															
CO (Carbon Monoxide)	0.0863	--																															
DT-ASCR (Drive Trace Absolute Speed Change Rating)	6.04	--																															
DT-EER (Drive Trace Energy Economy Rating)	0.62	--																															
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	7.03	--																															
MFR FE (Manufacturer Fuel Economy)	41.2615	41.2615																															
NOX (Nitrogen Oxide)	0.0039	--																															
HC-NM (Non-methane Hydrocarbon)	0.0008	--																															
NMOG (Non-methane organic gases)	0.0009	--																															
HC-TOTAL (Total Hydrocarbon)	0.0013	--																															
<table border="1"> <thead> <tr> <th>Test Result Name</th> <th>Unrounded Test Result</th> <th>Verify Calculated CREE/OPT-CREE</th> </tr> </thead> <tbody> <tr> <td>Carbon-Related Exhaust Emissions</td> <td>216</td> <td>216</td> </tr> </tbody> </table>				Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE	Carbon-Related Exhaust Emissions	216	216																								
Test Result Name	Unrounded Test Result	Verify Calculated CREE/OPT-CREE																															
Carbon-Related Exhaust Emissions	216	216																															
<table border="1"> <thead> <tr> <th>Test Result Name</th> <th>Unrounded Test Result</th> <th>Verify Calculated CO2</th> </tr> </thead> <tbody> <tr> <td>Carbon dioxide</td> <td>216.1351</td> <td>--</td> </tr> </tbody> </table>				Test Result Name	Unrounded Test Result	Verify Calculated CO2	Carbon dioxide	216.1351	--																								
Test Result Name	Unrounded Test Result	Verify Calculated CO2																															
Carbon dioxide	216.1351	--																															
Manufacturer Test Comments	24MY IK PE2 2.5T AWD 19" AS E0 (MCT) - HWY (ECO mode)																																

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family					VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	120,000 miles	Federal Tier 3 Bin 50	CREE	216	--	--	--	0.242171	--	216	--	--
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0.0009	--	1.03	--	0.0029	--	0.004	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0048	--	--	--	--	--	0.014	0.050	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0039	--	--	--	0.0067	--	0.011	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0.0009	--	1.03	--	0.0029	--	0.004	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0048	--	--	--	--	--	0.014	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0039	--	--	--	0.0067	--	0.011	99.999	Pass

NOTE: For Non-charge depleting tests, the Rounded Result for CREE/OPT-CREE Emission names are Verify-calculated values.

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10080616	Test Procedure	90 - US06
Exhaust Test # for this Evap Test	--	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)
Test Date	04/25/2023	Fuel	Gasoline
Fuel Batch ID	21T-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4718	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO2 BAG 1 (Bag 1 Carbon Dioxide)	534	--
FE BAG 1 (Bag 1 Fuel Economy)	16.2	16.2
CO2 BAG 2 (Bag 2 Carbon Dioxide)	293	--
FE BAG 2 (Bag 2 Fuel Economy)	29.5	29.5
CO (Carbon Monoxide)	0.2546	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	-1.31	--
DT-EER (Drive Trace Energy Economy Rating)	-0.43	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	-1.33	--
MFR FE (Manufacturer Fuel Economy)	25.0266	25.0266
NOX (Nitrogen Oxide)	0.0117	--
HC-NM (Non-methane Hydrocarbon)	0.0049	--
NMOG (Non-methane organic gases)	0.005	--
PM (Particulate Matter)	0.0017	--
HC-TOTAL (Total Hydrocarbon)	0.0068	--

Test Result Name	Unrounded Test Result	Verify Calculated CO2
Carbon dioxide	346.3083	--

Manufacturer Test Comments

24MY IK PE2 2.5T AWD 19" AS E10 - US06

Certification Summary Information Report

Test Group		VHYXV02.5GP5				Evaporative/Refueling Family				VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	150,000 miles	Federal Tier 3 Bin 50	CO	0.2546	--	--	--	0.04	--	0.295	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0.005	--	1.03	--	0.0029	--	0.008	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0167	--	--	--	--	--	0.026	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0117	--	--	--	0.0067	--	0.018	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	PM	0.0017	--	--	--	0	--	0.002	0.006	Pass
CA	150,000 miles	California LEV-IV ULEV50	CO	0.25	--	--	--	0.04	--	0.3	9.6	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0.005	--	1.03	--	0.0029	--	0.008	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0167	--	--	--	--	--	0.026	0.060	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0117	--	--	--	0.0067	--	0.018	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	PM	0.0017	--	--	--	0	--	0.002	0.006	Pass

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Test #	RHYYX10080618	Test Procedure	95 - SC03
Exhaust Test # for this Evap Test	--	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)
Test Date	04/26/2023	Fuel	Gasoline
Fuel Batch ID	21T-01	Fuel Calibration Number	1
Vehicle Class	LDV/Passenger Car	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	--		
Test Start Odometer Reading	4764	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	Yes

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
CO (Carbon Monoxide)	0.2769	--
DT-ASCR (Drive Trace Absolute Speed Change Rating)	3.2	--
DT-EER (Drive Trace Energy Economy Rating)	2.6	--
DT-IWRR (Drive Trace Inertia Work Ratio Rating)	4.09	--
MFR FE (Manufacturer Fuel Economy)	20.6689	20.6689
NOX (Nitrogen Oxide)	0.0082	--
HC-NM (Non-methane Hydrocarbon)	0	--
NMOG (Non-methane organic gases)	0	--
HC-TOTAL (Total Hydrocarbon)	0.0026	--

Test Result Name	Unrounded Test Result	Verify Calculated CO2
Carbon dioxide	419.2302	--

Manufacturer Test Comments

24MY IK PE2 2.5T AWD 19" AS E10 - SC03

Certification Summary Information Report

Test Group		VHYXV02.5GP5				Evaporative/Refueling Family				VHYXR0132GPG		
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	RAF	NMOG/NM HC Ratio	Diesel Adjustment Factor	Add DF	Mult DF	Certification Level	Standard	Pass/Fail
Fed	150,000 miles	Federal Tier 3 Bin 50	CO	0.2769	--	--	--	0.04	--	0.317	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG	0	--	1.03	--	0.0029	--	0.003	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NMOG+NOX	0.0082	--	--	--	--	--	0.018	99.999	Pass
Fed	150,000 miles	Federal Tier 3 Bin 50	NOX	0.0082	--	--	--	0.0067	--	0.015	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	CO	0.28	--	--	--	0.04	--	0.3	1.7	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG	0	--	1.03	--	0.0029	--	0.003	99.999	Pass
CA	150,000 miles	California LEV-IV ULEV50	NMOG+NOX	0.0082	--	--	--	--	--	0.018	0.050	Pass
CA	150,000 miles	California LEV-IV ULEV50	NOX	0.0082	--	--	--	0.0067	--	0.015	99.999	Pass

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG
-------------------	--------------	-------------------------------------	--------------

Emission Data Vehicle Information

Vehicle ID / Configuration	RG3U1L5TA082A / 0	Manufacturer Vehicle Configuration Number	0
Original Test Group Name	MHYXV03.5HT5	Original Evaporative/Refueling Family	MHYXR0142HTG
Original Test Vehicle Model Year	2021		

Vehicle Model

Represented Test Vehicle Make	Genesis	Represented Test Vehicle Model	G80
--------------------------------------	---------	---------------------------------------	-----

Leak Family Details

Leak Family Identifier	RG3	Leak Family Name	MHYXR0142HTG-RG3
-------------------------------	-----	-------------------------	------------------

Drive Sources and Fuel System Details

Drive Source and Fuel#	Drive Source	Fuel
1	Combustion Engine	Gasoline

Hybrid Indicator	No	Multiple Fuel Combustion	--
Multiple Fuel Storage	--	Rechargeable Energy Storage System Indicator	--
Fuel Cell Indicator	--	Rechargeable Energy Storage System, if 'Other'	--
Rechargeable Energy Storage System	--		
Off-board charge Capable Indicator	--		
Odometer Correction -- Initial	0	Odometer Correction Factor	0.9948
Odometer Correction Sign	+ = System Miles is equal to (Test odometer reading * Correction factor) + Initial system miles		
Odometer Correction Units	Miles		
Engine Code	G6DS-AC	Rated Horsepower	375
Displacement (liters)	3.5		
Air Aspiration Method	Turbocharged	Air Aspiration Method, if 'Other'	
Number of Air Aspiration Devices	2	Air Aspiration Device Configuration	Parallel
Charge Air Cooler Type	Liquid	Drive Mode While Testing	2-Wheel Drive, Rear
Shift Indicator Light Usage	Not equipped	Aged Emission Components	4,000 (mi)
Curb Weight (lbs)	4497	Equivalent Test Weight (pounds)	4750
GVWR (lbs)	5567	N/V Ratio	24.8
Axle Ratio	3.54		
Transmission Type	Semi-Automatic	# of Transmission Gears	8
Transmission Lockup	Yes	Creep Gear	No

Dynamometer Coefficients:

Target Coefficients			Set Coefficients			EPA Calculated Total Road Load Horse Power for City/Highway/Evap Coefficients	
Coefficient Category	A (lbf)	B (lbf/mph)	C (lbf/mph**2)	A (lbf)	B (lbf/mph)	C (lbf/mph**2)	
City/Highway/Evap	44.566	0.44728	0.017087	21.698	0.14745	0.018759	14.6

Emission Control Device Comments --

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG					
Manufacturer Test Vehicle Comments	21MY RG3 3.5T EVAP AWD 20"							
Test #	MHYX10062524	Test Procedure	38 - CA fuel 3-day evap.					
Exhaust Test # for this Evap Test	MHYX10062521	Test Fuel Type	46 - CARB LEV3 E10 Regular Gasoline					
Test Date	11/22/2019	Fuel	Gasoline					
Fuel Batch ID	19E-03	Fuel Calibration Number	1					
Vehicle Class	N/A	DF Type	Mfr. Determined					
Verify Test Lab ID	772-1, Jangduck-Dong							
E10 Evaporative Test Measurement Method	Calculated (1.08 x FID Total Hydrocarbons)							
Test Start Odometer Reading	4238	Odometer Units	M					
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--					
State of Charge Delta	--							
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	No					
Test Results								
Test Result Name		Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)					
HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)		0.1919	--					
Manufacturer Test Comments 21MY RG3 3.5L 20"(ETW:4750)-3DBL								
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail
Fed	150,000 miles	Federal Tier 3 Evap	HC-TOTAL-EQUIV	0.1919	0	0.192	0.3	Pass
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	HC-TOTAL-EQUIV	0.1919	0	0.192	0.3	Pass

Certification Summary Information Report

Test Group		VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG
Test #		MHYX91004651	Test Procedure	27 - California fuel 2-day evap
Exhaust Test # for this Evap Test		MHYX91004650	Test Fuel Type	46 - CARB LEV3 E10 Regular
Test Date		10/22/2020	Fuel	Gasoline
Fuel Batch ID		26757	Fuel Calibration Number	1
Vehicle Class		N/A	DF Type	Mfr. Determined
Verify Test Lab ID		--		
E10 Evaporative Test Measurement Method		Calculated (1.08 x FID Total Hydrocarbons)		
Test Start Odometer Reading		5077.1	Odometer Units	M
4WD Test Dyno		No	Diesel Adjustment Factor Usage	--
State of Charge Delta		--		
Drive Cycle Speed Tolerance Criteria		Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	No

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value
HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)	0.207219	--

Manufacturer Test Comments

Hot_Soak_HC_(g) = 0.044611, Diurnal (gHC) = 0.162608

Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail
Fed	150,000 miles	Federal Tier 3 Evap	HC-TOTAL-EQUIV	0.2072	0	0.207	0.3	Pass
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	HC-TOTAL-EQUIV	0.2072	0	0.207	0.3	Pass

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG						
Test #	MHYX10062526	Test Procedure	37 - California Fuel Running Loss						
Exhaust Test # for this Evap Test	MHYX10062521	Test Fuel Type	46 - CARB LEV3 E10 Regular Gasoline						
Test Date	11/22/2019	Fuel	Gasoline						
Fuel Batch ID	19E-03	Fuel Calibration Number	1						
Vehicle Class	N/A	DF Type	Mfr. Determined						
Verify Test Lab ID	772-1, Jangduck-Dong								
E10 Evaporative Test Measurement Method	Calculated (1.08 x FID Total Hydrocarbons)								
Test Start Odometer Reading	4238	Odometer Units	M						
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--						
State of Charge Delta	--								
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	No						
Test Results									
<table border="1"> <thead> <tr> <th>Test Result Name</th> <th>Unrounded Test Result</th> <th>Verify Calculated FE Equivalent Value (miles per gallon)</th> </tr> </thead> <tbody> <tr> <td>HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)</td> <td>0.001</td> <td>--</td> </tr> </tbody> </table>				Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)	HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)	0.001	--
Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)							
HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)	0.001	--							
Manufacturer Test Comments									
21MY RG3 3.5L 20"(ETW:4750) CA E10-RL									
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail	
Fed	150,000 miles	Federal Tier 3 Evap	HC-TOTAL-EQUIV	0.001	0	0	0.05	Pass	
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	HC-TOTAL-EQUIV	0.001	0	0	0.05	Pass	

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG						
Test #	MHYX10062527	Test Procedure	24 - Federal fuel refueling test (ORVR)						
Exhaust Test # for this Evap Test	MHYX10062523	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)						
Test Date	11/06/2019	Fuel	Gasoline						
Fuel Batch ID	18T-03	Fuel Calibration Number	1						
Vehicle Class	N/A	DF Type	Mfr. Determined						
Verify Test Lab ID	772-1, Jangduck-Dong								
E10 Evaporative Test Measurement Method	Calculated (1.08 x FID Total Hydrocarbons)								
Test Start Odometer Reading	4102	Odometer Units	M						
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--						
State of Charge Delta	--								
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	No						
Test Results									
<table border="1"> <tr> <th>Test Result Name</th> <th>Unrounded Test Result</th> <th>Verify Calculated FE Equivalent Value (miles per gallon)</th> </tr> <tr> <td>HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)</td> <td>0.006</td> <td>--</td> </tr> </table>				Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)	HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)	0.006	--
Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)							
HC-TOTAL-EQUIV (Total Hydrocarbon equivalent - Evap only)	0.006	--							
Manufacturer Test Comments									
21MY RG3 3.5L 20"(ETW:4750) FED E10-ORVR									
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail	
Fed	150,000 miles	Federal Tier 3 Evap	HC-TOTAL-EQUIV	0.006	0	0.01	0.2	Pass	
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	HC-TOTAL-EQUIV	0.006	0	0.01	0.2	Pass	

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG
Test #	MHYX10062528	Test Procedure	65 - Evap Canister Bleed Test
Exhaust Test # for this Evap Test	--	Test Fuel Type	46 - CARB LEV3 E10 Regular Gasoline
Test Date	11/28/2019	Fuel	Gasoline
Fuel Batch ID	19E-03	Fuel Calibration Number	1
Vehicle Class	N/A	DF Type	Mfr. Determined
Verify Test Lab ID	772-1, Jangduck-Dong		
E10 Evaporative Test Measurement Method	Calculated (1.08 x FID Total Hydrocarbons)		
Test Start Odometer Reading	4257	Odometer Units	M
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--
State of Charge Delta	--		
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	No

Test Results

Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value (miles per gallon)
HC-TOTAL (Total Hydrocarbon)	0.0148	--

Manufacturer Test Comments

21MY RG3 3.5L 20"(ETW:4750) CA E10-Bleed

Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail
Fed	150,000 miles	Federal Tier 3 Evap	HC-TOTAL	0.0148	0	0.015	0.02	Pass
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	HC-TOTAL	0.0148	0	0.015	0.02	Pass

Test Group		VHYXV02.5GP5		Evaporative/Refueling Family		VHYXR0132GPG																													
Test #		MHYX10062680		Test Procedure		67 - Leak Test - Port Near Canister																													
Exhaust Test # for this Evap Test		--		Test Fuel Type		48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)																													
Test Date		12/02/2019		Fuel		Gasoline																													
Fuel Batch ID		18T-03		Fuel Calibration Number		1																													
Vehicle Class		N/A		DF Type		Mfr. Determined																													
Verify Test Lab ID		772-1, Jangduck-Dong																																	
E10 Evaporative Test Measurement Method		--																																	
Test Start Odometer Reading		4257		Odometer Units		M																													
4WD Test Dyno		No		Diesel Adjustment Factor Usage		--																													
State of Charge Delta		--																																	
Drive Cycle Speed Tolerance Criteria		Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)		Road Speed Fan Usage		No																													
Test Results																																			
<table><tr><td colspan="2">Test Result Name</td><td colspan="2">Unrounded Test Result</td><td colspan="5">Verify Calculated FE Equivalent Value</td></tr><tr><td colspan="2">LEAK-DIA (Effective Leak Diameter (inches))</td><td colspan="2">0</td><td colspan="5">--</td></tr></table>									Test Result Name		Unrounded Test Result		Verify Calculated FE Equivalent Value					LEAK-DIA (Effective Leak Diameter (inches))		0		--													
Test Result Name		Unrounded Test Result		Verify Calculated FE Equivalent Value																															
LEAK-DIA (Effective Leak Diameter (inches))		0		--																															
Manufacturer Test Comments																																			
21MY RG3 3.5L 20"(ETW:4750) FED E10-Leak Test Port Near Canister																																			
<table><tr><td>Certification Region</td><td>Useful Life</td><td>Standard Level</td><td>Emission Name</td><td>Rounded Result</td><td>Add DF</td><td>Certification Level</td><td>Standard</td><td>Pass/Fail</td></tr><tr><td>Fed</td><td>150,000 miles</td><td>Federal Tier 3 Evap</td><td>LEAK-DIA</td><td>0</td><td>0</td><td>0</td><td>0.02</td><td>Pass</td></tr><tr><td>CA</td><td>150,000 miles</td><td>California LEV-IV Zero Evap (Option 2)</td><td>LEAK-DIA</td><td>0</td><td>0</td><td>0</td><td>0.02</td><td>Pass</td></tr></table>									Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail	Fed	150,000 miles	Federal Tier 3 Evap	LEAK-DIA	0	0	0	0.02	Pass	CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	LEAK-DIA	0	0	0	0.02	Pass
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail																											
Fed	150,000 miles	Federal Tier 3 Evap	LEAK-DIA	0	0	0	0.02	Pass																											
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	LEAK-DIA	0	0	0	0.02	Pass																											

Certification Summary Information Report

Test Group	VHYXV02.5GP5	Evaporative/Refueling Family	VHYXR0132GPG						
Test #	MHYX10062681	Test Procedure	68 - Leak Test - Port Near Fuel Pipe						
Exhaust Test # for this Evap Test	--	Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)						
Test Date	12/02/2019	Fuel	Gasoline						
Fuel Batch ID	18T-03	Fuel Calibration Number	1						
Vehicle Class	N/A	DF Type	Mfr. Determined						
Verify Test Lab ID	772-1, Jangduck-Dong								
E10 Evaporative Test Measurement Method	--								
Test Start Odometer Reading	4257	Odometer Units	M						
4WD Test Dyno	No	Diesel Adjustment Factor Usage	--						
State of Charge Delta	--								
Drive Cycle Speed Tolerance Criteria	Used Part 1066 (+/- 2.0 mph, +/- 1.0 sec)	Road Speed Fan Usage	No						
Test Results									
<table border="1"> <tr> <th>Test Result Name</th> <th>Unrounded Test Result</th> <th>Verify Calculated FE Equivalent Value</th> </tr> <tr> <td>LEAK-DIA (Effective Leak Diameter (inches))</td> <td>0</td> <td>--</td> </tr> </table>				Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value	LEAK-DIA (Effective Leak Diameter (inches))	0	--
Test Result Name	Unrounded Test Result	Verify Calculated FE Equivalent Value							
LEAK-DIA (Effective Leak Diameter (inches))	0	--							
Manufacturer Test Comments									
21MY RG3 3.5L 20"(ETW:4750) FED E10-Leak Test Port Near Fuel Pipe									
Certification Region	Useful Life	Standard Level	Emission Name	Rounded Result	Add DF	Certification Level	Standard	Pass/Fail	
Fed	150,000 miles	Federal Tier 3 Evap	LEAK-DIA	0	0	0	0.02	Pass	
CA	150,000 miles	California LEV-IV Zero Evap (Option 2)	LEAK-DIA	0	0	0	0.02	Pass	

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Fuel Properties			
Fuel Batch ID	22M-01	Fuel Calibration Number	1
Test Fuel Type	61 - Tier 2 Cert Gasoline	Fuel Batch Calibration Date	02/14/2022
Fuel Batch Calibration Effective Date	02/14/2022	Fuel Batch Calibration Ineffective Date	02/14/2025
Carbon Weight Fraction NMHC	--	Carbon Weight Fraction HC	--
Exhaust Carbon Weight Fraction	--	Fuel Methanol Volume Fraction	--
Fuel Density (grams/cubic ft)	--	Fuel Specific Gravity	0.743
Fuel Ethanol Volume Percent (%)	--	Fuel Net Heating Value / Fuel Net Heat of Combustion (E0) (BTU/lb)	18435
Fuel Net Heat of Combustion (E10) (MJ/kg)	--	Fuel Carbon Mass Fraction (E10)	--
Fuel Blend Carbon Weight Fraction / Fuel Carbon Mass Fraction (E0)	0.867	Weight Fraction CO2	--
Fuel Batch ID	26757	Fuel Calibration Number	1
Test Fuel Type	46 - CARB LEV3 E10 Regular Gasoline	Fuel Batch Calibration Date	07/27/2017
Fuel Batch Calibration Effective Date	07/27/2017	Fuel Batch Calibration Ineffective Date	07/27/2032
Carbon Weight Fraction NMHC	--	Carbon Weight Fraction HC	--
Exhaust Carbon Weight Fraction	--	Fuel Methanol Volume Fraction	--
Fuel Density (grams/cubic ft)	--	Fuel Specific Gravity	0.749
Fuel Ethanol Volume Percent (%)	9.8	Fuel Net Heating Value / Fuel Net Heat of Combustion (E0) (BTU/lb)	17958
Fuel Net Heat of Combustion (E10) (MJ/kg)	--	Fuel Carbon Mass Fraction (E10)	--
Fuel Blend Carbon Weight Fraction / Fuel Carbon Mass Fraction (E0)	0.827	Weight Fraction CO2	--
Fuel Batch ID	21T-01	Fuel Calibration Number	1
Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)	Fuel Batch Calibration Date	07/24/2021
Fuel Batch Calibration Effective Date	12/24/2021	Fuel Batch Calibration Ineffective Date	12/24/2024
Carbon Weight Fraction NMHC	--	Carbon Weight Fraction HC	--
Exhaust Carbon Weight Fraction	--	Fuel Methanol Volume Fraction	--
Fuel Density (grams/cubic ft)	--	Fuel Specific Gravity	0.746
Fuel Ethanol Volume Percent (%)	9.7	Fuel Net Heating Value / Fuel Net Heat of Combustion (E0) (BTU/lb)	17945
Fuel Net Heat of Combustion (E10) (MJ/kg)	--	Fuel Carbon Mass Fraction (E10)	--
Fuel Blend Carbon Weight Fraction / Fuel Carbon Mass Fraction (E0)	0.828	Weight Fraction CO2	--
Fuel Batch ID	19E-03	Fuel Calibration Number	1
Test Fuel Type	46 - CARB LEV3 E10 Regular Gasoline	Fuel Batch Calibration Date	08/08/2019
Fuel Batch Calibration Effective Date	10/29/2019	Fuel Batch Calibration Ineffective Date	10/29/2022
Carbon Weight Fraction NMHC	--	Carbon Weight Fraction HC	--
Exhaust Carbon Weight Fraction	--	Fuel Methanol Volume Fraction	--

Certification Summary Information Report

Test Group	VHYYXV02.5GP5	Evaporative/Refueling Family	VHYYXR0132GPG
Fuel Density (grams/cubic ft)	--	Fuel Specific Gravity	0.75
Fuel Ethanol Volume Percent (%)	9.6	Fuel Net Heating Value / Fuel Net Heat of Combustion (E0) (BTU/lb)	17917
Fuel Net Heat of Combustion (E10) (MJ/kg)	--	Fuel Carbon Mass Fraction (E10)	--
Fuel Blend Carbon Weight Fraction / Fuel Carbon Mass Fraction (E0)	0.827	Weight Fraction CO2	--
Fuel Batch ID	18T-03	Fuel Calibration Number	1
Test Fuel Type	48 - Tier 3 E10 Regular Gasoline (9 RVP @Low Alt.)	Fuel Batch Calibration Date	12/10/2018
Fuel Batch Calibration Effective Date	12/11/2018	Fuel Batch Calibration Ineffective Date	12/11/2021
Carbon Weight Fraction NMHC	--	Carbon Weight Fraction HC	--
Exhaust Carbon Weight Fraction	--	Fuel Methanol Volume Fraction	--
Fuel Density (grams/cubic ft)	--	Fuel Specific Gravity	0.745
Fuel Ethanol Volume Percent (%)	10.1	Fuel Net Heating Value / Fuel Net Heat of Combustion (E0) (BTU/lb)	17781
Fuel Net Heat of Combustion (E10) (MJ/kg)	--	Fuel Carbon Mass Fraction (E10)	--
Fuel Blend Carbon Weight Fraction / Fuel Carbon Mass Fraction (E0)	0.83	Weight Fraction CO2	--
Fuel Batch ID	22D-01	Fuel Calibration Number	1
Test Fuel Type	28 - Cold CO E10 Regular Gasoline (Tier 3)	Fuel Batch Calibration Date	07/29/2021
Fuel Batch Calibration Effective Date	05/10/2022	Fuel Batch Calibration Ineffective Date	05/10/2025
Carbon Weight Fraction NMHC	--	Carbon Weight Fraction HC	--
Exhaust Carbon Weight Fraction	--	Fuel Methanol Volume Fraction	--
Fuel Density (grams/cubic ft)	--	Fuel Specific Gravity	0.742
Fuel Ethanol Volume Percent (%)	9.9	Fuel Net Heating Value / Fuel Net Heat of Combustion (E0) (BTU/lb)	17925
Fuel Net Heat of Combustion (E10) (MJ/kg)	--	Fuel Carbon Mass Fraction (E10)	--
Fuel Blend Carbon Weight Fraction / Fuel Carbon Mass Fraction (E0)	0.828	Weight Fraction CO2	--

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family			VHYXR0132GPG		
Consolidated List of Standards										
Exhaust Standards										
Cert Region		California + CAA Section 177 states			Cert/In-Use Code			Cert		
Vehicle Class		LDV/Passenger Car			Standard Level			California LEV-IV ULEV50		
Fuel		Gasoline			Test Procedure			Fed. fuel 50 F exh.		
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std	
4,000 miles	CO	--	--	--	--	--	--	0	1.7	
4,000 miles	HCHO	--	--	--	--	--	--	--	0.016	
4,000 miles	NMOG	--	--	1.1	--	--	--	0	99.999	
4,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.100	
4,000 miles	NOX	--	--	--	--	--	--	0	99.999	
Cert Region		California + CAA Section 177 states			Cert/In-Use Code			Cert		
Vehicle Class		LDV/Passenger Car			Standard Level			California LEV-IV ULEV50		
Fuel		Gasoline			Test Procedure			Federal fuel 2-day exhaust (w/can load)		
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std	
150,000 miles	CO	--	--	--	--	--	--	0.04	1.7	
150,000 miles	HCHO	--	--	--	--	--	--	--	0.004	
150,000 miles	NMOG	--	--	1.1	--	--	--	0.0029	99.999	
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.050	
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999	
150,000 miles	PM	--	--	--	--	--	--	0	0.003	

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family			VHYXR0132GPG	
Cert Region		Federal			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			Federal Tier 3 Bin 50	
Fuel		Gasoline			Test Procedure			Federal fuel 2-day exhaust (w/can load)	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
120,000 miles	CREE	--	--	--	--	--	--	0.242171	999
120,000 miles	METHANE	--	--	--	--	--	--	0.0044	0.030
120,000 miles	N2O	--	--	--	--	--	--	0.0019	0.010
150,000 miles	CO	--	--	--	--	--	--	0.04	1.7
150,000 miles	CO-COMP	--	--	--	--	--	--	0	4.2
150,000 miles	HCHO	--	--	--	--	--	--	--	0.004
150,000 miles	NMOG	--	--	1.1	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.050
150,000 miles	NMOG+NOX-COMP	--	--	--	--	--	--	0	0.050
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999
150,000 miles	PM	--	--	--	--	--	--	0	0.003
Cert Region		Federal			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			Federal Tier 3 Bin 50	
Fuel		Gasoline			Test Procedure			Cold CO	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
50,000 miles	CO	--	--	--	--	--	--	0.01	10.0
120,000 miles	HC-NM	--	--	--	--	--	--	0.0021	0.3

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family			VHYXR0132GPG	
Cert Region		Federal			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			Federal Tier 3 Bin 50	
Fuel		Gasoline			Test Procedure			US06	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
150,000 miles	CO	--	--	--	--	--	--	0.04	99.999
150,000 miles	NMOG	--	--	1.03	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	99.999
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999
150,000 miles	PM	--	--	--	--	--	--	0	0.006
Cert Region		California + CAA Section 177 states			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			California LEV-IV ULEV50	
Fuel		Gasoline			Test Procedure			HWFE	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
150,000 miles	NMOG	--	--	1.03	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.050
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999
Cert Region		Federal			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			Federal Tier 3 Bin 50	
Fuel		Gasoline			Test Procedure			SC03	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
150,000 miles	CO	--	--	--	--	--	--	0.04	99.999
150,000 miles	NMOG	--	--	1.03	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	99.999
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999

Certification Summary Information Report

Test Group		VHYXV02.5GP5			Evaporative/Refueling Family			VHYXR0132GPG	
Cert Region		California + CAA Section 177 states			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			California LEV-IV ULEV50	
Fuel		Gasoline			Test Procedure			US06	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
150,000 miles	CO	--	--	--	--	--	--	0.04	9.6
150,000 miles	NMOG	--	--	1.03	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.060
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999
150,000 miles	PM	--	--	--	--	--	--	0	0.006
Cert Region		Federal			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			Federal Tier 3 Bin 50	
Fuel		Gasoline			Test Procedure			HWFE	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
120,000 miles	CREE	--	--	--	--	--	--	0.242171	999
150,000 miles	NMOG	--	--	1.03	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.050
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999
Cert Region		California + CAA Section 177 states			Cert/In-Use Code			Cert	
Vehicle Class		LDV/Passenger Car			Standard Level			California LEV-IV ULEV50	
Fuel		Gasoline			Test Procedure			SC03	
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
150,000 miles	CO	--	--	--	--	--	--	0.04	1.7
150,000 miles	NMOG	--	--	1.03	--	--	--	0.0029	99.999
150,000 miles	NMOG+NOX	--	--	--	--	--	--	0	0.050
150,000 miles	NOX	--	--	--	--	--	--	0.0067	99.999

Certification Summary Information Report

Test Group	VHYXV02.5GP5		Evaporative/Refueling Family			VHYXR0132GPG			
Cert Region	California + CAA Section 177 states		Cert/In-Use Code			Cert			
Vehicle Class	LDV/Passenger Car		Standard Level			California LEV-IV ULEV50			
Fuel	Gasoline		Test Procedure			Cold CO			
Useful Life	Emission Name	Rounded Result	RAF	NMOG / NMHC	Upward Diesel Adjustment Factor	Downward Diesel Adjustment Factor	Mult DF	Add DF	Std
50,000 miles	CO	--	--	--	--	--	--	0.01	10.0

Evaporative/Refueling Standards

Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal					
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap					
Test Procedure		Evap Canister Bleed Test									
Fuel		Useful Life		Emission Name		Rounded Result		Std		Add DF	
Gasoline		150,000 miles		HC-TOTAL		--		0.020		0	

Evaporative/Refueling Family	VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code	Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure	Leak Test - Port Near Fuel Pipe					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF	
Gasoline	150,000 miles	LEAK-DIA	--	0.02	0	

Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal	
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap	
Test Procedure		California Fuel Running Loss					
Fuel	Useful Life	Emission Name	Rounded Result		Std	Add DF	
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--		0.05	0	

Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code		Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure		California Fuel Running Loss					
Fuel	Useful Life	Emission Name	Rounded Result		Std	Add DF	
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--		0.05	0	

Certification Summary Information Report

Test Group		VHYXV02.5GP5		Evaporative/Refueling Family		VHYXR0132GPG	
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code		Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure		Leak Test - Port Near Canister					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	LEAK-DIA	--	0.02	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code		Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure		Evap Canister Bleed Test					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL	--	0.020	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code		Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure		CA fuel 3-day evap.					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--	0.300	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code		Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure		California fuel 2-day evap					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--	0.300	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal	
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap	
Test Procedure		CA fuel 3-day evap.					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--	0.300	0		

Certification Summary Information Report

Test Group		VHYXV02.5GP5		Evaporative/Refueling Family		VHYXR0132GPG	
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal	
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap	
Test Procedure		California fuel 2-day evap					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--	0.300	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal	
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap	
Test Procedure		Federal fuel refueling test (ORVR)					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--	0.20	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal	
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap	
Test Procedure		Leak Test - Port Near Fuel Pipe					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	LEAK-DIA	--	0.020	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		California + CAA Section 177 states	
Cert/In-Use Code		Cert		Standard Level		California LEV-IV Zero Evap (Option 2)	
Test Procedure		Federal fuel refueling test (ORVR)					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	HC-TOTAL-EQUIV	--	0.20	0		
Evaporative/Refueling Family		VHYXR0132GPG		Cert Region		Federal	
Cert/In-Use Code		Cert		Standard Level		Federal Tier 3 Evap	
Test Procedure		Leak Test - Port Near Canister					
Fuel	Useful Life	Emission Name	Rounded Result	Std	Add DF		
Gasoline	150,000 miles	LEAK-DIA	--	0.020	0		

Certification Summary Information Report

Test Group		VHXXV02.5GP5	Evaporative/Refueling Family	VHXXR0132GPG
Glossary				
Useful Life				
4	4,000 miles	120	120,000 miles	
50	50,000 miles	150	150,000 miles	
100	100,000 miles			
Emission Name				
HC-TOTAL	Total Hydrocarbon	COMB-CREE	Combined Carbon-Related Exhaust Emissions	
CO	Carbon Monoxide	COMB-OPT-CREE	Combined Optional Carbon-Related Exhaust Emissions	
CO2	Carbon dioxide	HC-TOTAL-EQUIV	Total Hydrocarbon equivalent - Evap only	
CREE	Carbon-Related Exhaust Emissions	METHANE-COMB	Combined CH4 for HD 2b/3 vehicles only	
OPT-CREE	Optional Carbon-Related Exhaust Emissions	N2O-COMB	Combined Nitrous Oxide for HD 2b/3 vehicles only	
NOX	Nitrogen Oxide	LEAK-DIA	Effective Leak Diameter (inches)	
PM	Particulate Matter	LEAK-GAS CAP	Gas Cap Leakage (cc/min)	
PM-COMP	SFTP Composite Particulate Matter	CO2-COMB	Combined Carbon Dioxide for HD 2b/3 Vehicles Only	
HC-NM	Non-methane Hydrocarbon	KW-HRS	Integrated DC KW-HRS	
OMHCE	Organic material Hydrocarbon Equivalent	CH4 BAG 1	Bag 1 Methane	
OMNMHCE	Organic material non-methane HC equivalent	CH4 BAG 2	Bag 2 Methane	
NMOG	Non-methane organic gases	CH4 BAG 3	Bag 3 Methane	
HCHO	Formaldehyde	CH4 BAG 4	Bag 4 Methane	
H3C2HO	Acetaldehyde	CO BAG 1	Bag 1 Carbon Monoxide	
HC-NM+NOX	SFTP Non-methane Hydrocarbon + Nitrogen Oxides for US06 or SC03	CO BAG 2	Bag 2 Carbon Monoxide	
HC-NM+NOX-COMP	SFTP Composite Non-methane Hydrocarbon + Nitrogen Oxides	CO BAG 3	Bag 3 Carbon Monoxide	
CO-COMP	SFTP Composite Carbon Monoxide	CO BAG 4	Bag 4 Carbon Monoxide	
ETHANOL	C2H5OH - Ethanol	NMOG BAG 1	Bag 1 Non-methane organic gases	
FE BAG 1	Bag 1 Fuel Economy	NMOG BAG 2	Bag 2 Non-methane organic gases	
FE BAG 2	Bag 2 Fuel Economy	NMOG BAG 3	Bag 3 Non-methane organic gases	
FE BAG 3	Bag 3 Fuel Economy	NMOG BAG 4	Bag 4 Non-methane organic gases	
FE BAG 4	Bag 4 Fuel Economy	ACT-DISTANCE BAG 1	Bag 1 Actual Distance	
MFR FE	Manufacturer Fuel Economy	ACT-DISTANCE BAG 2	Bag 2 Actual Distance	
HC	Hydrocarbon for Running Loss and ORVR	ACT-DISTANCE BAG 3	Bag 3 Actual Distance	
METHANE	CH4 - Methane	ACT-DISTANCE BAG 4	Bag 4 Actual Distance	
METHANOL	CH3OH - Methanol	HC-TOTAL BAG 1	Bag 1 Total Hydrocarbon	
N2O	Nitrous Oxide	HC-TOTAL BAG 2	Bag 2 Total Hydrocarbon	
SPITBACK	Spitback Hydrocarbon in grams	HC-TOTAL BAG 3	Bag 3 Total Hydrocarbon	
AMP-HRS	Integrated Amp-hours	HC-TOTAL BAG 4	Bag 4 Total Hydrocarbon	
START-SOC	System Start State of Charge Watt-hours	WATT-HRS BAG 1	Bag 1 Watt Hours	
END-SOC	System End State of Charge Watt-hours	WATT-HRS BAG 2	Bag 2 Watt Hours	

Certification Summary Information Report

Test Group		VHYYXV02.5GP5	Evaporative/Refueling Family		VHYYXR0132GPG
ACT-DISTANCE	Actual Distance Driven (miles)		WATT-HRS BAG 3	Bag 3 Watt Hours	
AS-VOLT	Average System Voltage		WATT-HRS BAG 4	Bag 4 Watt Hours	
CO2 BAG 1	Bag 1 Carbon Dioxide		WATT-HRS	Watt Hours	
CO2 BAG 2	Bag 2 Carbon Dioxide		HC-NM BAG 1	Bag 1 Non-methane Hydrocarbon	
CO2 BAG 3	Bag 3 Carbon Dioxide		HC-NM BAG 2	Bag 2 Non-methane Hydrocarbon	
CO2 BAG 4	Bag 4 Carbon Dioxide		HC-NM BAG 3	Bag 3 Non-methane Hydrocarbon	
NMOG+NOX	Non-methane organic gases plus Nitrogen Oxides		HC-NM BAG 4	Bag 4 Non-methane Hydrocarbon	
NMOG+NOX-COMP	SFTP Composite Non-methane Organic Gases + Nitrogen Oxides		N2O BAG 1	Bag 1 Nitrous Oxide	
DT-IWRR	Drive Trace Inertia Work Ratio Rating		N2O BAG 2	Bag 2 Nitrous Oxide	
DT-ASCR	Drive Trace Absolute Speed Change Rating		N2O BAG 3	Bag 3 Nitrous Oxide	
DT-EER	Drive Trace Energy Economy Rating		N2O BAG 4	Bag 4 Nitrous Oxide	
Certification Region					
CA	California + CAA Section 177 states		FA	Federal	
Exhaust Emission Standard Level					
B1	Federal Tier 2 Bin 1		HDV2B340	Federal Tier 3 HD Class 2b Transitional Bin 340	
B2	Federal Tier 2 Bin 2		HDV2B250	Federal Tier 3 HD Class 2b Bin 250	
B3	Federal Tier 2 Bin 3		HDV2B200	Federal Tier 3 HD Class 2b Bin 200	
B4	Federal Tier 2 Bin 4		HDV2B170	Federal Tier 3 HD Class 2b Bin 170	
B5	Federal Tier 2 Bin 5		HDV2B150	Federal Tier 3 HD Class 2b Bin 150	
B6	Federal Tier 2 Bin 6		HDV2B0	Federal Tier 3 HD Class 2b Bin 0	
B7	Federal Tier 2 Bin 7		HDV3B630	Federal Tier 3 HD Class 3 Transitional Bin 630	
B8	Federal Tier 2 Bin 8		HDV3B570	Federal Tier 3 HD Class 3 Transitional Bin 570	
B9	Federal Tier 2 Bin 9		HDV3B400	Federal Tier 3 HD Class 3 Bin 400	
B10	Federal Tier 2 Bin 10		HDV3B270	Federal Tier 3 HD Class 3 Bin 270	
B11	Federal Tier 2 Bin 11		HDV3B230	Federal Tier 3 HD Class 3 Bin 230	
HDV1	HDV1 (Federal HD chassis Class 2b GVW 8501-10000)		HDV3B200	Federal Tier 3 HD Class 3 Bin 200	
HDV2	HDV2 (Federal HD chassis Class 3 GVW 10001-14000)		HDV3B0	Federal Tier 3 HD Class 3 Bin 0	
L2	California LEV-II LEV		L4SULEV100	California LEV-IV SULEV100	
L2OP	California LEV-II LEV Optional		L4SULEV125	California LEV-IV SULEV125	
U2	California LEV-II ULEV		L4SULEV15	California LEV-IV SULEV15	
S2	California LEV-II SULEV		L4SULEV150	California LEV-IV SULEV150	
ZEV	California ZEV		L4SULEV170	California LEV-IV SULEV170	
OT	Other		L4SULEV175	California LEV-IV SULEV175	
T1	Federal Tier 1		L4SULEV20	California LEV-IV SULEV20	
PZEV	California PZEV		L4SULEV200	California LEV-IV SULEV200	
L2LEV160	California LEV-II LEV160		L4SULEV230	California LEV-IV SULEV230	
L2ULEV125	California LEV-II ULEV125		L4SULEV25	California LEV-IV SULEV25	
L2SULEV30	California LEV-II SULEV30		L4SULEV30	California LEV-IV SULEV30	
L2LEV395	California LEV-II LEV395		L4SULEV75	California LEV-IV SULEV75	

Certification Summary Information Report

Test Group		VHYXV02.5GP5	Evaporative/Refueling Family		VHYXR0132GPG
L2ULEV340	California LEV-II ULEV340		L4SULEV85	California LEV-IV SULEV85	
L2LEV630	California LEV-II LEV630		L4ULEV125	California LEV-IV ULEV125	
L2ULEV570	California LEV-II ULEV570		L4ULEV200	California LEV-IV ULEV200	
L3LEV160	California LEV-III LEV160		L4ULEV250	California LEV-IV ULEV250	
L3ULEV125	California LEV-III ULEV125		L4ULEV270	California LEV-IV ULEV270	
L3ULEV70	California LEV-III ULEV70		L4ULEV40	California LEV-IV ULEV40	
L3ULEV50	California LEV-III ULEV50		L4ULEV400	California LEV-IV ULEV400	
L3SULEV30	California LEV-III SULEV30		L4ULEV50	California LEV-IV ULEV50	
L3SULEV20	California LEV-III SULEV20		L4ULEV60	California LEV-IV ULEV60	
L3LEV395	California LEV-III LEV395		L4ULEV70	California LEV-IV ULEV70	
L3ULEV340	California LEV-III ULEV340		T4B170	Federal Tier 4 MDV Bin 170	
L3ULEV250	California LEV-III ULEV250		T4B150	Federal Tier 4 MDV Bin 150	
L3ULEV200	California LEV-III ULEV200		T4B125	Federal Tier 4 MDV Bin 125	
L3SULEV170	California LEV-III SULEV170		T4B100	Federal Tier 4 MDV Bin 100	
L3SULEV150	California LEV-III SULEV150		T4B85	Federal Tier 4 MDV Bin 85	
L3LEV630	California LEV-III LEV630		T4B75	Federal Tier 4 MDV Bin 75	
L3ULEV570	California LEV-III ULEV570		T4B70	Federal Tier 4 Bin 70	
L3ULEV400	California LEV-III ULEV400		T4B65	Federal Tier 4 Bin 65	
L3ULEV270	California LEV-III ULEV270		T4B60	Federal Tier 4 Bin 60	
L3SULEV230	California LEV-III SULEV230		T4B55	Federal Tier 4 Bin 55	
L3SULEV200	California LEV-III SULEV200		T4B50	Federal Tier 4 Bin 50	
T3B160	Federal Tier 3 Bin 160		T4B45	Federal Tier 4 Bin 45	
T3B125	Federal Tier 3 Bin 125		T4B40	Federal Tier 4 Bin 40	
T3B110	Federal Tier 3 Transitional Bin 110		T4B35	Federal Tier 4 Bin 35	
T3B85	Federal Tier 3 Transitional Bin 85		T4B30	Federal Tier 4 Bin 30	
T3SULEV30	Federal Tier 3 Transitional LEV-II SULEV30 Carryover		T4B25	Federal Tier 4 Bin 25	
T3B70	Federal Tier 3 Bin 70		T4B20	Federal Tier 4 Bin 20	
T3B50	Federal Tier 3 Bin 50		T4B15	Federal Tier 4 Bin 15	
T3B30	Federal Tier 3 Bin 30		T4B10	Federal Tier 4 Bin 10	
T3B20	Federal Tier 3 Bin 20		T4B5	Federal Tier 4 Bin 5	
T3B0	Federal Tier 3 Bin 0		T4B0	Federal Tier 4 Bin 0	
HDV2B395	Federal Tier 3 HD Class 2b Transitional Bin 395				
Transmission Type Code					
AMS	Automated Manual- Selectable (e.g. Automated Manual with paddles)	M	Manual		
A	Automatic	OT	Other		
AM	Automated Manual	SA	Semi-Automatic		
CVT	Continuously Variable	SCV	Selectable Continuously Variable (e.g. CVT with paddles)		
Drive System Code					
4	4-Wheel Drive	P	Part-time 4-Wheel Drive		

Certification Summary Information Report

Test Group		VHYYXV02.5GP5	Evaporative/Refueling Family		VHYYXR0132GPG
F	2-Wheel Drive, Front		A	All Wheel Drive	
R	2-Wheel Drive, Rear				
Additional Terms and Acronyms					
AFC	Alternative Fuel Converter		ICI	Independent Commercial Importer	
CSI	Certificate Summary Information		ORVR	Onboard Refueling Vapor Recovery	
DF	Deterioration Factor		SIL	Shift Indicator Light	
Evap	Evaporation, Evaporative		Trans	Transmission	