

## Cabot's #3600 CREOSOTE OIL

ACTIVE INGREDIENT:
Creosote Oil
INERT INGREDIENTS

80% 20%

4 LITERS --- 1.057 U. S. GALLONS

WARNING — KEEP OUT OF THE REACH OF CHILDREN SEE BACK PANEL FOR FURTHER WARNING STATEMENTS

## USE AND/OR HANDLING IS CONTRARY

## WARNING Keep out of the reach of children.

Keep away from heat and open flame. Do not get on skin. Do not breathe vapor or spray mist. Do not get in eyes or on clothing. Close container after each use. Harmful or fatal if swallowed. Do not induce vomiting. Call physician immediately. Before smoking or eating and after using, clean hands thoroughly. Do not use this product indoors, or any other confined areas, where the vapors may concentrate and cause injury to plant or animal life. Vapors will cause injury if adequate ventilation is not insured. Do not reuse container. Destroy when empty. This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste and container. Apply this product only as specified on this label. EPA Reg. No. 43-31.

CABOT'S #3600 CREOSOTE OIL is a Creosote distillate for protecting wood against decay. It penetrates deep into the wood preserving the interior as well as the surface. #3600 Creosote Oil is dark brown in color.

## DIRECTIONS

- 1. Apply with brush or spray, or by dipping.
- 2. All wood coming in contact with the soil should receive at least two applications with brush or spray, and if dipped should be immersed at least three minutes.
- 3. Two flowing coats should be applied.

COVERING POWER: One gallon covers about 100 square feet of roughsawn lumber, two coats.

Clean Your Brushes with Cabot's Brush Cleaner

Incorporated

MANUFACTURING CHEMISTS SINCE 187 BOSTON, MASSACHUSETTS 02108

EPA Est 43-MA-1