



Old Chelsea Works

Cabot's

#3770

CREOSOTE OIL

LIGHT COLORED
(Wood Preserving Shingle Oil)

ACTIVE INGREDIENTS:	
Gas-Tar Creosote Oil	98%
INERT INGREDIENTS:	
Water	2%
	<u>100%</u>

ONE U. S. GALLON

(5/6 IMPERIAL GALLON — 3.785 LITERS)

WARNING — KEEP OUT OF THE REACH OF CHILDREN
SEE BACK PANEL FOR FURTHER WARNING STATEMENTS

WARNING

Keep out of the reach of children.
Keep away from heat and open flame. Avoid prolonged contact with skin and breathing vapor and spray mist. Do not get in eyes or clothing. Close container after each use with adequate ventilation. Harmful if inhaled or absorbed through the skin. May cause severe burns. Do not induce vomiting. Consult physician immediately. Before smoking and after using, clean hands thoroughly. Do not contaminate water by cleaning equipment or disposal of waste and sludge. USDA Reg. No. 43-32.

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO THE INSTRUCTIONS.



WARNING

Keep out of the reach of children.

Keep away from heat and open flame. Avoid prolonged contact with skin and breathing of vapor and spray mist. Do not get in eyes or on clothing. Close container after each use. Use with adequate ventilation. Harmful if swallowed or absorbed through the skin. May produce severe burns. Do not induce vomiting. Call physician immediately. Before smoking or eating and after using, clean hands thoroughly. Do not contaminate water by cleaning of equipment or disposal of waste and container. USDA Reg. No. 43-32.

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS.



CABOT'S #3770 CREOSOTE OIL is a Creosote distillate for protecting wood against decay. It penetrates deep into the wood preserving the interior as well as the surface.

#3770 Creosote Oil is amber in color and is often referred to as a shingle stain oil.

DIRECTIONS

1. Apply with brush or spray, or by dipping.
2. All wood coming in contact with the soil should receive at least two applications with brush or spray, and if dipped should be immersed at least three minutes.

Covering Power: One gallon covers about 100 square feet of rough-sawn lumber, two coats.

Clean Your Brushes with Cabot's Brush Cleaner

Samuel Cabot

Incorporated
MANUFACTURING CHEMISTS SINCE 1877
BOSTON, MASS. 02108

