



Cabot's CONSERVO®

3300

Creosote Wood Preservative

(Contains Pentachlorophenol)

ACTIVE INGREDIENTS:

Creosote Oil	90.00%
Pentachlorophenol	1.27%
Other chlorophenols and related compounds	0.23%
INERT INGREDIENTS	8.50%

100.00%

4 LITERS — 1.057 U. S. GALLON

WARNING — KEEP OUT OF THE REACH OF CHILDREN
SEE SIDE PANEL FOR FURTHER WARNING STATEMENTS

WARNING

Keep out of the reach of children.

Keep away from heat and open flame. Avoid contact with skin. Do not breathe vapor or spray mist. Do not get in eyes or on clothing. Close container after each use. Use with adequate ventilation. Harmful if swallowed or absorbed through the skin. May produce severe burns. Do not induce vomiting. Call physician immediately. Before smoking or eating and after using, clean hands thoroughly. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies. Do not use where the product may come in contact with food, feed or livestock. Vapors will cause injury if adequate ventilation is not insured. Do not use this product indoors, or any other confined areas, where the vapors may concentrate and cause injury to plant or animal life.

This product is toxic to fish and wildlife; keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

EPA Reg. No. 43-71

CABOT'S CONSERVO is a specially prepared non-volatile Coal-Tar creosote oil which combines the three cardinal principles of wood preservation — Penetration, Protection, and Performance.

Penetration — Conservo penetrates deep into the wood preserving the interior as well as the surface.

Protection — Conservo contains Pentachlorophenol and tar acids which destroy decay-producing fungi and combine with the wood to give lasting protection.

Permanence — Conservo is non-volatile and insoluble to a very high degree, and therefore gives lasting protection. It will resist temperatures up to 420° F.

DIRECTIONS

Conservo can be applied in several ways, all easy and simple.

1. It can be put on like paint, with a large brush, a mop, or a spraying machine. Two heavy coats should be applied for best results.
2. The wood may be dipped in Conservo or soaked in it. Wood should be dipped for not less than three minutes; the longer the better.

Conservo flows freely at all temperatures and may be applied at any season of the year.

Covering Power: One gallon covers about 100 square feet of rough sawed lumber, two coats.

Clean Your Brushes with Cabot's Brush Cleaner

Samuel Cabot

Incorporated

MANUFACTURING CHEMISTS SINCE 1877
BOSTON, MASSACHUSETTS 02108

EPA-F-1 Ma-1

SELLER MAKES NO WARRANTY, EXPRESSED OR IMPLIED, CONCERNING THE USE OF THIS PRODUCT OTHER THAN INDICATED ON THE LABEL. BUYER ASSUMES ALL RISK OF USE AND/OR HANDLING OF THIS MATERIAL WHEN SUCH USE AND/OR HANDLING IS CONTRARY TO LABEL INSTRUCTIONS.

LITHO IN U.S.A. D.M. CORP.