

**Water Repellent
Protects and Preserves
Against Mildew and Rot**

*These stains meet Federal Specification
TT-W-572 B. Par. 3.7 for water repellency.

Five Year Limited Warranty

When applied to new wood according to the directions on our label, if this Cabot product cracks, peels or blisters within five years after purchase, Samuel Cabot Inc. will furnish any necessary additional product free of charge. We warrant the purchase price. This warranty does not include labor or shipping for the application of the product. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Samuel Cabot

Incorporated

MANUFACTURING CHEMISTS SINCE 1877
BOSTON, MASSACHUSETTS 02108

E.P.A. EST. 43-MA-1

E.P.A. REG. NO. 43-104



Cabot's® Semi-Transparent Stains

0380 - REDWOOD

**ONE U.S. GALLON — 3.785 LITERS
KEEP OUT OF THE REACH OF CHILDREN**

**WARNING: COMBUSTIBLE—HARMFUL OR FATAL IF SWALLOWED!
SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.**

ACTIVE INGREDIENTS:

bis (tributyltin) oxide 0.5%
Folpet (N, (trichloromethyl)thio)phthalimide 0.5%
INERT INGREDIENTS 99.0%

100.0%

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

Harmful or fatal if swallowed or absorbed through skin, or on clothing. May cause skin irritation. Close container after each use. Wear rubber gloves and protective clothing when handling freshly treated lumber. Wear a fresh air mask when spraying.

FIRST AID

Change contaminated clothing at once. Wash skin with soap and water. If swallowed do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Get immediate medical attention. In case of eye contact, flush with water for 15 minutes and get medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

COMBUSTIBLE—Do not use, pour, spill or store near heat or open flame. Avoid storage near feed or food products. Vapors will cause injury if adequate ventilation is not maintained.

RCM 382

Cabot's Semi-Transparent Stains

"The Stain that shows the Grain"

Cabot's Semi-Transparent Stains dye the wood fibers, penetrating deep into the surface, producing rich lively colors that enhance the beauty of the grain. They can be painted or stained over at any time.

Cabot's Semi-Transparent Stains are for use on exterior, horizontal or vertical siding, clapboards, and are especially effective on rough sawn wood surfaces such as shingles and shakes. For best results the wood should be porous — a Stain to be effective must be able to penetrate.

STORAGE AND DISPOSAL: Do not reuse empty container. Wrap container in plastic and put in trash collection. Do not use, pour, spill or store near heat or open flame. Avoid storage near feed or food products.

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER WHICH IS INCONSISTENT WITH THE INSTRUCTIONS ON THIS LABEL.

DIRECTIONS FOR USE

NOTE TO USER: Do not use this product indoors — for exterior use only. Do not treat wood intended for indoor use. Keep product away from domestic animals.

THE SURFACE: These stains should not be used on any previously painted or sealed surface. Do not thin the stain. Do not stain when the temperature is below 40°F. The surface must be clean and dry, free from wax, oil, grease, chalk and mildew. Do not stain in intense heat and sunlight. Do not use adjacent to fresh stucco. Cabot's Acrylic Latex Solid Color stain is recommended for this purpose.

STIRRING: Stir the stains thoroughly before applying them, and stir them frequently while applying to maintain a uniform solution. If the job requires more than one can of stain, mix all together in one large container.

APPLICATION: Apply, by brush, spray, or roller. Allow the wood, treated or untreated, to weather for 3 - 6 months before applying the stain. Two coats are recommended for best results.

Colors may vary slightly according to the color and porosity of the wood surfaces. A sample brushout is recommended.

DRYING TIME: 4 - 8 hours. Allow 12 hours between coats.

COVERING CAPACITY: On smooth surfaces approximately 250 square feet per gallon. On rough surfaces about 150 square feet per gallon.

These stains are in compliance with the requirements of the California Air Resource Board Model Rule for Architectural Coating. Also complies with the Philadelphia Air Management Regulation V — Non-Photochemically Reactive.

ED!
3.