52-212

ACCEPTED APK 12, 1911

UNDER THE FEDERAL INSECTIONSE FUNCTIONS AND ROP DEPOSITOR FOR ECONOMIC DUSING DEPOSITOR ED UNDER NU STZ ZEZUBBLET TO ATTACHED COOM MIS

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY

V	p	B		•
				100 000/

**U.S. Patent No. 2,476.512

VAPEX II insecticide is to be used in WEST equipment. VAPEX II is effective as a fog contact or surface spray.

CAUTION: Keep Out Of Reach Of Children. Do Not Take Internally.

Harmful if swallowed. Do not take internally. Avoid contamination of food Food processing plants should be fogged when not in operation. Food should be removed or covered during treatment. Food processing equipment should be covered or thoroughly cleaned before using. Store away from heat or open flames. Fabrics which are solled or dusty may be stained by insecticidal fogs.



manufactured by

42-16 WEST STREET LONG ISLAND CITY, NY 11101

2788A-371-5 PRINTED IN U.S.A.



DIRECTIONS FOR USE:

Flying Insects: Exposed stages of flies, fruit flies, mosquitoes, gnats, bees, wasps, hornets, indian meal moths, angoumois grain moths, mediterranean flour moths. To control these and similar small flying insects, turn off all ventilating equipment, close all windows and doors. Fog VAPEX II at the rate of 1 ounce per 1,000 cubic feet using the Jet-Fogger, WEST 1600 Fogger or Permanent Atomizer. Keep treated area closed for at least 10 minutes. Repeat as necessary. Do not remain in treated areas and ventilate the area after treatment is completed.

Crawling Insects: Exposed stages of cockroaches, waterbugs, silverfish, firebrats, booklice, bed bugs, ants, crickets, spider beetles, meal worms, cadelles, contused flour beetles, saw-toothed grain beetles, weevils, dermestids, spiders, ticks, lice, millipedes, centipedes, sowbugs.

For Space Spray-turn off all ventilating equipment, close all windows and doors. Fog VAPEX II at 2 ounces per 1,000 cubic feet, using a Jet-Fogger, WEST 1600 Fogger, or Permanent Atomizer. Keep treated area closed for at least 1 hour. Repeat as necessary.

For Contact or Surface Spray—Apply VAPEX II using the WEST 124-S or 610-S Sprayer. Spray directly on insects or where they are seen. Spray VAPEX II at the rate of 1 gallon per 1,000 square feet, coating the surface with a dew-like mist. Thoroughly treat all harborages and breeding areas, cracks, crevices, under sides of work tables, behind sinks and escutcheon plates, walls, window and door frames, elevator shafts and pits, behind and under equipment, laundry carts, garbage areas, warm dark moist areas, void spaces, shelves. Repeat as necessary.

Classified by Underwriters Laboratories, Inc. as to fire hazard only. Vapex 11. Classed 20 to 25 between Paraffin Oil and Kerosene in respect to fire hazard. See UL index of Classified Products.

INDEX							
		KEROSENE PARAFFIN					

USDA REG. No. 52-212