


Wood Preservative

CCA — Type C



Meets American Wood Preservers
Association Standard C-5



CAUSES SKIN BURNS AND EYE IRRITATION. HARMFUL
OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

NET WT 125

PRECAUTIONS:

Do not get in eyes, on skin, or
clothing. Wear goggles, rubber
gloves and Bureau of Mines ap-
proved respirator when handling.
Avoid breathing dust. Wash thor-
oughly after handling. Do not store
near food or feed. Use with ade-
quate ventilation.

POISON

FIRST AID — CALL A PHYSICIAN

If swallowed, induce vomiting by
drinking from a warm throat or quack
throat lozenge, with water to
follow. Do not induce vomiting if
the person is unconscious or
unable to swallow.

In case of contact, immediately re-
move contaminated clothing and
shoes. Flush eyes or skin with
plenty of water for at least 15 min-
utes. Wash clothing before reuse.
Do not contaminate shoes.

SPILL DISPOSAL: Do not reuse
container. Tighten closure. Trans-
port to a drum reconditioner or
destroy by perforating and crush-
ing and burning safely alone.

SPILLS: Sweep up or vacuum all
spills. Respiratory protection may
be required during cleanup. Do not
decontaminate clothing or other
materials.

DIRECTIONS:

Intended for use on any untreated
lumber products by pressure treat-
ment. Do not use on dry lumber.
To be used only in water solution.
Concentrations ranging from 10
percent to 40 percent.

Pressure treatment of lumber prod-
ucts with time-tested Preservatives
5-15 provides wood in all its form
with built-in protection against
termite and dry rot.

This product is toxic to fish and
wild life. Keep out of lakes, streams,
ponds. Do not contaminate water
by cleaning of equipment or dis-
posal of waste. Apply this product
in accordance with label directions.

For Industrial Use Only