



**“The Protector”**

**B-91 Blue Antifouling Paint Semi-Hard Type**

**DANGER!** KEEP OUT OF REACH OF CHILDREN. FLAMMABLE. MAY CAUSE SKIN IRRITATION OR EYE DAMAGE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. See additional precautions on back panel.

**NET 1 GALLON**

**3.8 Liters**

**B-91 ANTIFOULING PAINT** is a water-based paint designed to prevent the growth of barnacles, algae, and other marine organisms on the hulls of boats. It is applied to the hull and other submerged surfaces. The paint is applied with a brush or spray gun. It is available in two colors: white and black. The white color is used for the hull and the black color is used for the propeller and other fittings. The paint is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings. The paint is applied to the hull and other submerged surfaces. It is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings. The paint is applied to the hull and other submerged surfaces. It is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings.

Do not apply to any surface other than boat bottoms.

**DIRECTIONS FOR USE**

1. Clean hull with water and brush. Remove all old paint and fouling.

**GENERAL** Before starting, clean hull with water and brush. Remove all old paint and fouling. When sanding old bottom paint, always WET SAND and take precautions to avoid breathing sanding dust. NOTE: Face mask should be used when sanding.

2. Apply primer coat with brush or spray gun. Allow to dry 24 hours. Apply second coat with brush or spray gun. Allow to dry 24 hours. The paint is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings. The paint is applied to the hull and other submerged surfaces. It is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings.

**COVERAGE PER COAT** Approximately 4 sq. ft. per gallon. (Dependent on surface condition.)

**NUMBER OF COATS** 2 (or dependent on surface condition)

**DRYING TIME AT 70° F AND 50% RELATIVE HUMIDITY** Between coats: 6 hours. Full cure: 7 days maximum.

**THINNER** 2 Spar 110 (or other suitable thinner)

**CLEANER** 2 Spar 110 (or other suitable cleaner)

**OLD BOTTOM PAINTS** Over 100 years old. Apply wet sand and take precautions to avoid breathing sanding dust.

**WOOD BOTTOMS** Sand wood hulls with B-91.

3. Apply primer coat with brush or spray gun. Allow to dry 24 hours. Apply second coat with brush or spray gun. Allow to dry 24 hours. The paint is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings. The paint is applied to the hull and other submerged surfaces. It is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings.

**STEEL BOTTOMS** 1. Clean steel hulls with water and brush. Remove all old paint and fouling. 2. Apply primer coat with brush or spray gun. Allow to dry 24 hours. 3. Apply second coat with brush or spray gun. Allow to dry 24 hours. The paint is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings. The paint is applied to the hull and other submerged surfaces. It is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings.

**ALUMINUM BOTTOMS** 1. Clean aluminum hulls with water and brush. Remove all old paint and fouling. 2. Apply primer coat with brush or spray gun. Allow to dry 24 hours. 3. Apply second coat with brush or spray gun. Allow to dry 24 hours. The paint is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings. The paint is applied to the hull and other submerged surfaces. It is applied in two coats. The first coat is applied to the hull and the second coat is applied to the propeller and other fittings.

**PROHIBITIONS** Do not use on leaded glass or leaded paint.

**PESTICIDE STORAGE** Keep in original container. Do not use for other purposes.

**PESTICIDE DISPOSAL** Do not spray in water. Dispose of water in a safe manner.

**STORAGE AND DISPOSAL** Store in original container. Do not use for other purposes.

**PHYSICAL AND CHEMICAL HAZARDS** Flammable. Keep away from heat, open sparks, and flame.

**FIRST AID** In case of skin contact, wash thoroughly with soap and water. For eyes, flush immediately with plenty of water for 15 minutes and seek physician. If affected by breathing of vapor, move to fresh air. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.

**IN CASE OF FIRE** Use dry chemical, foam, water, etc. Do not use water on containers with water-reactive chemicals.

**CONTAINER DISPOSAL** Do not reuse or burn. Dispose of in accordance with local, state, and federal regulations. Do not use for other purposes.

**PRECAUTIONARY STATEMENTS** HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER** CONTAINS AROMATIC HYDROCARBONS AND PETROLEUM DISTILLATES

Do not get in eyes, on skin, or on clothing. Wear goggles, face shield, and rubber gloves when sanding. Do not breathe vapor. Spray must be done in well-ventilated area and disposed of in accordance with applicable regulations. Do not take internally.

**KEEP OUT OF REACH OF CHILDREN.**

**Use with adequate ventilation during application and drying.** In tanks and other confined areas, use only with adequate forced air ventilation to prevent dangerous concentrations of vapors which could lead to death from asphyxiation or from breathing when product is used in confined areas.

Approved by the Mining Enforcement and Safety Administration, US Bureau of Mines, and the National Institute for Occupational Safety and Health under the provisions of 30CFR 11. Prevent flames, sparks, welding and smoking.

**ENVIRONMENTAL HAZARDS** Do not contaminate water by cleaning of equipment or disposal of wastes.

**PHYSICAL AND CHEMICAL HAZARDS** Flammable. Keep away from heat, open sparks, and flame.

**FIRST AID** In case of skin contact, wash thoroughly with soap and water. For eyes, flush immediately with plenty of water for 15 minutes and seek physician. If affected by breathing of vapor, move to fresh air. If swallowed, CALL A PHYSICIAN IMMEDIATELY. DO NOT induce vomiting.

**IN CASE OF FIRE** Use dry chemical, foam, water, etc. Do not use water on containers with water-reactive chemicals.



**"The Protector"**

**B-91 Blue Antifouling Paint Semi-Hard Type**

**DANGER!** KEEP OUT OF REACH OF CHILDREN. FLAMMABLE. MAY CAUSE SKIN IRRITATION OR EYE DAMAGE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED.

See additional precautions on back panel.

**NET 1 QUART .95 Liters**

B-91 ANTIFOULING PAINT

WHEN THIS PAINT COMES  
DIRECTIONS FOR USE

GENERAL

COVERAGE PER QUART

NUMBER OF COATS  
DRYING TIME AT 70 F AND 50% RELATIVE HUMIDITY

THINNER  
CLEANER  
OLD BOTTOM PAINTS

ALL BOTTOMS

Koppers Company, Inc.

M. J. KOPPELSON

DO NOT APPLY TO ANTS SURFACE

FIBERGLASS BOTTOMS

STEEL BOTTOMS

ALUMINUM BOTTOMS

STORAGE AND DIS

PROHIBITIONS

PESTICIDE STORAGE

PESTICIDE DISPOSAL

**851 ANTIQUING PAINT**

Do not apply to any surface other than boat bottoms

**DIRECTIONS FOR USE**

**GENERAL**

Apply to clean, dry, smooth surfaces. For best results, sand and prime surfaces. Apply with brush or spray. Allow to dry 24 hours before use.

**COVERAGE PER COAT**

Approximately 100 sq. ft. per gallon per coat.

**NUMBER OF COATS**

Two coats are recommended.

**THINNER**

Use only the thinner specified on the label.

**CLEANER**

Use only the cleaner specified on the label.

**OLD BOTTOM PAINTS**

Remove all old paint before applying.

**WOOD BOTTOMS**

Apply to clean, dry, smooth wood surfaces.

**STEEL BOTTOMS**

Apply to clean, dry, smooth steel surfaces.

**FIBERGLASS BOTTOMS**

Apply to clean, dry, smooth fiberglass surfaces.

**ALUMINUM BOTTOMS**

Apply to clean, dry, smooth aluminum surfaces.

**WOOD BOTTOMS**

Apply to clean, dry, smooth wood surfaces.

**STEEL BOTTOMS**

Apply to clean, dry, smooth steel surfaces.

**FIBERGLASS BOTTOMS**

Apply to clean, dry, smooth fiberglass surfaces.

**ALUMINUM BOTTOMS**

Apply to clean, dry, smooth aluminum surfaces.

**WOOD BOTTOMS**

Apply to clean, dry, smooth wood surfaces.

**STEEL BOTTOMS**

Apply to clean, dry, smooth steel surfaces.

**FIBERGLASS BOTTOMS**

Apply to clean, dry, smooth fiberglass surfaces.

**ALUMINUM BOTTOMS**

Apply to clean, dry, smooth aluminum surfaces.

**WOOD BOTTOMS**

Apply to clean, dry, smooth wood surfaces.

**STEEL BOTTOMS**

Apply to clean, dry, smooth steel surfaces.

**FIBERGLASS BOTTOMS**

Apply to clean, dry, smooth fiberglass surfaces.

**ALUMINUM BOTTOMS**

Apply to clean, dry, smooth aluminum surfaces.

**WOOD BOTTOMS**

Apply to clean, dry, smooth wood surfaces.

**STEEL BOTTOMS**

Apply to clean, dry, smooth steel surfaces.

**FIBERGLASS BOTTOMS**

Apply to clean, dry, smooth fiberglass surfaces.

**ALUMINUM BOTTOMS**

Apply to clean, dry, smooth aluminum surfaces.

**WOOD BOTTOMS**

Apply to clean, dry, smooth wood surfaces.

Koppers Company, Inc.

ONE NORTH PARK STREET

Pittsburgh, Pa. 15219 Irving, Texas 75060 Los Angeles, Ca. 90040

Marietta, Ga. 30060 Newark, N.J. 07114

MADE IN U.S.A.

**CONTAINER DISPOSAL**

Do not reuse or dispose of in any way.

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

Keep out of reach of children. Use with adequate ventilation during application and drying.

**KEEP OUT OF REACH OF CHILDREN**

Use with adequate ventilation during application and drying. Avoid contact with skin, eyes, and clothing.

**ENVIRONMENTAL HAZARDS**

Do not apply to water bodies or wet surfaces.

**PHYSICAL AND CHEMICAL HAZARDS**

Flammable liquid. Avoid contact with oxidizing agents.

First Aid: In case of eye contact, flush with water for 15 minutes.

In case of fire, use foam, carbon dioxide, or dry chemical extinguishers.