100 - 1218

7/19/2012

#### UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON D C 20460 0001



OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

Tom Parshley Syngenta Crop Protection, Inc P O Box 18300 Greensboro, NC 27419

Subject Amended Reregistration Label Product Name Demon Max Insecticide EPA Registration Number 100 1218 EPA Decision Numbers 397726

JUL 19 2012

Dear Mr Parshley

The Agency, in accordance with the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, has completed reviewing all of the information submitted with your application to support the reregistration of the referenced product in connection with the **CYPERMETHRIN RED**, and has concluded that your submission is acceptable

NOTE This product is not being reregistered under sections 3(c)5 and 4(g) of FIFRA at this time

Please be reminded that 40 CFR Part 156 140(a)(4) requires that a batch code lot number or other code identifying the batch of the pesticide distributed and sold be placed on <u>non refillable</u> containers. The code may appear either on the label or durably marked on the container itself and can be added by non notification per PRN 98 10

Please note that the record for this product currently contains the Confidential Statements of Formulation (CSFs) listed below Any previously dated CSFs are superseded

Basic CSF, dated October 25, 2007

A copy of your label stamped Accepted is enclosed along with copies of the acute toxicity and product chemistry reviews completed for the subject product Products shipped after 12 months from the date of this amendment or the next printing of the label whichever occurs first must bear the new revised label. Your release for shipment of the product bearing the amended label constitutes acceptance of these conditions. If these conditions are not complied with the registration will be subject to cancellation in accordance with FIFRA sec. 6(e)

If you have any questions about this letter please contact Samantha Hulkower at 703 603 0683 or hulkower samantha@epa gov

Sincerely Yours,

Kc.

33

Richard J Gebken Product Manager (10) Insecticide Branch Registration Division (7504P)

Enclosures Label stamped Accepted Acute Toxicity Review dated June 14 2012 Product Chemistry Review dated July 23 2010

(

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON D C 20460

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

3|33

Mr Thomas Parshley Syngenta Crop Protection Inc PO Box 18300 Greensboro NC 27419

Subject Demon Max Insecticide EPA Reg No 100 1218 Date of Registrant Submission February 28 2012 Decision 461874

1

JUL 1 9 2012

Dear Mr Parshley

The labeling referred to above submitted in connection with registration under the Federal insecticide Fungicide and Rodenticide Act as amended is acceptable

Two (2) copies of the finished labeling must be submitted prior to releasing the product for shipment A stamped copy of the label is enclosed for your records If you have any questions you may contact Samantha Hulkower at (703) 603 0683 or Hulkower Samantha@epa gov

Sincerely Much

Rıchard Gebken Product Manager (10) Insecticide Branch Registration Division (7505P)

Enclosure Copy of Label Stamped Accepted

#### Demon® Max Insecticide

For use in on and around building and structures for the control of listed pests including lawns and landscape uses

For subterranean termite control product is to be used by individuals/firms licensed or registered by the state to apply termiticide products. States may have more restrictive requirements regarding qualifications of persons using this product. Consult the structural pest control regulatory agency of your state prior to use of this product.

Active Ingredient Cypermethrin <sup>1</sup>	
$(\pm)\alpha$ cyano (3 phenoxyphenyl)methyl( $\pm$ ) <i>cis trans</i> 3	
(2 2 dichloroethenyl) 2 2 dimethylcyclopropanecarboxylate*	25 3%
Other Ingredients	74 7%
Total	100 0%

<sup>1</sup>Pyrethroid Insecticide Contains petroleum distillates \**Cis/trans* ratio Min 45% (±) *cis* and max 55% (±) *trans* 

Demon Max Insecticide contains 2 lbs active ingredient per gal formulated as an emulsifiable concentrate

#### **KEEP OUT OF REACH OF CHILDREN**

#### WARNING/AVISO

Si usted no entiende la etiqueta busque a alguien para que se la explique a usted en detalle (If you do not understand the label find someone to explain it to you in detail)

#### See additional precautionary statements and directions for use inside booklet

EPA Reg No 100 1218 EPA Est XXXXX Product of XXXXX Formulated in the USA

SCP 1218A M (draft rereg c) Net Contents

ACCEPTED JUL 1 9 2012 Under the Federal Insecticide Fungicide and Rodenticide Act, as amended, for the pesticide registered under EPA Reg No 100-1218

(



	FIRST AID					
If swallowed	<ul> <li>Immediately call a poison control center or doctor for treatment advice</li> <li>Do not induce vomiting unless told to do so by the poison control center or doctor</li> <li>Do not give any liquid to the person</li> <li>Do not give anything by mouth to an unconscious person</li> </ul>					
lf on skın or clothıng	<ul> <li>Take off contaminated clothing</li> <li>Rinse skin immediately with plenty of water for 15 20 minutes</li> <li>Call a poison control center or doctor for treatment advice</li> </ul>					
lf inhaled	<ul> <li>Move person to fresh air</li> <li>If person is not breathing call 911 or an ambulance then give artificial respiration preferably by mouth to mouth if possible</li> <li>Call a poison control center or doctor for further treatment advice</li> </ul>					
lf ın eyes	<ul> <li>Hold eye open and rinse slowly and gently with water for 15 20 minutes</li> <li>Remove contact lenses if present after the first 5 minutes then continue rinsing eye</li> <li>Call a poison control center or doctor for treatment advice</li> </ul>					
	NOTE TO PHYSICIAN					
	Contains petroleum distillate Vomiting may cause aspiration pneumonia					
Have the product doctor or going for	t container or label with you when calling a poison control center or or treatment					
	HOT LINE NUMBER 24 Hour Medical Emergency Assistance (Human or Animal) demical Emergency Assistance (Spill Leak Fire or Accident) Call 1 800 888 8372					

2

(

(

#### PRECAUTIONARY STATEMENTS

#### Hazards to Humans and Domestic Animals

#### WARNING/AVISO

3

May be fatal if swallowed Harmful if absorbed through skin Harmful if inhaled Avoid contact with eyes skin or clothing Causes moderate eye irritation. Wash thoroughly with soap and water after handling and before eating drinking chewing gum using tobacco or using the toilet. Wear long sleeved shirt and long pants socks shoes and gloves. Remove and wash contaminated clothing before reuse. Avoid breathing spray mist. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

#### Personal Protective Equipment (PPE)

Some materials that are chemical resistant to this product are barrier laminate nitrile rubber  $\geq$  14 mils neoprene rubber  $\geq$  14 mils and Viton®  $\geq$  14 mils lf you want more options follow the instructions for category E on an EPA chemical resistance category selection chart

Mixers loaders applicators and other handlers must wear the following

- Long sleeve shirt and long pants
- Shoes and socks
- Chemical resistant gloves for mixers loaders and applicators using handheld
   equipment

Follow manufacturer s instructions for cleaning/maintaining PPE If no such instructions for washables exist use detergent and hot water Keep and wash PPE separately from other laundry

Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product s concentrate Do not reuse them

In addition all pesticide handlers must wear a respiratory protection device<sup>1</sup> when working in a non-ventilated space all pesticide handlers must wear protective eyewear (goggles and/or faceshield and/or shielded safety glasses with front brow and temple protection) when working in a non-ventilated space or when applying termiticide by rodding or sub-slab injection

<sup>1</sup> Use one of the following

- a NIOSH approved respirator with a N R P or HE filter
- a NIOSH approved respirator with an organic vapor (OV) approved cartridge or canister with N R P or HE prefilter
- TC 19C (Supplied air)

• **TC 13F** (Self contained breathing apparatus SCBA)

#### User Safety Recommendations

- Users should wash hands before eating drinking chewing gum using tobacco or using the toilet
- Users should remove clothing/PPE immediately if pesticide gets inside Then wash thoroughly and put on clean clothing
- Users should remove PPE immediately after handling this product As soon as possible wash thoroughly and change into clean clothing

#### **Environmental Hazards**

This pesticide is extremely toxic to fish and aquatic invertebrates Do not apply directly to or near water Drift and run off may be hazardous to fish in water adjacent to treated areas Do not contaminate water when disposing of equipment wash water or rinsate See **Directions for Use** for additional requirements

This product is <u>highly toxic to bees</u> exposed to direct treatment on blooming crops or weeds. Do not apply this product or allow it to drift to blooming crops or weeds while bees are actively visiting the treatment area.

For Treatment of Preconstruction Lumber and Logs Do not discharge effluent containing this product into lakes streams ponds estuaries oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority For guidance contact your State Water Board or Regional Office of the EPA

#### **Physical and Chemical Hazards**

Do not use or store near heat or open flame

#### CONDITIONS OF SALE AND LIMITATION OF WARRANTY AND LIABILITY

**NOTICE** Read the entire Directions for Use and Conditions of Sale and Limitation of Warranty and Liability before buying or using this product If the terms are not acceptable return the product at once unopened and the purchase price will be refunded

The Directions for Use of this product must be followed carefully It is impossible to eliminate all risks inherently associated with the use of this product. Ineffectiveness or other unintended consequences may result because of such factors as manner of use or application weather presence of other materials or other influencing factors in the use of the product which are beyond the control of SYNGENTA CROP PROTECTION LLC or Seller To the extent permitted by applicable law Buyer and User agree to hold SYNGENTA and Seller harmless for any claims relating to such factors

SYNGENTA warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated in the Directions for Use subject to the inherent risks referred to above when used in accordance with directions under normal use conditions To the extent permitted by applicable law (1) this warranty does not extend to the use of this product contrary to label instructions or under conditions not reasonably foreseeable to or beyond the control of Seller or SYNGENTA and (2) Buyer and User assume the risk of any such use TO THE EXTENT PERMITTED BY APPLICABLE LAW SYNGENTA MAKES NO WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE NOR ANY OTHER EXPRESS OR IMPLIED WARRANTY EXCEPT AS WARRANTED BY THIS LABEL

To the extent permitted by applicable law in no event shall SYNGENTA be liable for any incidental consequential or special damages resulting from the use or handling of this product TO THE EXTENT PERMITTED BY APPLICABLE LAW, THE EXCLUSIVE REMEDY OF THE USER OR BUYER, AND THE EXCLUSIVE LIABILITY OF SYNGENTA AND SELLER FOR ANY AND ALL CLAIMS, LOSSES, INJURIES OR DAMAGES (INCLUDING CLAIMS BASED ON BREACH OF WARRANTY, CONTRACT, NEGLIGENCE, TORT, STRICT LIABILITY OR OTHERWISE) RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT, SHALL BE THE RETURN OF THE PURCHASE PRICE OF THE PRODUCT OR, AT THE ELECTION OF SYNGENTA OR SELLER, THE REPLACEMENT OF THE PRODUCT

Syngenta and Seller offer this product and Buyer and User accept it subject to the foregoing Conditions of Sale and Limitation of Warranty and Liability which may not be modified except by written agreement signed by a duly authorized representative of Syngenta

5

### DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling

Do not apply this product in a way that will contact any person or pet either directly or through drift. Keep people and pets out of the area during application. Exit area immediately and remain outside the treated area until sprays have dried.

#### GENERAL RESTRICTIONS AND PRECAUTIONS

ť

For best results thoroughly wash out sprayer and screen with water and detergent before using Demon Max Insecticide

#### INDOOR USE RESTRICTIONS

Do not use water based sprays in or on conduits motor housings junction boxes switch boxes or other live electrical equipment because of possible shock hazard

During indoor surface application do not allow dripping or run off to occur During any application to overhead interior areas of structure cover surface below with plastic shielding or similar material

Do not apply this product in any rooms being used as a living eating or recovery area by patients the elderly or the infirm when they are in the room

Do not apply to classrooms when in use

Do not apply to areas of institutions (including libraries sport facilities etc.) when occupants are present in the immediate treatment area

Do not use as a space spray Use only in well ventilated areas

Do not use concentrate or emulsion in fogging equipment

Do not use in food areas of food handling establishments restaurants or other areas where food is commercially prepared or processed. Do not use in serving areas while food is exposed or facility is in operation. Serving areas are areas where prepared foods are served such as dining rooms but excluding areas where foods may be prepared or held. In the home all food processing surfaces and utensils should be covered during treatment or thoroughly washed before use. Exposed food should be covered or removed.

ſ

Do not use in warehouses while raw agricultural commodities for food or feed and/or raw or cured tobacco are being stored Do not use in greenhouses where crops for food or feed are grown

Do not apply to pets Remove birds and other pets before application Cover any water inhabited by fish (such as aquariums and ornamental fish ponds) during treatment and turn aquarium systems off

#### OUTDOOR USE RESTRICTIONS

All outdoor applications must be limited to spot or crack and crevice treatments only except for the following permitted uses

- Treatment to soil or vegetation around structures
- Applications to lawns turf and other vegetation
- Applications to building foundations up to a maximum height of 3 feet

All outdoor applications to <u>impervious surfaces</u> such as sidewalks driveways patios porches and structural surfaces (such as windows doors and eaves) are limited to <u>spot treatments or crack and crevice applications</u> only

#### **Applications around Swimming Pools**

Do not apply directly into sewers or drains or to any area like a gutter where drainage to storm sewers water bodies or aquatic habitat can occur. Do not allow the product to enter any drain during or after application

Do not apply directly to swimming pools or swimming pool systems

This product may be applied as a broadcast treatment to lawns and other vegetated areas <u>around</u> swimming pools or as a spot treatment or crack and crevice treatment to impermeable surfaces (such as tiled walkways) <u>around</u> pools

#### Application in and on Boats

Do not apply to boat surfaces which contact water Broadcast applications to exterior surfaces of boats are prohibited Spot treatments may be made to exterior surfaces that do not contact water

Use inside boats ships and other vessels is permitted. Do not allow product to drain or wash off into water bodies or other aquatic habitat

#### CAUTION ON APPLICATION TO VINYL SIDING

Each year prior to an application to vinyl siding treat a small area on each side of the structure where weathering is most severe allow to dry and observe for staining

Some types of vinyl siding particularly if aged or weathered may show some staining after application of an emulsifiable concentrate product. To completely eliminate the potential risk associated with staining it is suggested that a water based product such as Demand® CS be used

#### TERMITE CONTROL - GENERAL INFORMATION

(

Demon Max provides control of subterranean termites (including eastern subterranean western subterranean desert termite and Formosan subterranean termite) and when applied to wood may be used for spot treatment of drywood termites (*Incisitermes* spp)

Chemicals for soil treatment are used to establish a barrier against subterranean termite attack. The chemical emulsion must be adequately dispersed in the soil to provide a barrier between the wood in the structure and the termite colonies in the soil.

For the effective use of this product it is necessary that the service technician be familiar with current control practices including trenching rodding subslab injection and low pressure spray applications. These techniques must be correctly employed to prevent or control infestations by subterranean termite species of *Reticulitermes Zootermopsis Heterotermes* and *Coptotermes* (Formosan termite). Choice of appropriate procedures should include consideration of such variable factors as the design of the structure water table soil type soil compaction grade conditions location and type of domestic water supplies and drainage systems. The biology and behavior of the termite species involved are important factors to be known as well as suspected location of the colony and severity of the infestation within the structure to be protected.

Effective termite control also includes elimination of termite access to moisture by recommending repair of faulty construction grade and/or plumbing Remove all wood and cellulose containing debris in contact with soil from crawl spaces porches and around foundations

For advice concerning current control practices with relation to the specific local conditions consult resources in structural pest control and the State regulatory agency

#### TERMITE CONTROL USE RESTRICTIONS

When treating adjacent to an existing structure the applicator must check the area to be treated and immediately adjacent areas of the structure for visible and accessible cracks and holes to prevent any leaks or significant exposures to persons occupying the structure People present or residing in the structure during application must be advised to remove their pets and themselves from the structure if they see any signs of leakage After application the applicator is required to check for leaks

All leaks resulting in the deposition of termiticide in locations other than those prescribed on

8

this label must be cleaned up prior to leaving the application site Do not allow people or pets to contact contaminated areas or to reoccupy the contaminated area until the clean up is completed

Use anti backflow equipment or procedures to prevent siphonage of pesticide back into water supplies

Care should be taken that the treatment solution is not introduced into the gravel and/or pipe drainage system which may be located on the exterior of the foundation in close proximity to the footing of the structure

Do not treat soil that is water saturated or frozen

Do not treat when raining

Do not allow treatment to run off from the target area

Do not apply within 10 feet of storm drains Do not apply within 25 feet of aquatic habitats (such as but not limited to lake reservoirs rivers permanent streams marshes or natural ponds estuaries and commercial fish farm ponds)

Do not make on grade applications when sustained wind speeds are above 10 mph (at application site) at nozzle-end height

## SUBTERRANEAN TERMITE CONTROL (Including Eastern, Western, And Formosan Termites)

#### USE DIRECTIONS

Whenever possible make termite control applications near the structure foundation using soil injections

Apply a 0 25% 0 50% emulsion to establish subsurface termite control barriers as specified on product labeling

Consult State and local specifications for recommended distance of treatment areas from wells or if such regulations do not exist refer to Federal Housing Administration Specifications for guidance

9

#### MIXING DIRECTIONS

Mix the termiticide in the following manner

(

- 1 Fill tank ¼ to ¼ full with water
- 2 Start pump to begin by pass agitation and place end of treating tool in tank to allow circulation through hose
- 3 Add appropriate amount of Demon Max
- 4 Add remaining amount of water
- 5 Let pump run and allow recirculation through the hose for 2 3 minutes

#### **USE DILUTIONS**

	Tank Size							
Emulsion Concentration	1	Gal	25 (	Gal	50 (	Gal	100	Gal
(/ active)	Demon Max	Water	Demon Max	Water	Demon Max	Water	Demon Max	Water
0 25	13 oz	126 7 oz	32 0 oz	24 8 gal	0 5 gal	49 5 gal	1 0 gal	99 0 gal
0 50	2 6 oz	125 4 oz	64 0 oz	24 5 gal	1 0 gal	49 0 gal	2 0 gal	98 0 gal
1 00	5 1 oz	122 0 oz	128 0 oz	24 0 gal	2 0 gal	48 0 gal	4 0 gai	96 0 gal

Common units of measure

1 pint = 16 fluid ounces (oz )

1 gallon = 4 quarts = 8 pints = 128 fluid ounces (oz )

#### **APPLICATION VOLUMES**

To provide maximum control and protection against termite infestation apply the specified volume of the finished water and active ingredient emulsion as set forth in the use directions section of this label. If soil will not accept the labeled application volume the volume may be reduced provided there is a corresponding increase in concentration so that the amount of active ingredient applied to the soil remains the same. See **Volume Adjustment Chart** for specific information

**Note** Large reductions of application volume reduce the ability to obtain a continuous barrier. Variance is allowed when volume and concentration are consistent with label directed rates and a continuous barrier can still be achieved.

**Note** When volume is reduced the hole spacing for subslab injection and soil rodding may require similar adjustments to account for lower volume dispersal of the termiticide in the soil. Volume adjustments at 1% are not recommended for subslab injection

		Rate (% Emuls	ion)
Volume Allowed	0 25%	0 5%	1 0%
Horizontal (gallons emulsion/10 sq_ft)	1 gal	0 5 1 gal	0 25 0 5* gal
Vertical (gallons emulsion/10 lin ft )	4 gal	2 4 gal	1 2* gal

\*Not recommended for subslab injection

#### PRECONSTRUCTION SUBTERRANEAN TERMITE TREATMENT

Effective preconstruction subterranean termite control requires the establishment of an unbroken vertical and/or horizontal chemical barrier between wood in the structure and the termite colonies in the soil

Prior to each application applicators must notify the general contractor construction superintendent or similar responsible party of the intended termiticide application and intended sites of application and instruct the responsible person to notify construction workers and other individuals to leave the area to be treated during application and until the termiticide is absorbed into the soil

The applicator must ensure the treatment site is covered The applicator can cover the soil himself or notify the contractor on the site that 1) if the concrete slab cannot be poured over the treated soil within 24 hours of application the treated soil should be covered with a waterproof covering (such as polyethylene sheeting) and 2) that the contractor should cover the treated soil if precipitation occurs before the concrete slab is poured. Whenever possible make termite control applications near the structure foundation using soil injection.

To meet Federal Housing Administration termite proofing requirements follow the latest edition of the Housing and Urban Development (H U D ) Minimum Property Standards

#### DO NOT APPLY AT A LOWER DOSAGE AND/OR CONCENTRATION THAN SPECIFIED ON THIS LABEL FOR APPLICATIONS PRIOR TO THE INSTALLATION OF THE FINISHED GRADE

After grading is completed and prior to pouring of the slab slab supported or constructed porches and other critical areas make the following treatments

#### HORIZONTAL BARRIERS

Horizontal barriers may be established in areas intended for covering such as floors porches and other critical areas application shall be made by a low pressure spray (less than 50 p s I at the nozzle)

(

Apply the emulsion at the rate of 1 gal /10 sq ft to fill dirt If fill is washed gravel or other coarse material apply the emulsion at the rate of 1 1/2 gal /10 sq ft If concrete slabs cannot be poured over soil the same day it has been treated a waterproof cover such as polyethylene sheeting should be placed over the soil. This is not necessary if foundation walls have been installed around the treated soil.

#### VERTICAL BARRIERS

Vertical barriers may be established around the base of foundations plumbing back filled soil against foundation walls and other critical areas applications may be made by trenching and rodding into the trench or trenching Apply the emulsion at the rate of 4 gal /10 lin ft /ft of depth For example a footing 3 ft deep would require 12 gal of emulsion/10 lin ft

When treating foundations deeper than 4 ft apply the termiticide as the backfill is being replaced or if the construction contractor fails to notify the applicator to permit this treat the foundation to a minimum depth of 4 ft after the backfill has been installed. The applicator must trench and rod into the trench or trench along the foundation walls and around pillars and other foundation elements at the rate prescribed from grade to a minimum depth of 4 ft. When the top of the footing is exposed, the applicator must treat the soil adjacent to the footing to a depth not to exceed the bottom of the footing **However, in no case should a structure be treated below the footing**.

A trench need not be wider than 6 inches Rod from the base of a shallow trench to the top of the footings Low pressure spray (less than 50 p s i at the nozzle) may be used to treat soil which will be replaced in the trench Mix the emulsion with the soil as it is being replaced in the trench

Soil should be treated around sewer lines plumbing or around any other utility extending from the soil through a slab

#### HOLLOW MASONRY UNITS OF THE FOUNDATION AND/OR BASEMENT WALL (BELOW GRADE)

Treat so as to make a continuous chemical barrier in the voids Apply the emulsion at the rate of 2 gal /10 lin ft Apply the emulsion so it will reach the footing

#### HOLLOW MASONRY UNITS OF THE FOUNDATION

You may drill and treat voids in multiple masonry elements of the structure extending from the structure to the soil in order to create a continuous treatment barrier in the area to be treated. Apply at the rate of 2 gal of emulsion/10 lin ft of footing using a nozzle pressure of less than 25 p s i. When using this treatment access holes must be drilled below the sill plate and should be as close as possible to the footing as is practical.

Treatment of voids in block or rubble foundation walls must be closely examined Applicators must inspect areas of possible runoff as a precaution against application leakage in the treated areas Some areas may not be treatable or may require mechanical alteration prior to treatment

All leaks resulting in the deposition of termiticide in locations other than those prescribed on this label must be cleaned up prior to leaving the application site. Do not allow people or pets to contact contaminated areas or to reoccupy the contaminated areas of the structure until the clean up is completed.

Not for use in voids insulated with rigid foam

#### **CRAWL SPACES**

For crawl spaces apply at the rate of 4 gal of emulsion/10 lin ft /ft of depth from grade to the top of the footing Application may be made by trenching and rodding into the trench or trenching lf the footing is exposed at or above grade application should be made with special care to avoid washout around footing Treatment should include both sides of foundation and around all piers and pipes

- Rod holes should be spaced to provide a continuous chemical barrier
- Trench need not be wider than 6 inches nor below the foundation The emulsion should be mixed with the soil as it is being replaced in the trench

#### POST CONSTRUCTION TREATMENTS

Post construction applications may be made by subslab injection trenching and rodding into the trench or trenching using low pressure spray not exceeding 25 p s i at the nozzle

For applications made after the final grade is installed the applicator must trench and rod into the trench or trench along the foundation walls and around pillars and other foundation elements at the rate prescribed from grade to the top of the footing. When the footing is more than 4 ft below grade the applicator must trench and rod into the trench or trench along the foundation walls at the rate prescribed to a minimum depth of 4 ft. The actual depth of treatment will vary depending on soil type degree of compaction and location of termite activity. When the top of the footing is exposed the applicator must treat the soil adjacent to the footing to a depth not to exceed the bottom of the footing. **However, in no case should a structure be treated below the footing**.

Do not apply emulsion until location of heat or air conditioning ducts vents and water and sewer (or plumbing) lines are known and identified Caution must be taken to avoid contamination of these structural elements and airways

#### **After Treatment**

(

All holes in commonly occupied areas into which material has been applied must be plugged. Plugs must be in a non cellulose material or covered by an impervious non cellulose material.

#### SLAB ON GRADE

Apply the emulsion at the rate of 4 gal /10 lin ft /ft of depth Application shall be made by sub slab injection trenching and rodding into the trench or trenching Injectors should not extend below the tops of the footings

Treat the soil from grade to the top of the footing along the outside and where necessary along the inside of the foundation perimeter. Treatment may also be required along one side of a partition wall (especially where the wall is connected to the floor by fixtures inserted in the slab) and along cracks expansion joints and other critical areas

Drill holes should be spaced about 10 24 inches apart to provide a continuous chemical barrier (For best results application should be made with a lateral dispersion nozzle)

Where necessary drill through the foundation walls from the outside and inject the chemical just beneath the slab or along the inside of the foundation

Along the outside of the foundation walls where shallow foundations exist (1 ft or less) dig a narrow trench approximately 6 inches wide and not below the top of the footing Apply the emulsion at the rate of 2 gal /10 lin ft As the soil is being replaced into the trench apply another 2 gal /10 lin ft to the backfill

When making soil applications to the foundations extending deeper than 1 ft follow instructions under **Basements Outside Perimeter** (See exception for monolithic slabs immediately following )

**Note** For monolithic slab construction a vertical barrier may be established along the outside of foundation walls from grade to the bottom of the monolithic poured concrete foundation. Where the foundation extends deeper than 1 ft rod holes should not extend beneath the bottom of the monolithic poured concrete foundation.

#### HOLLOW MASONRY UNITS OF FOUNDATION WALLS

Drill and treat voids in multiple masonry elements of the structure extending from the structure to the soil in order to create a continuous treatment barrier in the area to be treated. Apply at the rate of 2 gal of emulsion/10 lin ft of footing using a nozzle pressure of less than 25 p s i. When using this treatment access holes must be drilled below the sill plate and should be as close as possible to the footing as is practical. Treatment of voids in block or rubble foundation walls must be closely examined.

applicators must inspect areas of possible runoff as a precaution against application leakage in the treated areas Some areas may not be treatable or may require mechanical alteration prior to treatment

All leaks resulting in the deposition of termiticide in locations other than those prescribed on this label must be cleaned up prior to leaving the application site. Do not allow people or pets to contact contaminated areas or to reoccupy the contaminated areas of the structure until the clean up is completed.

Not for use in voids insulated with rigid foam

When treating behind veneer care should be taken not to drill beyond the veneer if concrete blocks are behind the veneer both the blocks and the veneer may be drilled and treated at the same time

#### BASEMENTS

Apply the emulsion at the rate of 4 gal /10 lin ft /ft of depth from the grade to the top of the footing For example a footing 3 ft deep would require 12 gal of emulsion/10 lin ft Application shall be made by subslab injection trenching and rodding into the trench or trenching

#### Inside

Treatment may be required along inside of foundation walls and along one side of interior partition walls (or bearing walls) especially where the wall is connected by fixtures inserted in the floor Application may also be necessary around sewer pipes floor drains conduits or any cracks in the basement floor Drill holes should be spaced about 10 24 inches apart to provide a continuous chemical barrier

**Note** Sandy soils will tend to give less lateral dispersion than clay soils Spacing should be determined by soil type

#### **Outside Perimeter**

Applications must be made by trenching and rodding into the trench or trenching When rodding from grade or from the bottom of a shallow trench rod holes should be spaced in a manner that will allow for application of a continuous chemical barrier Rod holes should not extend beneath the top of the footings

A trench need not be wider than 6 inches Rod from the base of a shallow trench to the top of the footings Low pressure spray (not exceeding 25 p s i) may be used to treat soil which will be replaced in the trench Mix the emulsion with the soil as it is being replaced in the trench

#### ACCESSIBLE CRAWL SPACES

For crawl spaces apply vertical termiticide barriers at the rate of 4 gal of emulsion/10 In ft /ft of depth from grade to the top of the footing or if the footing is more than 4 ft below grade to a minimum depth of 4 ft Apply by trenching and rodding into the trench or trenching Treat both sides of foundation and around all piers and pipes Where physical obstructions such as concrete walkways adjacent to foundation elements prevent trenching treatment may be made by rodding alone. When soil type and/or conditions make trenching prohibitive rodding may be used. When the top of the footing is exposed, the applicator must treat the soil adjacent to the footing to a depth not to exceed the bottom of the footing. Read and follow the mixing and use direction section of the label if situations are encountered where the soil will not accept the full application volume.

- Rod holes and trenches must not extend below the bottom of the footing
- Rod holes must be spaced so as to achieve a continuous chemical barrier but in no case more than 12 inches apart
- Trenches must be a minimum of 6 inches deep or to the bottom of the footing whichever is less and need not be wider than 6 inches. When trenching in sloping (tiered) soil the trench must be stepped to ensure adequate distribution and to prevent termiticide from running off. The emulsion must be mixed with the soil as it is replaced in the trench.
- When treating crawl spaces turn off the air circulation system of the structure until application has been completed and all termiticide has been absorbed by the soil

#### INACCESSIBLE CRAWL SPACES

For inaccessible interior areas such as areas where there is insufficient clearance between floor joists and ground surfaces to allow operator access excavate if possible and treat according to the instructions for accessible crawl spaces. Otherwise apply one or a combination of the following two methods

- To establish a horizontal barrier apply to the soil surface 1 gal of emulsion/10 sq ft overall using a nozzle pressure of less than 25 p s i and a coarse application nozzle (e g Delavan Type RD Raindrop RD 7 or larger or Spraying Systems Co 8010LP TeeJet or comparable nozzle) For an area that cannot be reached with the application wand use one or more extension rods to make the application to the soil Do not broadcast or powerspray with higher pressures
- To establish a horizontal barrier drill through the foundation wall or through the floor above and treat the soil perimeter at a rate of 1 gal of emulsion/10 sq ft Drill spacing must be at intervals not to exceed 16 inches Many states have smaller intervals so check state regulations which may apply

When treating crawl spaces turn off the air circulation system of the structure until application has been completed and all termiticide has been absorbed by the soil

It is recommended that inadequately ventilated crawl spaces be brought into compliance with FHA Minimum Property Standards specifying 1 sq ft of ventilator opening/150 sq ft of crawl space area

#### **BATH TRAPS**

Where there is exposed soil beneath and around plumbing/waste pipe entrances through a concrete slab this soil may be treated with 0 5% dilution of this product

An access door for inspection and treatment should be cut and installed if not already present. After inspection and removal of any wood (form boards) or cellular debris treat the soil by rodding and/or drenching with 0 5% emulsion of this product.

#### **TERMITE RETREATMENT**

Retreatment for subterranean termites can only be performed if there is clear evidence of reinfestation or disruption of the barrier due to construction excavation or landscaping and/or evidence of the breakdown of the termiticide barrier in the soil These vulnerable or reinfested areas may be retreated in accordance with application techniques described in this product's labeling. The timing and type of these retreatments will vary depending on factors such as termite pressure soil types soil conditions and other factors which may reduce the effectiveness of the barrier

Annual retreatment of the structure is prohibited unless there is clear evidence that reinfestation or barrier disruption has occurred

#### STRUCTURES WITH WELLS/CISTERNS INSIDE FOUNDATIONS

Structures that contain wells or cisterns within the foundation of a structure can only be treated using the following techniques

- 1 Do not treat soil while it is beneath or within the foundation or along the exterior perimeter of a structure that contains a well or cistern. The treated backfill method must be used if soil is removed and treated outside/away from the foundation. The treated backfill technique is described as follows
  - a) Trench and remove soil to be treated onto heavy plastic sheeting or similar material or into a wheelbarrow
  - b) Treat the soil at the rate of 4 gal of dilute emulsion per 10 lin ft /ft of depth of the trench or 1 gal per 1 0 cu ft of soil See **Mixing Directions**

section of the label Mix thoroughly into the soil taking care to contain the liquid and prevent runoff or spillage

(

- c) After the treated soil has absorbed the diluted emulsion replace the soil into the trench
- 2 Treat infested and/or damaged wood in place using an injection technique such as described in the TREATMENT OF WOOD IN PLACE FOR CONTROL OF TERMITES CARPENTER ANTS, CARPENTER BEES AND WOOD INFESTING BEETLES section of this label

#### STRUCTURES WITH ADJACENT WELLS/CISTERNS AND/OR OTHER WATER BODIES

Applicators must inspect all structures with nearby water sources such as wells cisterns surface ponds streams and other bodies of water and evaluate at a minimum the treatment recommendations listed below prior to making an application

- 1 Prior to treatment if feasible expose the water pipe(s) coming from the well to the structure if the pipe(s) enter the structure within 3 ft of grade
- 2 Prior to treatment applicators are advised to take precautions to limit the risk of applying the termiticide into subsurface drains that could empty into any bodies of water These precautions include evaluating whether application of the termiticide to the top of the footer may result in contamination of the subsurface drain Factors such as depth to the drain system and soil type and degree of compaction should be taken into account in determining the depth of treatment
- 3 When appropriate (i e on the water side of the structure) the treated backfill technique (described above) can also be used to minimize off site movement of termiticide

#### FOAM APPLICATIONS

Demon Max emulsion may be converted to a foam and the foam used to treat voids to control or prevent termite ant bee wasp infestations or other arthropods harboring under slabs

Depending on the circumstances foam applications may be used alone or in combination with liquid emulsion applications. Applications may be made behind veneers piers chimney bases into rubble foundations into block voids or structural voids under slabs stoops porches or to the soil in crawlspaces and other similar voids.

(

Foam and liquid application must be consistent with volume and active ingredient instructions in order to ensure proper application has been made. The volume and amount of active ingredient are essential to an effective treatment. At least 75% of the labeled liquid emulsion volume of product must be applied with the remaining percent delivered to appropriate areas using foam application. Refer to label and use recommendations of the foam manufacturer and the foaming equipment manufacturer

Foam applications are generally a good supplement to liquid treatments in difficult areas but may be used alone in difficult spots

**Rates** Use a 0 25% 1 0% emulsion converted to foam with expansion characteristics from 2 20 times

Note When using a foaming product be sure that it is compatible with Demon Max

#### Applications under Slabs or to Soil in Crawl Spaces

- Applications should be made using Demon Max foam in combination with liquid emulsion applications
- The total amount of product applied with the combination of foam and liquid emulsion should be equivalent to that of an application using a liquid emulsion only

#### Applications to Other Areas

- Applications may be made using either Demon Max foam alone or in combination with a liquid emulsion
- Applications may be made behind veneers piers (concrete or wood) chimney bases into rubble foundations into block voids structural voids (i e between stud walls) poles stumps and wood in crawl spaces
- Applications may be made in other areas which include but are not limited to

Foundations penetrated by utility services Cracks and expansion joints Bath traps Areas where cement constructions have been poured adjacent to the foundation such as stairs patios and slab additions

#### POSTS, POLES AND OTHER CONSTRUCTIONS

Application may be made to create a chemical barrier in the soil around wooden construction such as signs and landscape ornamentation by applying a 0 25 0 5% emulsion Treat on all sides to create a continuous barrier around posts and poles

Use 1 gal of emulsion per ft of depth for poles and posts less than 6 inches in diameter For larger poles use 1 1/2 gal of emulsion /ft of depth For larger constructions use 4 gal /10 lin ft /ft of depth

For treatments made during installation the emulsion may be applied to the soil as it is replaced around the pole or post Previously installed poles and posts may be treated by subsurface injection or treated by gravity flow through holes made from the bottom of

(

Do not contaminate wells or cisterns

Į

#### UNDERGROUND SERVICES

Soil treatment around underground services may be made using a 0 25% 0 5% Demon Max emulsion to prevent attack by termites and ants

a trench around the pole or post Treat on all sides to create a continuous chemical

barrier Apply to a depth of 6 inches below the bottom of the wood

Examples of underground services are wires cables utility lines pipes and conduits Services may be within structures or located outside structures in right of ways or to protect long range (miles) or installations of services

Apply 2 4 gal of emulsion/10 lin ft to the bottom of the trench and allow to soak into the soil Lay services on the treated soil and cover with approximately 2 inches of fill soil Apply another 2 4 gal /10 lin ft over the soil surface to complete the treatment barrier In wide trenches only treat the soil in the area near the service It is important to establish a continuous barrier of treated soil surrounding the services

Where soil conditions will not accept application of specified volume of 0 25% emulsion the 0 5% emulsion may be applied at one half the application rate or 2 gal /10 lin ft

Finish filling the trench with untreated fill soil The soil where each service protrudes from the ground may be treated by trenching and rodding into the trench or trenching of no more than 1 2 gal of emulsion into the soil

**Precaution** Do not treat electrically active underground services

# TREATMENT OF WOOD IN PLACE FOR CONTROL OF TERMITES, CARPENTER ANTS, CARPENTER BEES AND WOOD-INFESTING BEETLES

In addition to subsurface applications this product may be used for treating infested wood in place. It can be applied to wood by crack and crevice tool coarse fan spray or injection. Overall broadcast spray applications must be limited to attics crawl spaces unfinished basements and similar generally unoccupied areas. In occupied indoor areas treat wood trim and exposed beams by brush or coarse spray directed only onto the wood to be treated.

Use this spray at a rate of 1 gal of diluted spray/1 000 sq ft of surface area

#### CONTROL OF WOOD INFESTING BEETLES

To control wood infesting insects such as powderpost beetle (*Lyctidae*) false powderpost beetles (*Bostrichidae*) deathwatch beetles (*Anobiidae*) old house borers (*Cerambycidae*) and ambrosia beetles (*Scolytidae*) in homes and other structures apply as a 0 25% emulsion containing Demon Max For treatment of small areas apply by brushing the emulsion evenly on wood surfaces For large or overhead areas apply as a coarse spray When spraying overhead interior areas of homes apartment buildings etc cover all surfaces below the area being sprayed with plastic sheeting or other material which could be disposed of by placing in trash if contamination from dripping occurs Sprayed surfaces should be avoided until spray has totally dried Do not use in structures occupied by animals to be used for food purposes or which produce products for human consumption

#### TERMITES ABOVE GROUND

For control of aerial colonies of subterranean termites (including Formosan termites) or for control of drywood termites in localized areas of infested wood in structures apply as a 0 1% 0 25% emulsion to voids and galleries in damaged wood and in spaces between wooden members of a structure and between wood and foundations where wood is vulnerable. Application may be made to inaccessible areas by drilling and then injecting the emulsion with a crack and crevice injector into the damaged wood or void spaces. Application to attics or crawl spaces unfinished basements or voids may be made with a coarse fan spray of 0 1% 0 25% emulsion to control subterranean termites in mud tubes or to kill winged forms of drywood termites. This type of application is not intended to be a substitute for soil treatment of subterranean termites. Make treatments at a rate of 1 gal. of the emulsion/1 000 sq. ft. of surface area

For termites active inside trees utility poles and/or fence posts drill to find the interior infested cavity and inject 0.1% emulsion using treatment tool with a splashback guard

Termite carton nests in trees or building voids may be injected with 0 25% 0 50% emulsion using a pointed injection tool. Multiple injection points to varying depths may be necessary. It is desirable to physically remove carton nest material from building voids when such nests are found.

#### **CARPENTER ANTS**

For control of carpenter ants in houses and other structures apply as a 0 25% emulsion for protection up to 5 weeks a 0 5% emulsion for protection up to 11 weeks and a 1 0% emulsion for protection up to 1 year with retreatment semiannually as needed around doors and windows and other places where carpenter ants enter the premises and where they crawl Spray into cracks and crevices or through openings or small drilled holes into voids where these ants or their nests are present. Use no more than a

25 33

sufficient amount of coarse spray to cover the area thoroughly but not to the point of runoff Do not exceed 1 gal of dilute emulsion/1000 sq ft of treated surface

For carpenter ants active inside trees utility poles and/or fence posts drill to find the interior infested cavity and inject 0 25% emulsion for protection up to 1 week using a treatment tool with a splashback guard Reapply under heavy reinfestation pressure

#### FIREWOOD PROTECTION FROM CARPENTER ANTS

(

Prior to laying in firewood soil beneath the cord(s) may be treated with a 0 25% 0 50% emulsion at 1 gal /10 sq ft to prevent carpenter ant infestation

#### CARPENTER BEES

Use a 0 1% emulsion for control of carpenter bees Liquid may be sprayed directly into gallery entrance holes Following treatment the entrance holes may be left open 24 hrs to be certain that returning adult bees are killed When there is no activity the hole may be closed with wood putty

#### TREATMENT OF PRECONSTRUCTION LUMBER AND LOGS\*

To protect unseasoned lumber and logs from wood destroying insects such as termites carpenter ants and beetles (ambrosia powder post old house borers and others) totally treat wood with a 0 25% to 0 5% emulsion. This solution can be applied by various methods including spraying brushing dipping and pressure treatment. Frequent monitoring of dip and pressure systems are necessary to ensure that the desired level of Demon Max is maintained. Wood can be handled after treatment when dry

- 1 For dip treatments the wood should be totally submersed in the solution until thoroughly wet and then allowed to dry in a suitable location. Dipping solutions to which Demon Max has been added should be agitated before use if left unused for long periods of time. Sediment, debris and other deposits should be periodically cleaned from the tank.
- 2 For pressure treatments the wood should be placed in the treatment chamber the Demon Max solution added and the system pressurized up to 250 p s i for up to 1 hour depending on the density and type of wood treated After the pressure is released and the system drained the wood should be placed in a suitable location for drying
- 3 For spray treatments the wood should be sprayed thoroughly including back and ends
- 4 For brush treatments all parts of wood surfaces should be thoroughly treated

22

(

\*Not approved for use in California

(

#### PEST CONTROL IN AND AROUND STRUCTURES--GENERAL INFORMATION

For residual pest control in and on buildings and structures and their immediate surroundings and on modes of transport Permitted areas of use include but are not limited to

- industrial buildings houses apartment buildings laboratories buses greenhouses
- the nonfood/feed areas of stores warehouses schools nursing homes hospitals (non patient areas) restaurants hotels and food manufacturing processing and servicing establishments vessels (ships boats) railcars trucks trailers aircraft (cargo and non cabin areas only)

Do not use in commercial greenhouses or nurseries Not for use on plants being grown for sale or other commercial use or for commercial seed production or for research purposes Do not use on food or feed crops

Demon Max is intended for dilution with water for spray application

Fill sprayer with the desired volume of water and add Demon Max Close and shake before use in order to ensure proper mixing Shake or re agitate sprayer before use if spraying is interrupted Make up only as required repeat treatments when needed

KEEP CHILDREN AND PETS OFF TREATED SURFACES UNTIL DRY

(

26|33

## PEST CONTROL IN AND AROUND STRUCTURES – APPLICATION PROCEDURES

#### **RECOMMENDED USE RATES**

(

Pests	Concentration of Active Ingredient	Dilution Rate
Ants Asian Cockroaches Boxelder Bugs Carpenter Ants Carpenter Bees Centipedes Chiggers <sup>b c</sup> Cockroaches (Maintenance) Crickets Earwigs Elm Leaf Beetle <sup>c</sup> Firebrats Fleas <sup>b</sup> Flies <sup>a</sup> Ground Beetles Millipedes Mosquitoes <sup>b</sup> Pillbugs Silverfish Sowbugs	0 1%	<sup>1</sup> ⁄₂ fl oz (1 tbsp ) per 1 gal water
Bees Cockroaches (Clean out) Scorpions Spiders Ticks Wasps Wood Infesting Beetles	0 2%	1 fl oz (2 tbsp ) per 1 gal water

Not for indoor use in California <sup>b</sup>Outdoor use only <sup>c</sup>Not approved for use in California

(

27 33

#### INDOOR USE

For crack and crevice and/or spot application for residual and contact control of ants carpenter ants cockroaches crickets spiders and certain other insect pests

#### Cockroaches, Spiders, Crickets, Scorpions, Silverfish, Ticks and Firebrats

Apply as a crack and crevice or spot application to areas where these pests hide such as baseboards corners storage areas closets around water pipes doors and windows attics and eaves behind and under refrigerators cabinets sinks furnaces and stoves the underside of shelves drawers and similar areas Also see **Outdoor Surfaces and Around Buildings** 

#### Ants

Apply to any trails around doors and windows and similar areas where ants (including carpenter ants) may be found Refer to barrier treatment directions to prevent infestation also see **Outdoor Surfaces and Around Buildings** 

#### Wasps and Bees

Application to nests should be made late in evening when insects are at rest Thoroughly spray nest and entrance and surrounding areas where insects alight also see **Outdoor Surfaces and Around Buildings** 

#### Boxelder Bugs Sowbugs, Pillbugs Millipedes Elm Leaf Beetle and Centipedes

Apply around doors and windows and similar areas where these pests may be found or where they may enter premises Spray baseboards storage areas and other locations Refer to barrier treatment directions to prevent infestation also see **Outdoor Surfaces** and Around Buildings

#### Flies

Apply directly to walls ceilings window screens and other fly resting areas as a residual surface treatment May be used inside residential buildings as well as in and around carports garages and storage sheds also see **Outdoor Surfaces and Around Buildings** 

#### Scorpions

Treat and remove accumulations of lumber firewood and other materials which serve as harborage sites Apply as a coarse spray thoroughly but not to the point of drip also see **Outdoor Surfaces and Around Buildings** 

25

#### FOOD HANDLING ESTABLISHMENTS

(Places other than private residences in which food is held processed prepared or served )

#### Non food Areas

Demon Max may be used as a general spot or crack and crevice treatment in nonfood areas Similar areas where insects hide or through which insects may enter should be treated

Examples of nonfood areas include garbage rooms lavatories floor drains (to sewers) entries and vestibules offices locker rooms machine rooms boiler rooms garages mop closets and storage (after canning or bottling)

#### **Food Areas**

Demon Max is not labeled for use in food areas Do not use in food areas of food handling establishments restaurants or other areas where food is commercially prepared or processed Do not use in serving areas while food is exposed or facility is in operation Serving areas are areas where prepared foods are served such as dining rooms but excluding areas where foods may be prepared or held. In the home all food processing surfaces and utensils should be covered during treatment or thoroughly washed before use Exposed food should be covered or removed. Not for use in USDA meat and poultry plants

Examples of food areas are areas for receiving storage packing (canning bottling wrapping boxing) preparing edible waste storage and enclosed processing systems (mills dairies edible oils syrups) Serving areas (when food is exposed and facility is in operation) also would be considered a food area

#### OUTDOOR USE

#### **Under Slabs**

Infestations of arthropods such as ants cockroaches and scorpions inhabiting under slab areas may be controlled by drilling and injecting or horizontal rodding and injecting 1 gal of 0 25% 0 5% emulsion/10 sq ft or 2 gal of emulsion/10 lin ft Product may also be applied through under structure insecticidal delivery systems such as piping or flexible tubing mounted under the structure. This treatment is not intended as a substitute for termite control

26

(

#### In Crawl Spaces

Broadcast Demon Max as a 0 25% to 0 5% emulsion to all surfaces in crawl spaces to control ants fleas cockroaches scorpions or other arthropods Product may also be applied through under structure insecticidal delivery systems such as piping or flexible tubing mounted under the structure. This treatment is not intended as a substitute for termite control. Treat surfaces thoroughly but not to point of run off

#### **Outdoor Surfaces and Around Buildings**

Apply Demon Max as a 0 1% emulsion as a residual treatment to outside surfaces of buildings including but not limited to exterior siding foundations porches window frames eaves patios garages refuse dumps lawns or grass areas adjacent or around private homes duplexes townhouses condominiums house trailers apartment complexes carports garages fence lines storage sheds barns and other residential structures commercial industrial and institutional buildings. Application may be made to soil trunks of woody ornamentals or other areas where pests congregate or have been seen. Base need for retreatment upon monitoring for pest presence. See **DIRECTIONS FOR USE** Caution on application to vinyl siding

#### **Barrier Treatment For Pests Around Structures**

Apply Demon Max as a 0 1% emulsion to a band of soil and vegetation 6 10 ft wide around and adjacent to the structure Also treat the foundation of the structure to a height of 2 3 ft Use a treatment volume of 2 10 gal per 1000 sq ft Higher volumes of water may be needed if mulch or leaf litter is present or dense foliage exists House siding may be treated if boxelder bugs elm leaf beetles earwigs silverfish or other similar pests are present See **DIRECTIONS FOR USE Caution on application to vinyl siding** 

## LAWN AND LANDSCAPE PEST CONTROL

(

Pest	Specific Instructions and Recommended Use Rates
Chinch Bugs <sup>a</sup> Mole Crickets <sup>a</sup> Fleas Ticks	For residential lawns apply Demon Max at the rate of 0 33 0 65 fl oz per 1000 sq ft in a volume of water sufficient for uniform coverage such as 3 20 gal. Use the lower rate to knock down pests and the higher rate where faster knockdown or greater residual is desired The maximum application rate on lawns and other turfgrass is 0 44 lb a i /A (0 0101 lb a i /1 000 ft <sup>2</sup> ) Lawn should not be longer than 3 inches at the time of application Base need for retreatment upon monitoring for pest presence. Application in combination with compatible surfactants may enhance penetration. Arid climates generally require the higher volume.
Ants Ant Mounds <sup>a</sup> Fıre Ants <sup>a</sup>	TableDrench Method (Ant Mounds Fire Ants)Apply 1 2gal of 0 1% Demon Max emulsion to each mound areaby sprinkling the mound until it is wetTreat a 2 ftdiameter circle around the moundFor mounds largerthan 12 inchesthe higher volume and wider treatmentdiameter (up to 4 ft ) may be neededFor best resultsapply in cool weathersuch as in early morning or lateevening hoursbut not in the heat of the day
Bark Beetles Borers Boxelder Bugs Elm Leaf Beetles Gypsy Moths (adults & caterpillars) <sup>a</sup>	To control Boxelder Bugs Elm Leaf Beetles Gypsy Moth Caterpillars apply Demon Max as a 0 1% emulsion Spray tree trunks building siding or wherever pests congregate thoroughly but not to the point of run off Borers and Bark Beetles To prevent infestation of trees and woody ornamentals spray the bark thoroughly but not to the point of run off using a 0 1% Demon Max emulsion

Not approved for use in California

(

31 33

# LAWN APPLICATION DILUTION TABLE Demon Max rate (oz) for 100 gal according to volume of application

Example For a Chinch bug application at the rate of 0 65 oz per 1000 ft<sup>2</sup> using 5 gal of solution per 1000 sq ft of lawn use 13 oz of Demon Max in a 100 gal tank (1 fl oz equals 30 ml)

Volume per 1000 ft <sup>2</sup>	Amount of Demon Max			
	0 33 oz / 1000 ft <sup>2</sup>	0 5 oz / 1000 ft <sup>2</sup>	0 65 oz / 1000 ft <sup>2</sup>	
5 gal	6 5 oz	10 0 oz	13 0 oz	
8 gal	4 0 oz	6 5 oz	8 0 oz	
10 gal	3 5 oz	5 0 oz	6 5 oz	
15 gal	2 0 oz	3 5 oz	4 5 oz	
20 gal	1 5 oz	2 5 oz	3 5 oz	

#### STORAGE AND DISPOSAL

Do not contaminate water food or feed by storage or disposal Open dumping is prohibited Do not reuse empty container

#### Pesticide Storage

Keep container closed when not in use Do not store near food or feed Protect from freezing In case of spill or leak on floor or paved surfaces soak up with sand earth or synthetic absorbent Remove to chemical waste area

#### Pesticide Disposal

Pesticide wastes are toxic Improper disposal of excess pesticide spray mixture or rinsate is a violation of Federal law If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance

#### Container Handling [less than 5 gallons]

Non refillable container Do not reuse or refill this container Offer for recycling if available Triple rinse container (or equivalent) promptly after emptying Triple rinse as follows Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip Fill the container ¼ full with water and recap Shake for 10 seconds Pour rinsate into application equipment or a mix tank or store rinsate for later use and disposal Drain for 10 seconds after the flow begins to drip Repeat this procedure two more times Then offer for recycling if available or puncture and dispose of in a sanitary landfill or by incineration or if allowed by state and local authorities by burning If burned stay out of smoke

#### Container Handling [Bulk/Mini Bulk]

Non refillable container Do not reuse or refill this container Offer for recycling if available Triple rinse container (or equivalent) promptly after emptying Triple rinse as follows Empty the remaining contents into application equipment or a mix tank Fill the container ¼ full with water Replace and tighten closures Tip container on its side and roll it back and forth ensuring at least once complete revolution for 30 seconds Stand the container on its end and tip it back and forth several times Turn the container over onto its other end and tip it back and forth several times Empty the rinsate into application equipment or a mix tank or store rinsate for later use and disposal Repeat this procedure two more times Then offer for recycling if available or puncture and dispose of in a sanitary landfill or by incineration or if allowed by state and local authorities by burning If burned stay out of smoke

#### CONTAINER IS NOT SAFE FOR FOOD, FEED OR DRINKING WATER

Demand® Demon® the ALLIANCE FRAME the SYNGENTA Logo and the PURPOSE ICON are trademarks of a Syngenta Group Company

Viton® trademark of E I du Pont de Nemours and Company

©2012 Syngenta

For non emergency (e g current product information) call Syngenta Crop Protection at 1 800 334 9481

Manufactured for Syngenta Crop Protection LLC P O Box 18300 Greensboro North Carolina 27419 8300

SCP 1218A M(draft rereg c)

DEM MAX 1218 M(draft rereg c) CLEAN – pl – 7/19/12 000100 01218 20120719 DEMON MAX\_REREG\_c\_JUL2012 pdf