ACTIVE INGREDIENT

PERCENT BY WEIGHT

Poly loxyethylene (dimo lediminio) ethylene dimethyliminio ethylene dichloride.

30 pct.

INERT INGREDIENT

70 pct.

Weight per gailon 8.97 pounds

Weight of Active Ingredient 2.69 pounds

APPLICATION

ALGEX NO. 829 is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleared to remove algal growth, microbiological slime and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of ALGEX NO. 829 per 1000 gallons of water, to provide a concentration of 16 - 40 parts per million of No. 829 based on the total weight of water in the system is recommended. Repeat initial dosage until control is achieved. Subsequent slug additions of .47 to 4.75 flud ounces of No. 829 per 1000 gallons of water 4 to 40 parts per million of No. 829) should be employed every 2 to 5 days or as needed. The trequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of the water cooling towers.

CAUTION

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public waters. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed or the label.

Rinse small empty container thoroughly with water and discard it. Do not reuse empty drum. Destroy by perforating or crushing and burying in a safe place.



CAUTION KEEP OUT OF THE REACH OF CHILDREN

