

WASATCH CHEMICAL COMPANY
SALT LAKE CITY, UTAH

PAINT-OVER DURACIDE

Contains 0.1 pounds of pentachlorophenol per gallon.
U. S. Pat. No. 2,840,225
Keep in original container for safety.

REGISTERED TRADE NAME OF TRADE MARK OF THE
WASATCH CHEMICAL COMPANY, SALT LAKE CITY, UTAH

ACTIVE INGREDIENTS:

Petroleum Distillate.....	94.60%
Pentachlorophenol, technical.....	4.37%
Other chlorophenols and related compounds.....	0.63%
<u>INERT INGREDIENTS:</u>	5.40%

NET CONTENTS:

TOTAL 100.00%

DIRECTIONS

Pentachlorophenol is insoluble in water and non-volatile. It remains in the wood after treatment. Paint-Over Duracide dries fast leaving a clean surface for painting, staining, etc.

SASH, FRAMES, DOORS, FLOOR JOIST, LUMBER, ETC.: Sash, frames, doors, etc. are treated after they have been assembled and sanded. Most mill work requires an immersion period of 3 to 5 minutes for proper penetration. Ten to 15 gallons of Duracide per 1,000 board feet are required for treatment. When the liquid is sprayed or brushed on, two or more flowing applications a few hours apart are required for deeper penetration.

GREENHOUSES AND NURSERIES: Seed flats, wooden greenhouse benches, cold frames, hot beds, and other structural frame work should be treated well in advance of use so that the solvent fumes will evaporate before planting. Seed flats may be soaked before or after assembly. Bench materials may be soaked before construction or sprayed or brushed afterward. Frame work in place should be dried out before brushing or spraying with Paint-Over Duracide. At least two coats are desirable. Allow at least one gallon for each 100 board feet to be treated. Be sure fumes are evaporated before planting.

POTATO CULMARS: Soak all peeled seasoned poles and timbers in a tank which may be made by welding open end oil drum halves together lengthwise, until duracide penetrates at least 3/4 inches. One gallon is required for each 14 foot pole 6 inches in diameter.

WARNING: Keep away from heat or open flame. Do not breathe vapor, fumes, or spray mist. Harmful if swallowed or absorbed through skin. Causes skin irritation. Avoid contact with eyes, skin or clothing. Wear goggles. Wash thoroughly with soap and water if contacted. Synthetic rubber is best for protection.

NON-WARRANTY: Wasatch Chemical Company and the seller make no warranty of any kind, expressed or implied, concerning the use of this product. Buyer assumes all risks of use or handling whether in accordance with directions or not.

FORM NO. 10 DATA

