

(RIGHT SIDE PANEL)

2,4-D LOW VOLATILE ESTER

DIRECTIONS FOR USE

WOODY PLANT CONTROL: To control 2,4-D susceptible woody plants such as Willow, Alder, Buckbrush, Sumac, and Elderberry in non-cropped or other waste areas, use 1-1/3 to 2 quarts in 100 gallons of water. Wet thoroughly all parts of the plants, including foliage and stems, to point of run-off.

GENERAL WEED CONTROL: On vacant lots, roadsides, and along fence rows use 2/3rds to 1-1/3 quarts of 2,4-D LOW VOLATILE ESTER in 100 gallons of water per acre. Thoroughly wet all foliage to run-off.

GENERAL INFORMATION

2,4-D LOW VOLATILE ESTER is recommended for controlling Arrowhead, Dandelion, Dock, Bindweed, Henbit, Lambsquarter, Mallow, Mustard, Peppergrass, Pigweed, Plantain, Ragweed, Shepherds' purse, Thistles, Wild Carrot, Wild Morning Glory, Wild Garlic, Wild Onion, and many other broad-leaved weeds.

PREPARATION OF SPRAY: Fill the spray tank with half the required amount of water, then add the recommended amount of 2,4-D LOW VOLATILE ESTER with agitation and continue filling the spray tank with water. Use enough water per acre to give uniform coverage. The amount of water required for low volume applications may vary from 5 to 25 gallons per acre. In any case, use the same amount of 2,4-D recommended per acre.

CAUTION: Avoid spray drift to susceptible plants such as cotton, tomatoes, flowers, grapes, fruit trees, and ornamentals. Spray drift may cause severe injury to both growing and dormant plants. Coarse sprays are less likely to drift. Although this ester is much less volatile than butyl or isopropyl esters, high temperatures may produce vapors after application which might injure 2,4-D sensitive plants growing nearby. DO NOT contaminate irrigation ditches or water used for domestic purposes. DO NOT store near fertilizers, seeds, insecticides, or fungicides. DO NOT take internally. Avoid contact with skin, eyes, or clothing. DO NOT use the same spray equipment for applying other materials to plants, as injury may result.

This product is licensed under one or more of the following United States patents:  
390,941, 2,394,916, 2,396,513, 2,412,510, 2,453,983, 2,472,347, Reg. 23,115.

NON-WARRANTY: Seller makes no warranty of any kind, expressed or implied, concerning the use of this product. Buyer assumes all risks of use or handling, whether in accordance with directions or not.

MANUFACTURED BY: WASATCH CHEMICAL COMPANY  
SALT LAKE CITY, UTAH

April 20, 1965

Resubmitted 10/27/67