

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

DEC 2 7 2011

Dawn Kominski Tessenderlo-Kerley, Inc. 2255 N. 44th Street, Suite 300 Phoenix, AZ 85008-3279

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

Subject:

SECTAGON-42

EPA Reg. No. 61842-6

Phase 2 RED Mitigation Amendment Label Dated May 31, 2011

EPA Decision Number 459138

Dear Ms. Kominski:

The amended label referred to above, submitted in connection with reregistration of metam sodium under the Federal Insecticide, Fungicide and Rodenticide Act as amended is acceptable provided the following label revisions are made and the following conditions are met:

LABEL REVISION

- 1. Page 6 Under the "Supervision of Handlers" section, bold the title "Fumigant Safe Handling Information" each time it appears in the last paragraph.
- 2. Page 7 Under Respiratory Protection and Stop Work Triggers, delete the underscore after the parentheses in the first paragraph.
- 3. Page 17-18 Under Calculating the Broadcast Equivalent Application Rate, replace the gray images with black & white images.
- 4. Page 20 -31 The minimum font size for the entire labeling is 12 pt. Make sure the buffer zone tables meet this requirement.
- 5. Page 32 Under "Restrictions for Difficult to Evacuate Sites," reformat the section like this:

"Difficult to evacuate sites are pre-K to grade 12 schools, state licensed daycare centers, nursing homes, assisted living facilities, hospitals, in-patient clinics, and prisons.

- No fumigant application with a buffer zone greater than 300 feet is permitted within 1/4 mile (1320 feet) of difficult to evacuate sites unless the site is not occupied by children from state-licensed day care centers, students (pre-K to grade 12), patients, or prisoners during the application and the 36-hour period following the end of the application.
- No fumigant application with a buffer zone of 300 feet or less is permitted within 1/8 mile (660 feet) of difficult to evacuate sites unless the site is not occupied by children from state-licensed day care centers, students (pre-K to grade 12), patients, or prisoners during the application and the 36-hour period following the end of the application."
- 6. Page 39 Increase the font size to a minimum of 12 point in the text box for "Conditions of Sales and Warranty."

CONDITIONS

- 1. EPA has determined that the risk mitigation measures on the revised label for this product are necessary to adequately protect human health and the environment. Therefore, pursuant to 40 CFR § 152.130(d), EPA has decided that no product bearing previously approved labeling may be sold or distributed (released for shipment) by its registrant after December 1, 2012. Wherever state approval is required for sale or distribution of this product with this new labeling, EPA strongly encourages you to submit an application to the state authority as soon as possible. You should be aware that the Agency does not intend to modify the December 1, 2012, deadline because of any failure to obtain state approvals.
- 2. Submit one copy of the final printed label that incorporates the required changes before the product is released for shipment.

One copy of the label stamped "Accepted with comments" is enclosed for your records. If you have any questions, please contact Jose Gayoso by phone at (703) 347-8652 or via email at gayoso.jose@epa.gov or Shaja Joyner by phone at (703) 308-3194 or email at joyner.shaja@epa.gov.

Sincerely,

Shaja B. Joyner

Product Manager (20)

Fungicide Branch

Registration Division (7504P)



RESTRICTED USE PESTICIDE DUE TO ACUTE INHALATION TOXICITY TO HUMANS.

For retail sale to and use by certified applicators or persons under their direct supervision and only for those uses covered by the certified applicator's certification.

In EPA Letter Dated

DEC 2 7 2011
Under the Federal Insecticide,
Fungicide, and Rodenticide Ac
as amended, for the pesticide
registered under EPA Reg. No.

Sectagon – 42

Agricultural Fumigant

FUMIGANT SOLUTION FOR SPECIFIC CROPS AS LISTED IN THIS LABEL

For suppression of: Nematodes, Fungi, Bacteria, Weeds, Weed seeds and Volunteer seeds.

42.2% SODIUM METHYLDITHIOCARBAMATE

ACTIVE INGREDIENT:

Contains 4.22 lbs. active ingredient per gallon.

DANGER PELIGRO

READ ENTIRE LABEL. USE STRICTLY IN ACCORDANCE WITH LABEL WARNINGS AND DIRECTIONS

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail.)

	FIRST AID
If on skin or clothing:	 Take off contaminated clothing. Rinse skin immediately with plenty of water for 15 – 20 minutes. Call a poison control center or doctor for treatment advice.
If in eyes:	 Hold eye open and rinse slowly and gently with water for 15 – 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
If inhaled:	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.
If swallowed:	 Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
	HOT LINE NUMBER
	ct container or label with you when calling a poison control center or doctor, or going for treatment. You may also 174-1975 for emergency medical treatment information.
	NOTE TO PHYSICIAN
Probable muco	usal damage may contraindicate the use of gastric lavage.

EPA Reg. No. 61842-6

EPA Est. No. 61842-ID-001

EPA Est. No. 61842-WA-002

Manufactured by: Tessenderlo Kerley, Inc. 2255 N. 44th Street, Suite 300 Phoenix, AZ 85008 USA 1-800-525-2803

NSFSPUS0710

Net Contents:



5/41

TABLE OF CONTENTS

F	PRECAUTIONARY STATEMENTS	4
	HAZARDS TO HUMANS AND DOMESTIC ANIMALS	4
	PERSONAL PROTECTIVE EQUIPMENT (PPE)	4
	PERSONAL PROTECTIVE EQUIPMENT (PPE) FOR RESPIRATORY PROTECTION	4
	USER SAFETY REQUIREMENTS	
	USER SAFETY RECOMMENDATIONS	4
	ENVIRONMENTAL HAZARDS	4
	DIRECTIONS FOR USE	5
	AGRICULTURAL USE REQUIREMENTS	5
	TERMS USED IN THIS LABELING	
	USE SITES	
	USE METHOD RESTRICTIONS	6
	CERTIFIED APPLICATOR TRAINING	
	HANDLERS	2000 200
	PROTECTION FOR HANDLERS	
	Supervision of Handlers	
	Exclusion of Non-Handlers from the Application Block and Buffer Zone	
	Providing, Cleaning, and Maintaining PPE	
	Air-purifying Respirator Availability	
	Respirator Fit Testing, Medical Qualification, and Training	
	Respiratory Protection and Stop Work Triggers	
	TARP PERFORATION AND/OR REMOVAL	
	ENTRY RESTRICTED PERIOD AND NOTIFICATION	
	Entry Restricted Period	
	Notification	
	MANDATORY GOOD AGRICULTURAL PRACTICES (GAPs)	
	MAXIMUM APPLICATION RATES FOR PRE-PLANT SOIL USES	
	CALCULATING THE BROADCAST EQUIVALENT APPLICATION RATE	
	GENERAL BUFFER ZONE REQUIREMENTS	
	Buffer Zone Proximity	
	Structures Under The Control Of The Owner Of The Application Block	
	Areas Not Under The Control Of The Owner Of The Application Block	
	BUFFER ZONE DISTANCES	
	Buffer Zone Tables	
	BUFFER ZONE CREDITS	
	POSTING FUMIGANT BUFFER ZONES	
	RESTRICTIONS FOR DIFFICULT TO EVACUATE SITES	
	EMERGENCY PREPAREDNESS AND RESPONSE MEASURES	
	Triggers for Emergency Preparedness and Response Measures	
	Fumigant Site Monitoring	
	Response Information For Neighbors	
	NOTICE TO STATE AND TRIBAL LEAD AGENCIES	
	EMERGENCY RESPONSE PLAN	
	SITE-SPECIFIC FUMIGATION MANAGEMENT PLAN (FMP)	
	Record-Keeping Procedures	
	POST-APPLICATION SUMMARY	
	Record-Keeping Procedures	
	PRODUCT INSTRUCTIONS	
	FRODUCT INSTRUCTIONS	34

6/41

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

- Corrosive: causes skin damage. May be fatal if absorbed through the skin. Do not get on skin or clothing.
- Prolonged or frequent repeated skin contact may cause allergic reactions in some individuals.
- · Harmful if swallowed.
- Harmful if inhaled. Irritating to eyes, nose, and throat. Avoid breathing vapor or spray mist.
- · Irritating to eyes. Do not get in eyes.

PERSONAL PROTECTIVE EQUIPMENT (PPE)

Some materials that are chemical-resistant to this product are barrier laminate or viton ≥ 14 mils. For more options, follow the instructions for category H on the chemical-resistance category selection chart.

Handlers applying via weed sprayer (see *Terms used in this labeling* section) while irrigation system is operating or handlers who may be exposed to liquid spray while repairing a malfunctioning chemigation system or shutting off equipment must wear:

- · chemical-resistant coveralls over long-sleeve shirt and long pants,
- · chemical-resistant gloves,
- · chemical-resistant footwear plus socks,
- · chemical-resistant headgear, and
- respirator of the type specified in the respiratory protection section in the PPE requirements on this label.

Handlers wearing chemical-resistant attire are limited to 30 minutes of exposure in any 60 minute period to prevent heat illness, and, as required by the Worker Protection Standard for Agricultural Pesticides, employers of these handlers must take any necessary steps to avoid heat illness.

Except as required above, handlers transferring or loading liquid formulations, handlers operating motorized ground equipment with open cabs, handlers repairing or inactivating irrigation or chemigation equipment during application, and handlers cleaning up spills or equipment, must wear:

- · coveralls over long-sleeve shirt and long pants,
- · chemical resistant gloves,
- · chemical resistant footwear plus socks,
- chemical-resistant apron if transferring or loading the fumigant or cleaning up spills or equipment,
- · protective eyewear, and
- respirator of the type specified in the PPE requirements for respiratory protection section in the PPE requirements on this label if triggered.

All other handlers including handlers operating motorized ground equipment with closed cabs (except for handlers who set up and calibrate chemigation and irrigation equipment and start the application from inside the application block) as stated in this labeling must wear:

- · long-sleeve shirt and long pants,
- · shoes plus socks, and
- respirator of the type specified in the respiratory protection section in the PPE requirements on this label if triggered.

All handlers who set-up and calibrate chemigation and irrigation equipment and start the application from inside the application block must wear:

- · long-sleeve shirt and long pants,
- · shoes plus socks,
- · protective eyewear, and
- respirator of the type specified in the respiratory protection section in the PPE requirements on this label if triggered.

PERSONAL PROTECTIVE EQUIPMENT (PPE) FOR RESPIRATORY PROTECTION

When an air-purifying respirator is required under this label's Directions for Use, Protection for Handlers, Respiratory Protection and/or Stop Work Triggers section, handlers must wear at minimum either:

- A NIOSH-certified full-facepiece air-purifying respirator equipped with an organic vapor (OV, NIOSH approval prefix TC-23C) cartridge and a particulate prefilter (Type N, R, P, or HE NIOSH approval number prefix TC-84A) or
 - a gas mask with a canister approved for organic vapor (NIOSH approval number prefix TC-14G).

Cartridges or canisters must be replaced when odor or sensory irritation from this product becomes apparent during use, if the measured concentration of MITC is greater than 6000 ppb (6 ppm), or in the absence of any other instructions or indications of service life, at the end of each day's work period, whichever occurs first.

USER SAFETY REQUIREMENTS

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

DO NOT transport contaminated clothing inside a closed vehicle unless stored in a sealed container. Wash or dispose as specified.

USER SAFETY RECOMMENDATIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.
- Remove PPE immediately after handling this product. Wash the outside
 of gloves before removing. As soon as possible, wash thoroughly and
 change into clean clothing.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to mammals, birds, aquatic invertebrates and fish. Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment wash waters or rinsate.

Metam-sodium has certain properties and characteristics in common with chemicals that have been detected in groundwater (highly soluble in water and has low adsorption to soil).

For untarped applications, leaching and runoff may occur if there is heavy rainfall after soil fumigation.

USE PRECAUTIONS

Keep off desirable lawns and plants. Do not apply within 3 feet of the drip line of desirable plants, shrubs or trees. Do not use in confined areas without adequate ventilation OR where fumes may enter nearby dwellings. Do not use in greenhouses. Keep container tightly closed when not in use. Do not store near feed or food.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Store in a cool, dry place, keep container closed when not in use. Do not store below 0° F. Product crystallizes at lower temperatures. Warm or store at higher temperatures and mix to redissolve crystals and assure uniformity before use.

Do not stack more than three drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instruction, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: [NON-REFILLABLE CONTAINERS1 Nonrefillable container. Do not reuse or refill this container. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.



Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean the container before final disposal, empty the remaining contents from this container into application equipment or mix tank. Fill the container about 10 percent full with water. Agitate vigorously or recirculate water with the pump for 2 minutes. Pour or pump rinsate into application equipment or rinsate collection system. Repeat this rinsing procedure two more times. Then offer for recycling if available or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

NOTE OF WARNING: CONTAINER IS NOT SAFE FOR FOOD, FEED OR DRINKING WATER!

DIRECTIONS FOR USE Restricted Use Pesticide

For suppression of: Nematodes, Fungi, Bacteria, Weeds, Weed seeds and Volunteer seeds.

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Do not apply when wind speed favors drift beyond the area intended for treatment. Only handlers may be in the application block from the start of the application until the entry restricted period ends, and in the buffer zone during the buffer zone period. For any requirements specific to your State or Tribe, consult the agency responsible for pesticide regulation.

AGRICULTURAL USE REQUIREMENTS

Use this product only in accordance with its labeling and with the Worker Protection Standard, 40 CFR 170. This Standard contains requirements for the protection of agriculture workers on farms, forests, nurseries, and greenhouses, and handlers of agricultural pesticides. It contains requirements for training, decontamination, notification and emergency assistance. For entry-restricted period and notification requirements, see the *Entry Restricted Period* and *Notification* sections of this labeling. The requirements in this box only apply to uses of this product that are covered by the Worker Protection Standard (WPS).

PPE For Entry During the Entry-Restricted Period: PPE for entry that is permitted by this labeling is listed in the *Personal Protective Equipment (PPE)* section of this labeling.

TERMS USED IN THIS LABELING

<u>Soil Fumigant Training Program</u>: Certified applicator training that provides information on (1) how to correctly apply the fumigant, including how to comply with new label requirements; (2) how to protect handlers and bystanders; (3) how to determine buffer zone distances; (4) how to complete an FMP and the post-application summary; (5) how to determine when weather and other site-specific factors are not favorable for fumigant application; (6) how to comply with required GAPs and how to document compliance with GAPs in the FMP; and (7) how to develop and implement emergency response plans.

<u>Fumigant Safe Handling Information:</u> Information that must be provided annually to handlers that must include the following: (1) what fumigants are and how they work, (2) safe application and handling of soil fumigants, (3) air monitoring and respiratory protection requirements for handlers, (4) early signs and symptoms of exposure, (5) appropriate steps to take to mitigate exposures, (6) what to do in case of an emergency, and (7) how to report incidents.

<u>Application Block</u>: Area within the perimeter of the fumigated portion of a field (including furrows, irrigation ditches, roadways). The perimeter of the application block is the border that connects the outermost edges of total area treated with the fumigant product.

Application Rate: The ratio of fumigant mass applied compared to the soil surface area (e.g., lbs of product per acre). The application rate is expressed on this labeling in terms of either the "treated area application rate" or the "broadcast equivalent application rate." The "treated area application rate" relates to only the rate of fumigant applied to the portion of the field that is fumigated (e.g., rate within the bed or strips). The "broadcast equivalent application rate" relates to the rate of fumigant applied within the entire perimeter of the application block. For bedded

and strip applications, the "broadcast equivalent application rate" must be calculated to determine the buffer zone distance required by this labeling.

Start of the Application: The time at which the furnigant is first delivered/dispensed into the soil in the application block.

Application is Complete: The time at which the fumigant has stopped being delivered/dispensed into the soil and the soil has been sealed; drip lines have been purged (if applicable). For applications with water seals, the application is complete at the time at which the fumigant has stopped being delivered/dispensed into the soil.

Entry Restricted Period: This period begins at the start of the application and expires depending on the application method and if tarps are used when the tarps are perforated and removed. Entry into the application block during this period is only allowed for appropriately PPE-equipped handlers performing handling tasks. See the Entry Restricted Period and Notification section for additional information.

<u>Buffer Zone</u>: An area established around the perimeter of each application block. The buffer zone must extend outward from the edge of the application block perimeter equally in all directions.

<u>Buffer Zone Period</u>: Begins at the start of the application and lasts for a minimum of 48-hours after the application is complete. Non-handlers must be excluded from the buffer zone during the buffer zone period.

<u>Difficult to Evacuate Sites</u>: Pre-K to Grade 12 schools, state licensed daycare centers, nursing homes, assisted living facilities, hospitals, inpatient clinics, and prisons.

Owner: Any person who has a present possessory interest (fee, leasehold, rental, or other) in an agricultural establishment. A person who has both leased such agricultural establishment to another person and granted that same person the right and full authority to manage and govern the use of such agricultural establishment is not an owner. See definition of "owner" in WPS (40 CFR §170.3).

<u>Roadway</u>: Portion of a street or highway improved, designed or ordinarily used for vehicular travel, exclusive of the sidewalk or shoulder even if such sidewalk or shoulder is used by persons riding bicycles. In the event a highway includes two or more separated roadways, the term *roadway* shall refer to any such roadway separately.

Representative Handling Task: For air monitoring, the locations and handler activities sampled must represent each handler's exposure occurring within the application block. For example, for an application consisting of a seven-handler crew (1 tractor driver, 1 tractor co-pilot, 4 shovelers, and 1 certified applicator supervising) two breathing zone samples could be collected: one sample for the tractor co-pilot and one sample for a downwind shoveler. Results of previous sampling may indicate which tasks and locations are worst case and therefore representative of all handlers.

High Release Height Center Pivot or Lateral Move Irrigation Applications: (1) Release height OR spray height greater than 8 feet, and (2) there is greater than 30 lbs. PSI at the sprinkler head.

Medium Release Height Center Pivot or Lateral Move Irrigation Applications: (1) Release height AND spray height is less than 8 feet, AND (2) 29 lbs. or less PSI at the sprinkler head, AND (3) there are no end guns.

Low Release Height-Solid Stream Center Pivot or Lateral Move Irrigation Applications: (1) Release height and spray height is less than 4 feet, AND (2) 29 lbs. or less PSI at the sprinkler head, AND (3) application system produces a solid stream, and (4) there are no end guns.

<u>Solid Stream</u>: An uninterrupted liquid stream that remains generally as a coarse flow until contacting the intended target. An example of a solid stream application is Smart Drop®, also known as drizzle boom. Any application system that employs sprayheads or nozzles with moving parts that produce a rotating or oscillating spray pattern (e.g., rotators, spinner, nutators, and wobblers) or that otherwise break up the stream into droplets does not qualify as a solid stream nozzle.

Weed Sprayer: In this labeling, weed sprayer refers to a tank that holds 100-500 gallons combined with an off-set spray boom that creates a

swath about 4 feet on each side of an orchard tree row, leaving the untreated grassy middle to grow.

USE SITES

Only for use on the following:

Cover crops (i.e., crops planted between periods of regular crop production to prevent soil erosion);

Crops grown solely for seed;

As well as (in alphabetical order):

alfalfa; amaranth (including leafy amaranth, Chinese spinach, tampala); anise; apple (including balsam, crabapple); apricot; artichokes; arugula (roquette); asparagus (nursery production only); barley; basil; beans (including: lima, green, fava, seed beans); beet (including garden);

berry (including black satin berry, blackberry, blueberry, boysenberry, chesterberry, lowberry, wild raspberry, youngberry, darrowberry, dewberry, cloudberry, elderberry, Cherokee blackberry, coryberry, European barberry, huckleberry, hullberry, gooseberry, cranberry, highbush cranberry, Himalayaberry, jostaberry, juneberry, Saskatoon berry, lingonberry, loganberry, lavacaberry, lucretiaberry, mammoth blackberry, marionberry, bingleberry, mountain pepper berries, mulberry, olallieberry, dirksen thornless berry, nectarberry, Oregon evergreen berry, partridgeberry, phenomenalberry, rangeberry, raspberry (black and red), ravenberry, riberry, rossberry, schisandra berry, serviceberry, Shawnee blackberry, strawberry)

bok choy; broccoli; brussels sprouts; cabbage (including Napa); calabaza; calamondin; cardoon; carrot; casaba; cauliflower; celeriac; celery (including: Chinese); celtuce; chayote (fruit); che; cherry (including: sweet and tart, chokecherry, pincherry); chervil; cheyenne; Chilean guava; Chinese greens; Chinese okra; Chinese waxgourd (Chinese preserving melon); chinquapin; chironja; chrysanthemum; cilantro; citrus citron; citrus hybrids; collard; corn salad; corn; cotton; cress (including: upland, yellow rocket, winter cress); cucumber (including: Chinese cucumber); cucuzza; currant, (including: black, red, native and other varieties and hybrids);

dandelion; dill; dock (sorrel); eggplant; endive (escarole); fennel, Florence (finochio); forest seedlings; garland; garlic; gherkin; ginger; gourd; grape; grapefruit; hechima; herbs (all); honey balls; honeysuckle; hyotan; kale; kiwifruit (including: fuzzy and hard); kohlrabi; kumquat; leek; lemon; lettuce (including: head and leaf); lime; loquat; mandarin (incluing: tangerine and satsuma); mango; mayhaw; maypop;

melon (including: bitter melon, cantaloupe, hybrids and/or cultivars, citron melon, Crenshaw melon, golden pershaw melon, mango melon, honeydew melon, muskmelon, Persian melon, pineapple melon, Santa Claus melon, snake melon, watermelon);

mint; muntries; mustard; nectarine; nursery stock (fruit seedlings and rose bushes only); nursery tree crops (including crops like maple, ash, dogwood);

nut (including: almond, beech nut, cashew, chestnut, hickory nut, Brazil nut, macadamia nut (bush nut), filbert (hazelnut), pecan, pistachio, walnut (black and English/Persian); onion; orach; orange (including: sour an sweet); ornamentals; parsley; peas (including: English and garden); peach; peanut; pear (including: oriental and balsam); pepper; phalsa; plum (including: Chickasaw and Damson); plumcot; potato; prune (fresh); pummelo; pumpkin; purslane (including: garden and winter); quince;

radicchio (red chicory); radish (including Oriental); rappini; rhubarb; rye; salal; sea buckthorn; soybean; spinach (including: New Zealand, Malabar, Indian); squash, (including: summer, winter, butternut, straightneck, Acorn, crookneck, hubbard, scallop, spaghetti); sugar beet; sweet potato; swiss chard; tangelo; tangor; tobacco; tomatoes; tree nuts (orchard replant only); turf (including golf courses); turnip; vegetable marrow; wheat; yams; zucchini.

Use only according to label. Do not apply this product through any irrigation system unless the labeling on chemigation is followed.

USE METHOD RESTRICTIONS

The use of this product is restricted to the methods described in this label. Use in greenhouses or any other enclosed structure or confined area is prohibited. Application with handheld equipment is prohibited. Application with cement grinder and shredder equipment is prohibited. Open-pour applications are prohibited. Do not apply this product through traveler or big gun application systems.

CERTIFIED APPLICATOR TRAINING

Any certified applicator supervising a soil fumigant application must have successfully completed one of the soil fumigant training programs listed on the following EPA website http://www.epa.gov/fumiganttraining for the active ingredient(s) in this product. The training must be completed in the time frames listed on the website. The FMP must document the date and location where the soil fumigant training program was completed.

HANDLERS

The following activities are prohibited from being performed by anyone other than persons who have been appropriately trained and equipped as handlers in accordance with the requirements in WPS (40 CFR Part 170):

- Monitoring fumigant air concentrations;
- Cleaning up fumigant spills (this does not include emergency personnel not associated with the fumigation application);
- · Handling or disposing of fumigant containers;
- Cleaning, handling, adjusting, or repairing the parts of fumigation equipment that may contain fumigant residues; and
- Performing any handling tasks as defined by the WPS (40 CFR 170). The following activities are prohibited from being performed in the application block from the start of the application until the entry-restricted period ends and in the buffer zone during the buffer zone period by anyone other than persons who have been appropriately trained and equipped as handlers in accordance with the requirements in the WPS (40 CFR Part 170), (NOTE: persons repairing, and monitoring tarps are considered handlers for the duration listed below). Prohibited activities (except for trained and equipped handlers) include:
- Participating in the application as supervisors, loaders, drivers, tractor co-pilots, shovelers, cross ditchers, or as other direct application participants;
- · Installing, repairing, operating or removing irrigation equipment;
- · Performing scouting, crop advising, or monitoring tasks;
- Installing, perforating (cutting, punching, slicing, poking), or removing tarps; and
 - Repairing or monitoring tarps until 14 days after application is complete if tarps are not perforated and removed during those 14 days. NOTE: see Tarp Perforation and/or Removal section on this labeling for requirements about when tarps are allowed to be perforated.

Handlers do not include local, state, or federal officials performing inspection, sampling, or other similar official duties.

PROTECTION FOR HANDLERS

Supervision of Handlers

For all applications except water run: from the start of the application until the application is complete, a certified applicator must be at the application block in the line of sight of the application and must directly supervise all persons performing handling activities.

For water-run applications (e.g., sprinkler/chemigation, wheel line, center pivot, lateral move, drip, flood, etc.), a certified applicator must be in the line of sight of the application at the start of the application including setup, calibration, and initiation of the application. A certified applicator may leave but must return at least every two hours to visually inspect the equipment to ensure proper functioning and must directly supervise all Worker Protection Standard trained handlers until the application is complete. Worker Protection Standard-trained handlers may perform the monitoring functions in place of a certified applicator but they must be under the supervision of a certified applicator and be able to communicate with a certified applicator at all times during monitoring activities via cell phone or other means.

For handling activities that take place after the application is complete until the entry restricted period expires, the certified applicator is not required to be on-site, but must have communicated in a manner that can be understood by the site owner and handlers responsible for carrying out those activities the information necessary to comply with the label and procedures described in the FMP (e.g., emergency response plans and procedures)

IMPORTANT: This requirement does not override the requirements in the Worker Protection Standard for Agricultural Pesticides for information exchange between operators of agricultural establishments and commercial pesticide applicators.

The certified applicator must provide Fumigant Safe Handling Information to each handler or confirm that within the past 12 months, each handler has received Fumigant Safe Handling Information in a manner he/she can



understand. Fumigant Safe Handling Information will be provided where this product is purchased or at www.epa.gov/fumiganttraining.

Exclusion of Non-Handlers from the Application Block and Buffer Zone

The certified applicator supervising the application and the owner of the establishment where the application is taking place must make sure that all persons who are not trained and PPE-equipped and who are not performing one of the handling tasks as stated in this labeling are:

- excluded from application block during the entry restricted period, and
- excluded from the buffer zone during the buffer zone period (see buffer zone exemption for transit on roadways in Buffer Zone Requirements section).

Local, state, or federal officials performing inspection, sampling, or other similar official duties are not excluded from the application block or the buffer zone by this labeling. The certified applicator supervising the application and the owner of the establishment where the application is taking place are not authorized to, or responsible for, excluding those officials from the application block or the buffer zone.

Providing, Cleaning, and Maintaining PPE

The employer of any handler (as stated in this label) must make sure that all handlers are provided and correctly wear the required PPE. The PPE must be cleaned and maintained as required by the Worker Protection Standard for Agricultural Pesticides.

Air-purifying Respirator Availability

The employer of any handler must confirm that an air-purifying respirator and appropriate cartridges of the type specified in the PPE section of this labeling are immediately available for each handler who will wear one. At least one handler must have the appropriate air-purifying respirator and cartridges available (see *Respirator Fit Testing, Medical Qualification, and Training* section for additional requirements).

Exception: Air-purifying respirators do not need to be made available for handlers performing fumigant site monitoring tasks outside of the buffer zone.

Respirator Fit Testing, Medical Qualification, and Training

Using a program that conforms to OSHA's requirements (see 29 CFR Part 1910.134), employers must verify that any handler that uses a respirator is:

- · Fit-tested and fit-checked,
- · Trained, and
- Examined by a qualified medical practitioner to ensure physical ability to safely wear the style of respirator to be worn. A qualified medical practitioner is a physician or other licensed health care professional who will evaluate the ability of a worker to wear a respirator. The initial evaluation consists of a questionnaire that asks about medical conditions (such as a heart condition) that would be problematic for respirator use. If concerns are identified, then additional evaluations, such as a physical exam, might be necessary. The initial evaluation must be done before respirator use begins. Handlers must be reexamined by a qualified medical practitioner if their health status or respirator style or use-conditions change.

Upon request by local/state/federal/tribal enforcement personnel, employers must provide documentation how they have complied with these requirements.

Respiratory Protection and Stop Work Triggers

The following procedures must be followed to determine whether an airpurifying respirator is required or if operations must cease for any person performing a handling task (except for fumigant site monitoring outside of the buffer zone) as stated in this label.

- If at any time any handler experiences sensory irritation (tearing, burning of the eyes or nose) then either:
 - An air-purifying respirator must be worn by all handlers who remain in the application block or surrounding buffer zone, or
 - Operations must cease and handlers not wearing an air-purifying respirator must leave the application block and surrounding buffer zone.

- Handlers can remove air-purifying respirators or resume operations if two consecutive breathing-zone samples taken at the handling site at least 15 minutes apart show that levels of MITC have decreased to less than 600 ppb (0.6 ppm), provided that handlers do not experience sensory irritation.
- During the collection of air samples, an air-purifying respirator must be worn by the handler taking the air samples. Samples must be taken at the location where the irritation was first experienced. When using monitoring devices to monitor air concentration levels, a direct read detection device, such as an electronic device or a colorimetric device (e.g. Draeger, Sensidyne) must be used. The devices must have sensitivity of at least 600 ppb (0.6 ppm) for MITC. Persons using direct read detection devices must follow the manufacturer's directions.
- When breathing zone samples are required, they must be taken outside respiratory protection equipment and within a ten inch radius of the handler's nose and mouth.
- When air-purifying respirators are worn, air monitoring samples must be collected at least every 2 hours in the breathing zone of a handler performing a representative handling task.
- If at any time: (1) a handler experiences any sensory irritation when wearing an air-purifying respirator, or (2) a MITC air sample is greater than or equal to 6,000 ppb (6 ppm), then all handler activities must cease and handlers must be removed from the application block and surrounding buffer zone.
- Handlers can resume work activities without air-purifying respirators if
 two consecutive breathing-zone samples taken at the handling site at
 least 15 minutes apart show levels of MITC have decreased to less than
 600 ppb (0.6 ppm), provided that handlers do not experience sensory
 irritation. During the collection of air samples an air-purifying respirator
 must be worn by the handler taking the air samples. Samples must be
 taken at the location where the irritation was first experienced or where
 sample(s) were greater than or equal to 6000 ppb (6 ppm).
- Handlers can resume work activities if all the following conditions exist provided that the appropriate air-purifying respirator is worn:
 - Two consecutive breathing zone samples for MITC taken at the handling site at least 15 minutes apart must be less than 6,000 ppb (6 ppm),
 - Handlers do not experience sensory irritation while wearing the air-purifying respirator, and
 - Filter cartridges/canisters have been changed.
 - During the collection of air samples an air-purifying respirator must be worn by the handler taking the air samples. Samples must be taken at the location where the irritation was first experienced or where sample(s) were greater than or equal to 6000 ppb (6 ppm).

TARP PERFORATION AND/OR REMOVAL

IMPORTANT: Persons perforating, repairing, removing, and/or monitoring tarps are defined, within certain time limitations, as handlers (see *Handlers* section), and they must be provided the PPE and other protections for handlers as required on this labeling and in the Worker Protection Standard for Agricultural Pesticides.

- Tarps must not be perforated until a minimum of 5 days (120 hours) have elapsed after the application is complete, unless a weather condition exists which necessitates the need for early perforation or removal (see Early Tarp Removal for Broadcast Applications Only and Early Tarp Perforation during Flood Prevention Activities for Bedded Applications Only requirements).
- If tarps are perforated within 14 days after the application is complete, tarp removal must not begin until at least 2 hours after tarp perforation is complete.
- If tarps are perforated but not removed within 14 days after the application is complete, planting or transplanting must not begin until at least 48 hours after the tarp perforation is complete.
- If tarps are not perforated or removed within 14 days after the application is complete, planting or transplanting may take place while the tarps are being perforated.
- Each tarp panel used for broadcast fumigation must be perforated.
- Tarps may be perforated manually ONLY for the following situations:
 - At the beginning of each row when a coulter blade (or other device which performs similarly) is used on a motorized vehicle such as an ATV.
 - In fields that are 1 acre or less.
 - During flood prevention activities.



- In all other instances tarps must be perforated (cut, punched, poked, or sliced) only by mechanical methods.
- Tarp perforation for broadcast fumigations must be completed before noon.
- For broadcast fumigations, tarps must not be perforated if rainfall is expected within 12 hours.
- Early Tarp Removal for Broadcast Applications Only:
 - Tarps may be removed before the required 5 days (120 hours) if adverse weather conditions have compromised the integrity of the tarp, provided that the compromised tarp poses a safety hazard. Adverse weather includes high wind, hail, or storms that blow tarps off the field and create a hazard, e.g., tarps blowing into power lines and onto roads. A compromised tarp is a tarp that due to an adverse weather condition is no longer performing its intended function and is creating a hazard.
- Early Tarp Perforation during Flood Prevention Activities for Bedded Applications Only:
 - Tarp perforation is allowed before the 5 days (120 hours) have elapsed.
 - Tarps must be immediately retucked and packed after soil removal.

ENTRY RESTRICTED PERIOD AND NOTIFICATION

Entry Restricted Period

Entry into the application block (including early entry that would otherwise be permitted under the Worker Protection Standard) by any person – other than a correctly trained and PPE-equipped handler who is performing a handling task listed on this labeling – is PROHIBITED from the start of the application until:

- 5 days (120 hours) after the application is complete for untarped applications, or
- 5 days (120 hours) after application is complete if tarps are not perforated and removed for at least 14 days after the application is complete, or
- 48 hours after tarps perforation is complete if tarps will be perforated within 14 days after the application is complete and will not be removed for at least 14 days after the application is complete, or
- Tarp removal is completed if tarps are both perforated and removed less than 14 days after the application is complete.

NOTES

- See Tarp Perforation and/or Removal section on this labeling for requirements about when tarps are allowed to be perforated.
- If early tarp removal occurs for a broadcast application the entry restricted period is a minimum of 5 days after the application is complete.
- When listing application information for soil fumigant applications to comply with Part 170.122 of the WPS, list the entry restricted period time frame in place of the REI.

Notification

Notify workers of the application by warning them orally and by posting Fumigant Treated Area signs.

The signs must bear the skull and crossbones symbol and state:

- · "DANGER/PELIGRO,"
- "Area under fumigation, DO NOT ENTER/NO ENTRE,"
- Metam Sodium fumigation in Use."
- . The date and time of fumigation,
- · The date and time the entry restricted period is over,
- · "Sectagon 42", and
- Name, address, and telephone number of the certified applicator in charge of the fumigation.

Post Furnigant Treated Area sign instead of the Worker Protection Standard sign for this application but follow all Worker Protection Standard requirements pertaining to location, legibility, text size, and sign size (40 CFR § 170.120).

Post the Fumigant Treated Area signs at all entrances to the application block no sooner than 24 hours prior to application.

Fumigant Treated Area signs must remain posted for no less than the duration of the entry restricted period.

Fumigant Treated Area signs must be removed within 3 days after the end of the entry restricted period.

MANDATORY GOOD AGRICULTURAL PRACTICES (GAPs)

The following GAPs must be followed during all fumigant applications.

Shank Applications Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see Identifying Unfavorable Weather Conditions section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

• Unfavorable weather conditions block upward movement of air, which results in trapping fumigant vapors near the ground. The resulting air mass can move off-site in unpredictable directions. These conditions typically exist within an hour prior to sunset and continue past sunrise and may persist as late as noontime. Unfavorable conditions are common on nights with limited cloud cover and light to no wind and their presence can be indicated by ground fog or smog and can also be identified by smoke from a ground source that flattens out below a ceiling layer and moves laterally in a concentrated cloud.

Soil Conditions, Injection Depth, and Soil Sealing

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

The injection point for bedded and broadcast shank injection applications shall be a minimum of 3 inches from the final soil/air interface. Chisel traces must be eliminated following an application and the soil surface must be sealed immediately after application using one or more of the following methods:


- Compaction with a bed-shaper, roller, press wheel, coil packer, ring packer, or similar device, OR
- Covering the treated soil with 3-6 inches of untreated soil, OR
- Applying a minimum of a ½-inch of water beginning immediately after application begins and completing the water treatment within four hours, OR
- · Covering treated area with a tarp.

Tarps (when tarps are used in Sectagon 42 applications)

- · A written tarp plan must be developed and included in the FMP
- Once a tarp is perforated, the application is no longer considered tarped.
- Tarps must be installed immediately after the fumigant is applied to the soil.

Soil Temperature

- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in



Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For **coarse** textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon. For **moderately coarse** textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water

capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For fine textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

 If there is insufficient moisture throughout the top six inches of soil immediately prior to the application, the soil moisture must be adjusted.
 If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage before or during injection. To conserve existing soil moisture, tillage should be done as close to the time of application as possible.

Application and Equipment Considerations

- Do not apply or allow fumigant spill onto the soil surface. Injectors must be placed below the soil surface before product flow begins. Each injection line must either have a check valve located as close as possible to the final injection point, or drain/purge the line of any remaining fumigant prior to lifting injection shanks from the ground. Do not lift injection shanks from the soil until the shut-off valve has been closed and the fumigant has been depressurized (passively drained) or purged (actively forced out via air compressor) from the system.
- Application equipment must be in good working order.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Dry disconnect couplings (closed transfer system) must be installed on tanks and transfer hoses.
- · Sight gauges and pressure gauges must be properly functioning.
- Nozzles and metering devices must be the correct size and sealed and unobstructed.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- Each nozzle must be equipped with a flow monitor, e.g. mechanical, electronic, or Red-ball type monitor.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- All rigs must include a filter to remove any particulates from the fumigant, and a check valve that is visible to the tractor driver during

- application to prevent backflow of the fumigant into the pressurizing cylinder.
- All rigs must include a flow meter or a flow monitoring device.
- All rigs must have a constant pressure system with orifice plates to ensure the proper amount of fumigant is applied.
- Valves (e.g., backflow, shut-off), vacuum relief valves, and low pressure drains must be in place, operational, and leak free.
- Use only positive displacement pumps. Do NOT use impellors made of brass, aluminum, or galvanized material.
- Before using a furnigation rig for the first time, or when preparing it for use after storage, the operator must check the following items carefully:
 - Check the filter, and clean or replace the filter element as
 - Check all tubes and chisels/shanks to make sure they are free of debris and obstructions.
 - Check and clean the orifice plates.

Spray Blade Applications (includes bed-top blade and soil cap applications)

Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

• Unfavorable weather conditions block upward movement of air, which results in trapping fumigant vapors near the ground. The resulting air mass can move off-site in unpredictable directions. These conditions typically exist prior to sunset and continue past sunrise and persist as late as noontime. Unfavorable conditions are common on nights with limited cloud cover and light to no wind and their presence can be indicated by ground fog or smog and can also be identified by smoke from a ground source that flattens out below a ceiling layer and moves laterally in a concentrated cloud.

Soil Conditions, Injection Depth, and Soil Sealing

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Apply the product mixture on the soil immediately ahead of the bedshaping equipment or tiller. The soil surface must be compacted immediately after application using one or more of the following methods:

- Compaction with a bed-shaper, roller, press wheel, coil packer, ring packer, or similar device, OR
- Covering the treated soil with 3-6 inches of untreated soil, OR
- Applying a minimum of a ¼-inch of water beginning immediately after application begins and completing the water treatment within four hours, OR
- · Covering treated area with a tarp.



Tarps (when tarps are used in Sectagon 42 applications)

- · A written tarp plan must be developed and included in the FMP
- Once a tarp is perforated, the application is no longer considered tarped.

Soil Temperature

- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For **coarse** textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon.

For moderately coarse textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For **fine** textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

 If there is insufficient moisture throughout the top six inches of soil immediately prior to the application, the soil moisture must be adjusted.
 If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage before or during injection. To conserve existing soil moisture, tillage should be done as close to the time of application as possible.

Application and Equipment Considerations

- Do not apply or allow fumigant to drain or drip onto the soil surface.
- · Application equipment must be in good working order.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Dry disconnect couplings (closed transfer system) must be installed on all tanks and transfer hoses.
- Sight gauges and pressure gauges must be properly functioning.
- Nozzles and metering devices must be the correct size and sealed and unobstructed.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- Each nozzle must be equipped with a flow monitor, e.g. mechanical, electronic, or Red-ball type monitor.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.

- All rigs must include a filter to remove any particulates from the fumigant, and a check valve that is visible to the tractor pilot during application to prevent backflow of the fumigant into the pressurizing cylinder.
- Before using a fumigation rig for the first time, or when preparing it for use after storage, the operator must check the following items carefully:
 - Check the filter, and clean or replace the filter element as required.
 - Check all tubes and chisels to make sure they are free of debris and obstructions.
 - Check and clean the orifice plates.

Rotary Tiller Applications Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

• Unfavorable weather conditions block upward movement of air, which results in trapping fumigant vapors near the ground. The resulting air mass can move off-site in unpredictable directions. These conditions typically exist prior to sunset and continue past sunrise and persist as late as noontime. Unfavorable conditions are common on nights with limited cloud cover and light to no wind and their presence can be indicated by ground fog or smog and can also be identified by smoke from a ground source that flattens out below a ceiling layer and moves laterally in a concentrated cloud.

Soil Conditions, Injection Depth, and Soil Sealing

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Spray or drip the product mixture on the soil immediately ahead of the bed-shaping equipment or tiller. The soil surface must be compacted immediately after application using one or more of the following methods:

- Compaction with a bed-shaper, roller, press wheel, coil packer, ring packer, or similar device, OR
- · Covering the treated soil with 3-6 inches of untreated soil, OR
- Applying a minimum of a ¼-inch of water beginning immediately after application begins and completing the water treatment within four hours, OR
- Covering treated area with a tarp.

Tarps (when tarps are used in Sectagon 42 applications)

- · A written tarp plan must be developed and included in the FMP
- Once a tarp is perforated, the application is no longer considered tarped.

Soil Temperature



- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For coarse textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon. For moderately coarse textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For **fine** textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

If there is insufficient moisture throughout the top six inches of soil
immediately prior to the application, the soil moisture must be adjusted.
If there is adequate soil moisture below six inches, soil moisture can be
brought to the surface by tillage before or during injection. To conserve
existing soil moisture, tillage should be done as close to the time of
application as possible.

Application and Equipment Considerations

- . Do not apply or allow fumigant to drain or drip onto the soil surface.
- · Application equipment must be in good working order.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Dry disconnect couplings (closed transfer system) must be installed on all tanks and transfer hoses.
- Sight gauges and pressure gauges must be properly functioning.
- Nozzles and metering devices must be the correct size and sealed and unobstructed.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- Each nozzle must be equipped with a flow monitor, e.g. mechanical, electronic, or Red-ball type monitor.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- All rigs must include a filter to remove any particulates from the fumigant, and a check valve that is visible to the tractor driver during application to prevent backflow of the fumigant into the pressurizing cylinder.
- Before using a fumigation rig for the first time, or when preparing it for use after storage, the operator must check the following items carefully:

- Check the filter, and clean or replace the filter element as required.
- Check all tubes and chisels shanks to make sure they are free of debris and obstructions.
- Check and clean the orifice plates.

Center Pivot Applications Wind Speed

- For lateral move or center pivot applications: 1) not using a solid stream type nozzle, OR 2) having a release height or spray height greater than 4 feet, OR 3) having 30 lbs or greater PSI at the sprinkler head, wind speed at the application site must be a minimum of 2 mph at the start of the application or forecasted to reach 5 mph during the application and the maximum wind speed is 10 mph.
- For lateral move or center pivot applications using: 1) solid stream, AND
 2) having release height and spray height less than 4 feet, AND 3) having 29 lbs. or less PSI at the sprinkler head, wind speed at the application site must be a minimum of 2 mph at the start of the application or forecasted to reach 5 mph during the application and the maximum wind speed is 25 mph.

Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

Unfavorable weather conditions block upward movement of air, which
results in trapping fumigant vapors near the ground. The resulting air
mass can move off-site in unpredictable directions. These conditions
typically exist prior to sunset and continue past sunrise and persist as
late as noontime. Unfavorable conditions are common on nights with
limited cloud cover and light to no wind and their presence can be
indicated by ground fog or smog and can also be identified by smoke
from a ground source that flattens out below a ceiling layer and moves
laterally in a concentrated cloud.

Soil Conditions

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Except when applying over cover crops as set forth in the Product Instructions, crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Soil Temperature

- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F, measured at 3 inches in depth.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture



- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For coarse textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon. For moderately coarse textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For fine textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

 If there is insufficient moisture throughout the top six inches of soil immediately prior to the application, the soil moisture must be adjusted.
 If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage prior to the application. To conserve soil moisture, tillage should be done as close to the time of application as possible.

Flushing Irrigation Lines

• Do not allow fumigant to remain in the irrigation system after the application is complete. After application of the fumigant, flush the injection and irrigation system with untreated water. The flush time must be adequate to purge the fumigant from the injection and irrigation system, but should be less than the amount that could over-saturate the beds. If common lines are used for both the fumigant application and the water treatment/seal (if applied), these lines must be adequately flushed before starting the water treatment/seal.

Application and Equipment Considerations

- Anti-siphon and back-flow prevention devices must be installed and in working order.
- Tanks must be in good condition to ensure product does not spill or leak.
- Tanks must have sealable covers on access ports.
- · Tanks must have proper pesticide labels affixed to them.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- Use only positive displacement pumps. Do NOT use impellors made of brass, aluminum, or galvanized material.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- The system must contain a functional check valve, vacuum relief valve, inspection port, and low-pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow.

- The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid toward the injection pump.
- The pesticide injection pipeline must also contain a functional, normallyclosed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.
- The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops.
- The irrigation line or water pump must include a functional pressure switch that will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected.
- Systems must use a metering pump such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.
- Any alternatives to the required safety devices in this label must conform to the list of EPA-approved alternative devices.

Solid Set Sprinkler Applications Wind Speed

 Wind speed at the application site must be a minimum of 2 mph at the start of the application or forecasted to reach 5 mph during the application and the maximum wind speed is 10 mph.

Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

Unfavorable weather conditions block upward movement of air, which
results in trapping fumigant vapors near the ground. The resulting air
mass can move off-site in unpredictable directions. These conditions
typically exist prior to sunset and continue past sunrise and persist as
late as noontime. Unfavorable conditions are common on nights with
limited cloud cover and light to no wind and their presence can be
indicated by ground fog or smog and can also be identified by smoke
from a ground source that flattens out below a ceiling layer and moves
laterally in a concentrated cloud.

Soil Conditions

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Except when applying over cover crops as set forth in the Product Instructions, crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Soil Temperature



- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F, measured at 3 inches in depth.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For **coarse** textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon.

For moderately coarse textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For **fine** textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

 If there is insufficient moisture throughout the top six inches below the surface of soil immediately prior to the application, the soil moisture must be adjusted. If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage prior to the application. To conserve soil moisture, tillage should be done as close to the time of application as possible.

Flushing Irrigation Lines

• Do not allow fumigant to remain in the irrigation system after the application is complete. After application of the fumigant, flush the injection and irrigation system with untreated water. The flush time must be adequate to purge the fumigant from the injection and irrigation system, but should be less than the amount that could over-saturate the beds. If common lines are used for both the fumigant application and the water treatment/seal (if applied), these lines must be adequately flushed before starting the water treatment/seal.

Application and Equipment Considerations

- Anti-siphon and back-flow prevention devices must be installed and in working order.
- Tanks must be in good condition to ensure product does not spill or leak.
- · Tanks must have sealable covers on access ports.
- Tanks must have proper pesticide labels affixed to them.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- Use only positive displacement pumps. Do NOT use impellors made of brass, aluminum, or galvanized material.

- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- The system must contain a functional check valve, vacuum relief valve, inspection port, and low-pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow.
- The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid toward the injection pump.
- The pesticide injection pipeline must also contain a functional, normallyclosed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.
- The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops.
- The irrigation line or water pump must include a functional pressure switch that will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected.
- Systems must use a metering pump such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.
- Any alternatives to the required safety devices in this label must conform to the list of EPA-approved alternative devices.

Drench Applications Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

• Unfavorable weather conditions block upward movement of air, which results in trapping fumigant vapors near the ground. The resulting air mass can move off-site in unpredictable directions. These conditions typically exist prior to sunset and continue past sunrise and persist as late as noontime. Unfavorable conditions are common on nights with limited cloud cover and light to no wind and their presence can be indicated by ground fog or smog and can also be identified by smoke from a ground source that flattens out below a ceiling layer and moves laterally in a concentrated cloud.

Soil Conditions

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Soil Temperature

16/41

- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F, measured at 3 inches in depth.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For **coarse** textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon.

For moderately coarse textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For fine textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

- If there is insufficient moisture throughout the top six inches below the surface of soil immediately prior to the application, the soil moisture must be adjusted. If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage before the application. To conserve soil moisture, tillage should be done as close to the time of application as possible.
- Applications must be followed immediately with 0.20 to 0.50 inches of water through solid set sprinklers.
- A minimum of two or more water seals must be applied; one water seal on the first evening of the application and the second on the second evening of the day after application.

Application and Equipment Considerations

- Anti-siphon and back-flow prevention devices must be installed and in working order.
- Tanks must be in good condition to ensure product does not spill or leak.
- · Tanks must have sealable covers on access ports.
- · Tanks must have proper pesticide labels affixed to them.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Dry disconnect couplings (closed transfer system) must be installed on all tanks and transfer hoses.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- Each nozzle must be equipped with a flow monitor, e.g., mechanical electronic, or Red-ball type monitor.

- To inject fumigant, use a metering system, effectively designed and constructed of materials that are compatible with the fumigant and capable of being fitted with system interlocking controls.
- Nozzles and metering devices are of correct size and are sealed and unobstructed.
- The system must contain a functional check valve, vacuum relief valve, inspection port, and low-pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow.
- The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid toward the injection pump.
- The pesticide injection pipeline must also contain a functional, normallyclosed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.
- The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops.
- The irrigation line or water pump must include a functional pressure switch that will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected.
- Systems must use a metering pump such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.
- Any alternatives to the required safety devices in this label must conform to the list of EPA-approved alternative devices.

Drip ApplicationsWeather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

Unfavorable weather conditions block upward movement of air, which
results in trapping fumigant vapors near the ground. The resulting air
mass can move off-site in unpredictable directions. These conditions
typically exist prior to sunset and continue past sunrise and persist as
late as noontime. Unfavorable conditions are common on nights with
limited cloud cover and light to no wind and their presence can be
indicated by ground fog or smog and can also be identified by smoke
from a ground source that flattens out below a ceiling layer and moves
laterally in a concentrated cloud.

Soil Conditions

- Soil must be in good tilth, free of large clods, and tilled at a minimum to
 the depth of the treatment zone. Large clods can prevent effective soil
 sealing and reduce effectiveness of the application. If subsurface soil
 compaction layers (hardpans) are present within the intended
 fumigation treatment zone, a deep tillage to fracture these layers must
 occur prior to or during the soil fumigant application.
- Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the



fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Soil Temperature

- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F, measured at 3 inches in depth.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:

For **coarse** textured soils (fine sand and loamy fine sand) there must be enough moisture (50 - 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon.

For moderately coarse textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.

For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 - 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.

For fine textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 - 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.

For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.

 If there is insufficient moisture throughout the top six inches below the surface of soil immediately prior to the application, the soil moisture must be adjusted. If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage prior to the application. To conserve soil moisture, tillage should be done as close to the time of application as possible.

Tarps (when tarps are used in Sectagon 42 applications)

- A written tarp plan must be developed and included in the FMP
- Application to blocks with previously laid and perforated tarps is allowed, but once a tarp is perforated, the application is no longer considered tarped. Therefore, the application would not be eligible for tarp buffer zone credits.

Flushing Drip Irrigation Lines

• After application of the fumigant, continue to irrigate the area with water to flush the injection and irrigation system with untreated water. Do not allow fumigant to remain in the irrigation system after the application is complete. The total volume of water must be adequate to completely remove the fumigant from the irrigation system, but should be less than the amount that could over-saturate the beds. If common lines are used for both the fumigant application and the water treatment/seal (if applied), these lines must be adequately flushed before starting the water treatment/seal and/or normal irrigation practices.

Application and Equipment Considerations

 Anti-siphon and back-flow prevention devices must be installed and in working order.

- Tanks must be in good condition to ensure product does not spill or leak
- · Tanks must have sealable covers on access ports.
- · Tanks must have proper pesticide labels affixed to them.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- The drip irrigation system (main lines, headers, drip tape) must be thoroughly checked for leaks before the start of the application. An adequate run-time and pressure are needed to detect leaks. Look for puddling along major pipes (holes on pipes or leaky joints), at the top and ends of rows (leaky connections, open drip tape), in the furrows and on the bed surface (damaged drip tape, malfunctioning emitters).
- To inject furnigant, use a metering system, effectively designed and constructed of materials that are compatible with the furnigant and capable of being fitted with system interlocking controls.
- The system must contain a functional check valve, vacuum relief valve, inspection port, and low-pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow.
- The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid toward the injection pump.
- The pesticide injection pipeline must also contain a functional, normallyclosed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.
- The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops.
- The irrigation line or water pump must include a functional pressure switch that will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected.
- Systems must use a metering pump such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.
- Nozzles and metering devices are of correct size and are sealed and unobstructed.
- Any alternatives to the required safety devices in this label must conform to the list of EPA-approved alternative devices.

Flood Basin, Furrow and Border Applications Weather Conditions

- To determine if unfavorable weather conditions exist or are predicted (see *Identifying Unfavorable Weather Conditions* section) and whether an application should proceed, the National Weather Service weather forecast must be checked by the certified applicator supervising the application:
 - o on the day of, but prior to the start of the application, and
 - on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.
- Do not apply if an air-stagnation advisory issued by the National Weather Service is in effect for the area in which the application is planned, during the application, or the 48 hours after the application is complete.
- Do not apply if light wind conditions (< 2 mph) are forecast to persist for more than 18 consecutive hours from the time the application starts until 48 hours after the application is complete.
- Detailed National Weather Service forecasts for local weather conditions, wind speed, and air stagnation advisories may be obtained online at: http://www.nws.noaa.gov, on NOAA weather radio, or by contacting your local National Weather Service Forecasting Office.

Identifying Unfavorable Weather Conditions

O Unfavorable weather conditions block upward movement of air, which results in trapping fumigant vapors near the ground. The resulting air mass can move off-site in unpredictable directions. These conditions typically exist prior to sunset and continue past sunrise and persist as late as noontime. Unfavorable conditions are common on nights with limited cloud cover and light to no wind and their presence can be indicated by ground fog or smog and can also be identified by smoke

18/41

from a ground source that flattens out below a ceiling layer and moves laterally in a concentrated cloud.

Soil Conditions

- o Soil must be in good tilth, free of large clods, and tilled at a minimum to the depth of the treatment zone. Large clods can prevent effective soil sealing and reduce effectiveness of the application. If subsurface soil compaction layers (hardpans) are present within the intended fumigation treatment zone, a deep tillage to fracture these layers must occur prior to or during the soil fumigant application.
- o Plant residue that is present must not interfere with the application or the soil seal. Non-decomposed plant material may harbor pests that will not be controlled by fumigation. Crop residue that is present must lie flat to permit the soil to be sealed effectively and limit the natural "chimneys" that may occur in the soil when plant residue is present. These "chimneys" allow the soil fumigants to move through the soil quickly and escape into the atmosphere. This may create potentially harmful conditions for workers and bystanders and limits the efficacy of the fumigant. Plant residue on the field serves to prevent soil erosion from both wind and water.

Tarps (when tarps are used in Sectagon 42 applications)

- · A written tarp plan must be developed and included in the FMP
- Once a tarp is perforated, the application is no longer considered tarped.

Soil Temperature

- At the beginning of the application, the soil temperature at the injection depth must be between 35° and 90°F, measured at 3 inches in depth.
- If air temperatures have been above 100°F in any of the three days prior to application, then soil temperature must be measured and recorded in the FMP. Record temperature measurements at the application depth or 12 inches, whichever is shallower.

Soil Moisture

- The soil moisture in the top six inches of soil must be between 60% to 80% of available water capacity immediately prior to the application, subject to the exception below.
- EXCEPTION: In areas where soil moisture must exceed available water capacity to form a bed (e.g., certain regions in Florida), soil moisture content may exceed the 80%.
- If appropriate measuring equipment is not used to determine whether
 the soil moisture in the top six inches of soil is between 60% to 80%
 available water capacity immediately prior the application, the USDA
 Feel and Appearance Method test may be used to estimate whether the
 60% to 80% soil moisture content requirement is met:
 - For **coarse** textured soils (fine sand and loamy fine sand) there must be enough moisture (50 75% of available water capacity) to form a weak ball with loose and clustered sand grains on fingers, darkened color, moderate water staining on fingers, will not ribbon.
 - For **moderately coarse** textured soils (sandy loam and fine sandy loam) there must be enough moisture (50 75% of available water capacity) to form a ball with defined finger marks, very light soil/water staining on fingers, darkened color will not stick.
 - For **medium** textured soils (sandy clay loam, loam, and silt loam) there must be enough moisture (50 75% of available water capacity) to form a ball, very light staining on fingers, darkened color, pliable, and forms a weak ribbon between the thumb and forefinger.
 - For fine textured soils (clay, clay loam, and silty clay loam) there must be enough moisture (50 75% of available water capacity) to form a smooth ball with defined finger marks, light soil/water staining on fingers, ribbons between thumb and forefinger.
 - For fields with more than one soil texture, soil moisture content in the lightest textured (most sandy) areas must comply with this soil moisture requirement. The field may be divided into areas of similar soil texture and the soil moisture of each area should be adjusted as needed. Coarser textured soils can be fumigated under conditions of higher soil moisture than finer textured soils; however, if the soil moisture is too high, fumigant movement will be retarded and effectiveness of the treatment will be reduced. Previous and/or local experience with the soil to be treated or the crop to be planted can often serve as a guide to conditions that will be acceptable. If there is uncertainty in determining the soil moisture content of the area to be treated, a local extension service or soil conservationist or pest control advisor (agriculture consultant) should be consulted for assistance.
- If there is insufficient moisture throughout the top six inches below the surface of soil immediately prior to the application, the soil moisture must be adjusted. If there is adequate soil moisture below six inches, soil moisture can be brought to the surface by tillage prior to the

application. To conserve existing soil moisture, tillage should be done as close to the time of application as possible.

Application and Equipment Considerations

- o Systems using a gravity flow pesticide dispersing system must meter the pesticide into the water at the head of the field and downstream of a hydraulic discontinuity such as a drop structure or weir box to decrease potential for water source contamination from backflow if water flow stops.
- Meter at a steady rate into 3 to 18 inches of water per treated acre during irrigation. IMPORTANT: Prior to starting the application, always inspect ditches and border areas to ensure containment of the irrigation waters. Apply only into field head ditch. DO NOT APPLY INTO ANY LATERAL DITCHES.
- o Back-flow prevention devices must be installed and in working order.
- Tanks must be in good condition to ensure product does not spill or leak.
- Dry disconnect couplings (closed transfer system) must be installed on all tanks and transfer hoses.
- o Tanks must have sealable covers on access ports.
- o Tanks must have proper pesticide labels affixed to them.
- All tanks, hoses, fittings, valves and connections must be serviceable, tightened, sealed and not leaking.
- Use only tanks, hoses and fittings designed to withstand the pressure of the system and resistant to metam.
- For undiluted product, aluminum, brass, copper, galvanized iron, and zinc materials cannot be used.
- To inject fumigant, use a metering system, effectively designed and constructed of materials that are compatible with the fumigant and capable of being fitted with system interlocking controls.
- o Flow rates must be calibrated and checked for each application.
- All previous materials applied with the system must be cleaned thoroughly prior to fumigant application.
- o System must be flushed after application to totally remove all fumigant.

MAXIMUM APPLICATION RATES FOR PRE-PLANT SOIL USES

 Maximum application rate is 320 lbs metam sodium/A and 76 gallons Sectagon-42/A.

CALCULATING THE BROADCAST EQUIVALENT APPLICATION RATE


To calculate the broadcast equivalent rate for bedded or strip applications the following information is needed:

- gallons of product per treated acre
- · strip or bed bottom width (inches)
- center-to-center row spacing (inches)
- application block size (acres)

Gallons of product per treated acre is the ratio of total amount of product applied to the size of the total area treated (e.g., the rate of product applied in the bed). For bedded or strip applications, the total area treated is the summation of the area (i.e., length x width) of each treated bed bottom or strip that is located within the application block as shown by the black areas in Figure 1 (e.g., black areas are 0.6A or 60% of the area within the application block). The area of the space between the beds/strips is not factored in the total area treated.


The application block size is the acreage within the perimeter of the fumigated portion of a field (including furrows, irrigation ditches, roadways). The perimeter of the application block is the border that connects the outermost edges of total area treated with the fumigant product.

Figure 1. Bedded/Strip Application (1 acre application block)



The "broadcast equivalent rate" must be calculated with the following formula:


broadcast equivalent rate (gallons product/acre)



gallons product/ treated acre applied in the strip or bed

- The bed width must be measured from the bottom of bed.
- The center-to-center row spacing must calculate as shown in Figure 2.
- If there are any ditches, waterways, drive rows and other areas that are not fumigated that are in the application block, multiply the above broadcast equivalent equation by (total area of strips or beds + row spacing)/(application block size). A sample calculation is provided below

Figure 2. Center Row Spacing







Sample broadcast equivalent rate calculation

Assumptions:

- o Application method is shank bedded
- Bed width is 30 inches (measured at the bottom of bed)
- o Center-to-center row spacing is 60 inches
- 200 gallons of product per treated acre is applied in the beds
- o Total application block size is 10 acres
- Ditch in the middle of application block is 0.25 acres
- o Area of beds + row spacing is 9.75 acres



broadcast equivalent rate (gallons product/acre)



= 97.5 gallons product/acre

41

GENERAL BUFFER ZONE REQUIREMENTS

A buffer zone must be established for every fumigant application. The following describes the general buffer zone requirements:

- An area established around the perimeter of each application block.
 The buffer zone must extend outward from the edge of the application block perimeter equally in all directions.
- All non-handlers, including field workers, residents, pedestrians, and other bystanders, must be excluded from the buffer zone during the buffer zone period except for transit (see Buffer Zone Exemptions for Transit on Roadways).
- Local, state, or federal officials performing inspection, sampling, or
 other similar official duties are not excluded from the application
 block or the buffer zone by this labeling. The certified applicator
 supervising the application and the owner of the establishment
 where the application is taking place are not authorized to, or
 responsible for, excluding those officials from the application block or
 the buffer zone.
- The buffer zone period begins at the start of the application and lasts for a minimum of 48-hours after the application is complete.

Buffer Zone Proximity

- Before the start of application, the certified applicator must determine whether their buffer zone will overlap any metam sodium or metam potassium (or other MITC generating pesticides) buffer zone(s).
- To reduce the potential for off-site movement from multiple fumigated fields, buffer zones from multiple metam sodium or metam potassium (or other MITC generating pesticides) application blocks must not overlap UNLESS:
 - A minimum of 12 hours have elapsed from the time the earlier application(s) is complete until the start of the later application, and
 - Fumigant Site Monitoring or Response Information for Neighbors have been implemented if there are any residences or businesses within 300 feet of any of the buffer zones

In addition, only for Low Release Height-Solid Stream Center Pivot Applications:

- Before the application begins, the certified applicator must determine whether the application block or its resulting buffer will overlap with a buffer that is already in effect.
- To reduce the potential for off-site movement from multiple fumigated fields, buffer zones from multiple metam sodium or metam potassium application blocks may not overlap UNLESS:
 - Both application blocks are treated using low release heightsolid stream center pivot systems. The 12 hour waiting period does not apply in this instance.
 - NOTE: Under this exception, buffer zones may only overlap with those from application blocks that are not within the same field (i.e., application blocks must be in separate fields that are treated with a different center pivot rig also equipped with low release height etc.). For buffers from application blocks within the same field to overlap, 12 hours must elapse from the completion of the first application until the start of the subsequent application.
 - Emergency preparedness and response measures specified in the label have been implemented if there are any homes, businesses, or property not within the control of the fumigator within 300 feet of each buffer zone.

Structures Under The Control Of The Owner Of The Application Block

- Buffer zones must not include buildings used for storage (e.g., sheds, barns, garages), UNLESS:
 - The storage buildings are not occupied during the buffer zone period, and
 - The storage buildings do not share a common wall with an occupied structure.

Areas Not Under The Control Of The Owner Of The Application Block

- Buffer zones must not include residential areas (e.g., employee housing, private property), buildings (e.g., commercial, industrial), outdoor residential areas (e.g., lawns, gardens, play areas) and other areas that people may occupy, UNLESS:
 - The occupants provide written agreement, prior to the start of the application, that they will voluntarily vacate the buffer zone during the entire buffer zone period, and
 - Reentry by occupants and other non-handlers must not occur until.
 - o The buffer zone period has ended, and
 - Sensory irritation is not experienced upon re-entry.
- Buffer zones must not include agricultural areas owned and/or operated by persons other than the owner of the application block, UNLESS:
 - The owner of the application block can ensure that the buffer zone will not overlap with a metam sodium or metam potassium (or other MITC generating pesticides) buffer zone from any other property owners, except as provided in the Buffer Zone Proximity section, and
 - The owner of the other property provides written agreement to the applicator that they, their employees, and other persons will stay out of the buffer zone during the entire buffer zone period.
- Buffer zones must not include roadways and rights of way UNLESS:
 - 1. The area is not occupied during the buffer zone period, and
 - Entry by non-handlers is prohibited during the buffer zone period.

<u>Buffer Zone Exemptions for Transit on Roadways</u>
Vehicular and bicycle traffic on public and private roadways through the buffer zone is permitted. (NOTE: Buffer zones are not permitted to include bus stops or other locations where persons wait for public transit.)

- For all other publicly owned and/or operated areas such as parks, sidewalks, permanent walking paths, playgrounds, and athletic fields, buffer zones must not include these areas UNLESS:
 - 1. The area is not occupied during the buffer zone period,
 - Entry by non-handlers is prohibited during the buffer zone period, and
 - Written permission to include the public area in the buffer zone is granted by the appropriate state and/or local authorities responsible for management and operation of the area.

Certified applicators must comply with all local laws and regulations.

See the Posting section for additional requirements that may apply.

BUFFER ZONE DISTANCES

Buffer zone distances must be calculated using the application rate and the size of the application block.

- Buffer zone distances must be based on look-up tables in this labeling (25 feet is the minimum distance regardless of site-specific application parameters).
- If after applying all applicable buffer zone credits the buffer zone is greater than ½ mile (2,640 ft), then the application is prohibited.
- Tables 1-12 as appropriate for the method of application must be used to determine the minimum buffer distances. Round up to the nearest rate and block size, where applicable. Applications are prohibited for rates or block sizes that exceed what is presented in the buffer zone tables.

Table 1. Shank Injection Application - Broadcast Buffer Zone Distances in Feet

10						100	-		-	9	1		1	1					-		,	-	-	-	8	00	3	6	6	103	DI	1			1	7	7/	11	1:	16	34	1	1	1	2	NI.	36	20	21	22	22	23	234	200		
140	30	30	200	200	an an	30	- CO	100	33	9	0.0	40	0.0	-	C .	40	63	44	6.7	5.0	63	79	99	69	17	27	76	31	85	90	98	66	101	113	118	123	121	132	137	141	146	151	17.0	160	1603	174	170	183	191	195	198	202	202	21.0	444	
170	2	Q	9	2 1	35	2 2	25	26.	286	OS.	2.0	36	100	37	-	410	700	47	40	51	53	38	53	59	19	63	65	69	7.3	77	81	85	69	93	101	105	109	113	117	121	125	179	133	137	141	149	153	157	164	167	021	173	22	100	707	
100	2	2	3 3	C	3 %	75.	25	34	250	2	31	37	30	0	1	3.0	3.4	38	36	39	41	42	3	45	47	97	20	53	56	59	62	65	1 00	2,4	10	80	83	36	89	92	95	88	101	TUN	101	113	116	119	130	132	135	137	139	144	-	
30	2	9 1	Q	9 %	34	8	22	36	32	×	No.	36	100	-	-	3 5	33	35	2.6	38	39		42	3	45	47	46	SI	53	56	88	19	200	90	77	73	2	78	81	550	980	88	16	15	30	101	103	105	115	117	119	121	123	133	4467	
08	23 1	2 2	9 3	9 %	35	25	25	255	25	2	35	25	36	200	200	000	21	32	27	35	37	38	22	41	42	3	45	47	8	52	×	57	60	63	99	83	202	73	22	11	0.8	82	200	98	61	86	96	86	100	102	104	105	107	111		
R	2 :	67	3 7	3 %	32	25	25	25	25	23	30	25	36	200	200	2 70	36	29	30	31	33	×	35	36	38	39	40	42	45	47	49	52	5 3	2 02	61	63	53	3	202	72	2	111	Z	81	2 5	N.S.	010	93	36	97	86	100	102	101	400	
09	2	2	2 2	0 %	7.	3%	22	2%	20	25	36	35	26	20	100	36	36	25	36	27	28	30	31	32	33	×	35	37	40	42	44	47	40	53	95	200	9	63	65	67	N	77	M	No.	200	1 E M	98	88	06	65	93	9.5	96 00	200	707	
3	2	9	9 1	Q ×	35	25	22	25	2	2	34	35	36	36	200	36	36	35	36	28	27	28	29	30	31	32	33	X	35	36	37	38	30	41	42	43	44	45	46	47	48	20	15	24	2 2	1 5	28	57	58	59	909	19	69	6.0	8	
40	2 2	2 2	2 2	3 %	25.	25	25	25	25	23	250	35	36	36	35	36	36	25	36	33	25	25	36	27	28	29	30	31	32	33	R	35	37	3.0	388	39	40	41	42	43	44	45	466	/9	40	60	15	52	53	53	Z	55	98	24	200	
35	22 ::	2 10	3 2	2 %	25	25	25	25	25	25	20	35	36	36	36	36	36	25	25	22	25	25	25	36	22	28	Q	30	31	32	33	2	2 20	36	37	302	39	40	41	42	43	44	W ::	9 2	47	48	49	20	15	52	53	53	3 5	20	30	
30	2 :	2 12	2 3	3 12	12	75.	25	25	25	22	20	35	36	36	36	36	36	25	25	23	25	23	15	13	36	17	38	23	30	31	32	32	2.4	34	36	37	38	39	39	40	41	42	43	7 :	40 40	100	47	48	49	30	51	52	53	10	-	
A	2 1	9 1	7 1	2 %	X	2	22	25	2	R	8	×	36	36	36	×	×	2	25	23	×	10	22	22	22	29	27	28	R	30	30	31	32	34	38	18	36	37	328	33	40	41	4	7 5	40	4	99	999	47	48	49	S	15 25	23	300	
30	9 1	2 %	3 1	36	25	25	25	22	22	22	25	25	36	36	36	36	35	25	25	23	25	25	25	25	25	25	25	26	27	27	28	0 :	30	2 2	32	33	34	35	33	35	37	38	58 50	NA AN	9 59	19	42	43	2	45	45	46	47	40 An		
2	2 %	3 %	2 %	3 6	2	23	25	25	2	2	33	35	34	36	36	36	2	22	25	23	23	22	10	23	25	23	25	25	25	23	23	0 1	3 2	×	20	256	27	28	328	52	SZ	Q.	u u	15	22	189	2	34	35	3.6	36	37	38	28 00	-	
10	2 %	3 16	31.	35	25	25	25	25	25	25	25	25	36	36	36	36	2.5	25	. 25	23	25	25	25	25	23	25	23	25	25	25	23	22	3,5	35	22	22	25	25	25	25	22	72	36	100	37	28.	28	29	29	30	30	31	31	2		
2	07	3 %	36	34	25	75	25	25	25	23	25	35	35	35	36	36	25	33	25	23	23	23	25	25	25	25	25	25	25	25	25	57	25	35	22	25	25	25	23	25	25	25	22	200	2 %	35	36	36	22	22	28	38	29	30	-	
09	2 2	3 %	2 %	3 %	25	75	25	25	25	23	25	25	35	36	36	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	9 2	35	35	25	25	25	25	25	25	2	75	72	0 %	38	25	25	25	25	25	26	36	77	36		
1	27.50	35	36	3.6	25	25	25	25	25	25	25	25	25	36	36	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	2 2	3.6	25	25	25	25	25	25	25	25	25	25	200	35	25	25	25	25	25	25	25	25	36		
9	3 %	3 16	36	36	25	25	25	25	25	23	25	25	25	36	36	35	25	25	25	23	25	25	25	25	23	25	25	25	25	25	25	2 :	25.	25	25	22	25	25	22	25	25	25	22	27	34	22	25	25	25	25	25	25	25	38		
2	2 10	3 %	36	3,5	25	25	25	25	25	23	25	25	25	36	36	35	25	25	25	25	22	25	25	25	25	25	25	25	25	25	25	67	2,4	25	22	22	25	25	22	25	23	22	2 "	0 76	34	23	25	25	25	23	23	25	22	38	-	
4	200	2 16	1 16	25	25	25	25	25	25	25	23	25	25	36	36	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	22	25	25	25	25	25	25	25	25	52	25	25	000	20	25	25	25	25	25	23	25	25	35	-	
*	2 %	3 %	36	25	25	25	25	22	25	23	23	25	25	36	36	25	25	25	25	25	25	25	25	23	25	25	25	25	25	25	25	2 2	35	25	25	22	25	25	25	22	22	2	23	200	3 8	2	25	25	25	25	23	25	25	35	-	
2	2 2	35	×	25	22	25	25	22	25	23	2	25	25	35	36	25	25	23	25	25	25	22	25	25	25	25	23	25	25	25	25	9 2	7.	35	25	25	25	25	52	25	2	75	25	22	34	23	25	25	25	25	23	25	22	38		
7	2 %	35	36	35	22	25	25	25	25	25	23	25	25	26	26	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	75	67	35	25	25	25	25	25	25	25	27	13	75	000	3 %	23	25	25	25	25	25	25	20	38	-	
1	5 1	, 0	9	111	12	13	14	15	16	18	19	30	21	33	22	25	26	22	28	29	31	32	33	34	35	36	36	39	40	41	42	2 :	de	47	48	49	20	52	53	X	3	36	388	200	63	62	63	65	99	42	68	69	2 2	7.1	-	
W/189																																									1	1	1	1	1							-		-	-	

Table 2. Shank Injection Application - Broadcast with Water Seal Buffer Zone Distances in Feet

36	3 2	7	25	25	25	2 2	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	52	25	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	22	3 5	25	25	25	25	25	25	25	25	25	25 25	25	25	35
36	3 30	0	25	25	25	27 26	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	2 2	2 26	25	25	25	25	25	25	2 2	2 2	25	25	25	25	25	25	25	2 4	25	25	25	25	25	25	25	25	22	3 %	25 25	25	25	25
36	30	9	25	25	25	2 2	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	22	2 2	25	25	25	25	25	25	25	2 2	22 25	25	25	25	25	25	25	25	2 20	25	25	25	25	25	25	25	25	25	35	25 25	25	25	25
36	3 20	7	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	20 20	25	25	25	25	25	25	25	25	25	25	25 25	25	25	25
36	36	3	25	25	25	20 30	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	22	35	25	25	25	25	25	25	2 2	25 25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	35	25	25	25	25
35	36	9	25	25	2 2	25 25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	22	2 2	35	25	25	25	25	25	25	2 2	25 25	25	25	25	25	25	25	25	2 26	25	25	25	25	25	25	25	25	2 20	35	25	25	25	25
25	36	67	25	25	52	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	52	22 20	35	25	25	25	25	25	25	22 22	25	25	25	25	25	25	25	25	20 20	25	25	25	25	25	25	25	25	22	35	25	25	25	25
25	35	3	25	25	22 20	25	25	25	25	25	25	25	25	25	.25	25	25	25	25	25	25	25	22	0 10	35	25	25	25	25	25	25	2 2	2 12	25	25	25	25	25	25	25	35	25	25	25	25	25	25	25	25	25 25	35	25	25	25	25
25	30	2	25	25	52	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	2 2	2 2	35	25	25	25	25	25	25	52	25 25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	2 20	3 %	25	25	25	25
25	25	3 :	22	25	C) II	3 %	25	25	25	25	25	25	25	25	25	25	25	25	23	25	25	23	3 8	2 2	35	25	25	25	25	25	25	2 2	2 %	25	25	25	25	25	25	25	35	25	25	25	25	25	25	25	25	2 2	35	25	25	25	25
25	25	3	25	25	2 2	25	25	25	25	25	25	25	25	25	25.	25	25	25	25	25	25	52	2 2	0 20	35	25	25	25	25	25	25	2 2	25 25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	2 25	35	25	25	25	25
25	25	3 2	22	25	20 20	25	25	25	25	25	25	25	25	25	25	25	25	25	52	25	25	22	0 10	0 20	35.	25	25	25	25	25	25	0 20	2 20	25	25	25	25	25	25	25	35	25	25	25	25	25	25	25	25	35	35	25 25	25	25	25
25	25	3 2	52	22	2 2	25	25	25	25	25	25	25	25	25	25	25	25	25	2	25	25	2	0 2	20	25	25	25	. 25	25	25	25	0 10	25 25	25	25	25	25	25	25	25	25	25	25	25	25	25	. 25	25	25	35	35	25 25	25	25	25
25	25	3 3	25	25	3 2	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	2	0 10	20 20	35	25	25	25	25	25	25	20 20	25 25	25	25	25	25	25	25	25	3 2	25	25	25	25	25	25	25	25	25	35	25	25	25	25
25	25	3 4	52	52	20	25	25	25	25	25	25	25	25	25	25	25	25	25	52	25	25	2	62 20	20 20	25	25	25	25	25	25	25	25	25 25	25	25	25	25	25	25	25	35	25	25	25	25	25	25	25	25	25 25	35	25	25	25	25
25	25	3 6	2	2 2	20	25	25	25	25	25	25	25	25	25	25	25	25	25	2	25	23	2 2	67 20	25	25	25	25	25	25	25	25	0 20	25	25	25	25	25	25	25	25 25	35	25	25	25	25	25	25	25	25	25	25	25.52	25	25	25
25	25	3 0	52	52	20 30	25	25	25	25	25	25	25	25	25	25	25	25	25	52	25	25	23	0 2	20 30	25	25	25	25	25	25	25	20 20	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	36	35	25	25	25	25
25	25	3 2	2	22	25	25	25	25	25	25	25	25	25	25	25	25	25	25	57	25	25	2 2	2 20	25	25	25	25	25	25	25	25	20 20	35 52	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
25	25	3 6	2	2 2	20	25	25	25	25	25	25	25	25	25	25	25	25	25	2	25	52	2 2	52	25	25	25	25	25	25	25	25	25 25	25 25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
25	25	3 2	27	2 2	35	25	25	25	25	25	25	25	25	25	25	25	25	25	0	25	2 2	2 2	20 20	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	22 25	25	25	25	25	25	25	25	25	25	25	25	25 25	25	25	25
25	25	3 2	2 :	2 2	35	25	25	25	25	25	25	25	25	25	25	25	25	25	2	25	2 2	0 2	2 20	25	25	25	25	25	25	25	25	35	35 25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	35	25	25	25	25
25	25	3 20	0 2	200	35	25	25	25	25	25	25	25	25	25	25	25	25	52	0	52	2 2	0 10	200	35	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25	25
25	25	3 20	2 2	0 10	35	25	25	25	25	25	25	25	25	25	25	25	25	25	0	52	2 2	2 2	20	35	25	25	25	25	25	25	25	3 20	25	25	25	25	25	25	25	22 25	25	25	25	25	25	25	25	25	25	35	25	25	25	25	25
											16-11							1	1		1																															25			
											300																																									72			
	-	1		1	1	-	1	-	1	1	1	2	2	2	2	14	2	1				.3		100	1 00	63	8	4	4	4	4	1	4	4	4	w)	4)	41	"	.,		6	9	9	9	2	2	1	-	-	-	-	-		

{0118.002 / 111 / 00087047.DOC}

Table 3. Shank Injection Application - Bedded Buffer Zone Distances in Feet

25 38 40 50 60 170 180 130 1150 200 30 46 60 75 90 105 120 135 175 200 43 56 73 88 103 118 133 148 163 173 205 200 250 66 83 48 113 118 133 148 163 175 235 288 80 83 88 110 115 143 143 145 175 188 238 238 80 95 110 112 140 155 170 185 200 250 300 80 95 110 123 140 155 170 185 200 250 300 300 80 101 115 138 149 151 170 185 200 250 250 320 320	25 38 40 50 60 10 113 120 200 30 45 50 75 90 106 113 115 120 200 43 56 75 90 106 120 135 150 200 250 55 70 10 113 148 133 148 153 253 258 80 110 115 126 143 143 148 179 188 238 268 300 259 300	25 38 40 50 60 170 180 130 150 200 30 45 60 75 90 105 113 115 150 200 43 56 73 88 103 118 133 148 113 125 173 253 55 70 83 96 113 118 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 133 148 134 135 170 135 170 135 170 135 170 135 170 135 170 135 149 136 134 136 134 138 136 130 236 338 334 102	25 38 40 50 60 170 80 190 113 150 200 30 46 60 75 90 105 120 135 175 200 43 56 73 88 103 118 133 148 163 175 250 250 66 83 96 113 118 133 148 163 175 235 258 80 83 96 113 149 151 170 185 200 250 300 80 101 116 123 140 153 170 185 200 250 300 80 101 116 123 140 151 170 185 200 250 300 80 101 114 129 144 159 174 185 200 250 300 300 102 120 </th <th>25 39 40 50 60 80 90 115 150 200 26 38 49 106 126 126 115 200 200 30 45 60 75 90 106 129 115 115 200 250 68 83 46 113 128 143 143 160 152 110 205 200 250 80 86 110 115 143 143 146 160 175 188 238 288 80 100 113 140 155 170 155 170 250 300 260 80 101 112 143 143 143 140 150 170 150 200 250 300 260 300 300 300 300 300 300 300 300 300 300 300 300 <td< th=""><th>25 25 36 44 50 60 70 80 100 113 126 126 200 238 26 30 63 76 60 77 80 100 113 115 125 150 200 236 26 30 63 76 106 116 118 143 150 150 200 250 300 53 68 83 58 110 115 118 148 160 120 200</th></td<></th>	25 39 40 50 60 80 90 115 150 200 26 38 49 106 126 126 115 200 200 30 45 60 75 90 106 129 115 115 200 250 68 83 46 113 128 143 143 160 152 110 205 200 250 80 86 110 115 143 143 146 160 175 188 238 288 80 100 113 140 155 170 155 170 250 300 260 80 101 112 143 143 143 140 150 170 150 200 250 300 260 300 300 300 300 300 300 300 300 300 300 300 300 <td< th=""><th>25 25 36 44 50 60 70 80 100 113 126 126 200 238 26 30 63 76 60 77 80 100 113 115 125 150 200 236 26 30 63 76 106 116 118 143 150 150 200 250 300 53 68 83 58 110 115 118 148 160 120 200</th></td<>	25 25 36 44 50 60 70 80 100 113 126 126 200 238 26 30 63 76 60 77 80 100 113 115 125 150 200 236 26 30 63 76 106 116 118 143 150 150 200 250 300 53 68 83 58 110 115 118 148 160 120 200
30 45 60 75 30 115 120 135 136 136 250 250 55 70 85 100 115 118 145 160 175 225 275 66 83 96 113 118 145 160 175 225 275 86 101 115 110 125 140 115 170 252 276 275 86 101 116 123 140 115 176 131 206 250 313 106 123 116 123 144 119 176 131 206 253 313 107 120 124 115 176 135 126 123 326 325 326 108 120 125 124 119 126 120 225 300 326 326 326 108	30 45 60 75 39 115 120 135 136 136 250 250 55 70 85 100 115 130 145 160 175 225 275 80 83 10 115 130 145 160 175 226 275 80 80 101 115 140 155 170 185 200 250 376 80 101 116 123 140 155 170 186 203 250 260 250 80 101 116 123 149 159 174 189 204 206 262 300 286 333 105 114 129 143 159 174 189 204 212 205 252 300 361 106 124 125 140 155 174 189 204	30 45 60 75 90 118 135 145 150 150 250 250 250 55 70 85 100 115 116 115 116 123 146 155 173 186 173 225 275 86 103 111 125 140 151 170 185 236 286 86 104 115 140 151 170 185 220 252 275 93 106 123 140 151 170 185 200 252 286 93 106 123 139 153 174 189 204 219 273 235 326 336 105 114 129 144 159 174 189 204 219 273 326 336 1105 134 139 155 174 189 204	30 45 60 75 39 115 120 135 130 250 250 55 70 85 100 115 118 118 116 125 213 213 250 250 66 83 70 115 110 115 110 115 120 145 160 175 252 275 86 101 116 123 140 115 170 185 200 250 250 275 285 99 114 125 144 159 176 131 206 252 300 350 313 313 313 313 314 318 201 252 300 350 326 328 <td>30 45 60 75 39 118 133 146 155 150 250 250 55 70 85 100 115 118 146 155 170 223 275 66 83 96 113 149 145 160 175 226 275 80 95 113 149 145 146 152 170 252 275 86 101 116 123 140 153 170 189 273 206 250 376 95 114 125 140 153 170 189 204 213 205 253 300 361 105 120 123 144 159 174 189 204 212 205 203 325 300 361 105 124 155 170 186 201 217 222 300</td> <td>30 45 60 75 39 115 120 135 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 137 136 137 136 137 136 137 136 137 136 137 138 238 288 80 101 116 113 146 115 117 118 206 253 275 288 80 101 116 113 146 115 117 118 206 263 300 286 99 114 129 143 159 174 189 204 212 208 333 338 105 114 129 146 159 144 189 204 213 205 238 338 1105 134 159 140</td>	30 45 60 75 39 118 133 146 155 150 250 250 55 70 85 100 115 118 146 155 170 223 275 66 83 96 113 149 145 160 175 226 275 80 95 113 149 145 146 152 170 252 275 86 101 116 123 140 153 170 189 273 206 250 376 95 114 125 140 153 170 189 204 213 205 253 300 361 105 120 123 144 159 174 189 204 212 205 203 325 300 361 105 124 155 170 186 201 217 222 300	30 45 60 75 39 115 120 135 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 136 137 136 137 136 137 136 137 136 137 136 137 138 238 288 80 101 116 113 146 115 117 118 206 253 275 288 80 101 116 113 146 115 117 118 206 263 300 286 99 114 129 143 159 174 189 204 212 208 333 338 105 114 129 146 159 144 189 204 213 205 238 338 1105 134 159 140
55 70 86 100 115 130 145 160 175 225 275 325 66 81 98 110 113 128 138 138 208 236 328 338 86 101 116 113 146 153 170 191 206 256 300 326 338 452 93 104 115 140 153 148 159 200 256 303 325 450 105 114 115 140 153 148 159 204 213 275 325 450 106 120 114 159 149 159 201 221 203 325 450 108 120 120 121 120 121 222 300 326 400 111 131 148 149 151 131 213 223	55 70 86 100 115 130 145 160 175 225 275 325 88 98 198 113 128 143 158 173 188 238 238 338 86 95 110 125 140 155 170 150 205 300 300 98 104 125 140 151 176 151 206 263 303 308 130 148 123 144 153 164 153 174 206 273 303 475 105 124 135 164 153 174 201 225 303 303 475 105 124 135 169 186 201 223 303 323 475 105 124 136 137 223 234 328 438 438 112 136	55 70 85 100 115 130 145 160 175 225 275 325 66 95 19 113 128 143 158 173 188 238 238 338 86 101 115 125 140 152 170 181 206 263 303 338 93 108 121 144 153 174 189 213 275 263 338 475 108 108 123 144 159 174 189 213 275 326 358 475 108 120 120 123 144 159 174 189 219 219 275 309 358 475 108 128 143 143 143 143 143 143 143 144 150 144 150 201 223 309 301 475 <td>55 70 86 110 115 130 145 160 175 225 275 325 68 81 98 110 113 128 138 138 208 236 328 338 86 10 95 110 125 140 155 170 191 206 256 300 308 338 99 10 116 113 146 151 110 170 203 300</td> <td>55 70 86 100 115 130 145 160 175 225 275 325 68 81 100 113 128 143 156 173 188 238 238 338 86 95 110 113 128 140 151 170 180 206 263 308 338 99 114 125 140 153 140 151 170 180 206 263 338 452 99 114 123 144 153 144 153 140 220 206 263 338 450 100 124 153 144 153 144 153 144 153 144 215 140 223 233 325 450 102 124 153 144 153 144 154 154 223 223 303 403</td> <td>55 70 85 100 115 130 145 160 175 225 275 325 86 95 119 113 118 143 156 173 206 208 238 338 86 105 116 113 146 151 176 191 206 263 308 338 93 108 123 144 153 168 139 219 275 325 325 450 109 114 125 144 153 164 153 174 225 203 326 450 108 124 139 144 159 174 152 204 225 326 326 450 108 124 139 146 156 101 227 229 308 338 475 112 139 148 136 131 201 222 309</td>	55 70 86 110 115 130 145 160 175 225 275 325 68 81 98 110 113 128 138 138 208 236 328 338 86 10 95 110 125 140 155 170 191 206 256 300 308 338 99 10 116 113 146 151 110 170 203 300	55 70 86 100 115 130 145 160 175 225 275 325 68 81 100 113 128 143 156 173 188 238 238 338 86 95 110 113 128 140 151 170 180 206 263 308 338 99 114 125 140 153 140 151 170 180 206 263 338 452 99 114 123 144 153 144 153 140 220 206 263 338 450 100 124 153 144 153 144 153 144 153 144 215 140 223 233 325 450 102 124 153 144 153 144 154 154 223 223 303 403	55 70 85 100 115 130 145 160 175 225 275 325 86 95 119 113 118 143 156 173 206 208 238 338 86 105 116 113 146 151 176 191 206 263 308 338 93 108 123 144 153 168 139 219 275 325 325 450 109 114 125 144 153 164 153 174 225 203 326 450 108 124 139 144 159 174 152 204 225 326 326 450 108 124 139 146 156 101 227 229 308 338 475 112 139 148 136 131 201 222 309
66 83 96 113 128 143 158 173 188 238 238 338 86 106 95 110 125 140 155 170 187 200 209 300 338 338 86 101 116 123 146 153 176 181 206 263 300 350 350 99 114 123 144 159 174 189 219 219 288 338 475 108 124 159 174 186 201 222 309 361 400 108 124 159 176 186 201 223 309 351 400 112 144 159 176 186 201 223 309 361 400 112 143 159 176 186 201 223 329 348 450 <td>66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 140 153 169 191 206 263 300 350 93 108 114 123 144 153 174 189 271 275 328 338 475 106 120 120 155 166 186 201 229 309 350 475 108 124 159 177 186 201 221 229 309 351 475 112 128 156 186 201 221 229 309 351 475 112 143 156 177 131 207 223 329 328 438<td>66 83 96 113 128 143 156 173 188 238 238 338 80 95 110 125 140 155 170 185 200 250 300 336 98 101 116 131 146 161 176 181 206 263 313 456 99 114 129 156 186 189 204 219 273 326 450 105 120 135 156 165 186 201 221 275 326 475 110 123 143 159 174 189 204 219 277 239 316 475 110 123 143 150 165 186 201 223 309 361 475 110 135 143 150 191 207 223 329 336 445<td>66 83 96 113 128 143 156 173 188 238 238 338 86 106 15 140 155 170 187 186 20 20 30 338 86 101 116 123 146 151 176 181 20 253 33 455 99 114 123 144 159 174 189 201 225 30 352 450 108 124 159 176 186 201 222 309 351 400 108 124 159 176 186 201 221 222 309 361 400 112 134 159 175 191 207 223 309 361 425 112 144 159 176 191 207 223 309 361 400 112</td><td>66 83 96 113 128 143 156 173 186 238 238 338 86 101 115 140 155 140 157 191 200 203 300 336 93 101 116 123 146 161 170 181 206 263 303 336 475 93 108 123 144 153 174 189 201 275 326 326 450 106 124 136 144 159 174 189 201 275 326 326 475 108 124 136 144 156 180 137 279 309 351 475 108 124 136 149 127 271 272 309 371 475 112 139 156 180 191 207 223 239 342<td>66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 144 153 168 183 198 213 275 323 450 93 108 113 144 153 174 189 213 275 328 338 475 105 120 123 144 153 174 189 201 229 309 350 475 106 123 143 156 165 186 201 223 309 351 475 107 123 143 156 186 201 223 309 351 475 112 143 156 186 201 223 239 361 431</td></td></td></td>	66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 140 153 169 191 206 263 300 350 93 108 114 123 144 153 174 189 271 275 328 338 475 106 120 120 155 166 186 201 229 309 350 475 108 124 159 177 186 201 221 229 309 351 475 112 128 156 186 201 221 229 309 351 475 112 143 156 177 131 207 223 329 328 438 <td>66 83 96 113 128 143 156 173 188 238 238 338 80 95 110 125 140 155 170 185 200 250 300 336 98 101 116 131 146 161 176 181 206 263 313 456 99 114 129 156 186 189 204 219 273 326 450 105 120 135 156 165 186 201 221 275 326 475 110 123 143 159 174 189 204 219 277 239 316 475 110 123 143 150 165 186 201 223 309 361 475 110 135 143 150 191 207 223 329 336 445<td>66 83 96 113 128 143 156 173 188 238 238 338 86 106 15 140 155 170 187 186 20 20 30 338 86 101 116 123 146 151 176 181 20 253 33 455 99 114 123 144 159 174 189 201 225 30 352 450 108 124 159 176 186 201 222 309 351 400 108 124 159 176 186 201 221 222 309 361 400 112 134 159 175 191 207 223 309 361 425 112 144 159 176 191 207 223 309 361 400 112</td><td>66 83 96 113 128 143 156 173 186 238 238 338 86 101 115 140 155 140 157 191 200 203 300 336 93 101 116 123 146 161 170 181 206 263 303 336 475 93 108 123 144 153 174 189 201 275 326 326 450 106 124 136 144 159 174 189 201 275 326 326 475 108 124 136 144 156 180 137 279 309 351 475 108 124 136 149 127 271 272 309 371 475 112 139 156 180 191 207 223 239 342<td>66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 144 153 168 183 198 213 275 323 450 93 108 113 144 153 174 189 213 275 328 338 475 105 120 123 144 153 174 189 201 229 309 350 475 106 123 143 156 165 186 201 223 309 351 475 107 123 143 156 186 201 223 309 351 475 112 143 156 186 201 223 239 361 431</td></td></td>	66 83 96 113 128 143 156 173 188 238 238 338 80 95 110 125 140 155 170 185 200 250 300 336 98 101 116 131 146 161 176 181 206 263 313 456 99 114 129 156 186 189 204 219 273 326 450 105 120 135 156 165 186 201 221 275 326 475 110 123 143 159 174 189 204 219 277 239 316 475 110 123 143 150 165 186 201 223 309 361 475 110 135 143 150 191 207 223 329 336 445 <td>66 83 96 113 128 143 156 173 188 238 238 338 86 106 15 140 155 170 187 186 20 20 30 338 86 101 116 123 146 151 176 181 20 253 33 455 99 114 123 144 159 174 189 201 225 30 352 450 108 124 159 176 186 201 222 309 351 400 108 124 159 176 186 201 221 222 309 361 400 112 134 159 175 191 207 223 309 361 425 112 144 159 176 191 207 223 309 361 400 112</td> <td>66 83 96 113 128 143 156 173 186 238 238 338 86 101 115 140 155 140 157 191 200 203 300 336 93 101 116 123 146 161 170 181 206 263 303 336 475 93 108 123 144 153 174 189 201 275 326 326 450 106 124 136 144 159 174 189 201 275 326 326 475 108 124 136 144 156 180 137 279 309 351 475 108 124 136 149 127 271 272 309 371 475 112 139 156 180 191 207 223 239 342<td>66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 144 153 168 183 198 213 275 323 450 93 108 113 144 153 174 189 213 275 328 338 475 105 120 123 144 153 174 189 201 229 309 350 475 106 123 143 156 165 186 201 223 309 351 475 107 123 143 156 186 201 223 309 351 475 112 143 156 186 201 223 239 361 431</td></td>	66 83 96 113 128 143 156 173 188 238 238 338 86 106 15 140 155 170 187 186 20 20 30 338 86 101 116 123 146 151 176 181 20 253 33 455 99 114 123 144 159 174 189 201 225 30 352 450 108 124 159 176 186 201 222 309 351 400 108 124 159 176 186 201 221 222 309 361 400 112 134 159 175 191 207 223 309 361 425 112 144 159 176 191 207 223 309 361 400 112	66 83 96 113 128 143 156 173 186 238 238 338 86 101 115 140 155 140 157 191 200 203 300 336 93 101 116 123 146 161 170 181 206 263 303 336 475 93 108 123 144 153 174 189 201 275 326 326 450 106 124 136 144 159 174 189 201 275 326 326 475 108 124 136 144 156 180 137 279 309 351 475 108 124 136 149 127 271 272 309 371 475 112 139 156 180 191 207 223 239 342 <td>66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 144 153 168 183 198 213 275 323 450 93 108 113 144 153 174 189 213 275 328 338 475 105 120 123 144 153 174 189 201 229 309 350 475 106 123 143 156 165 186 201 223 309 351 475 107 123 143 156 186 201 223 309 351 475 112 143 156 186 201 223 239 361 431</td>	66 83 96 113 128 143 156 173 188 238 238 338 86 95 110 125 140 155 170 185 200 203 300 336 93 108 101 115 144 153 168 183 198 213 275 323 450 93 108 113 144 153 174 189 213 275 328 338 475 105 120 123 144 153 174 189 201 229 309 350 475 106 123 143 156 165 186 201 223 309 351 475 107 123 143 156 186 201 223 309 351 475 112 143 156 186 201 223 239 361 431
80 350 110 115 140 155 170 185 200 250 300 350 93 101 110 112 146 153 176 185 200 263 313 350 350 99 114 129 144 159 174 189 204 219 278 335 475 105 120 135 150 165 180 195 210 225 300 350 400 105 130 155 170 186 195 201 225 300 350 400 110 130 155 170 186 197 223 239 319 372 400 111 133 156 180 197 213 223 239 339 438 111 148 164 180 197 213 225 246 325 324	80 350 140 155 170 185 200 250 300 350 93 100 11 11 12 140 153 170 185 200 228 313 350 350 99 114 112 144 159 174 189 204 219 275 325 450 106 120 120 165 166 180 201 225 309 350 475 110 120 135 155 170 186 201 227 239 309 350 400 112 128 143 159 177 191 207 223 239 319 372 425 112 139 156 186 201 222 239 319 435 438 438 112 143 156 186 201 223 239 36 450 <td>80 350 140 155 170 185 200 250 300 350 93 100 111 112 140 153 170 185 200 263 313 350 350 350 350 350 350 350 350 350 350 350 350 350 450 350 450 350 450</td> <td>80 11 11 12 140 15.5 170 185 200 250 300 350 93 101 110 112 146 15.1 170 185 200 263 313 350 350 93 102 113 113 114 115 114 115 114 115 117 118 219 219 275 325 450 105 120 125 114 159 170 186 201 225 300 350 400 105 120 135 150 170 186 201 223 309 361 475 112 134 156 170 180 203 224 300 361 426 112 134 156 186 191 203 223 246 328 438 438 112 131 148 166 180<</td> <td>80 350 140 155 140 155 200 250 300 350 99 101 116 112 140 151 170 135 200 253 313 350 99 108 123 138 156 163 189 204 213 275 325 450 105 114 129 165 189 204 219 273 273 326 450 105 120 120 120 155 170 189 204 219 273 309 350 470 112 128 143 156 170 186 201 221 239 309 350 400 112 139 156 170 186 201 221 239 309 475 112 139 156 170 186 201 222 239 309 435 438</td> <td>80 150 140 155 170 185 200 250 300 350 93 106 111 111 112 140 153 170 185 200 228 313 350 350 99 114 112 118 153 168 183 194 215 217 275 325 350 475 105 114 1129 116 180 201 221 275 326 350 475 110 113 115 110 105 201 201 225 309 350 475 112 112 113 115 110 107 217 221 239 319 375 425 112 113 115 110 107 213 223 309 361 425 112 113 116 110 201 222 239 313 43</td>	80 350 140 155 170 185 200 250 300 350 93 100 111 112 140 153 170 185 200 263 313 350 350 350 350 350 350 350 350 350 350 350 350 350 450 350 450 350 450	80 11 11 12 140 15.5 170 185 200 250 300 350 93 101 110 112 146 15.1 170 185 200 263 313 350 350 93 102 113 113 114 115 114 115 114 115 117 118 219 219 275 325 450 105 120 125 114 159 170 186 201 225 300 350 400 105 120 135 150 170 186 201 223 309 361 475 112 134 156 170 180 203 224 300 361 426 112 134 156 186 191 203 223 246 328 438 438 112 131 148 166 180<	80 350 140 155 140 155 200 250 300 350 99 101 116 112 140 151 170 135 200 253 313 350 99 108 123 138 156 163 189 204 213 275 325 450 105 114 129 165 189 204 219 273 273 326 450 105 120 120 120 155 170 189 204 219 273 309 350 470 112 128 143 156 170 186 201 221 239 309 350 400 112 139 156 170 186 201 221 239 309 475 112 139 156 170 186 201 222 239 309 435 438	80 150 140 155 170 185 200 250 300 350 93 106 111 111 112 140 153 170 185 200 228 313 350 350 99 114 112 118 153 168 183 194 215 217 275 325 350 475 105 114 1129 116 180 201 221 275 326 350 475 110 113 115 110 105 201 201 225 309 350 475 112 112 113 115 110 107 217 221 239 319 375 425 112 113 115 110 107 213 223 309 361 425 112 113 116 110 201 222 239 313 43
93 108 123 138 159 139 159 204 219 279 445 450 105 114 112 144 159 114 1159 117 118 219 225 320 325 450 105 120 135 140 159 140 159 201 219 225 300 350 400 108 124 139 155 170 186 201 223 239 319 351 400 115 131 148 164 180 197 213 239 329 326 400 115 131 148 164 180 197 213 239 328 339 438 118 155 118 109 219 223 239 326 450 118 156 118 208 225 248 256 325	93 108 123 158 133 168 133 168 213 275 275 475 475 105 114 129 144 159 174 189 204 219 278 338 475 105 120 135 155 176 186 201 221 209 361 475 112 128 139 155 177 186 201 227 239 361 475 111 128 143 159 177 191 207 223 239 319 361 475 111 128 143 160 186 201 223 239 319 361 435 111 132 148 160 197 221 223 339 435 438 111 132 148 186 203 223 239 334 435 112	93 108 123 138 158 133 168 133 168 134 159 224 225 255 450	93 108 123 158 129 129 270 275 475 475 99 114 129 144 159 174 189 204 219 278 325 450 105 120 135 170 186 189 204 219 278 338 475 105 120 155 180 195 210 225 309 361 400 112 128 150 155 170 186 207 223 239 319 371 400 115 131 143 156 180 191 207 223 239 319 371 425 112 133 143 156 186 203 223 239 339 450 112 134 156 186 197 213 225 246 328 384 450 122 133<	93 108 123 158 133 158 133 158 134 159 273 275 325 450 106 123 134 129 134 159 174 189 204 219 278 338 475 106 120 135 150 165 186 201 227 239 309 360 400 112 128 159 177 186 201 227 239 309 361 475 111 128 143 159 177 191 207 223 239 394 425 111 128 143 156 110 207 223 239 394 435 112 139 156 118 209 223 239 394 435 121 131 136 131 208 223 239 366 437 468	93 106 123 138 158 138 158 139 158 219 250 250 450
99 114 129 144 159 174 189 204 219 288 338 475 105 130 135 150 165 180 195 20 225 300 350 400 108 124 139 155 170 186 207 223 239 319 351 400 115 131 143 156 170 191 207 223 239 319 372 425 111 133 156 186 197 213 236 246 328 339 436 111 135 156 186 203 223 239 326 450 450 121 135 156 136 136 232 239 324 450 450 122 138 236 249 252 343 260 452 452 128 146<	99 114 129 144 159 174 189 204 219 288 338 475 105 120 120 165 180 189 201 225 309 361 475 112 124 139 155 170 186 217 221 239 319 361 431 112 128 143 159 170 186 201 223 239 319 361 435 115 136 186 197 203 223 239 319 372 435 111 139 156 186 203 223 239 328 438 438 111 139 156 186 203 223 239 324 463 112 143 140 208 225 243 260 340 463 112 143 150 124 223	99 114 129 144 159 174 189 204 219 288 338 475 105 120 120 135 150 165 180 189 201 225 309 350 400 110 128 135 150 170 186 201 221 229 309 361 400 111 128 143 156 170 180 201 223 239 319 351 425 118 136 156 178 186 203 223 246 328 383 438 118 136 178 196 187 225 249 274 405 450 120 143 166 178 196 225 249 267 356 416 475 121 143 160 178 210 224 269 366 426 4	99 114 129 144 159 174 189 204 219 288 338 475 105 130 135 146 150 180 189 201 225 300 350 400 103 130 155 170 186 201 223 293 319 351 400 111 138 143 155 170 180 201 223 239 319 372 400 111 138 143 156 186 190 213 236 246 328 339 436 112 133 143 146 180 191 225 248 266 328 438 436 112 143 156 178 191 208 225 249 267 356 410 123 143 160 178 191 222 249 267 3	99 114 129 144 159 174 189 204 219 288 338 475 105 120 120 165 180 189 201 225 369 360 400 112 129 155 170 186 217 221 239 319 361 431 112 138 158 170 186 201 227 239 319 367 425 112 138 156 186 197 201 229 239 319 372 425 112 138 156 186 197 201 229 239 394 435 438 112 139 156 178 191 202 229 239 394 435 438 112 131 131 208 223 243 260 470 463 463 112 141	99 114 129 144 159 174 189 204 219 288 338 475 105 120 120 120 180 180 200 225 309 360 400 110 124 139 155 170 180 201 221 239 361 400 111 128 143 159 170 180 201 223 239 361 425 400 111 131 143 156 180 191 207 223 239 361 435 400 111 131 143 160 186 203 223 239 326 432 438 <
105 120 135 150 165 180 195 210 225 300 350 400 108 124 139 155 170 186 201 221 223 309 361 413 115 131 143 155 170 191 207 223 239 319 372 425 115 131 148 164 180 197 213 239 246 328 339 450 111 135 152 166 180 197 213 229 236 377 465 450 121 135 152 169 178 131 208 225 243 367 465 465 121 136 178 131 210 225 243 267 356 416 465 122 123 223 239 256 244 366	105 120 135 150 165 180 185 210 225 309 350 400 112 124 135 155 170 186 201 221 223 309 361 400 112 124 143 155 170 191 207 223 239 319 361 425 115 131 148 166 186 203 219 223 239 319 351 425 112 132 148 166 186 203 223 239 328 438 438 112 139 156 178 191 208 225 233 326 326 463 12 143 156 178 196 224 267 356 416 463 12 143 160 178 196 214 232 269 366 416 47	105 120 135 150 165 180 185 210 225 300 350 400 110 124 135 150 170 186 201 223 239 351 400 115 128 143 155 170 186 201 223 239 319 371 425 115 131 143 156 186 197 213 236 246 328 383 438 118 135 173 136 203 225 283 267 326 456 121 139 156 178 136 274 225 274 366 475 468 122 143 160 178 136 214 232 267 356 416 475 123 146 160 178 210 219 225 274 366 475 488	105 120 135 150 165 180 195 204 225 300 350 400 108 124 139 155 170 186 201 217 223 309 351 400 115 131 143 155 170 191 207 223 239 319 372 405 115 131 148 169 186 203 223 239 319 372 438 121 132 143 156 186 203 223 239 349 450 121 133 149 191 207 225 246 328 384 450 122 143 160 178 191 208 225 249 267 366 415 475 123 146 160 178 191 219 232 249 267 366 475	105 120 135 150 165 180 195 210 225 300 350 400 108 124 139 155 170 186 201 223 239 350 400 115 131 143 155 170 186 203 239 324 351 425 115 131 143 164 180 197 213 239 246 328 339 426 111 135 152 186 203 223 239 377 465 456 121 134 165 186 203 225 246 328 384 450 121 135 173 136 214 232 243 267 356 415 463 122 143 222 243 256 274 366 427 468 123 143 260 22	105 120 135 150 165 180 185 210 225 300 350 400 110 124 135 150 155 170 180 201 221 223 309 361 400 111 128 143 155 170 180 201 223 239 319 351 400 111 131 143 156 186 186 201 223 239 319 351 435 112 113 143 156 173 191 207 223 239 347 405 485 112 113 131 201 214 225 243 260 347 405 463 112 143 156 178 136 214 225 243 267 356 416 475 112 143 156 178 136 214
105 124 129 170 180 201 217 242 243 351 413 115 138 143 159 170 190 201 227 239 319 372 413 115 131 148 164 180 197 213 239 246 328 383 438 111 135 152 166 186 203 229 253 338 394 450 121 139 131 208 225 248 260 356 456 121 148 169 136 216 225 238 394 450 121 148 160 178 136 216 275 36 416 463 122 148 201 232 236 274 366 416 468 123 148 206 225 244 263 281	100 124 139 139 140 143 140 150 170 180 201 271 232 319 361 413 115 118 143 164 110 197 213 236 246 328 383 450 118 135 152 166 116 197 213 236 246 328 383 450 112 135 152 166 178 191 203 219 253 238 394 450 121 139 156 178 196 203 219 256 237 338 394 450 122 143 160 178 136 204 266 347 405 463 123 143 165 183 201 213 238 269 274 366 475 468 131 169 188 206	110 124 129 170 140 211 221 223 239 319 351 421 115 138 143 159 170 190 207 221 223 239 319 372 425 115 131 148 166 180 197 213 236 246 328 339 450 121 135 152 186 203 225 248 256 347 405 450 121 139 150 209 225 248 256 347 405 475 122 143 160 178 191 208 225 249 267 356 415 475 123 146 160 178 136 214 232 249 267 356 416 475 138 150 182 21 225 244 268 284 4	110 124 129 170 180 201 217 221 239 319 361 413 115 138 143 159 170 190 207 221 232 339 372 438 115 131 148 164 180 197 213 239 236 339 450 121 135 152 168 186 203 225 246 328 394 450 121 139 156 178 191 208 225 246 326 416 450 123 146 160 178 191 214 222 249 267 356 416 475 123 146 160 178 219 219 225 249 366 475 488 500 131 150 188 206 225 244 266 326 488	110 124 129 170 140 201 217 221 232 319 361 413 115 138 143 159 170 190 201 201 227 239 319 372 413 115 138 143 164 180 197 213 239 239 339 450 118 135 152 169 186 203 219 256 238 338 438 450 121 139 156 178 191 200 225 246 326 347 465 450 121 139 140 200 225 243 260 347 465 465 131 150 188 206 225 244 263 281 437 468 500 131 150 188 206 225 244 263 284 436	110 124 129 170 140 211 212 313 314 315 415 115 138 143 159 170 190 213 232 233 319 372 425 115 131 143 166 186 197 213 236 246 328 383 438 115 131 166 186 191 225 246 253 336 450 450 122 143 156 178 191 209 225 254 267 356 416 450 123 143 150 178 192 214 225 259 274 406 475 486 123 146 150 178 192 211 231 236 274 366 415 475 488 133 148 150 177 197 211 231
115 131 148 164 180 197 213 236 246 378 383 438 118 135 152 169 186 203 229 236 253 338 394 450 121 139 156 173 191 208 225 243 260 367 465 463 128 143 169 178 196 214 208 267 366 416 463 128 148 169 183 201 214 238 256 274 366 416 463 131 150 188 206 225 244 263 281 375 438 500	115 131 148 164 180 197 213 236 246 378 383 438 118 135 152 169 186 203 219 236 253 338 394 450 121 139 156 173 191 208 225 243 260 347 405 463 123 143 160 178 196 214 228 269 267 346 475 463 123 146 165 118 201 219 238 256 274 366 477 468 131 169 188 206 225 244 283 286 375 438 500 135 154 173 192 211 231 250 288 384 448 513	115 131 148 164 180 197 213 236 246 378 383 438 438 118 135 156 186 180 203 225 243 266 378 384 450 121 135 169 186 225 243 260 347 405 405 125 143 160 178 191 208 225 249 267 356 415 475 128 146 165 188 201 219 228 289 366 427 488 131 150 169 188 201 219 228 284 269 281 448 500 131 149 167 211 231 234 266 281 384 448 500 132 148 177 149 225 224 286 281 344	115 131 148 164 180 197 213 236 236 328 338 438 112 135 152 169 186 203 219 226 253 338 394 450 121 139 156 178 191 208 225 249 267 366 416 460 123 146 165 178 210 214 222 249 267 366 415 475 131 150 188 206 225 249 267 366 475 488 131 150 188 206 225 249 267 366 475 488 500 133 154 177 197 211 222 224 266 288 384 488 501 141 161 187 197 236 226 226 376 384	115 131 148 164 180 197 213 236 236 328 338 438 118 135 152 169 186 203 229 236 253 338 394 450 121 139 156 173 131 208 225 243 260 456 463 128 143 169 178 191 214 232 263 267 356 416 463 131 150 169 188 206 225 244 263 281 375 438 500 131 150 169 188 206 225 244 263 281 375 448 513 132 154 173 197 211 231 280 283 384 446 513 144 165 178 177 217 232 282 282	115 131 148 164 180 197 213 236 236 328 338 438 118 135 152 169 186 203 219 236 253 338 394 450 121 139 156 178 191 208 225 243 260 347 405 463 125 143 160 178 196 214 232 269 267 366 416 463 131 150 169 188 206 225 244 263 281 375 488 500 131 150 189 206 225 244 263 281 375 488 500 132 144 156 177 112 231 250 288 384 448 513 132 124 162 222 224 266 288 384
118 135 152 169 186 203 219 236 253 338 394 450 450 121 139 156 173 131 208 225 243 260 347 405 463 125 143 160 178 196 214 228 249 267 366 416 463 128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500	118 135 152 169 186 203 219 236 253 338 394 450 450 121 139 156 173 191 208 225 243 260 347 405 463 125 143 156 178 196 214 228 289 267 356 416 475 128 146 165 188 201 219 238 256 224 366 427 486 131 159 188 206 225 244 283 375 438 500 133 154 173 192 211 231 250 288 384 448 513	118 135 152 169 186 203 219 236 253 338 394 450 121 139 156 173 191 206 225 243 260 347 405 463 123 143 150 178 196 214 232 284 267 356 416 475 123 146 165 118 201 219 228 284 366 427 486 131 150 169 188 201 231 250 288 384 448 513 138 156 177 197 217 236 226 228 384 448 513	118 135 152 169 186 203 219 256 253 338 394 450 121 139 156 173 131 208 225 243 260 416 465 128 146 166 178 191 219 232 274 366 416 465 131 150 181 201 219 238 256 274 366 417 468 131 150 188 206 225 224 268 281 375 438 500 132 154 177 197 271 231 250 286 281 375 438 500 133 158 177 197 231 226 226 288 384 448 513 141 161 181 202 242 262 286 376 478 513	118 135 152 166 186 203 219 256 253 338 394 450 121 139 156 173 191 208 225 243 260 347 405 463 121 139 156 178 196 214 222 249 267 366 416 463 131 150 169 188 206 225 244 263 281 375 438 500 132 144 173 192 211 231 280 288 384 488 500 138 156 173 197 211 231 280 288 384 488 513 138 156 173 212 221 282 282 384 489 512 144 161 181 202 222 282 302 470 489 512	118 135 152 166 186 203 219 236 253 338 394 450 450 121 139 156 173 191 208 225 243 260 347 405 463 125 143 160 178 196 214 228 256 274 366 412 463 131 150 169 188 206 225 244 263 281 375 488 500 131 156 173 192 211 231 256 288 384 448 513 132 156 173 192 211 231 250 288 384 448 513 143 161 181 207 222 224 226 228 384 459 525 144 165 186 207 222 222 222 324
121 139 156 173 191 208 225 243 260 347 405 465 465 128 149 156 188 196 214 222 249 267 366 416 415 465 128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500	121 139 156 173 191 208 225 243 260 347 405 465 465 125 143 160 178 196 214 228 286 267 356 416 475 128 146 165 183 201 219 228 256 224 366 427 488 131 169 188 206 225 244 283 375 438 500 135 131 231 231 250 288 384 448 513	121 139 156 173 191 208 225 243 260 347 405 465 463 125 143 160 178 196 214 232 249 267 356 416 475 128 146 165 188 201 219 238 256 274 356 427 488 131 159 169 188 206 225 274 356 438 438 50 132 144 173 192 211 231 250 288 344 448 513 138 156 177 197 217 236 256 278 394 459 525	121 139 156 173 191 208 225 243 260 347 405 465 463 128 143 160 178 196 214 222 249 267 36 416 465 465 131 156 169 188 206 225 244 263 281 375 438 500 131 150 178 197 211 231 250 283 381 478 500 132 154 177 197 271 230 269 288 384 488 513 141 161 177 197 271 236 269 288 384 488 513 141 161 181 202 242 256 288 384 459 513	121 139 156 173 191 208 225 243 260 347 405 463 125 149 166 178 196 214 222 249 267 416 475 131 169 188 206 225 244 263 281 375 438 500 138 156 177 197 211 231 260 288 384 448 513 138 156 177 197 217 226 262 276 288 384 448 513 144 165 188 202 222 282 202 384 448 513 144 165 186 271 222 282 202 403 470 525 144 165 186 207 248 282 302 413 481 550	121 139 156 173 191 208 225 243 260 347 405 465 125 143 156 178 196 214 228 289 267 475 405 465 131 150 169 188 206 225 244 268 281 375 486 500 131 150 169 188 206 225 244 268 281 375 488 500 138 156 177 197 211 231 250 288 384 448 513 141 161 181 207 212 226 286 288 384 448 513 144 165 186 207 222 222 282 302 403 470 550 148 165 186 206 228 289 309 413 481
125 143 160 178 196 214 222 249 267 356 416 475 475 128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500	125 143 160 178 196 214 223 249 267 356 416 475 128 146 165 188 201 219 228 258 224 356 427 438 131 150 169 188 206 223 281 375 438 500 132 231 231 231 236 288 384 448 513	125 143 160 178 196 214 223 249 267 356 416 475 128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500 132 144 173 192 211 231 250 289 384 448 513 138 156 177 197 217 236 256 278 394 459 525	125 143 160 178 196 214 222 249 267 356 416 475 128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500 138 173 197 211 231 236 288 394 448 513 138 189 177 197 217 236 256 256 394 459 525 141 161 181 202 222 242 262 286 302 403 470 538	125 143 160 178 196 214 222 249 267 356 416 475 128 146 165 188 200 229 228 256 224 366 427 486 131 150 169 188 200 225 244 283 281 375 438 500 138 154 173 197 211 231 250 288 384 448 513 138 177 197 217 236 256 276 298 384 448 513 144 161 181 187 212 222 248 286 396 470 459 550 144 165 186 186 278 288 396 470 550	125 143 160 178 196 214 222 249 267 356 416 475 128 146 165 188 200 225 244 283 281 375 436 475 478 135 154 173 192 211 231 250 288 384 448 513 138 156 177 197 217 231 250 288 384 448 513 141 161 181 202 222 242 286 384 448 513 144 165 186 202 222 222 282 302 403 470 550 148 165 186 206 225 282 302 403 470 550 148 165 186 206 225 222 282 302 403 470 550
128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500	128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 438 500 135 154 173 192 211 231 250 269 288 384 448 513	128 146 165 188 201 219 238 256 274 366 427 488 131 150 169 188 20 225 244 269 288 375 438 500 138 173 192 11 231 250 289 289 344 488 513 138 177 197 217 236 256 289 344 458 513 138 177 197 217 236 256 276 295 344 459 525	128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 488 500 138 154 177 197 211 231 220 269 288 384 448 500 141 161 197 217 236 256 269 388 344 459 553 141 161 181 202 242 262 262 362 344 459 553	128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 225 244 263 281 375 448 500 135 154 173 192 211 231 250 269 288 384 448 513 138 158 177 177 236 256 295 394 459 556 144 165 186 206 227 242 262 282 309 413 481 550	128 146 165 183 201 219 238 256 274 366 427 488 131 150 169 188 206 222 244 263 281 375 438 500 138 144 173 192 211 231 250 289 288 344 448 513 141 165 177 197 217 236 256 276 295 394 459 525 141 165 186 202 272 282 282 392 409 470 538 148 165 186 190 211 232 283 286 392 409 470 538 148 169 190 211 227 283 286 302 422 470 536
131 150 169 188 206 225 244 263 281 375 438 500	131 150 169 188 206 225 244 263 281 375 438 500 135 154 173 192 211 231 250 269 288 384 448 513	131 150 169 188 206 225 244 263 281 375 438 500 132 144 175 192 211 231 224 283 281 344 448 500 138 157 127 211 231 236 288 344 448 500 138 177 197 217 236 266 286 344 459 525	131 150 169 188 206 225 244 263 281 375 438 500 135 154 177 197 211 231 250 269 288 384 488 550 138 156 177 197 211 236 256 298 384 488 553 141 161 181 202 226 242 256 236 394 459 555 141 161 181 202 222 242 262 262 302 470 538	131 150 169 188 206 225 244 263 281 375 488 500 135 154 173 192 211 231 250 269 288 384 448 513 138 158 177 197 217 236 256 285 394 459 555 141 161 181 202 242 262 282 302 403 470 538 144 165 186 206 227 248 268 289 309 413 481 550	131 150 169 188 206 225 244 263 281 375 438 500 135 154 173 192 211 231 250 266 288 384 448 513 138 177 197 217 236 256 282 394 479 555 144 165 186 207 242 282 302 403 470 588 148 169 190 211 232 253 274 295 316 413 481 550
	135 154 173 192 211 231 250 269 288 384 448 513	135 154 173 192 231 231 230 269 288 384 448 513 138 158 177 197 217 236 256 276 295 394 459 525	135 134 173 192 211 231 250 269 288 384 448 513 138 158 177 197 217 236 256 276 295 394 459 525 141 161 181 202 222 242 262 282 302 403 470 538	135 144 173 192 211 231 250 269 288 384 448 513 138 158 177 197 217 236 256 276 298 394 459 555 141 161 181 202 222 282 302 470 470 588 144 165 186 206 227 248 268 282 305 413 481 550	135 144 173 192 211 231 250 269 288 384 448 513 138 158 177 197 217 236 256 276 295 394 459 555 141 161 181 202 222 222 282 289 302 403 470 538 144 165 186 206 227 248 268 389 309 413 481 550 148 169 190 211 232 253 274 256 316 422 492 563

Table 4. Spray Blade and Rotary Tiller Applications Buffer Zone Distance in Feet

80	25	25	25	25	25	25	25	72	118	164	210	248	285	323	
70	25	25	25	25	25	25	25	64	103	142	180	218	255	293	
09	25	25	25	25	25	25	25	57	88	119	150	188	225	263	
50	25	25	25	25	25	25	25	42	58	74	90	135	180	225	
40	25	25	25	25	25	25	25	25	25	25	25	75	125	275	
30	25	25	25	25	25	25	25	25	25	25	25	64	103	142	
20	25	25	25	25	25	25	25	25	25	25	25	49	73	97	
8 9 10	25	25	25	25	25	25	25	25	25	25	25	34	43	52	
6	25	25	25	25	25	25	25	25	25	25	25	32	39	47	
- 00	25	25	25	25	25	25	25	25	25	25	25	30	36	41	
7	25	25	25	25	25	25	25	25	25	25	25	29	32	36	
9	25	25	25	25	. 25	25	25	25	25	25	25	27	29	30	
5	25	25	25	25	25	25	25	25	25	25	25	25	25	25	W
1	25	25	25	25	25	25	25	25	25	25	25	25	25	25	
Gal/A	00	13	19	23	28	33	38	42	47	52	56	61	99	70	

Table 5. Center Pivot and Lateral Move Application (High Release Height*) Buffer Zone Distance in Feet

	160	800	900	1000	1100	1200	1300	1400	1550	1700	1850	2000	2150	2300	2450	2000
	140	009	700	800	006	1000	1100	1200	1350	1500	1650	1800	1950	2100	2250	2400
	120	400	200	009	200	800	900	1000	1150	1300	1450	1600	1750	1900	2050	0000
	110	350	450	550	650	750	850	950	1100	1250	1400	1550	1688	1825	1963	2400
	100	300	400	200	009	200	800	006	1050	1200	1350	1500	1625	1750	1875	0000
	06	250	350	450	550	650	750	850	1000	1150	1300	1450	1563	1675	1788	1000
	80	200	300	400	200	009	700	800	950	1100	1250	1400	1500	1600	1700	1000
()	70	200	300	400	488	575	663	750	888	1025	1163	1300	1400	1500	1600	1700
Application Block Size (acres)	09	200	300	400	475	550	625	700	825	950	1075	1200	1300	1400	1500	1500
tion Block	50	100	200	300	382	463	544	625	719	813	206	1000	1100	1200	1300	1400
Applica	40	100	200	300	363	425	488	550	638	725	813	006	975	1050	1125	TOUR
	30	7.5	138	200	569	338	407	475	557	638	719	800	850	006	950	1000
	20	75	138	200	250	300	350	400	450	200	550	009	650	200	750	ovo
	10	20	100	150	200	250	300	350	375	400	425	450	488	525	563	2009
	5	20	100	150	188	225	263	300	313	325	338	350	363	375	389	400
	1	20	80	125	160	185	202	220	235	250	262	275	288	300	312	325
	Gal/A	00	13	19	23	28	33	38	42	47	52	56	19	99	70	75

^{*} This buffer zone distance table is for center pivot and lateral move irrigation equipment in which the: 1) release height OR spray height greater than 8 feet, and 2) there is > 30 lbs psi at the sprinkler head.

27/41

Table 6. Center Pivot and Lateral Move Application (Medium Release Height**) Buffer Zone Distance in Feet

160		700	800	006	1000	1100	1200	1350	1500	1650	1800	1950	2100	2250	
140	400	500	009	700	800	900	1000	1150	1300	1450	1600	1750	1900	2050	
120	200	300	400	200	009	700	800	950	1100	1250	1400	1550	1700	1850	-
110	150	250	350	450	550	650	750	006	1050	1200	1350	1488	1625	1763	
100	100	200	300	400	200	009	700	850	1000	1150	1300	1425	1550	1675	
90	88	169	250	350	450	550	650	800	950	1100	1250	1363	1475	1588	
80	75	138	200	300	400	200	009	750	006	1050	1200	1300	1400	1500	
70	75	138	200	288	375	463	550	889	825	963	1100	1200	1300	1400	4100
9	75	138	200	275	350	425	200	625	750	875	1000	1100	1200	1300	
20	20	75	100	182	263	344	425	519	613	707	800	006	1000	1100	0000
40	20	75	100	163	225	288	350	438	525	613	700	775	850	925	0000
30	25	50	75	125	175	225	275	357	438	519	009	650	200	750	000
20	25	20	75	107	138	169	200	250	300	350	400	450	200	550	200
10	25	20	75	94	113	132	150	175	200	225	250	288	325	363	***
5	25	38	20	63	75	88	100	113	125	138	150	263	175	188	000
1	25	25	25	37	50	62	75	87	100	112	125	138	150	162	475
Gal/A	00	13	19	23	28	33	38	42	47	52	56	19	99	70	25

^{**} This buffer zone distance table is for center pivot and lateral move irrigation equipment in which the: 1) release height AND spray height is less than 8 feet, AND 2) 29lbs. or less PSI at the sprinkler head, AND 3) there are no end guns.

Table 7. Center Pivot and Lateral Move Application (Low Release Height-Solid Stream***) Buffer Zone Distance in Feet Application Block Size lacres)

110 120 140	125 150 350	188 225 425	250 300 500	325 375 575	400 450 650	475 525 725	920 600 800	544 700 900	738 800 1000	008	900	800 900 1000 1100	800 900 1000 1100 1200	800 900 1000 1100 1200 1300
1000	1000	150 1	200 2	275 3	350 4	425 4	500 5	588	675 7			1	1	111111111111111111111111111111111111111
90	88	138	188	254	319	385	450	532	613	613	613 694 775	613 694 775 857	613 694 775 857 938	613 694 775 857 938 1019
80	75	125	175	232	288	344	400	475	550	550	550 625 700	550 625 700 775	550 625 700 775 850	550 625 700 775 850 925
70	63	100	138	192	244	297	350	419	488	488	488 557 625	488 557 625 694	488 557 625 694 763	488 557 625 694 763
40 50 60	20	75	100	150	200	250	300	363	425	425	425 488 550	425 488 550 613	425 488 550 613 675	425 488 550 613 675 738
50	25	50	75	119	163	207	250	294	338	338	338	338 382 425 494	338 382 425 494 563	338 382 425 494 563 632
40	25	20	75	107	138	169	200	238	275	313	275 313 350	275 313 350 413	313 350 350 413 475	275 313 350 413 475 538
30	25	38	20	75	100	125	150	188	225	225	225 263 300	225 263 300 350	225 263 300 350 400	225 263 300 350 400 450
20	25	38	20	70	89	107	125	157	188	188	219 250	188 219 250 288	219 250 288 325	219 220 250 288 288 325 325
10	25	38	20	63	75	88	100	125	150	150	150	150	150 175 200 225 250 250	150 175 200 225 250 275
5	25	25	25	35	20	63	75	94	113	113	113	113 132 150 163	113 132 150 163 175	113 132 150 163 175 178
1	25	25	25	30	35	40	50	09	70	70	70 85 105	70 85 105 125	70 85 105 125 145	70 85 105 125 145 165
Gal/A	8	13	19	23	28	33	38	42	47	47	47 52 56	47 52 56 56	47 52 56 61 66	47 52 56 61 60 70

Table 8. Solid Set Sprinkler Application Buffer Zone Distance in Feet

	0	0	0	10	0	0	10	0	0	10	10	10	10	10	10	Te
	120	200	300	400	500	909	700	800	950	1100	1250	1400	1550	1700	1850	טטטנ
	110	150	250	350	450	550	650	750	900	1050	1200	1350	1488	1625	1763	1000
	100	100	200	300	400	200	009	200	850	1000	1150	1300	1425	1550	1675	1900
	90	88	169	250	350	450	550	029	800	950	1100	1100	1363	1475	1588	17nn
	80	75	138	200	300	400	200	009	750	900	1050	1200	1300	1400	1500	1600
	70	75	138	200	288	375	463	550	889	825	963	1100	1200	1300	1400	1500
	09	75	138	200	275	350	425	200	625	750	875	1000	1100	1200	1300	1Ann
	20	20	75	100	182	263	344	425	519	613	707	800	006	1000	1100	1200
	40	20	75	100	163	225	288	350	438	525	613	700	775	850	925	1000
	30	25	20	75	125	175	225	275	357	438	519	009	650	700	750	800
(acres)	20	25	20	75	107	138	169	200	250	300	350	400	450	200	550	009
ication Block Size (10	25	20	75	94	113	132	150	175	200	225	250	288	325	363	400
plication B	6	25	48	70	87	105	123	140	163	155	208	230	283	295	328	360
Appl	8	25	45	65	81	98	114	130	150	146	190	210	278	265	293	320
	7	25	43	09	75	90	106	120	138	140	173	190	273	235	258	280
	9	25	40	55	69	83	6	110	125	131	155	170	268	205	223	240
	5	25	38	20	63	75	88	100	113	125	138	150	263	175	188	200
	4	25	38	20	09	70	83	94	105	116	127	138	226	163	175	188
	3	25	38	20	58	29	78	88	97	106	116	125	189	150	163	175
	2	25	38	20	57	65	73	81	88	97	104	113	152	138	150	163
	1	25	38	20	55	62	89	75	80	87	93	100	115	125	137	150
	/A	00	13	19	23	28	33	38	42	47	52	26	19	99	70	75

Table 9. Drench Application Buffer Zone Distances in Feet

234	281	230	275	422	469	516	563	609	656	703	750	797	844	891	938	984	1031	1078	1125	1172	1219	1266	1313	1359	1406	1453	1500	1547	1594	1641	1588	1781	1828	1875	1922	1969	2016	2063	2109	2126	2250	2297	2344	2391	2438	2484	2531	2578	2625	2640	2686	2733	2025	2872	2918	
211	253	200	220	380	422	464	506	548	591	633	675	717	759	802	844	886	928	970	1013	1055	1097	1139	1181	1223	1266	1308	1350	1392	1434	1477	1519	1007	1645	1688	1730	1772	1814	1856	1898	1941	1963	2067	2109	2152	2194	2236	2278	2320	2363	2405	2447	2489	2531	2616	2640	
195	224	272	213	35.0	391	430	469	508	547	586	625	664	703	742	781	820	859	868	938	776	1016	1055	1094	1133	1172	1211	1250	1289	1328	1367	1406	Char	1523	1563	1602	1641	1680	1719	1758	1/9/	1075	1914	1953	1992	2031	2070	2109	2148	2188	7227	2266	2305	2344	2422	2461	- Cana
180	216	253	200	323	359	395	431	467	503	539	575	611	647	683	719	755	791	827	863	868	934	970	1006	1042	1078	1114	1150	1186	1222	1258	1294	1266	1402	1438	1473	1509	1545	1581	1617	1653	1735	1761	1797	1833	1869	1905	1941	1977	2013	2048	2084	2120	2136	2228	2264	
164	197	220	262	295	328	361	394	427	459	492	525	558	591	623	656	689	722	755	788	820	853	886	919	952	984	1017	1050	1083	1116	1148	1181	1247	1280	1313	1345	1378	1411	1444	1477	1509	1575	1608	1641	1673	1706	1739	1772	1805	1838	1870	1903	1936	1969	2034	2067	2000
156	188	210	250	281	313	344	375	406	438	469	200	531	563	594	625	929	688	719	750	781	813	844	875	906	938	696	1000	1031	1063	1094	1155	1188	1219	1250	1281	1313	1344	1375	1406	1438	1500	1531	1563	1594	1625	1656	1688	1719	1750	1781	1813	1844	1906	1938	1969	4000
141	169	197	225	253	281	309	338	366	394	422	450	478	506	534	563	591	619	647	675	703	731	759	788	816	844	872	006	928	956	384	1013	1069	1097	1125	1153	1181	1209	1238	1266	1234	1350	1378	1406	1434	1463	1491	1519	1547	1575	1603	1631	1659	1716	1744	1772	-
125	150	175	2000	225	250	275	300	325	350	375	400	425	450	475	200	525	550	575	009	625	650	675	200	725	750	775	800	825	850	875	900	950	975	1000	1025	1050	1075	1100	1125	1130	1200	1225	1250	1275	1300	1325	1350	1375	1400	1425	1450	1475	1525	1550	1575	-
109	131	152	175	197	219	241	263	284	306	328	350	372	394	416	438	459	481	503	525	547	569	291	613	634	929	678	700	722	744	766	788	831	853	875	768	919	941	963	984	1000	1050	1072	1094	1116	1138	1159	1181	1203	1225	1247	1269	1291	1334	1356	1378	
102	122	142	163	183	203	223	244	264	284	305	325	345	366	386	406	427	447	467	488	208	528	548	569	589	609	630	029	029	169	711	75.7	777	792	813	833	853	873	894	914	334	975	995	1016	1036	1056	1077	1097	1117	1138	1158	1178	1198	1239	1259	1280	2000
94	113	131	150	169	188	206	225	244	263	281	300	319	338	356	375	394	413	431	450	469	488	206	525	544	563	581	009	619	638	656	604	713	731	750	692	788	806	825	844	803	100	919	938	926	975	994	1013	1031	1050	1069	1088	1106	1144	1163	1181	****
86	103	120	138	155	172	189	206	223	241	258	275	292	309	327	344	361	378	395	413	430	447	464	481	498	516	533	250	267	584	209	610	653	670	889	705	722	739	756	773	16/	825	842	859	877	894	911	928	945	963	086	766	1014	1031	1066	1083	
70	28	98	113	127	141	155	169	183	197	211	225	239	253	267	281	295	309	323	338	352	366	380	394	408	422	436	450	464	478	492	200	534	548	563	577	591	909	619	633	047	100	689	703	717	731	745	759	773	788	802	816	830	858	872	886	
55	99	11	88	86	109	120	131	142	153	164	175	186	197	208	219	230	241	252	263	273	284	295	306	317	328	339	350	361	372	383	334	416	427	438	448	459	470	481	492	203	535	536	547	558	569	580	591	209	613	623	634	645	959	678	689	
51	19	1	18	16	102	112	122	132	142	152	163	173	183	193	203	213	223	234	244	254	264	274	284	295	305	315	325	335	345	355	300	386	396	406	416	427	437	447	457	407	411	498	508	518	528	538	548	559	569	579	589	599	620	630	640	
47	56	99	K	84	28	103	113	122	131	141	150	159	169	178	188	197	206	216	225	234	244	253	263	272	281	291	300	309	319	328	338	356	366	375	384	394	403	413	422	451	ASD	459	469	478	488	497	206	516	525	534	544	553	572	581	591	
44	53	62	1 1	80	88	26	106	115	124	133	142	150	159	168	17.1	186	195	203	212	221	230	239	248	256	265	274	283	292	301	310	222	336	345	354	363	371	380	389	398	407	410	433	442	451	460	469	478	486	495	504	513	522	539	548	557	
42	50	58	67	75	. 83	92	100	108	117	125	134	142	150	159	167	175	184	192	200	500	217	225	234	242	250	259	267	275	284	767	300	317	325	334	342	350	359	367	375	200	700	409	417	426	434	442	451	459	467	476	484	492	509	517	526	
										1						1			R									9					1	13				1	-														477			
																									1	1			1										1									400	1	1	422		437			1
16			1																												-																						412			
																																																					379			
												1																1				1								-													347 3			
									1																																					1							72 3			
																																1		1						1																

1/2 mile (2,640 feet) then the application is prohibited.

	80	25	88	150	163	175	188	200	238	275	313	350	400	450	200	550	584	634	684	734	784	834	884	934
	70	25	76	125	140	150	163	175	207	250	269	300	350	400	450	200	531	563	594	625	959	889	719	750
	09	25	63	100	113	125	138	150	175	200	225	250	300	350	400	450	478	206	534	563	591	619	647	675
	20	25	20	75	82	88	94	100	125	150	175	200	250	300	350	400	425	450	475	200	525	550	575	009
	40	25	20	75	82	88	98	100	113	125	138	150	200	250	300	350	372	394	416	438	459	481	503	525
	30	25	38	20	57	63	69	75	94	113	132	150	188	225	263	300	319	338	356	375	394	413	431	450
	20	25	38	20	57	63	69	75	82	88	94	100	125	150	175	200	213	225	238	250	263	275	288	300
	10	25	25	25	32	38	44	50	57	63	69	75	82	88	94	100	106	113	119	125	131	138	144	150
acres)	6	25	25	25	31	35	40	45	52	58	64	70	76	80	85	90	96	101	107	113	118	124	129	135
ock Size (a	00	25	25	25	29	33	36	40	47	53	59	65	69	73	92	80	85	90	95	100	105	110	115	120
Application Block Size (acres)	7	25	25	25	28	30	33	35	42	48	54	09	63	65	89	70	74	79	83	88	92	96	101	105
App	9	25	25	25	26	28	29	30	37	43	49	55	26	58	59	09	64	89	71	75	79	83	98	06
	5	25	25	25	25	25	25	25	32	38	44	50	20	20	20	50	55	09	65	70	75	80	85	06
	4	25	25	25	25	25	25	25	30	35	39	44	46	47	49	20	54	58	62	99	70	74	78	82
	3	25	25	25	25	25	25	25	29	32	35	38	41	44	47	20	53	56	59	62	65	89	7.1	75
	2	25	25	25	25	25	25	25	27	28	30	31	37	41	46	20	52	54	56	58	09	62	64	99
	1	25	25	25	25	25	25	25	25	25	25	25	32	38	44	20	51	52	53	54	55	99	57	58
	Gal/A	4	7	6	12	14	16	19	21	23	26	28	31	33	35	38	40	42	45	47	49	52	54	56

Table 11. Flood Basin, Furrow, and Border Application Buffer Zone Distances in Feet

1 00	25	2 2	35	39	44	48	53	57	19	99	70	74	79	83	88	92	96	101	105	109	114	118	123	12/	131	140	144	149	153	158	162	166	171	175	104	188	193	197	201	206	210	214	219	223	222	236	241	245	249	254	258	267	271	276
1	25	22	30	44	48	53	58	63	89	73	78	82	87	92	97	102	107	111	116	121	126	131	130	140	145	155	160	165	170	174	179	184	189	194	200	208	213	218	223	228	233	237	242	247	257	262	266	17.2	276	281	286	767	300	305
200	25	27 22	43	48	53	58	64	69	74	80	85	90	96	101	106	112	117	122	128	133	138	143	149	154	155	170	175	181	186	191	197	202	207	213	223	228	234	239	244	250	255	260	266	277	282	287	292	298	303	308	313	324	329	335
-	25	35	46	52	58	64	69	7.5	81	87	93	98	104	110	116	121	127	133	139	145	150	156	102	108	170	185	161	197	202	208	214	220	225	231	242	249	254	260	266	272	278	283	289	292	305	312	318	324	330	335	341	347	358	364
,	25	300	2	56	63	69	75	81	88	94	100	106	113	119	125	131	138	144	150	156	163	109	173	181	188	200	200	213	219	225	231	238	244	250	262	269	275	281	288	294	300	306	313	319	323	338	344	350	356	363	369	381	388	394
	34	40	7 5	80	67	74	81	87	24	101	108	114	121	128	134	141	148	155	191	168	175	181	188	150	707	215	222	228	235	242	249	255	292	269	200	284	296	302	309	316	323	329	336	343	355	363	370	376	383	390	396	403	417	423
-	36	43	200	65	72	79	98	93	101	108	115	122	129	137	144	151	158	165	173	180	187	151	107	208	272	220	237	244	252	259	266	273	280	288	2002	305	316	323	331	338	345	352	359	367	381	388	395	403	410	417	424	431	446	453
	38	46	5 5	69	11	84	92	100	107	115	123	130	138	145	153	191	168	176	184	191	199	207	214	7777	230	245	253	260	268	276	283	291	299	306	514	326	337	345	352	360	368	375	383	390	320	413	421	429	436	444	452	455	475	482
,	41	49	20	3 2	81	89	98	106	114	122	130	138	146	154	163	171	179	187	195	203	211	219	277	230	260	260	268	276	284	293	301	309	317	325	355	249	358	366	374	382	390	398	406	414	423	439	447	455	463	471	479	496	504	512
2	43	52	00	77	86	95	103	112	120	129	138	146	155	163	172	180	189	198	206	215	223	232	241	249	256	275	284	292	301	309	318	327	335	344	355	370	378	387	395	404	413	421	430	438	147	464	473	481	490	498	507	270	533	541
3	55	99	00	86	109	120	131	142	153	164	175	186	197	208	219	230	241	252	263	273	284	295	306	317	328	250	361	372	383	394	405	416	427	438	448	470	481	492	503	514	525	536	547	258	200	591	602	613	623	634	645	667	678	689
2	63	75	100	113	125	138	150	163	175	188	200	213	225	238	250	263	275	288	300	313	325	338	350	363	375	300	400	425	438	450	463	475	488	200	513	528	550	563	575	588	009	613	625	638	000	675	889	700	713	725	738	763	775	788
2	R	\$ 8	113	177	141	155	169	183	197	211	225	239	253	267	281	295	309	323	338	352	366	380	394	408	422	450	450	478	492	206	520	534	248	563	115	FINE	619	633	647	199	675	689	703	717	7.45	759	773	788	802	816	830	858	872	988
200	78	96	105	141	156	172	188	203	219	234	250	266	281	297	313	328	344	329	375	391	406	422	438	453	469	404	516	531	547	563	578	594	609	625	041	672	688	703	719	734	750	766	781	797	010	844	859	875	168	906	922	938	696	984
3	06	108	144	162	180	198	216	234	252	270	288	305	323	341	329	377	395	413	431	449	467	485	203	521	539	207	593	611	629	647	999	683	701	719	755	772	791	809	827	845	863	880	898	916	934	970	886	1006	1024	1042	1060	1096	1114	1132
07	102	122	163	183	203	223	244	264	284	305	325	345	366	386	406	427	447	467	488	208	528	548	569	589	609	020	670	169	711	731	752	772	792	813	833	872	894	914	934	955	975	995	1016	1036	1077	1097	1117	1138	1158	1178	1198	1219	1259	1280
200	113	136	ECT 101	204	227	249	272	295	317	340	363	385	408	430	453	476	498	521	244	266	589	612	634	657	089	JUE TOE	748	770	793	816	838	861	884	906	929	205	796	1020	1042	1065	1088	1110	1133	1155	1301	1223	1246	1269	1291	1314	1337	1359	1405	1427
00	125	150	CVT	225	250	275	300	325	350	375	400	425	450	475	200	525	250	575	009	625	650	675	700	725	750	000	825	850	875	900	925	950	975	1000	1025	1075	1100	1125	1150	1175	1200	1225	1250	1275	1300	1350	1375	1400	1425	1450	1475	1500	1550	1575
0	137	164	191	246	273	301	328	355	383	410	438	465	492	520	547	574	209	629	929	684	711	738	766	793	820	040	6/2	930	957	984	1012	1039	1066	1094	1211	1176	1203	1230	1258	1285	1313	1340	1367	1395	1422	1477	1504	1531	1559	1586	1613	1641	1695	1723
00	148	178	807	267	297	327	356	386	416	445	475	505	534	564	594	623	653	683	713	742	772	805	831	861	891	920	080	1009	1039	1069	1098	1128	1158	1188	1217	1247	1306	1336	1366	1395	1425	1455	1484	1514	1544	1603	1633	1663	1692	1722	1752	1781	1841	1870
200	160	192	477	300	320	352	384	416	448	480	513	545	577	609	641	673	705	737	769	801	833	865	897	929	961	353	1057	1089	1121	1153	1185	1217	1249	1281	1313	1340	1409	1441	1473	1505	1538	1570	1602	1634	1000	1730	1762	1794	1826	1858	1890	1922	1986	2018
700	172	206	741	200	344	378	413	447	481	516	550	584	619	653	889	722	756	791	825	829	894	928	963	997	1031	11000	1134	1169	1203	1238	1272	1306	1341	1375	1409	1470	1513	1547	1581	1616	1650	1684	1719	1753	1/88	1856	1891	1925	1959	1994	2028	2063	2131	2166
		7	7	0 0	6 6	4	4	50	54	58	62	99	2	74	78	82	85	89	93	97	101	105	109	113	117	177	128	1328	136	140	144	148	152	156	160	160	1719	175	179	183	187	191	195	199	203	210	214	218	222	226	230	2344	242	246

Table 12. Weed Sprayer Application Buffer Zone Distances in Feet

	120	400	200	009	700	800	900	1000	1150	1300	1450	1600	1750	1900	2050	2200
	110	350	450	550	650	750	850	950	1100	1250	1400	1550	1688	1825	1963	2100
	100	300	400	200	009	700	800	006	1050	1200	1350	1500	1625	1750	1875	2000
	96	250	350	450	550	920	750	850	1000	1150	1300	1450	1563	1675	1788	1900
	80	200	300	400	200	009	200	800	950	1100	1250	1400	1500	1600	1700	1800
	70	200	300	400	488	575	699	750	888	1025	1163	1300	1400	1500	1600	1700
	09	200	300	400	475	550	625	700	825	950	1075	1200	1300	1400	1500	1600
Size (acres	50	100	200	300	382	463	544	625	719	813	206	1000	1100	1200	1300	1400
Application Block Size (acres)	40	100	200	300	363	425	488	550	638	725	813	006	975	1050	1125	1200
Applica	30	75	138	200	592	338	407	475	557	638	719	800	850	006	950	1000
	20	75	138	200	250	300	350	400	450	200	550	009	029	200	750	800
	10	20	100	150	200	250	300	350	375	400	425	450	488	525	563	009
	5	20	100	150	188	225	263	300	313	325	338	350	363	375	389	400
	1	20	80	125	160	185	205	220	235	250	262	275	288	300	312	325
	Gal/A	8	13	19	23	28	33	38	42	47	52	99	19	99	70	75

34/41

BUFFER ZONE CREDITS

The buffer zone distances for Sectagon 42 applications may be reduced by the percentages listed below. Credits may be added, but credits cannot exceed 80%. Also, the minimum buffer zone distance is 25 feet regardless of buffer zone credits available.

- See http://www.tarpcredits.epa.gov for a list of tarps that have been tested and determined to qualify for buffer reduction credits. Only tarps listed on this website qualify for buffer reduction credits.
- 10% reduction in buffer zone distance, IF the organic content of the soil in the application block is ≥ 1% - 2%; a 20% reduction is buffer zone distance, IF the organic content of the soil in the application block is >2% - 3%; and a 30% reduction in the buffer zone distance, IF the organic content of the soil in the application block is >3%.
- 10% reduction in buffer zone distance, IF the soil temperature is measured to be 50°F or less. Record temperature measurements at the application depth or 12 inches, whichever is shallower.
- 10% reduction in the buffer zone distance, IF the clay content of the soil in the application block is greater than 27%.

Examples of Buffer Zone Calculations with Credits Applied

If the buffer zone is 50 feet and the application qualifies for a buffer zone reduction credit since the soil organic content is 1.5%, then the buffer zone can be reduced by 10%, i.e., reduced by 5 feet based on the following calculation: 50 feet – (50 feet x 10%) = 45 feet.

If the buffer zone is 50 feet and the application qualifies for two buffer zone credits since the soil organic content is 1.5% and the clay content is greater than 27%, then the buffer zone can be reduced by 20% (10% organic content credit + 10% clay content credit), i.e., reduced by 10 feet based on the following calculation 50 feet - (50 feet x 20%) = 40 feet.

POSTING FUMIGANT BUFFER ZONES

- Posting of a buffer zone is required unless there is a physical barrier that prevents bystander access to the buffer zone.
- Buffer Zone signs must be placed along or outside the perimeter of the buffer zone, at all usual points of entry and along likely routes of approach from areas where people not under the owner's control may approach the buffer zone.
 - Some examples of points of entry include, but are not limited to, roadways, sidewalks, paths, and bike trails.
 - Some examples of likely routes of approach include, but are not limited to, the area between a buffer zone and a roadway, or the area between a buffer zone and a housing development.
 - When posting, the certified applicator supervising the application must ensure compliance with all local laws and regulations.
- Buffer Zone signs must meet the following criteria:
 - The printed side of the sign must face away from the application block toward areas from which people could approach.
 - Signs must remain legible during the entire posting period and must meet the general standards outlined in the WPS for sign size, text size, and legibility (see 40 CFR §170.120).
 - Signs must be posted no sooner than 24 hours prior to the start of the application and remain posted until the buffer zone period has expired.
 - Signs must be removed within 3 days after the end of the buffer zone period.
 - Buffer Zone signs which meet the criteria above will be provided at points of sale for applicators to use. Templates may be downloaded from http://www.epa.gov/pesticides/reregistration/soil-fumigants/.
 - The Buffer Zone signs must contain the following information:
 - The 'Do Not Walk' symbol
 - DO NOT ENTER/NO ENTRE,
 - Metam Sodium Sectagon 42 Fumigant BUFFER ZONE.
 - Contact information for the certified applicator in charge of the fumigation.

Exception: If multiple contiguous blocks are fumigated within a 14-day period, the entire periphery of the contiguous blocks' buffer zones may be posted. Buffer Zone signs must be posted no sooner than 24-hours prior to the start of the first application. The signs must remain posted

until the last buffer zone period expires and signs must be removed within 3-days after the buffer zone period for the last block has expired.

RESTRICTIONS FOR DIFFICULT TO EVACUATE SITES

- Difficult to evacuate sites are pre-K to grade 12 schools, state licensed daycare centers, nursing homes, assisted living facilities, hospitals, in-patient clinics, and prisons. No furnigant application with a buffer zone greater than 300 feet is permitted within 1/4 mile (1320 feet) of difficult to evacuate sites unless the site is not occupied by children from state-licensed day care centers, students (pre-K to grade 12), patients, or prisoners during the application and the 36-hour period following the end of the application.
- No fumigant application with a buffer zone of 300 feet or less is permitted within 1/8 mile (660 feet) of difficult to evacuate sites unless the site is not occupied by children from state-licensed day care centers, students (pre-K to grade 12), patients, or prisoners during the application and the 36-hour period following the end of the application.

EMERGENCY PREPAREDNESS AND RESPONSE MEASURES

If the buffer zone is 25 feet, then the *Emergency Preparedness and Response Measures* are not applicable.

Triggers for Emergency Preparedness and Response Measures

The certified applicator must either follow the directions under the Fumigant Site Monitoring section or follow the directions under the Response Information for Neighbors section if:

- the buffer zone is greater than 25 feet but less than or equal to 100 feet, and there are residences or businesses within 50 feet from the outer edge of the buffer zone, or
- the buffer zone is greater than 100 feet but less than or equal to 200 feet, and there are residences or businesses within 100 feet from the outer edge of the buffer zone, or
- the buffer zone is greater than 200 feet but less than or equal to 300 feet, and there are residences or businesses within 200 feet from the outer edge of the buffer zone, or
- the buffer zone is greater than 300 feet or the buffer zones overlap, and there are residences or businesses within 300 feet from the outer edge of the buffer zone.

Fumigant Site Monitoring

NOTE: Fumigant Site Monitoring is ONLY required if the Emergency Preparedness and Response Measures are triggered AND directions from the Response Information for Neighbors section are not followed.

From the start of the application until the buffer zone period expires, a certified applicator or handler(s) under his/her supervision must:

- Monitor for sensory irritation in areas between the buffer zone outer perimeter and residences and businesses that trigger this requirement.
- Monitoring for sensory irritation must begin in the evening on the day
 of application and continue until the buffer zone period expires.
 Monitor a minimum of 8 times during the buffer zone period, including
 these periods:
 - 1 hour before sunset,
 - during the night,
 - 1 hour after sunrise, and
 - during daylight hours.

Implement the emergency response plan immediately if a handler monitoring experiences sensory irritation.

Response Information For Neighbors

NOTE: Response Information for Neighbors is ONLY required if the Emergency Preparedness and Response Measures are triggered AND directions from the Fumigant Site Monitoring section are not followed.



The certified applicator supervising the application must ensure that residences and businesses that trigger the requirement have been provided the response information at least 1 week before the application starts. The information provided may include application dates that range for no more than 4 weeks. If the application does not occur when specified, the information must be delivered again.

Information that must be included:

- The location of the application block.
- Fumigant(s) applied including the active ingredient, name of the fumigant product(s), and the EPA Registration number.
- · Contact information for the applicator and property owner.
- Time period in which the application is planned to take place (must not range more than 4 weeks).
- Early signs and symptoms of exposure to the fumigant(s) applied, what to do, and who to call if you believe you are being exposed (911 in most cases).
- How to find additional information about fumigants.

The method used to share the response information for neighbors can be accomplished through mailings, door hangers, or other methods that will effectively inform the residences and businesses within the required distance from the edge of the buffer zone.

NOTICE TO STATE AND TRIBAL LEAD AGENCIES

If your state and/or tribal lead agency requires notice, information must be provided to the appropriate state or tribal lead agency prior to the application. Please refer to www.epa.gov/fumigantstatenotice for a list of states and tribal lead agencies that require notice and information on how to submit the information.

The information that must be provided to state and tribal lead agencies includes the following:

- Location of the application blocks,
- Fumigant(s) applied including EPA registration number,
- · Applicator and property owner contact information, and
- Time period that fumigation may occur.

EMERGENCY RESPONSE PLAN

The certified applicator must include in the FMP a written emergency response plan that identifies:

- · evacuation routes,
- locations of telephones,
- contact information for first responders and local/state/federal/tribal personnel, and
- emergency procedures/responsibilities (e.g., adding water to the field, repairing tarps, fixing equipment, evacuating upwind) if:
 - o there is an incident,
 - sensory irritation is experienced outside of the buffer zone, and/or there are equipment/tarp/seal failure or complaints, or other emergencies.

SITE-SPECIFIC FUMIGATION MANAGEMENT PLAN (FMP)

Prior to the start of application, the certified applicator supervising the application must verify that a site-specific fumigation management plan (FMP) exists for each application block. In addition, an agricultural operation fumigating multiple application blocks may format the FMP in a manner whereby all of the information that is common to all the application blocks is captured once, and any information unique to a particular application block or blocks is captured in subsequent sections.

The FMP must be prepared by the certified applicator, the site owner, registrant, or other party.

The certified applicator must verify in writing (sign and date) that the sitespecific FMP(s) reflects current site conditions before the start of application.

Each site specific FMP must contain the following elements:

- Certified Applicator Supervising the Application
 - o Name,
 - o Phone number,
 - o Pesticide applicator license and/ or certificate number,
 - o Specify if commercial or private applicator
 - o Employer name,

- Employer address, and
- Date and location of completing EPA approved soil furnigant training program.
- o General site information
 - Application block location (e.g., county, township-range-quadrant), address, or global positioning system (GPS) coordinates
 - o Name, address, and, phone number of application block owner
 - o Map, aerial photo, or detailed sketch showing:
 - application block location
 - application block dimensions
 - buffer zone dimensions
 - property lines
 - roadways
 - rights-of-ways
 - sidewalks
 - permanent walking paths
 - bus stops
 - nearby application blocks
 - surrounding structures (occupied and non-occupied)
 - locations of Buffer Zone signs, and
 - locations of difficult to evacuate sites with distances from the application block labeled
- o General application information
 - Target application date/window,
 - o Fumigant product name, and
 - o EPA registration number.
- o Tarp Plan (if tarp is used)
 - Schedule for checking tarps for damage, tears, and other problems
 - o Minimum size of damage that will be repaired
 - Factors used to determine when tarp repair will be conducted
 - o Equipment/methods used to perforate tarps
 - Target dates for perforating tarps
 - Target dates for removing tarps
- o Soil conditions
 - Description of soil texture and moisture in application block.
 - o Method used to determine soil moisture, and
 - Soil temperature measurements if air temperatures were above 100°F in any of the 3 days prior to the application
- Buffer zones
 - o Application method,
 - Injection depth,
 - Application rate from lookup table on label,
 - Application block size from lookup table on label.
 - o Credits applied and measurements taken (if applicable),
 - Tarp brand name, lot number, thickness, manufacturer, batch number, and part number
 - Organic matter content
 - Clay content
 - Soil temperature
 - o Buffer zone distance, and
 - Description of areas in the buffer zone that are not under the control of the owner of the application block. If buffer zones extend onto areas not under the control of the owner, attach the written agreement and keep it with the FMP
- Record Emergency Response Plan as described in the Emergency Response Plan section
- Posting of Fumigant Treated Area and Buffer Zone
 - Person(s) who will post and remove (if different) Fumigant Treated Area and Buffer Zone signs, and
 - Location of Buffer Zone signs
- Emergency Preparedness and Response Measures (if applicable)
 - Fumigant site monitoring (if applicable):
 - When and where it will be conducted;
 - Response information for neighbors (if applicable):
 - List of residences and businesses informed,
 - Name and phone number of person providing information, and
 - Method of providing the information
- State and/or tribal lead agency advance notification (if state and/or tribal lead agency requires notice, provide a list of contacts that were notified and date notified)
- Plan describing how communication will take place between the certified applicator supervising the application, the owner, and other on-site handlers (e.g., tarp perforators/removers, irrigators) for complying with

36/41

label requirements (e.g., buffer zone location, buffer zone start and end times, timing of tarp perforation and removal, PPE)

 Name and phone number of persons contacted by the certified applicator, and

Date contacted

• Handler (including Certified Applicators) Information and PPE

Names, addresses and phone numbers of handlers

- Names, addresses, and phone numbers for employers of handlers
- Tasks that each handler is authorized and trained to perform

o Date of PPE training for each handler

Applicable handler PPE including:

Long-sleeved shirts/long pants, shoes, socks

Chemical-resistant apron

- Chemical-resistant footwear and socks

- Protective eyewear (not goggles)

- Chemical-resistant gloves

Air-purifying respirators

- Respirator make, model, type, style, size, and cartridge/canister type
- Other PPE

For handlers: Confirmation of receipt of Fumigant Safe Handling Information

- For certified applicator(s) supervising the application: Completion date and location of the soil fumigant training program listed on the following EPA website http://www.epa.gov/fumiganttraining for the active ingredient(s) in this product
- For handlers designated to wear air-purifying respirators:
 - date of medical qualification to wear a respirator,

date of respirator training, and

date of fit-testing for the respirator

- Unless exempted in the Protection of Handlers section, verify that:
 - at minimum 1 handler has the appropriate respirators and cartridges/canisters during handler activities, and
 - the employer has confirmed that the appropriate respirator and cartridges/canisters are immediately available for each handler who will wear one

o Air monitoring plan

 If sensory irritation is experienced, indicate whether operations will cease or operations will continue with use of an air-purifying respirator

For monitoring the breathing zone:

- Representative handler tasks to be monitored
- Monitoring equipment to be used, and

Timing of the monitoring

o Good Agricultural Practices (GAPs)

 Identify (e.g., list, attach applicable label section) applicable mandatory GAPs

o Pesticide Product Labels and Material Safety Data Sheets (MSDS)

 Ensure that labels and MSDSs are on-site and readily available for employees to review.

Record-Keeping Procedures

The owner of the application block as well as the certified applicator supervising the application must keep a signed copy of the site-specific FMP for 2 years from the date of application. For situations where an initial FMP is developed and certain elements do not change for multiple application blocks (e.g. applicator information, certified applicator, handlers, record-keeping procedures, emergency procedures) only elements that have changed need to be updated in the site-specific FMP provided the following:

 the certified applicator supervising the application has verified that those elements are current and applicable to the application block before it is fumigated

 Record-keeping requirements are followed for the entire FMP (including elements that do not change).

The certified applicator must make a copy of the FMP immediately available for viewing by handlers involved in the fumigation. The certified applicator or the owner of the application block must provide a copy of the FMP to any local/state/federal/tribal enforcement personnel who request the FMP. In the case of an emergency, the FMP must be made immediately available when requested by local/state/federal/tribal emergency response and enforcement personnel. The certified

applicator supervising the application must ensure the FMP is at the application block during all handler activities.

Within 30 days after the application is complete, the certified applicator supervising the application must complete a Post-Application Summary.

POST-APPLICATION SUMMARY

The Post-Application Summary must contain the following elements:

o Actual date and time of the application,

o Application rate,

o Size of application block

o Weather Conditions

 Summary of the National Weather Service weather forecast during the application and the 48 hours after the application is complete including:

o wind speed, and

o air stagnation advisory (if applicable)

Forecast must be checked on the day of, but prior to the start of the application, and on a daily basis during the application if the time period from the start of the application until the application is complete is greater than 24 hours.

o Tarp damage and repair information (if applicable)

o Date of tarp damage discovery,

o Location and size of tarp damage,

o Description of tarp/tarp seal/tarp equipment failure, and

o Date and time of tarp repair completion.

Tarp perforation/removal details (if applicable)
 Date and time tarps were perforated,

Date and time tarps were periorated,
 Date and time tarps were removed, and

Record if tarps were perforated and/or removed early.
 Describe the conditions that caused early tarp perforation and/or removal

o Complaint details (if applicable)

o Person filing complaint (e.g., on-site handler, person off-site),

- If off-site person, name, address, and phone number of person filing complaint, and
- Description of control measures or emergency procedures followed after complaint
- Description of incidents, equipment failure, or other emergency and emergency procedures followed (if applicable)

o Air monitoring results:

When sensory irritation experienced:

- Date, time, location, and handler task/activity where irritation was observed and
- Resulting action (e.g., implement emergency response plan, cease operations, continue operations with airpurifying respirators)

o When using a direct read detection device:

- Sample date(s), time(s), locations, and concentrations
- Handler task/activity monitored (if applicable), and
- Resulting action (e.g., cease operations, continue operations with air-purifying respirators).

Water-run application monitoring

- Record monitoring date(s) and time(s)
- o Name of person(s) monitoring

o Record observations:

Is the equipment functioning properly,

Description of corrective action (if applicable), and

Other comments

o Fumigant Treated Area and Buffer Zone Signs

o Dates of posting and removal

 Any deviations from the FMP (e.g., changes in emergency response actions, changes in handler information, changes in handlers responsible for completing emergency tasks, changes in communication between certified applicator, owner, and other handlers).

Record-Keeping Procedures

The owner of the application block as well as the certified applicator supervising the application must keep a signed copy of the Post-Application Summary for 2 years from the date of application).

PRODUCT INSTRUCTIONS

Sectagon 42 is a water-soluble liquid. When applied to properly prepared soil, the liquid is converted into a gaseous furnigant. After a sufficient waiting period, the gas dissipates, leaving the soil ready for planting. Sectagon 42 is recommended for the suppression of weeds, plant



parasitic nematodes, and soilborne fungi that cause reductions in the yield and quality of ornamental, food and fiber crops.

Sectagon 42 will suppress only those pests in the fumigation zone at the time of treatment. Recontamination may occur subsequent to the

fumigant's dissipation from the soil.

Weeds and germinating weed seeds that are suppressed include Annual bluegrass, Bermuda grass, Chickweed, Dandelion, Ragweed, Henbit, Lambsquarter, Amaranthus sp. (Pigweed, Careless weed), Watergrass, Johnsongrass, Nutgrass, Wild morningglory, Purslane, Barnyardgrass, Crabgrass, Groundsel, Prickly lettuce, Pineappleweed, Nettleaf, Goosefoot, Nightshade, Shepherdspurse, Stinging nettle, Malva, London rocket, and Fiddleneck. The best weed suppression is obtained when Sectagon 42 is applied to weeds that are actively growing.

The soil-borne plant pathogenic fungi suppressed include species of Verticillium, Rhizoctonia, Pythium, Phytophthora, Sclerotinia.

The plant parasitic nematodes which Sectagon 42 suppresses include Root knot, Lesion, Dagger, Lance, Needle, Pin, Reniform, Stunt, Stubby root. Sting and Spiral.

Note: Sectagon 42 will only suppress nematodes that are in the fumigated zone at the time of treatment. The fumigated zone is defined as the depth of penetration that Sectagon 42 achieves at the time of application. In Oregon and Washington, Sectagon 42 will only suppress Miloidogyne Chitwoodi. Other pests suppressed include symphilids or garden centipedes.

TREATMENT GUIDELINES

For optimum results from soil furnigation with Sectagon 42 certain procedures should be observed at designated times in the treatment program. Described in this section are important guidelines for each of the four stages of the treatment process:

Planning a Sectagon 42 Application Preparing a Field for Application Applying Sectagon 42

Preparing for Planting after Application of Sectagon 42

Your sales representative will help you select the best treatment program for your particular needs.

PLANNING A SECTAGON 42 APPLICATION

Time of Application

Apply Sectagon 42 after harvest and 14 to 21 days before a new crop is planted. In some areas of North America, fall applications are preferred because the fumes dissipate over the winter, allowing planting to begin as soon as favorable springtime conditions arrive.

Application Rate

Apply 1 to 75 gallons of Sectagon 42 per treated acre depending on crop, target pest, and soil properties. Soil properties to consider when determining the application rate include the depth of soil to be treated, soil texture and percent organic matter.

Application in Tank Mix with Liquid Fertilizer

Sectagon 42 may be injected in a mixture with liquid fertilizers. Since the composition of liquid fertilizers vary considerably, the physical compatibility of each fertilizer/Sectagon 42 tank mix should be checked by using the following procedure:

Mix a small quantity of Sectagon 42 and liquid fertilizer in a glass container. Sectagon 42 and fertilizer should be mixed in the same ratio as they will be applied to the field (i.e., if 40 gallons of Sectagon 42 and 40 gallons of liquid fertilizer are to be applied per acre, then Sectagon 42 and fertilizer should be mixed in the jar in a 40:40 or 1:1 ratio). Agitate the liquids to attain a complete mixture.

If a uniform mix cannot be made, the mixture should not be used. If the mixture remains uniform for 30 minutes, the combination may be used. Should the mixture separate after 30 minutes, but readily remixes uniformly with agitation, the mixture can be used if adequate agitation is maintained in the tank.

DO NOT PLACE CAPS ON JAR, AS INCOMPATIBLE MIXES MAY EVOLVE HYDROGEN SULFIDE GAS.

USE PROMPTLY AFTER MIXING WITH WATER OR FERTILIZER. DO NOT ALLOW SOLUTION TO STAND.

Flush all equipment with water after each day's use. Disassemble valves and clean carefully.

Target Pest and Depth of Treatment

For suppression of weeds and fungi causing seed or seedling diseases, treatment of only the top 1 to 4 inches of soil may be required (see application specific requirements in the Good Agricultural Practices section of this label). For suppression of nematodes and fungi which occur throughout the rhizosphere, treatment to depths of greater than 4 inches

may be required. For a given soil type, the required application rate will increase proportionately with the depth of treatment required.

For example, if 25 gallons of Sectagon 42 per acre is required to treat 4 inches, then 50 gallons of Sectagon 42 will be required to treat to a depth of 8 inches. Choose the appropriate application method to distribute Sectagon 42 evenly throughout the soil to the required depth.

Organic Matter in the Soil

Because of the absorbing effect of humus, soils with high levels of organic matter under the surface require higher than usual doses of Sectagon 42 with the maximum application rate being 75 gallons per acre. For example, muck soils require twice the amount of fumigant that would be used in mineral soils.

Soil Texture

Application rates will vary with the soil texture. For instance, clay soils require more Sectagon 42 than light sandy soil.

Soil Temperature During Treatment

At the time of fumigation, the soil temperature should be in the range of $40^{\circ}F-90^{\circ}F$ (1.6°-32°C).

Phytotoxicity

Sectagon 42 is phytotoxic. Protect valuable, non-target plants by stopping soil applications of Sectagon 42 at least 3 feet short of the drip line of trees, shrubs, and other desirable plants. Crop injury, lack of effectiveness, or illegal pesticide residues in the crop can result from nonuniform distribution of treated water.

APPLYING SECTAGON 42

Use of Diluted Sectagon 42

Do not store the diluted product. Use Sectagon 42 promptly after it has been mixed with water. In dilute solutions in water Sectagon 42 decomposes over a period of days. Although Sectagon 42 is stable in its concentrated form, it is unstable in acid dilutions.

CHEMIGATION-GENERAL PROCEDURES

When applying by chemigation methods the following precautions must be observed.

Apply this product only through sprinkler systems including center pivot, lateral move, end tow, side (wheel) roll, solid set, or hand move; flood (basin); furrow; border, or drip (trickle) irrigation systems. Do not apply this product through any other type of irrigation system.

Crop injury, lack of effectiveness, or illegal pesticide residues in the crop

can result from nonuniform distribution of treated water.

If you have questions about calibration, you should contact State Extension Service specialists, equipment manufacturers or other experts. Do not connect an irrigation system used for pesticide application to a public water system unless the pesticide label-prescribed safety devices for public water systems are in place.

A person knowledgeable of the chemigation system and responsible for its operation, or under the supervision of the responsible person, shall shut the system down and make necessary adjustments should the need arise.

CHEMIGATION SYSTEMS CONNECTED TO PUBLIC WATER SYSTEMS

NOTE: Tessenderlo Kerley, Inc. does not encourage connection of chemigation systems to public water systems. The following information is provided for users who have evaluated all alternative application and water source options before choosing to make such a connection.

Public water system means a system for the provision to the public of piped water for human consumption if such system has at least 15 service connections or regularly serves an average of at least 25 individuals daily at least 60 days out of the year.

Chemigation systems connected to public water systems must contain a functional, reduced-pressure zone, backflow preventer (RPZ) or the functional equivalent in the water supply line upstream from point of pesticide introduction. As an option to the RPZ, the water from the public water system should be discharged into a reservoir tank prior to pesticide introduction. There shall be a complete physical break (air gap) between the outlet end of the fill pipe and the top or overflow rim of the reservoir tank measuring of at least twice the inside diameter of the fill pipe.

GENERAL INSTRUCTIONS FOR SPRINKLER SYSTEMS

NOTICE: Do not operate irrigation systems without safety valves or other devices to prevent back siphoning of Sectagon 42 into water sources. Irrigation water treated with Sectagon 42 should be maintained on the treated area until the water is absorbed by the soil. The tank containing Sectagon 42 must be connected to the discharge side of the irrigation pump or other pressurized equipment attached to the irrigation line. Do not apply in irrigation systems that result in overlapping application of



Sectagon 42. Do not apply when weather conditions favor drift from target areas.

PREPARING FOR PLANTING AFTER APPLICATION OF SECTAGON 42

Effect of Rain

If a Sectagon 42 application is rained on less than 24 hours after treatment, lack of suppression at and near the soil surface may result.

Recontamination

Precautions must be taken to prevent recontamination of treated soil with weed seeds, plant pathogenic fungi and plant parasitic nematodes. Use clean seeds and/or plants. Before farm equipment is driven into the treated area, it should be rinsed free of the untreated soil from other fields. Interval Between Treatment and Planting

Because Sectagon 42 can be harmful to germinating and/or living plants, an appropriate interval must be observed between soil fumigation and planting. On well-drained soils which have a light to medium texture and which are not excessively wet or cold (when soil is colder than 40°F or contains more moisture than 80% available water capacity) following application, planting can begin 14 to 21 days after treatment. If soils are heavy or especially high in organic matter, or if they remain wet and or cold (below 60°F or 15°C) following application, a minimum interval of 30 days should be observed.

Aeration before planting

Soils including soils high in clay or organic matter, should be allowed to aerate and dry thoroughly after treatment with Sectagon 42. During cold and/or wet (when soil is colder than 40°F or contains more moisture than 80% available water capacity) weather, frequent shallow cultivation can aid the escape of Sectagon 42 from the soil.

Testing for Dissipation of Sectagon 42

After the waiting period has passed, if there are any questions about the complete escape of Sectagon 42 from the soil, transplant a seedling into the treated soil. If the plant develops normally without any signs of chemical injury, crop planting can begin.

USES, APPLICATION METHODS & RATES FIELD APPLICATION WHERE ENTIRE AREA IS BEING TREATED

POWER ROLL SEAL METHOD (NON-TARP)

Use a RO-TO-VATE & ROLL Applicator only. Contact your local agricultural extension service, distributor or the manufacturer for approved RO-TOVATE & ROLL Application specifications.

When to Treat: Apply Sectagon 42 2 to 6 weeks prior to planting, whenever soil type and conditions permit. For best results with annual crops, treat the soil each year. Do not use Sectagon 42 to treat any type of soil when it is cold and/or wet (when soil is colder than 35°F or contains more moisture than 80% available water capacity).

Application: Use undiluted Sectagon 42 to the desired depth below the final soil surface. (Contact your dealer or the manufacturer for the specifications for suitable application equipment).

IMPORTANT SOIL TREATMENT PRECAUTIONS

Crops to be hilled: For crops that require soil movement (hilling) prior to or after planting, incorporate Sectagon 42 to a depth that will allow the tillage required to occur without penetrating below the depth of treatment (see application specific requirements in the Good Agricultural Practices section of this label).

Crops to be bedded: For crops to be bedded, care must be taken that exposed sides of raised beds are not cracked or open compared to the power rolled surface. If necessary, add power rollers of the required height or other sealing equipment to the ends of the bedding equipment to seal the sides.

Note: The use of Sectagon 42 for the suppression of weeds, weed seeds and shallow inhabiting soil fungi requires that NO SOIL CULTIVATION OCCUR FOLLOWING TREATMENT until time of planting.

This method of treating soil with Sectagon 42 will not be effective for the suppression of nematodes outside the treated zone. This method of Sectagon 42 application can be used in combination with other soil furnigants to suppress the nematodes persisting in the surface 1 to 6 inches of soil normally not suppressed with injected soil furnigants.

Zone of treatment will be limited by diameter of applicator. If pest is deeper than applicator can treat to, use a different method. For further information contact your local agricultural extension service or the manufacturer.

SOIL INJECTION

Use injectors (shanks, blades, fertilizer wheels, plows, etc.) to apply Sectagon 42 at the rate of 15 to 75 gallons per acre into well prepared soil. Follow immediately with a bedshaper, roller press wheel, or similar device, or cover with an adequate amount of soil to seal the fumigant into the soil.

Example: apply through injectors placed 4 inches below surface and 5 inches apart.

SPRINKLER SYSTEM

Use only those sprinkler systems which give large water droplets to prevent excess loss. Use 37.5 to 75 gallons Sectagon 42 per acre for suppression of nematodes and fungi at a depth of 24 inches. For suppression of weeds and fungi at a depth of 8 inches or less, use 15 to 75 gallons per acre. Inject the Sectagon 42 in enough water to reach to desired treatment depth. The product should be continuously metered into the irrigation system throughout the entire application period. Flush the system with only enough water to clear lines. If the soil surface dried quickly, reseal it with 15 minutes of water once a day for the next day or two.

To prevent runoff of treatment solution during sprinkler application, do not exceed the infiltration rate of the solution into the soil. Should runoff occur, isolate it from growing crops and water sources. Once collected, reapply it to the treated area. See use precautions in "CHEMIGATION" section.

CHECK OR FLOOD IRRIGATION

Meter Sectagon 42 at a steady rate into water during irrigation. Use 40 to 75 gallons of Sectagon 42 per acre, depending upon the kind of pest and depth desired, in 3 to 18 inches of water per acre. See use precautions in "CHEMIGATION" section.

DISC APPLIED METHOD

Spray Sectagon 42 immediately in front of disc. Use 15 to 75 gallons per acre. Follow immediately with a roller to smooth and compact the soil surface.

DRIP IRRIGATION

Sectagon 42 may be injected into drip irrigation systems prior to planting. The area must be calculated in accordance with the size of the band treated. Apply 40 gallons per broadcast acre in one acre inch of water (27,000 gallons). The resulting concentration is 700 ppm on a weight basis. (Example: if the emitters irrigate 10% of each acre then use 5 gallons Sectagon 42 in 2,700 gallons water). Inject continuously. Do not slug treat. See use precautions in "CHEMIGATION" section.

APPLICATION TO BED OR ROWS

POWER ROLL SEAL METHOD (NON-TARP)

Use a modified RO-TO-VATE & ROLL Applicator only. Contact your local agricultural extension service, distributor or the manufacturer for approved RO-TO-VATE & ROLL Applicator specifications.

When to treat: Apply Sectagon 42 2 to 6 weeks prior to planting whenever soil type and conditions permit. For best results with annual crops, treat the soil each year. Do not use Sectagon 42 to treat any type of soil when it is cold and/or wet (when soil is colder than 35°F or contains more moisture than 80% available water capacity).

Application: Use undiluted Sectagon 42 Apply with suitable application equipment that will ensure incorporation of Sectagon 42 to the desired depth below the final soil surface. (Contact your dealer or the manufacturer for the specifications for suitable application equipment).

IMPORTANT SOIL TREATMENT PRECAUTIONS

Crops to be hilled: For crops that require soil movement (hilling) prior to or after planting, incorporate Sectagon 42 to a depth that will allow the tillage required to occur without penetrating below the depth of treatment (see application specific requirements in the Good Agricultural Practices section of this label).

Crops to be bedded: For crops to be bedded, care must be taken that exposed sides of raised beds are not cracked or open compared to the power rolled surface. If necessary, add power rollers of the required height or other sealing equipment to the ends of the bedding equipment to seal the sides.

Note: The use of Sectagon 42 for the suppression of weeds, weed seeds and shallow inhabiting soil fungi requires that NO SOIL CULTIVATION OCCUR FOLLOWING TREATMENT until time of planting.

This method of treating soil with Sectagon 42 will not be effective for the suppression of nematodes outside the treated zone. This method of



Sectagon 42 application can be used in combination with other soil fumigants to suppress the nematodes persisting on the surface 1 to 6 inches of soil normally not suppressed with injected soil fumigants.

Zone of treatment will be limited by diameter of applicator. If pest is deeper than applicator can treat to, use a different method. For further information contact your local agricultural extension service or the manufacturer.

SOIL INJECTION

Sectagon 42 at the rate of 50 to 75 gallons per treated acre (1 to 1.5 pints per 100 sq. ft.), may be injected into preformed plant beds following the directions given above under soil injection. If a wider treated band is desired, space 2 or more injectors (shanks, blades, fertilizer wheels, etc.) at desired intervals to cover the desired treating width. Seal immediately. If Sectagon 42 is injected into established plant beds to terminate growth of a previous crop, and to fumigate the bed in preparation for planting a subsequent crop, the terminated crop should not be used for any food or feed purposes after Sectagon 42 has been applied.

SOIL COVERING METHOD (BED-OVER METHOD)

Sectagon 42 may be sprayed or dripped onto the soil immediately ahead of bed-shaping equipment. Follow immediately with a bedshaper, roller press wheel, or similar device, or cover with an adequate amount of soil to seal the fumigant into the soil. The recommended rate of Sectagon 42 is 40 to 75 gallons per acre of treated soil, approximately equivalent to .5 to 1.5 pints per 100 linear ft. of 12-inch wide row.

DRIP IRRIGATION

During pre-irrigation, check drip tape for uniform distribution and repair if necessary. Apply 15 to 75 gallons Sectagon 42 per treated acre (0.25 to 1.5 pints per 100 sq. ft. of treated soil) using enough water to thoroughly wet entire desired treatment zone. During the entire irrigation period, inject Sectagon 42 continuously into drip line as close as possible to treatment area. Two or more lines per bed may be needed to ensure full coverage. Weed suppression will not be satisfactory if too much water is applied (if 80% available water capacity is exceeded). An adequate concentration of Sectagon 42 must be present at the time of weed seed germination in order to be effective. See use precautions in "CHEMIGATION" section.

DRENCH METHOD

Sectagon 42 may be applied to finished beds in enough water to soak at least 2 inches deep for suppression of shallow seeded weeds. To avoid contamination by untreated soil, do not disturb the treated area. Apply 15 to 75 gallons of Sectagon 42 per treated acre.

ADDITIONAL RECOMMENDATIONS

TOBACCO PLANT BEDS

Fall applications are recommended wherever possible. Read and follow DIRECTIONS FOR USE carefully. Treatment in the South should generally be made before November 30.

DRENCH METHOD: Apply 2 gallons Sectagon 42 in 150 to 200 gallons of water per 100 sq. yd. Application may be made with sprinklers, sprayers with nozzles or any suitable equipment. Follow directions given above for seed bed treatment.

SYMPHYLID SUPPRESSION

Soil should be in good seed bed condition to a depth of 8 to 10 inches. Maintain adequate moisture during spring season. Treat during July-August when symphylids are in the upper soil surface. Apply 15 gallons Sectagon 42 per acre using blade or chisel injector. Inject below level of symphylid concentration, usually 6 to 8 inches. Pack soil immediately after application.

NOTE: Sectagon 42 will only suppress nematodes which are in the furnigated zone at the time of treatment.

POTATOES

For suppression of potato pests such as Root knot nematodes, Weed seeds, Verticullum dahlias (Early maturity disease).

Apply 30 to 75 gallons Sectagon 42 per acre using injectors (shanks, blades, fertilizer wheels, plows, etc.) Follow immediately with a bedshaper, roller press wheel or similar device or cover with an adequate amount of soil to seal the fumigant into the soil.

Sprinkler system preplant application – Use 37.5 to 75 gallons of Sectagon 42 per acre. Inject into a sprinkler system that can deliver an even water distribution for the area being treated. Inject all of the

Sectagon 42 needed for the area covered and apply in enough water to reach the desired treatment depth. Soil temperature should be in the range of 35°F to 90°F in the treatment zone. Soil moisture immediately prior to treatment must be 60 to 80% of available water capacity down to 24" level. Soil condition must facilitate even moisture penetration without runoff. Do not apply when plants are present. See use precautions in "CHEMIGATION" section.

NOTE: Sectagon 42 will suppress Root knot nematodes in the fumigated zone at the time of treatment. The fumigated zone is defined as the depth of penetration that Sectagon 42 achieves at the time of application.

If high numbers or deep nematodes are identified, anticipate nematodes to build up throughout the growing season. Some damage will occur unless additional action is taken.

Sectagon 42 has no soil residual and reinfestation of a field can occur from numerous sources such as deep nematode populations, seed pieces, irrigation water, equipment contamination and blowing wind.

EARLY MATURITY DISEASES OF POTATOES IN OREGON

Apply 30 gallons Sectagon 42 per acre using injectors (shanks, blades, fertilizer wheels, plows, etc.) Follow immediately with a bedshaper, roller press wheel or similar device or cover with an adequate amount of soil to seal the fumigant into the soil.

NOTE: Sectagon 42 will suppress Root knot nematodes in the fumigated zone at the time of treatment. The fumigated zone is defined as the depth of penetration that Sectagon 42 achieves at the time of application.

MINT

Verticilium wilt control.

When infestation is limited to small spots in a field, spread can be reduced by treating the soil with 75 gallons Sectagon 42 per treated acre (1½ pints per 100 sq. ft.) using injector blade or thin shank injector rig with injectors spaced at intervals to cover the desired treating width.

WHEAT AND BARLEY

For suppression of certain root diseases caused by Early season soil fungi – before applying Sectagon 42 cultivate the area to be treated to break up clods. Apply 2 to 7.5 gallons per treated acre 14 to 21 days before planting. Sectagon 42 may be diluted with water or non-acidic liquid fertilizer immediately before applying. Inject Sectagon 42 to a depth of 5 to 8 inches into moist soil. Space injector shanks at intervals to cover the desired treating width.

Do not mix Sectagon 42 with acidic fertilizer or other acidic solutions. Use only in areas which receive 15 or more inches of rainfall per year.

PEANUTS

Cylindrocladlium Black Rot (CBR) Suppression:

Apply Sectagon 42 at the following rates:

CBR-resistant cultivar (NC8C): 7.5 gallons per treated acre or 4 pints per 1,000 feet of treated row CBR-susceptible peanut cultivars (Florigant, GK-3, NC-5 Keel 29): 15 gallons per treated acre or 8 pints per 1,000 feet of treated row.

CBR-highly susceptible cultivars (VA 81B, NC7): use of Sectagon 42 is not recommended.

Soil Preparation: Before applying Sectagon 42 residue from the previous crop should be decomposed (enhanced by fall discing) and plowed under in the spring with moldboard plow. Soil incorporated preplant herbicides must be applied before application of Sectagon 42.

Application: Apply Sectagon 42 with a gravity flow regulator through chisel-type or counter-type applicators. Center each applicator, one per row, in front of a bedshaper to mark the location of chemical deposition. Sectagon 42 should be deposited 6 to 8 inches below the soil surface of beds. Bed and applicator spacing should coincide with row spacing at planting. Soil temperatures must be in the range of 60°F to 90°F at injection depth before application.

Tillage and Planting after Application: Do not mix treated soil with untreated soil by tillage or other cultural practices. Plant peanuts in the center of treated beds no earlier than 14 days following application of Sectagon 42. An at-planting nematicide treatment will be necessary in fields with heavy infestation of Root knot, Ring and/or String nematode.

FOR SUPPRESSION OF SPECIFIC ORCHARD DISEASES (SUCH AS SPECIFIC APPLE REPLANT DISEASE)

Use 62 to 75 gallons of Sectagon 42 per treated acre. It is best to have the replant site prepared to a planting consistency which includes irrigating to 70% available water capacity before Sectagon 42 application. Treatment can be made in the Fall or Spring before planting but Fall application is the preferred timing. Spring application can be riskier because the interval between treatment and planting is critical; see CAUTIONS listed below. Do not harvest fruit within one (1) year of application. Application with handheld equipment is prohibited.

There are three application techniques that may be used: 1) Entire orchard site, 2) Individual tree row site, and 3) Individual tree plant site.

40

Entire orchard site: Inject the desired amount of Sectagon 42 into a sprinkler system to treat the entire replant site. Figure the irrigation schedule required to cover the desired treatment depth. Start the irrigation system and inject the Sectagon 42 one-third to one-half way through the cycle making sure to leave enough time at the end of the cycle to seal the application with plain water.

Individual tree row site: Two methods of application may be used to apply Sectagon 42 to individual tree row sites: Method One is to apply Sectagon 42 through a portable irrigation system such as a sprinkler or drip system; Method Two is to apply the desired amount of Sectagon 42 through a weed sprayer while the irrigation system is running. For either method and after identifying the position of the future tree row site, apply Sectagon 42 one-third to one-half way through the required irrigation cycle leaving enough time at the end of the cycle to apply plain water, sealing the Sectagon 42 in the ground.

Individual tree plant site: Use 18 to 24 fluid ounces of Sectagon 42 per 100 gallons of water. Use 16 gallons of this solution in a 4 by 4 foot planting hole. Water and product amount adjustments can be made to accommodate different size planting holes to ensure product movement to desired depth. Replace dirt removed.

TARPING: Tarping of replant sites is required when near (1/2 mile) to populated areas, such as schools, hospitals, commercial or office buildings, factories, residential areas, etc. Tarping is not required if treatment is farther than 1/2 mile from such populated areas.

CAUTIONS: INTERVAL BETWEEN TREATMENT AND PLANTING Because Sectagon 42 is harmful to living plants, an appropriate interval must be observed between Sectagon 42 application and planting. On well-drained soils which have a light to medium texture and are not excessively wet or cold following application, planting can begin 21 to 30 days after treatment. If soils are heavy or especially high in organic matter or if they remain wet and/or cold (below 60°F) following application, a minimum interval of 30 to 45 days should be observed. Where the dosage approaches the 75 gallons per acre rate, wait at least 60 days.

HARVEST OF ANY FRUIT WITHIN ONE (1) YEAR OF TREATMENT IS PROHIBITED.



CONDITIONS OF SALE — LIMITED WARRANTY AND LIMITATIONS OF LIABILITY AND REMEDIES

The directions on this label are believed to be reliable and must be followed carefully. Insufficient control of pests and/or injury to the crop to which the product is applied may result from the occurrence of extraordinary or unusual weather conditions, or the failure to follow the label directions, or good application practices, all of which are beyond the control of Tessenderio Kerley, Inc., or seller. In addition, failure to follow label directions may cause injury to crops, animals, man or the environment. Tessenderio Kerley, Inc. warrants that this product conforms to the chemical description on the label and is reasonably fit for the purpose referred to in the directions for use, subject to the factors noted above which are beyond the control of Tessenderio Kerley, Inc. Expenderio Kerley, Inc. warranty, liability and remedies.

NOTICE TO BUYER: Purchase of this material does not confer any rights under patents of countries outside of the United States. Sectagon and NovaSource are registered trademarks of Tessenderlo Kerley, Inc.

Manufactured for: Tessenderlo Kerley, Inc. 2255 N. 44th Street, Suite 300 Phoenix, AZ 85008 USA 1-800-525-2803