

AM31

201-62

1/3

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

A copper-free fast drying polyvinyl chloride type anti-fouling coating for marine use in both fresh and salt water.

GENERAL -- Do not apply at film thicknesses in excess of those specified. Do not apply directly to bare metal or wood. Do not apply during fog, mist, or rain. Do not use for potable water or food contact service. Do not add unspecified solvents or mix with other paints. Clean equipment immediately after use with Vinyl-Cote Standard Reducer No. 7090, Hot Weather Reducer No. 7091, or Methyl Ethyl Ketone. Refer to this product's Protective Maintenance Coatings Data Sheet for detailed recommendations, and primer recommendations for painting new surfaces.

MATERIAL PREPARATION Mix thoroughly using a heavy duty power mixer with a surface scraping action type blade until smooth and free flowing.

NEW CONSTRUCTION - Consult Glidden specifications for surface preparation, protective coatings, and maintenance of aluminum and steel marine equipment before application of VINYL COTE™ No-Cop Anti-Fouling Coating. VINYL COTE No Cop may be applied over VINYL COTE intermediate coats at any time after application providing the surface is clean and free from contamination.

REFRESHER COAT -- As soon as vessel is dry docked and before hull dries, remove contamination. When surface is dry, wipe with No. 7090 or No. 7091 solvent, spot prime, apply build coats as necessary and apply complete refresher coat of Anti-Fouling.

APPLICATION Apply by spray. Use other methods only when absolutely necessary. Recommended application is one coat of VINYL COTE Anti-Fouling at a minimum dry film thickness of 2 mils. If more than one coat is applied, allow one hour drying between coats. Vessel may be launched one hour after application is completed.

THINNING Use No. 7090 or No. 7091 reducers for spray. Do not reduce for brush or roll application.

NOTE: If application is desired over coatings other than the recommended VINYL-COTE System, consult your Glidden Representative.

IMPORTANT: Do not store or apply at temperature below 50°F.

STORAGE AND DISPOSAL

Keep closures tight and upright to prevent leakage. Keep container closed when not in use. Store below 100°F. Do not incinerate closed containers as they may explode when exposed to extreme heat or fire. In case of spillage, absorb and dispose of on site or at an approved waste disposal facility. Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE DISPOSAL

Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

SCM. GLIDDEN COATINGS & RESINS • Cleveland, Ohio 44115
DIVISION OF SCM CORPORATION

ACCEPTED
SEP 25 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No.



Vinyl-Cote™ No-Cop™ ANTI-FOULING COATING

7080 White (178-W-401)

ACTIVE INGREDIENT	7.9%
bis(tributyltin)oxide	
INERT INGREDIENTS	92.1%
Total	100.0%

CONTAINS METHANOL AND PETROLEUM DISTILLATES

EPA Establishment No. 200 TX-1
EPA Registration No. 200-62

FOR COMMERCIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN.
DANGER!
See side panel for additional precautionary statements.

ONE GALLON 3.785L



PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame.

DANGER! FLAMMABLE. MAY IGNITE EXPLOSIVELY.

Keep away from heat, sparks and open flame. Do not smoke. Vapors may ignite explosively. Extinguish all flames, burners, stove, heaters and pilot lights and disconnect all electrical motors and appliances before use and until all vapors are gone. Use portable explosion-proof lighting and ventilating equipment connected to exterior self-contained power source. Nonexplosion proof equipment must be placed well away from areas where vapors may collect. Use non-ferrous tools and wear conductive and nonsparking shoes in areas where explosion hazards exist. Vapors may spread long distances.

USE ONLY WITH ADEQUATE VENTILATION

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT THE CURRENT PROTECTIVE MAINTENANCE COATINGS DATA SHEET AND MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT. EMERGENCY PHONE: (216) 826-5566.

LIMITATION OF LIABILITY

We guarantee our product to conform to Glidden's specifications. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

It is

A copper-free fast
GENERAL — Do not use in fog, mist, or rain. Disconnect equipment immediately. Refer to this product for new surfaces.

MATERIAL PREPARATION — free flowing.

NEW CONSTRUCTION — steel marine equipment. VINYL COTE intermediate.

REFRESHER COAT — or No. 7091 solvent.

APPLICATION — Apply COTE Anti-Fouling may be launched on.

THINNING — Use No.

NOTE: If application

IMPORTANT: Do not

STORAGE

Keep closures tightly closed containers at an approved

PESTICIDE

Pesticide wastes cannot be disposed. Hazardous Waste

CONTAINER

Triple rinse for approved State

200-30

EPA REG

0-17-88



**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
(AND DOMESTIC ANIMALS)
DANGER!**

Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. Causes eye irritation. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer.

Avoid contact with skin, eyes, or clothing. Avoid breathing vapor, spray mist, dust or chips from sanding. Wash thoroughly with any soap and water after handling and before eating or smoking. Use with adequate ventilation.

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. **Get medical attention.**

Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage.

If on skin: Wash with plenty of soap and water. **Get medical attention.**

If in eyes: Flush with plenty of water. **Get medical attention if irritation persists.**

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. **Get medical attention.**

While spraying and/or sanding boat surface, wear a mask or a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

ENVIRONMENTAL HAZARD

This product is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

Made in U.S.A.
©1984 SCM Corp.

VI
N
AN
70

ACTIVE INGREDIENTS
bis (Tributyltin)oxide
INERT INGREDIENTS
Total

CONTAINS

EPA Establishment No.
EPA Registered

FOR CONSUMER USE

KEEP OUT OF REACH OF CHILDREN
DANGER
See side panel for more information

ONE GALLON