

Glidden®

SPREAD oil stain

PRESERVATIVE
WATER REPELLENT
WARRANTED

DANGER! Keep out of reach
of children. Combustible.
See back panel for first aid, precautionary statements,
and other information.

ACTIVE INGREDIENTS	
Pentachlorophenol	2.50%
Bis (Tri-n-Butyltin) Oxide	0.30%
INERT INGREDIENTS	97.20%
Total	100.00%

740 CLEAR OIL FINISH
ONE GALLON 3.785 L

EPA Reg. No. 200-73 EPA Est. No. 200-PA-02,
200-GA-01, 200-CA-01, 200-IL-01, 200-TX-01

PRECAUTIONARY STATEMENTS - HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water for 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE.** Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash receptacle. Keep away from food and feed.

A durable water preservative and water repellent clear oil finish for above ground use only that preserves and enhances the natural grain beauty of all types of wood shingles, shakes, siding, panels, decks and fencing - rough or smooth. Lumber pre-treated with other preservatives should weather and cease to minimize discoloration and/or lifting of the stain. **DO NOT TEST.**

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MIXING PREPARATION

- Mix thoroughly, stirring with a smooth, lifting motion. Apply unthinned.
- If necessary, may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of clear finish.
- Do not thin with water, oils, other clear finishes or paints.

SURFACE PREPARATION

- **General and Sawn Wood:** All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other contaminants that might affect adhesion or performance.
- **Rufty or Cracks:** Close large openings with caulk.
- **Remove Mildew:** scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite-type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Remove surfaces under eaves, porch ceilings or recesses to remove accumulated contaminants. **Be sure all surfaces are in good condition.**
- **Previously Stained:** Use this product over old semi-transparent stain only. (If previous stain is "solid-color" type, use **SPRO Exterior Solid Color Stain**.)

NOTE: The original color will be deepened by a new application of this clear finish.

APPLICATION

- One gallon covers approximately 200-300 square feet on smooth surfaces and about 150-200 square feet on rough surfaces.
- Use on exterior surfaces only. Stir frequently during application.
- Best applied by brushing, working well into surface. Roller and pad application should be supplemented by brushing to fill crevices.
- Spray at only 15-20 lb. pressure to avoid frothing. Use spray masks or hoods.
- Always protect on an inconspicuous area to assure desired results.
- **Horizontal Work:** Do only 4 to 6 boards at a time, extending each work area to structural breaks such as doors, windows, or corners.
- **Vertical Work:** Do only 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- Do not apply when surface or atmospheric temperatures are below 50°F.
- Dries to touch in 1-2 hours under normal conditions (70°F., 50% R.H.). Second coats on rough or textured woods may be applied after 24 hours drying.
- Clean tools and equipment with No. 60 **SPRO** Brush & Roller Cleaner or paint thinner (mineral spirits).

NON-PHOTOCHEMICALLY REACTIVE

ACCEPTED

OCT 27 1981

U.S. Forest Service, Forest Sciences Laboratory, 3200 SW Jefferson Way, Corvallis, OR 97331

Doc-73