

Glidden

Spilled oil stain


WATER REPELLENT
WARRANTED

DANGER! KEEP OUT OF REACH
OF CHILDREN
See back panel for additional safety information

EPA Reg. No. 200-74 EPA Est. No. 200-PA-02,
200-GA-01, 200-CA-01, 200-IL-01, 200-TX-01

ACTIVE INGREDIENTS
2, 4, 6, 8 Tetra-
chloroophthalonitrile 0.70%
Bis (Tri-n-Butyltin) Oxide 0.31%
INERT INGREDIENTS 98.99%
Total 100.00%

SEMI-TRANSPARENT
732 Redwoodtone
ONE GALLON 3.785 L



NON-PHOTOCHEMICALLY REACTIVE

NOV 1 8 1968
For the Federal Insecticide, Fungicide and Rodenticide Act, registered under EPA Reg. No. 800-74

Product Spec. No. 100-572-8

PRECAUTIONARY STATEMENTS—HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water for 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE.** Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

A durable wood preservative and water repellent semi-transparent exterior stain for above-ground use only that penetrates into the wood to protect and enhance the wood grain beauty of all types of wood shingles, shakes, rough siding, panels, decks and fencing. May also be used on wood lawn furniture. May be top coated with a clear exterior varnish if desired, except when used on shingles, shakes and large areas of siding. Lumber pre-treated with commercial preservatives should weather one season to minimize discoloration and/or lifting of the stain. **DO NOT USE ON PAINTED SURFACES.**

NOTE: DRAMATONE® Colorant must be added to Tint Bases before application. See Glidden color literature.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly, stirring with a smooth, lifting motion to assure color uniformity.
- Apply undiluted for one coat application.
- If necessary for reapplying two coats, first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of stain. Do not mix with water, oils, other stains or paints.
- May be used with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden color literature.

SURFACE PREPARATION

- **General Use for Rough Wood**—All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other contaminants that might affect adhesion or performance. Putty all cracks, close large openings with caulk.
- **Remove Mildew**—scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite-type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Scuff surfaces under eaves, porch ceilings or recesses to remove accumulated contaminants. Make sure all surfaces are thoroughly dry.
- **Previously Stained**—Use this product over old semi-transparent stain only. (If previous stain is "solid color" type, use Special Purpose Solid Color Oil Stain.) **NOTE:** The original color will be deepened by a new application of this stain even when it is already weathered to the new color.

APPLICATION

- One gallon covers approximately 200-300 square feet on smooth surfaces and about 150-200 square feet on rough surfaces.
- Use on exterior surfaces only. Stir frequently during application.
- Always protect on an inconspicuous area to assure desired results. Apply carefully to avoid dark lap marks.
- Stain is best applied by brushing, working well into surface. Roller and pad application should be supplemented by brushing to fill crevices. Spray at only 15-20 lbs. pressure to avoid frothing. Use spray masks or hood.
- **Horizontal Work**—Do only 4 to 6 boards at a time, extending each work area to structural breaks such as doors, windows, trimmings.
- **Vertical Work**—Do only 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- Do not apply when surface or atmospheric temperatures are less than 50°F.
- Dries to touch in 6-8 hours under normal conditions (70°F., 50% R.H.). Recoat after 12 hours minimum.
- Clean tools and equipment with No. 60 SPRED Brush & Roller Cleaner or paint thinner (mineral spirits).