

Glidden


SPRINKLED Oil Stain

ACTIVE INGREDIENTS
2, 4, 5, 6 Tetra-
chlorophthalonitrile 0.68%
Bi (Tri-n-Butyl) Oxide 0.30%
INERT INGREDIENTS 99.02%
Total 100.00%

**SEMI-TRANSPARENT
727 Harvest Gold
ONE GALLON 3.785 L**

DANGER! KEEP OUT OF REACH
OF CHILDREN
See back panel for additional information

EPA Reg. No. 200-79, EPA Est. No. 200-PA-02,
200-GA-01, 200-CA-01, 200-IL-01, 200-TX-01



NON-PHOTOCHEMICALLY
REACTIVE

ACCEPTED

NOV 13 1981

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 200-79

PRECAUTIONARY STATEMENTS—HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR IRRITANT IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, flood with water for 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water bodies. Remove water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water and store in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE.** Do not use or store near open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container for trash collection. Keep away from food and feed.

A durable wood preservative and water repellent semi-transparent exterior stain for above-ground use only that penetrates wood to protect and enhance the wood grain beauty of all types of wood shingles, shakes, rough siding, panels, decks and also be used on wood lawn furniture. May be top coated with a clear exterior varnish if desired, except when used on large areas of siding. Lumber pre-treated with commercial preservatives should weather one season to minimize end/or lifting of the stain. **DO NOT USE ON PAINTED SURFACES.**

NOTE: DRAMATONE® Colorant must be added to Tint Base before application. See Glidden color literature.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly, stirring with a smooth, lifting motion to assure color uniformity.
- Apply undiluted for one coat application.
- If necessary (when applying two coats), first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon. Do not thin with water, oils, other stains or paints.
- May be tinted with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden color literature.

SURFACE PREPARATION

- General use for New Wood—All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other coating that might affect adhesion or performance. Putty all cracks, close large openings with caulk.
- Remove mildew—scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite bleach in three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid irritation. Scrub surfaces under eaves, porch ceilings or recesses to remove accumulated contaminants. Make sure all surfaces are completely dry.
- Previously Stained—Use this product over old semi-transparent stain only. (If previous stain is "solid color" type, use Solid Color Oil Stain.) **NOTE:** The original color will be deepened by a new application of this stain even when it is close to the new color.

APPLICATION

- One gallon covers approximately 200-300 square feet on smooth surfaces and about 150-200 square feet on rough surfaces.
- Use on exterior surfaces only. Stir frequently during application.
- Always pretest on an inconspicuous area to assure desired results. Apply carefully to avoid dark lap marks.
- Stain is best applied by brushing, working well into surface. Roller and pad application should be supplemented by crevices. Spray at only 15-20 lbs. pressure to avoid frothing. Use spray masks or hoods.
- Horizontal Work—Do only 4 to 6 boards at a time, extending each work area to structural breaks such as doors, windows, etc.
- Vertical Work—Do only 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- Do not apply when surface or atmospheric temperatures are less than 50°F.
- Dries to touch in 6-8 hours under normal conditions (70°F., 50% R.H.). Recoat after 12 hours minimum.
- Clean tools and equipment with No. 60 SPRED Brush & Roller Cleaner or paint thinner (mineral spirits).