

Glidden

# SPRED oil stain

PRESERVATIVE  
WATER REPELLENT  
WARRANTED

**THREE YEAR  
LIMITED WARRANTY**

When applied according to label instructions over a properly prepared surface Glidden warrants that its SPRED Oil Exterior Stain will not crack, peel or blister for 3 years from date of application. Unsatisfactory performance resulting from breakdown of previous coatings and/or substrates are not covered by this warranty. If this stain fails to perform as warranted, Glidden will supply an equal amount of stain, or refund the purchase price.

This Warranty specifically excludes labor or cost of labor. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

**DANGER! KEEP OUT OF REACH  
OF CHILDREN. COMBUSTIBLE.**

See back panel for additional precautionary statements.

ACTIVE INGREDIENTS	
2, 4, 5, 6 Tetra-	
chlorosophthalonitrile	0.45%
Bs (Tri-n-Butyltin) Oxide	0.10%
INERT INGREDIENTS	99.25%
Total	100.00%

**SOLID COLOR**  
**707 Harvest Gold**  
**ONE GALLON 3.785 L**

EPA Reg. No. 200-90 EPA Est. No. 200-PA-02,  
200-GA-01, 200-CA-01, 200-IL-01, 200-TX-01

**PRECAUTIONARY STATEMENTS—HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER!** KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

**FIRST AID:** If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water for 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

**ENVIRONMENTAL HAZARDS:** This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

**PHYSICAL OR CHEMICAL HAZARDS:** To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. **COMBUSTIBLE**. Do not use or store near heat or open flame.

**STORAGE AND DISPOSAL:** Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

A durable wood preservative and water repellent stain for above ground use only that protects and beautifies all types of wood shingles, shakes, and rough siding, panels and fencing. Protection and hiding of surface is usually obtainable in one coat without appreciably altering the textural beauty of wood. Lumber pre-treated with commercial preservatives should weather one season to minimize discoloration and/or lifting of the stain. **NOT FOR USE ON YARD FURNITURE, FLOORS OR DECKS. NOT RECOMMENDED FOR USE ON HARDBOARD (PRESSED WOOD, FIBERBOARD) OR SIMILAR MANUFACTURED BUILDING MATERIALS.**

**NOTE:** DRAMATONE® Colorant must be added to Tint Bases before application. See Glidden color literature.

**DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**MATERIAL PREPARATION**

- Mix thoroughly, stirring with a smooth, lifting motion to assure color uniformity.
- Apply unthinned for one coat application.
- If necessary (when applying two coats), first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of stain. Do not thin with water, oils, other stains or paints.
- May be tinted with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden color literature.

**SURFACE PREPARATION**

- **General and for New Wood**—All surfaces must be dry, well cured and cleaned of dirt, oil, wax or any other contaminants that might affect adhesion or performance. Putty all cracks, close large openings with caulk.
- **Remove mildew**—scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite-type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Scrub surfaces under eaves, porch ceilings or recesses to remove accumulated contaminants. Make sure all surfaces are internally dry.
- **Previously Finished Wood**—Remove blistered, peeling or cracked paint by scraping. Feather sand edges. Lightly sand all hard, glossy old finishes. Unweathered surfaces under eaves, porch ceilings, etc., must be scrubbed with water to remove contaminants. Seal structural cracks.
- **Metal (Gutters, Flashing)**—Prime bare iron or steel with No. 999 SPRED Gloss Metal Primer. Prime bare galvanized metal, including aluminum, with No. 998 SPRED Gloss Galvanized Primer.

**APPLICATION**

- One gallon covers approximately 200-300 sq. ft. on smooth surfaces, 150-200 sq. ft. on rough surfaces and 300-400 sq. ft. on stained or painted surfaces. Coverage varies due to degree of surface texture and porosity.
- Use on exterior surfaces only. Stir frequently during application.
- Always pretest on an inconspicuous area to assure desired results. Apply carefully to avoid dark lap marks.
- Stain is best applied by brushing, working well into surface. Supplement roller and pad application by brushing to fill crevices. Spray at only 30-50 lbs. pressure. Use spray masks or hoods. For airless spray, use 513 tip at 1500 psi.
- **Horizontal Work**—Do only 4 to 6 boards at a time, extending each work area to structural breaks such as doors, windows, or corners.
- **Vertical Work**—Do only 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- Do not apply when surface or atmospheric temperatures are less than 50°F.
- Dries to touch in 6-8 hours under normal conditions (70°F., 50% R.H.). Recoat after 24 hours minimum.
- Clean tools and equipment with No. 60 SPRED Brush & Roller Cleaner or paint thinner (mineral spirits), or xylene (xyol).

L.C. 188270

**SCM** GLIDDEN COATINGS & RESINS • Cleveland, Ohio 44115  
DIVISION OF SCM CORPORATION

NON-PHOTOCHEMICALLY  
REACTIVE

ACCEPTED

GB