THREE YEAR
LIMITED WARRANTY

SPRED O
Exterior Stain will not crack peel
or blister

This Warranty specifically excludes
labor or cost of labor

Glidden

spred oil stain

DANGER: KEEP OUT OF REA
FLAMMABLE OR COMBUSTIBLE.

EPA Reg. No. 200-66 EPA Est. No. 200-PA-02,
200-GA-01, 200-IL-01, 200-TX-01

ACTIVE INGREDIENTS

2, 4, 5, 6 Tetra-chloroisophthalonitrile	0.42%
Bis (Tri-n-Butyltin) Oxide	0.30%
INERT INGREDIENTS	99.28%
Total	100.00%

SOLID COLOR
710 Historic Tan
ONE GALLON 3.785 L

PRECAUTIONARY STATEMENTS—HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

[illegible] well ventilated area. Do not breathe vapor or spray mist. [illegible] eyes, on skin or clothing. Wear rubber gloves and [illegible] when applying or handling freshly treated lumber.

FIRST AID: [illegible] skin wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes immediately [illegible] water. [illegible] physician. If swallowed [illegible] induce vomiting call a physician.

ENVIRONMENTAL HAZARDS: [illegible] toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: [illegible] spontaneous combustion soak dry cloths in water after use or place in a closed metal container away from buildings and other combustible materials. COMBUSTIBLE. Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not contaminate or store inside the home. Do not reuse empty container. Wrap container and put in trash [illegible]. Keep away from food and feed.

NON PHOTOCHEMICALLY REACTIVE

A durable wood preservative and water repellent stain for above ground use only that protects and beautifies all types of wood shingles, shakes, [illegible] and fencing. Protection and hiding of surface is usually obtainable in one coat without appreciably altering the natural beauty of wood. Lumber pre-treated with commercial preservatives should weather one season to minimize discoloration of the stain. **NOT FOR USE ON YARD FURNITURE, FLOORS OR DECKS. NOT RECOMMENDED FOR USE ON HARDBOARD (PRESSED WOOD, FIBERBOARD) OR SIMILAR MANUFACTURED BUILDING MATERIALS.**

NOTE: DRAMATONE® colorant must be added to Tint Bases before [illegible]. See Glidden color literature.

DIRECTIONS FOR USE

[illegible] use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly stirring with a smooth [illegible] to assure color uniformity.
- Apply [illegible] for the [illegible].
- [illegible] when applying [illegible] may be thinned with up to one pint of paint thinner, mineral spirits per gallon of [illegible] with water [illegible].
- [illegible] DRAMATONE Multi-Purpose Colorants [illegible] as specified in Glidden color literature.

SURFACE PREPARATION

- **General and for New Wood:** All surfaces must be dry, well [illegible] and free of dirt, dust or wax or any other contaminants that [illegible] cracks, close large open ends with caulk.
- [illegible] with a solution of one tablespoon of trisodium phosphate, a good quality detergent and one pint hypochlorite type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and [illegible]. Scrub surfaces and crevices [illegible] to remove accumulated contaminants. Make sure all surfaces are in [illegible].
- **Previously Finished Wood:** Remove loosened peeling or cracked paint by scraping. Feather sand edges. Lightly sand all hard, glossy [illegible]. Unweathered surfaces, under eaves, porch ceilings, etc., must be scrubbed with water to remove contaminants. Seal [illegible].
- **Metal (Gutters, Flashing):** [illegible] steel with [illegible] SPRED Gloss Metal Primer. Prime bare galvanized metal, including [illegible] with [illegible] SPRED Gloss Galvanized Primer.

APPLICATION

- One gallon covers approximately 300-400 sq. ft. on smooth surfaces, 250-300 sq. ft. on rough surfaces and 300-400 sq. ft. on tapered or garted surfaces. Average coverage will be influenced by degree of surface texture and porosity.
- [illegible] surfaces by stirring frequently during application.
- Always pretest [illegible] to assure desired results. Apply carefully to avoid dark lap marks.
- [illegible] established by brushing with [illegible] and pad application by brushing to fill crevices. Spray at [illegible] pressure [illegible] masks or hoods for airless spray use 0.3 tip at 1500 psi.
- **Horizontal Work:** [illegible] boards at a time, [illegible] area to structural breaks such as joints, windows or corners.
- **Vertical Work:** [illegible] 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- [illegible] when surface or atmospheric temperatures are less than 50°F.
- [illegible] 50% R.H. Recoat after [illegible].
- [illegible] with [illegible] SPRED Brush & R[illegible] paint thinner, mineral spirits or xylene. [illegible]

GB

GLIDDEN COATINGS & RESINS · Cleveland, Ohio 44115