

Glidden

SPREAD Oil Stain

THREE YEAR LIMITED WARRANTY

When you use Glidden Exterior Stain, you can be sure that your exterior surfaces will be protected for years to come. SPREAD Oil Exterior Stain will not crack, peel or blister for three years from date of application. It is formulated with a special resin that provides a long-lasting, protective film. It is available in a variety of colors to match your home's exterior.

This Warranty specifically excludes labor or cost of labor. It is void where prohibited by law. For more information, contact your local Glidden distributor.

DANGER! KEEP OUT OF REACH OF CHILDREN.

EPA Reg. No. 200-97 EPA Est. No. 200-PA-02,
200-MA-01, 200-CA-01, 200-IL-01, 200-TX-01

ACTIVE INGREDIENTS
2, 4, 6, 8 Tetra-
chlorophthalonitrile 0.47%
Bis (11-n-Butyltin) Oxide 0.30%
PAINT INGREDIENTS 99.23%

Total 100.00%
SOLID COLOR
701 Beon
ONE GALLON 3.785 L



NON PHOTOCHEMICALLY REACTIVE

PRECAUTIONARY STATEMENTS – HAZARDS TO HUMANS AND DOMESTIC ANIMALS
DANGER! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT AND OPEN FLAME.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, on skin or clothing. Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flush with water for 15 minutes. Call a physician if swallowed. Do not induce vomiting. Call a physician.

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment and disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: May ignite spontaneously in contact with water. Wash with water after use or place in colored metal container away from buildings and other combustible materials. **COMBUSTIBLE**. Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash. Do not keep away from food and feed.

A durable wood preservative and water repellent stain for above ground use only that protects and beautifies all types of wood shingles, shakes, and roof siding, panels and fencing. Protection and luster of surface is usually obtainable in one coat without appreciably altering the texture, beauty of wood. Lumber pre-treated with commercial preservatives should weather one season to minimize discoloration and odor of the stain. **NOT FOR USE ON YARD FURNITURE, FLOORS OR DECKS. NOT RECOMMENDED FOR USE ON HARDBOARD (PRESSED WOOD, FIBERBOARD) OR SIMILAR MANUFACTURED BUILDING MATERIALS.**

NOTE: DRAMATONE® Colorant must be added to Tint Bases before application. See Glidden color literature.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly, stirring with a smooth, fitting motion to assure color uniformity.
- Apply unthinned for one coat application.
- If necessary (when applying two coats), first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of stain. Do not thin with water. Use other stain for parts.
- May be thinned with DRAMATONE Multi Purpose Colorants only, as specified in Glidden color literature.

SURFACE PREPARATION

- **General and for New Wood:** All surfaces must be dry, well-cured and cleaned of dirt, dust, oil, wax or any other oil fat parts that might affect the stain's performance. Putty all cracks, close large openings with caulk.
- **Remove old stain:** Scrub with soap or mild detergent, or dry powdered laundry detergent and one quart hypochlorite type household bleach in three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Scrub surfaces under eaves, porch ceilings or recesses to remove accumulated contaminants. Make sure all surfaces are in ready-to-stain condition.
- **Previously Finished Wood:** Remove blistered, peeling or cracked paint by scraping. Feather sand edges. Lightly sand all hard, glossy surfaces. On weathered surfaces under eaves, porch ceilings, etc., must be scrubbed with water to remove contaminants. Seal with wood preservative.
- **Metal (Gutters, Flashing):** Prime bare metal or steel with No. 999 SPRED Cross Metal Primer. Prime bare galvanized metal including aluminum with No. 999-1 FIBERBOARD Galvanized Primer.

APPLICATION

- One quart covers approximately 100-300 sq. ft. on smooth surfaces, 150-200 sq. ft. on rough surfaces and 300-400 sq. ft. on stained or painted surfaces. Actual coverage due to degree of surface texture and porosity.
- Use on exterior surfaces only. Stir frequently during application.
- Always protect surrounding areas to assure desired results. Apply carefully to avoid dark lap marks.
- Stain is best applied by brushing, working well into surface. Supplement roller and pad application by brushing to fill crevices. Spray at only 30-40 psi. Always use spray masks or hoods. For airless spray, use 5/32" tip at 1500 psi.
- **Horizontal Work:** Apply to 4" x 6" boards at a time, extending each work area to a full board length. Use doors, windows, etc. as guides.
- **Vertical Work:** Apply only 4" x 6" boards or 8" x complete panel at a time, brushing full length up to bottom.
- Do not apply when surface or air temperatures are less than 50°F.
- Do not touch for 24 hours before rain or conditions 70°F-50°F RH. Recoat after 24 hours, if necessary.
- Do not use in conjunction with No. 999-1 SPRED Brush & Roller applicator. Use only with Glidden sprays, spray equipment, etc.

GB