

1 of 2
Pg 21
REG. # 200-100

ACCEPTED
OCT 11 1985
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under EPA Reg. No. 200-100



ENDURANCE

OIL STAIN

THREE YEAR LIMITED WARRANTY

When applied according to label instructions, over a properly prepared surface, Glidden warrants that its ENDURANCE Oil Exterior Stain will not crack, peel or blister for 3 years from date of application. Unsatisfactory performance resulting from breakdown of previous coatings and/or substrates are not covered by this warranty. If this stain fails to perform as warranted, Glidden will supply an equal amount of stain, or refund the purchase price.

This Warranty specifically excludes labor or cost of labor. Some states do

SEMI-TRANSPARENT

WATER REPELLENT

9733

NOTE: DRAMATONE® Colorant must be added to Tint Bases before application. See Glidden color literature.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

MATERIAL PREPARATION

- Mix thoroughly, stirring with a smooth, lifting motion to assure color uniformity.
- Apply unthinned for one coat application.
- If necessary (when applying two coats), first coat may be thinned with up to one pint of paint thinner (mineral spirits) per gallon of stain. Do not thin with water, oils, other stains or paints.
- May be tinted with DRAMATONE Multi-Purpose Colorants only, as specified in Glidden color literature.

SURFACE PREPARATION

- General and for New Wood—All surfaces must be dry, well cured and cleaned of dust, dirt, oil, wax or any other contaminants that might affect adhesion or performance. Putty all cracks, close large openings with caulk.
- Remove mildew—scrub with solution of one tablespoon dry powdered laundry detergent and one quart hypochlorite-type household bleach to three quarts warm water. Rinse thoroughly with water. Wear protective glasses and rubber gloves to avoid eye and skin irritation. Scrub surfaces under eaves, porch ceilings or recesses to remove accumulated contaminants. Make sure all surfaces are internally dry.
- Previously Stained—Use this product over old semi-transparent stain only. (If previous stain is "solid color" type, use ENDURANCE Exterior Solid Color Oil Stain.) NOTE: The original color will be deepened by a new application of this stain even when it is closely matched to the new color.

APPLICATION

- One gallon covers approximately 200-300 square feet on smooth surfaces and about 150-200 square feet on rough surfaces.
- Use on exterior surfaces only. Stir frequently during application.
- Always pretest on an inconspicuous area to assure desired results. Apply carefully to avoid dark lap marks.
- Stain is best applied by brushing, working well into surface. Roller and pad application should be supplemented by brushing in all crevices. Spray at only 15-20 lbs. pressure to avoid frothing. Use spray masks or hoods.
- Horizontal Work—Do only 4 to 6 boards at a time, extending each work area to structural breaks such as doors, windows, or corners.
- Vertical Work—Do only 4 to 6 boards or one complete panel at a time, finishing fully from top to bottom.
- Do not apply when surface or atmospheric temperatures are less than 50°F.
- Dries to touch in 6-8 hours under normal conditions (70°F., 60% R.H.). Recoat after 12 hours minimum.
- Clean tools and equipment with No. 60 SPRED Brush & Roller Cleaner or paint thinner (mineral spirits).

L.C. 369101

stain to control fungal growth on wood

68

ACCEPTED

GLIDDEN GLIDDEN COATINGS & RESINS, Cleveland, Ohio 44115
DIVISION OF ICM CORPORATION

OCT 11 1985

Under the Federal Insecticide, Fungicide, and Rodenticide Act, an inspection of the pesticide registered under EPA Reg. No. 200-102